

SAFETY DATA SHEET

According to the Hazardous Products Regulations

Ethyl PROXITOL

Version
1.1

Revision Date:
2023-11-23

SDS Number:
800001033949

Print Date: 2023-11-30
Date of last issue: 16.02.2022
Date of first issue: 16.02.2022

SECTION 1. IDENTIFICATION

Product name : Ethyl PROXITOL

Product code : U5129

Manufacturer or supplier's details

Manufacturer/Supplier : **Shell Chemicals Canada**
PO Box 4280 STN C
CALGARY AB T2T 5Z5
Canada

Telephone : 1-855-697-4355

Telefax : 1-866-213-7508

Emergency telephone number

CHEMTREC (24 hr) : 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Solvent.

Restrictions on use : This product must not be used in applications other than the above without first seeking the advice of the supplier.

Other information : PROXITOL is a trademark owned by Shell Trademark Management B.V. and Shell Brands Inc. and used by affiliates of Shell plc.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Eye irritation : Category 2

Specific target organ toxicity
- single exposure : Category 3 (Narcotic effects)

GHS label elements

Hazard pictograms :



SAFETY DATA SHEET

According to the Hazardous Products Regulations

Ethyl PROXITOL

Version
1.1

Revision Date:
2023-11-23

SDS Number:
800001033949

Print Date: 2023-11-30
Date of last issue: 16.02.2022
Date of first issue: 16.02.2022

Signal word	: Warning
Hazard statements	: PHYSICAL HAZARDS: H226 Flammable liquid and vapour. HEALTH HAZARDS: H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.
Precautionary statements	: Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P370 + P378 In case of fire: Use appropriate media to extinguish. P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/ doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 If eye irritation persists: Get medical advice/ attention. Storage: P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. Disposal: P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regulations.

Other hazards which do not result in classification

Vapours are heavier than air. Vapours may travel across the ground and reach remote ignition sources causing a flashback fire danger.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

SAFETY DATA SHEET

According to the Hazardous Products Regulations

Ethyl PROXITOL

Version
1.1

Revision Date:
2023-11-23

SDS Number:
800001033949

Print Date: 2023-11-30
Date of last issue: 16.02.2022
Date of first issue: 16.02.2022

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance
Substance name : Ethyl PROXITOL 52125-53-8
Synonyms : EP, PGEE

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Propylene Glycol Monoethyl Ether	52125-53-8	99 - 100 -

Stabilized with 25 ppm BHT.

SECTION 4. FIRST-AID MEASURES

General advice : Not expected to be a health hazard when used under normal conditions.

If inhaled : Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.

In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.
If persistent irritation occurs, obtain medical attention.

In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses, if present and easy to do. Continue rinsing.
Transport to the nearest medical facility for additional treatment.

If swallowed : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.

Most important symptoms and effects, both acute and delayed : Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination.
Continued inhalation may result in unconsciousness and death.
No specific hazards under normal use conditions.
Skin irritation signs and symptoms may include a burning sensation, redness, or swelling.
Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.
No specific hazards under normal use conditions.
Ingestion may result in nausea, vomiting and/or diarrhoea.

Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the

SAFETY DATA SHEET

According to the Hazardous Products Regulations

Ethyl PROXITOL

Version
1.1

Revision Date:
2023-11-23

SDS Number:
800001033949

Print Date: 2023-11-30
Date of last issue: 16.02.2022
Date of first issue: 16.02.2022

incident, injury and surroundings.

Notes to physician

: IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!
Call a doctor or poison control center for guidance.
Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
- Unsuitable extinguishing media : None
- Specific hazards during fire-fighting : The vapour is heavier than air, spreads along the ground and distant ignition is possible.
Carbon monoxide may be evolved if incomplete combustion occurs.
- Specific extinguishing methods : Standard procedure for chemical fires.
- Further information : Clear fire area of all non-emergency personnel.
Keep adjacent containers cool by spraying with water.
- Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Observe the relevant local and international regulations
Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.
Local authorities should be advised if significant spillages cannot be contained.
The vapour is heavier than air, spreads along the ground and distant ignition is possible.
Vapour may form an explosive mixture with air.
Avoid contact with skin, eyes and clothing.
Isolate hazard area and deny entry to unnecessary or unprotected personnel.
Stay upwind and keep out of low areas.
- Environmental precautions : Shut off leaks, if possible without personal risks. Remove all

SAFETY DATA SHEET

According to the Hazardous Products Regulations

Ethyl PROXITOL

Version	Revision Date:	SDS Number:	Print Date: 2023-11-30
1.1	2023-11-23	800001033949	Date of last issue: 16.02.2022
			Date of first issue: 16.02.2022

possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Ventilate contaminated area thoroughly. Monitor area with combustible gas indicator.

Methods and materials for containment and cleaning up : For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

Additional advice : For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7. HANDLING AND STORAGE

General Precautions : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Ensure that all local regulations regarding handling and storage facilities are followed.

Advice on safe handling : Avoid contact with skin, eyes and clothing.
Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.
Bulk storage tanks should be diked (bunded).
Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.
Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to

SAFETY DATA SHEET

According to the Hazardous Products Regulations

Ethyl PROXITOL

Version
1.1

Revision Date:
2023-11-23

SDS Number:
800001033949

Print Date: 2023-11-30
Date of last issue: 16.02.2022
Date of first issue: 16.02.2022

reduce the risk.

The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.

Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.

Do NOT use compressed air for filling, discharging, or handling operations.

Glycol ethers can be peroxide formers.

Avoidance of contact : Strong oxidising agents.

Product Transfer : Refer to guidance under Handling section.

Storage

Conditions for safe storage : The vapour is heavier than air. Beware of accumulation in pits and confined spaces.
Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Packaging material : Suitable material: For containers, or container linings use mild steel, stainless steel.
Unsuitable material: Natural, butyl, neoprene or nitrile rubbers.

Unsuitable material: Aluminum, Most plastics.

Container Advice : Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers.

Specific use(s) : Not applicable

Ensure that all local regulations regarding handling and storage facilities are followed.
See additional references that provide safe handling practices: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).
IEC/TS 60079-32-1: Electrostatic hazards, guidance

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of	Control parameters / Permissible	Basis
------------	---------	------------------------	----------------------------------	-------

SAFETY DATA SHEET

According to the Hazardous Products Regulations

Ethyl PROXITOL

Version
1.1

Revision Date:
2023-11-23

SDS Number:
800001033949

Print Date: 2023-11-30
Date of last issue: 16.02.2022
Date of first issue: 16.02.2022

		exposure)	concentration	
1-ethoxypropan-2-ol	1569-02-4	TWA	50 ppm	ACGIH
		STEL	200 ppm	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods <http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods <http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances <http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany <http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

Engineering measures

- : Use sealed systems as far as possible.
- Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.
- Local exhaust ventilation is recommended.
- Firewater monitors and deluge systems are recommended.
- Eye washes and showers for emergency use.
- Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
- The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.
- Appropriate measures include:

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.

Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of

SAFETY DATA SHEET

According to the Hazardous Products Regulations

Ethyl PROXITOL

Version
1.1

Revision Date:
2023-11-23

SDS Number:
800001033949

Print Date: 2023-11-30
Date of last issue: 16.02.2022
Date of first issue: 16.02.2022

equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type A boiling point >65°C (149°F)].

Hand protection
Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Butyl rubber. Nitrile rubber. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

SAFETY DATA SHEET

According to the Hazardous Products Regulations

Ethyl PROXITOL

Version
1.1

Revision Date:
2023-11-23

SDS Number:
800001033949

Print Date: 2023-11-30
Date of last issue: 16.02.2022
Date of first issue: 16.02.2022

-
- | | |
|--------------------------|---|
| Eye protection | : Wear goggles for use against liquids and gas.
Wear full face shield if splashes are likely to occur. |
| Skin and body protection | : Wear antistatic and flame-retardant clothing, if a local risk assessment deems it so.
Skin protection is not required under normal conditions of use.
For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure.
If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes. |
| Thermal hazards | : Not applicable |
| Protective measures | : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers. |

Environmental exposure controls

- | | |
|----------------|--|
| General advice | : Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.
Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.
Information on accidental release measures are to be found in section 6. |
|----------------|--|

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- | | |
|-----------------------------|-------------------------------|
| Appearance | : Liquid. |
| Colour | : clear |
| Odour | : Ethereal |
| Odour Threshold | : Data not available |
| pH | : Data not available |
| Melting / freezing point | : < -70 °C / < -94 °F |
| Boiling point/boiling range | : 129 - 136 °C / 264 - 277 °F |
| Flash point | : 40 °C / 104 °F |
| | Method: PMCC / ASTM D3278 |

SAFETY DATA SHEET

According to the Hazardous Products Regulations

Ethyl PROXITOL

Version	Revision Date:	SDS Number:	Print Date: 2023-11-30
1.1	2023-11-23	800001033949	Date of last issue: 16.02.2022
			Date of first issue: 16.02.2022

Evaporation rate	: 0.5
Flammability	
Flammability (solid, gas)	: Data not available
Lower explosion limit and upper explosion limit / flammability limit	
Upper explosion limit	: 12 %(V)
Lower explosion limit	: 1.3 %(V)
Vapour pressure	: 1,200 Pa (20 °C / 68 °F)
Relative vapour density	: 3.5
Relative density	: 0.91 (20 °C / 68 °F) Method: ASTM D4052
Density	: ca. 897 kg/m ³ (20 °C / 68 °F)Method: ASTM D4052
Solubility(ies)	
Water solubility	: Completely miscible. (20 °C / 68 °F)
Partition coefficient: n-octanol/water	: log Pow: < 1
Auto-ignition temperature	: 255 °C / 491 °F
Decomposition temperature	: Data not available
Viscosity	
Viscosity, dynamic	: 2.21 mPa.s (20 °C / 68 °F) Method: ASTM D445
Viscosity, kinematic	: Data not available
Explosive properties	: Not applicable
Oxidizing properties	: Data not available
Surface tension	: 41.5 mN/m
Conductivity	: Electrical conductivity: > 10,000 pS/m, A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be a static accumulator.
Molecular weight	: 104.1 g/mol

SAFETY DATA SHEET

According to the Hazardous Products Regulations

Ethyl PROXITOL

Version
1.1

Revision Date:
2023-11-23

SDS Number:
800001033949

Print Date: 2023-11-30
Date of last issue: 16.02.2022
Date of first issue: 16.02.2022

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: No hazardous reaction is expected when handled and stored according to provisions
Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Avoid heat, sparks, open flames and other ignition sources. Prevent vapour accumulation. In certain circumstances product can ignite due to static electricity. Exposure to air or moisture over prolonged periods.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	: Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s). Information given is based on product testing, and/or similar products, and/or components.
----------------------	--

Information on likely routes of exposure

Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

Acute toxicity

Components:

Propylene Glycol Monoethyl Ether:

Acute oral toxicity : LD 50: > 5,000 mg/kg
Remarks: Low toxicity

Acute inhalation toxicity : Remarks: Low toxicity if inhaled.
Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

According to the Hazardous Products Regulations

Ethyl PROXITOL

Version
1.1

Revision Date:
2023-11-23

SDS Number:
800001033949

Print Date: 2023-11-30
Date of last issue: 16.02.2022
Date of first issue: 16.02.2022

Acute dermal toxicity : LD 50: > 5,000 mg/kg
Remarks: Low toxicity

Skin corrosion/irritation

Components:

Propylene Glycol Monoethyl Ether:

Remarks: Slightly irritating to skin.

Serious eye damage/eye irritation

Components:

Propylene Glycol Monoethyl Ether:

Remarks: Causes serious eye irritation.

Respiratory or skin sensitisation

Components:

Propylene Glycol Monoethyl Ether:

Remarks: Not a sensitiser.

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Components:

Propylene Glycol Monoethyl Ether:

Genotoxicity in vivo : Remarks: No evidence of mutagenic activity.

Carcinogenicity

Components:

Propylene Glycol Monoethyl Ether:

Remarks: Not a carcinogen.

Based on available data, the classification criteria are not met.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Components:

SAFETY DATA SHEET

According to the Hazardous Products Regulations

Ethyl PROXITOL

Version
1.1

Revision Date:
2023-11-23

SDS Number:
800001033949

Print Date: 2023-11-30
Date of last issue: 16.02.2022
Date of first issue: 16.02.2022

Propylene Glycol Monoethyl Ether:

Effects on fertility :

Remarks: Not a developmental toxicant.
Does not impair fertility.
Based on available data, the classification criteria are not met.

STOT - single exposure

Components:

Propylene Glycol Monoethyl Ether:

Remarks: May cause drowsiness or dizziness.
High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness.
Inhalation of vapours or mists may cause irritation to the respiratory system.

STOT - repeated exposure

Components:

Propylene Glycol Monoethyl Ether:

Remarks: Based on available data, the classification criteria are not met.

Further information

Components:

Propylene Glycol Monoethyl Ether:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment : Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Incomplete ecotoxicological data are available for this product.
The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.

Ecotoxicity

Components:

Propylene Glycol Monoethyl Ether:

Toxicity to fish (Acute toxicity) : LC50: > 100 mg/l
Remarks: Practically non toxic:
Based on available data, the classification criteria are not met.

Toxicity to crustacean (Acute toxicity) : EC50: > 100 mg/l
Remarks: Practically non toxic:
Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

According to the Hazardous Products Regulations

Ethyl PROXITOL

Version
1.1

Revision Date:
2023-11-23

SDS Number:
800001033949

Print Date: 2023-11-30
Date of last issue: 16.02.2022
Date of first issue: 16.02.2022

Toxicity to algae/aquatic plants (Acute toxicity) : EC50: > 100 mg/l
Remarks: Practically non toxic:

Toxicity to fish (Chronic toxicity) : Remarks: NOEC/NOEL > 100 mg/l

Toxicity to crustacean(Chronic toxicity) : Remarks: NOEC/NOEL > 100 mg/l

Toxicity to bacteria : IC50: > 100 mg/l
Remarks: Practically non toxic:
Based on available data, the classification criteria are not met.

Persistence and degradability

Components:

Propylene Glycol Monoethyl Ether:

Biodegradability : Remarks: Readily biodegradable.

Bioaccumulative potential

Partition coefficient: n-octanol/water : log Pow: < 1

Components:

Propylene Glycol Monoethyl Ether:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

Mobility in soil

Components:

Propylene Glycol Monoethyl Ether:

Mobility : Remarks: If product enters soil, it will be highly mobile and may contaminate groundwater.
Dissolves in water.

Other adverse effects

no data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Recover or recycle if possible.
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
Do not dispose into the environment, in drains or in water

SAFETY DATA SHEET

According to the Hazardous Products Regulations

Ethyl PROXITOL

Version
1.1

Revision Date:
2023-11-23

SDS Number:
800001033949

Print Date: 2023-11-30
Date of last issue: 16.02.2022
Date of first issue: 16.02.2022

courses.

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.

Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be complied with.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging

: Drain container thoroughly.
After draining, vent in a safe place away from sparks and fire.
Residues may cause an explosion hazard.
Do not, puncture, cut, or weld uncleaned drums.
Send to drum recoverer or metal reclaimer.

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

SECTION 14. TRANSPORT INFORMATION

TDG

UN number : 3271
Proper shipping name : ETHERS, N.O.S.
(1-ethoxypropan-2-ol)
Class : 3
Packing group : III
Labels : 3
Marine pollutant : no

International Regulations

IATA-DGR

UN/ID No. : UN 3271
Proper shipping name : ETHERS, N.O.S.
(1-ethoxypropan-2-ol)
Class : 3
Packing group : III
Labels : 3

IMDG-Code

UN number : UN 3271
Proper shipping name : ETHERS, N.O.S.

SAFETY DATA SHEET

According to the Hazardous Products Regulations

Ethyl PROXITOL

Version
1.1

Revision Date:
2023-11-23

SDS Number:
800001033949

Print Date: 2023-11-30
Date of last issue: 16.02.2022
Date of first issue: 16.02.2022

(1-ethoxypropan-2-ol)

Class	: 3
Packing group	: III
Labels	: 3
Marine pollutant	: no

Maritime transport in bulk according to IMO instruments

Pollution category	: Z
Ship type	: 3
Product name	: Propylene glycol monoalkyl ether

Special precautions for user

Remarks	: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.
---------	--

Additional Information	: This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry. Transport in bulk according to Annex II of Marpol and the IBC Code
-------------------------------	--

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

The components of this product are reported in the following inventories:

AIIC	: Listed
DSL	: Listed
IECSC	: Listed
ENCS	: Listed
KECI	: Listed
NZIoC	: Listed
PICCS	: Listed

SAFETY DATA SHEET

According to the Hazardous Products Regulations

Ethyl PROXITOL

Version	Revision Date:	SDS Number:	Print Date: 2023-11-30
1.1	2023-11-23	800001033949	Date of last issue: 16.02.2022
			Date of first issue: 16.02.2022

TCSI : Listed

TSCA : Listed

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

Revision Date : 2023-11-23

SAFETY DATA SHEET

According to the Hazardous Products Regulations

Ethyl PROXITOL

Version
1.1

Revision Date:
2023-11-23

SDS Number:
800001033949

Print Date: 2023-11-30
Date of last issue: 16.02.2022
Date of first issue: 16.02.2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN