Regulation 1907/2006/EC

GTL Solvent GS 2735

Version 2.0 Revision Date 27.04.2018 Print Date 05.09.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : GTL Solvent GS 2735

Product code : Q6529

Registration number : 01-2120086661-52-0000

Synonyms: Hydrocarbons C16-C22, n-alkanes, isoalkanes, <2%

aromatics

CAS-No. : 2170468-39-8 EC-No. : 942-086-0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Solvent.

Substance/Mixture Please refer to Ch16 for the registered uses under REACH.

Uses advised against : This product must not be used in applications other than the

above without first seeking the advice of the supplier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : Shell Chemicals Europe B.V.

PO Box 2334

3000 CH Rotterdam

Netherlands

Contact person : Shell Chemicals South East Europe

Telephone : +30 210 9895 700 +31 (0)10 441 5137 / +31 (0)10 441 5191 Telefax : +30 210 9895 744 +31 (0)20 716 8316 / +31 (0)20 713 9230

Email Contact for Safety Data : sccmsds@shell.com

Sheet

1.4 Emergency telephone number

+44 (0) 1235 239 670

Отрова център: +359 2 9154 409

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters

airways.

2.2 Label elements

1 / 21 800010023138 BG

Version 2.0 Revision Date 27.04.2018 Print Date 05.09.2022

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

Signal word : Danger

Hazard statements : PHYSICAL HAZARDS:

Not classified as a physical hazard

according to CLP criteria. HEALTH HAZARDS:

H304 May be fatal if swallowed and enters

airwavs.

ENVIRONMENTAL HAZARDS:

Not classified as environmental hazard

according to CLP criteria.

Supplemental Hazard

Statements

EUH066

Repeated exposure may cause skin

dryness or cracking.

Precautionary statements : Prevention:

P243 Take precautionary measures against static

discharge.

Response:

P301 + P310 IF SWALLOWED: Immediately call a

POISON CENTER/doctor.

P331 Do NOT induce vomiting.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to

appropriate waste site or reclaimer in accordance with local and national

regulations.

2.3 Other hazards

The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

May form flammable/explosive vapour-air mixture.

This material is a static accumulator.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable airvapour mixtures can occur.

Repeated exposure may cause skin dryness or cracking.

SECTION 3: Composition/information on ingredients

3.1 Substances

2 / 21 800010023138 BG

Version 2.0 Revision Date 27.04.2018 Print Date 05.09.2022

Hazardous components

Chemical name	CAS-No. EC-No.	Concentration [%]
Alkanes, C16-C22-branched	2170468-39-8	<= 100
and linear	942-086-0	

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Not expected to be a health hazard when used under normal

conditions.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

If inhaled : No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Flush exposed area with

water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.

In case of eye contact : Flush eye with copious quantities of water.

Remove contact lenses, if present and easy to do. Continue

rinsina.

If persistent irritation occurs, obtain medical attention.

If swallowed Call emergency number for your location / facility.

If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : If material enters lungs, signs and symptoms may include

coughing, choking, wheezing, difficulty in breathing, chest

congestion, shortness of breath, and/or fever.

Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Potential for chemical pneumonitis.

Call a doctor or poison control center for guidance.

Version 2.0 Revision Date 27.04.2018 Print Date 05.09.2022

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon

dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing

media

Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Clear fire area of all non-emergency personnel. Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Flammable vapours may be present even at temperatures below the flash point. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Will float and can be reignited on surface water.

5.3 Advice for firefighters

Special protective equipment

for firefighters

: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

Specific extinguishing

methods

Further information

: Standard procedure for chemical fires.

: Keep adjacent containers cool by spraying with water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Observe all relevant local and international regulations.

Notify authorities if any exposure to the general public or the

environment occurs or is likely to occur.

Local authorities should be advised if significant spillages

cannot be contained.

6.1.1 For non emergency personnel: Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or

unprotected personnel.

Do not breathe fumes, vapour. Do not operate electrical equipment. 6.1.2 For emergency responders:

Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or

unprotected personnel.

Do not breathe fumes, vapour.

Version 2.0 Revision Date 27.04.2018 Print Date 05.09.2022

Do not operate electrical equipment.

6.2 Environmental precautions

Environmental precautions

: Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.

Monitor area with combustible gas indicator.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up

: For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely

Ventilate contaminated area thoroughly.

If contamination of site occurs remediation may require

specialist advice.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet... For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

General Precautions : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For quidance on selection of personal protective equipment see

Chapter 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine

appropriate controls for safe handling, storage and disposal of this material.

Ensure that all local regulations regarding handling and

storage facilities are followed.

Version 2.0 Revision Date 27.04.2018 Print Date 05.09.2022

7.1 Precautions for safe handling

Advice on safe handling : Avoid inhaling vapour and/or mists.

Avoid contact with skin, eyes and clothing.

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Bulk storage tanks should be diked (bunded).

When using do not eat or drink.

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Product Transfer : Even with proper grounding and bonding, this material can still

accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/s until fill pipe submerged to twice its diameter, then ≤ 7 m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or

handling operations.

Refer to guidance under Handling section.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Other data : Storage Temperature: Ambient.

Bulk storage tanks should be diked (bunded). Locate tanks away from heat and other sources of ignition. Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions. Must be stored in a diked (bunded) well- ventilated area, away from sunlight, ignition sources and other sources of heat. Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products which are not harmful or toxic to man or to the environment. Electrostatic charges will be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk. The vapours in the

GTL Solvent GS 2735

Version 2.0	Revision Date 27.04.2018	Print Date 05.09.2022
	head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.	
Packaging material	 Suitable material: For containers, or conta steel, stainless steel., For container paints zinc silicate paint. Unsuitable material: Avoid prolonged cont butyl or nitrile rubbers. 	, use epoxy paint,
Container Advice	Do not cut, drill, grind, weld or perform sim near containers.	nilar operations on or
7.3 Specific end use(s)		
Specific use(s)	 Please refer to Ch16 and/or the annexes f uses under REACH. 	or the registered
	See additional references that provide safe for liquids that are determined to be static American Petroleum Institute 2003 (Protect Ignitions Arising out of Static, Lightning an National Fire Protection Agency 77 (Recon Static Electricity). IEC/TS 60079-32-1: Electrostatic hazards	accumulators: ction Against d Stray Currents) or mmended Practices

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
RCP Aliphatic dearom. solvents 200 - 250		TWA	1.050 mg/m3	EU HSPA

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Version 2.0 Revision Date 27.04.2018 Print Date 05.09.2022

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.isp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

8.2 Exposure controls

Engineering measures The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Eve washes and showers for emergency use.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

: If material is handled such that it could be splashed into eyes, Eye protection

> protective evewear is recommended. Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of

> gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile

Version 2.0 Revision Date 27.04.2018 Print Date 05.09.2022

> rubber gloves. Incidental contact/Splash protection: PVC. neoprene or nitrile rubber gloves For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Skin and body protection

Skin protection is not required under normal conditions of use. For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure. If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.

Protective clothing approved to EU Standard EN14605.

Wear antistatic and flame retardant clothing, if a local risk assessment deems it so.

Respiratory protection

: If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. If air-filtering respirators are suitable for conditions of use: Select a filter suitable for the combination of organic gases and vapours and particles meeting EN14387 and EN143 [Filter type A/P for use against certain organic gases and vapours with a boiling point >65°C (149°F) and for use against particles].

Version 2.0 Revision Date 27.04.2018 Print Date 05.09.2022

Thermal hazards : Not applicable

Hygiene measures : Wash hands before eating, drinking, smoking and using the

> toilet. Launder contaminated clothing before re-use. Do not ingest. If swallowed then seek immediate medical assistance.

Environmental exposure controls

General advice : Take appropriate measures to fulfil the requirements of

relevant environmental protection legislation. Avoid

contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water.

Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local

environmental legislation.

Information on accidental release measures are to be found in

section 6.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

: Data not available Colour

Odour : odourless

Odour Threshold : Data not available

Ηq Not applicable

: Data not available Melting / freezing point

: 283 - 360 °C Boiling point/boiling range

Flash point : 143 °C

Evaporation rate : Data not available

Flammability (solid, gas) : Not applicable

Upper explosion limit : 7 %(V)

Regulation 1907/2006/EC

GTL Solvent GS 2735

Version 2.0 Revision Date 27.04.2018 Print Date 05.09.2022

Lower explosion limit : 0,5 %(V)

Vapour pressure : Data not available
Relative vapour density : Data not available
Relative density : Data not available
Density : < 0,8 g/cm3 (20 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: Data not available

Auto-ignition temperature : :

200 °C

Decomposition temperature : Data not available

Viscosity

Viscosity, dynamic : Data not available
Viscosity, kinematic : Data not available
Explosive properties : Not classified

Oxidizing properties : Data not available

9.2 Other information

Conductivity: < 100 pS/m

The conductivity of this material makes it a static

accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semiconductive if its conductivity is below 10,000 pS/m., Whether a liquid is nonconductive or semiconductive, the precautions are

the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid

Molecular weight : Data not available

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

GTL Solvent GS 2735

Version 2.0 Revision Date 27.04.2018 Print Date 05.09.2022

No hazardous reaction is expected when handled and stored according to provisions. Stable under normal conditions of use.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.

In certain circumstances product can ignite due to static

electricity.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

10.6 Hazardous decomposition products

Hazardous decomposition

products

: Hazardous decomposition products are not expected to form

during normal storage.

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this

material undergoes combustion or thermal or oxidative

degradation.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Basis for assessment : Information given is based on product testing, and/or similar

products, and/or components.

exposure

Information on likely routes of : Exposure may occur via inhalation, ingestion, skin absorption,

skin or eye contact, and accidental ingestion.

Acute toxicity

Product:

: LD50 Rat: > 5000 mg/kg Acute oral toxicity

Remarks: Low toxicity:

Based on available data, the classification criteria are not met.

: Remarks: LC50 greater than near-saturated vapour Acute inhalation toxicity

concentration.

Low toxicity if inhaled.

Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 Rabbit: > 2000 mg/kg

12 / 21 800010023138 BG

Regulation 1907/2006/EC

GTL Solvent GS 2735

Version 2.0 Revision Date 27.04.2018 Print Date 05.09.2022

Remarks: Low toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis., Not irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: Not irritating to eye.

Respiratory or skin sensitisation

Product:

Remarks: Not a sensitiser., Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
Alkanes, C16-C22-branched and linear	No carcinogenicity classification.

Reproductive toxicity

Product:

:

Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair fertility.

STOT - single exposure

Product:

GTL Solvent GS 2735

Version 2.0 Revision Date 27.04.2018 Print Date 05.09.2022

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Further information

Product:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

Summary on evaluation of the CMR properties

Germ cell mutagenicity-

Assessment

: This product does not meet the criteria for classification in

categories 1A/1B.

Carcinogenicity -

Assessment

: This product does not meet the criteria for classification in

categories 1A/1B.

Reproductive toxicity -

Assessment

: This product does not meet the criteria for classification in

categories 1A/1B.

SECTION 12: Ecological information

12.1 Toxicity

: Incomplete ecotoxicological data are available for this product. Basis for assessment

> The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.

Product:

Toxicity to fish (Acute

: LL50 : > 100 mg/l

toxicity)

Remarks: Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to crustacean (Acute

toxicity)

: EL50: > 100 mg/l

Remarks: Practically non toxic:

Based on available data, the classification criteria are not met.

Regulation 1907/2006/EC

GTL Solvent GS 2735

Version 2.0 Revision Date 27.04.2018 Print Date 05.09.2022

Toxicity to algae/aquatic plants (Acute toxicity)

: EL50: > 100 mg/l Remarks: Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic

toxicity)

: Remarks: Data not available

Toxicity to crustacean

: Remarks: Data not available

(Chronic toxicity)

Toxicity to microorganisms

: IC50: > 100 mg/l

(Acute toxicity)

Remarks: Practically non toxic:

Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: Oxidises rapidly by photo-chemical reactions in air.,

Readily biodegradable.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Has the potential to bioaccumulate.

Partition coefficient: n-

octanol/water

: Remarks: Data not available

12.4 Mobility in soil

Product:

: Remarks: Floats on water., If it enters soil, it will adsorb to soil Mobility

particles and will not be mobile.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : The substance does not fulfill all screening criteria for

persistence, bioaccumulation and toxicity and hence is not

considered to be PBT or vPvB.

12.6 Other adverse effects

Product:

Additional ecological

information

: Does not have ozone depletion potential.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

15 / 21 800010023138

BG

Version 2.0	Revision Date 27.04.2018	Print Date 05.09.2022
Product	: Recover or recycle if possible.	

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water courses

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be complied with.

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard. Do not puncture,

cut or weld uncleaned drums.

Send to drum recoverer or metal reclaimer.

Comply with any local recovery or waste disposal regulations.

SECTION 14: Transport information

14.1 UN number

ADN : Not regulated as a dangerous good ADR : Not regulated as a dangerous good RID : Not regulated as a dangerous good IMDG : Not regulated as a dangerous good IATA : Not regulated as a dangerous good

14.2 Proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good

GTL Solvent GS 2735

Version 2.0 Revision Date 27.04.2018 Print Date 05.09.2022

IMDG : Not regulated as a dangerous good IATA : Not regulated as a dangerous good

14.5 Environmental hazards

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Chapter 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category : Not applicable
Ship type : Not applicable
Product name : Not applicable
Special precautions : Not applicable

Additional Information: This product may be transported under nitrogen blanketing.

Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a

confined space entry.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation

(Annex XIV)

: Product is not subject to Authorisation under REACH.

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: This product does not contain

(Regulation (EC) No

1907/2006 (REACH), Article 57).

substances of very high concern

Other regulations : The regulatory information is not intended to be

comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

DSL : Listed EINECS : Listed

TSCA : Not listed on TSCA

15.2 Chemical safety assessment

Version 2.0 Revision Date 27.04.2018 Print Date 05.09.2022

A Chemical Safety Assessment was performed for all substances of this product.

SECTION 16: Other information

Abbreviations and Acronyms

The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial Hygienists

ADR = European Agreement concerning the International

Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut fur Normung
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission

EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and

Toxicology Of Chemicals

ECHA = European Chemicals Agency

EINECS = The European Inventory of Existing Commercial

Chemical Substances

EL50 = Effective Loading fifty

ENCS = Japanese Existing and New Chemical Substances Inventory

EWC = European Waste Code

GHS = Globally Harmonised System of Classification and

Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IC50 = Inhibitory Concentration fifty

IL50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous Goods

INV = Chinese Chemicals Inventory

IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables

KECI = Korea Existing Chemicals Inventory

LC50 = Lethal Concentration fifty

LD50 = Lethal Dose fifty per cent.

LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading

LL50 = Lethal Loading fifty

MARPOL = International Convention for the Prevention of

Pollution From Ships

Version 2.0 Revision Date 27.04.2018 Print Date 05.09.2022

> NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level

OE HPV = Occupational Exposure - High Production Volume

PBT = Persistent, Bioaccumulative and Toxic

PICCS = Philippine Inventory of Chemicals and Chemical Substances

PNEC = Predicted No Effect Concentration

REACH = Registration Evaluation And Authorisation Of

Chemicals

RID = Regulations Relating to International Carriage of

Dangerous Goods by Rail SKIN_DES = Skin Designation STEL = Short term exposure limit

TRA = Targeted Risk Assessment

TSCA = US Toxic Substances Control Act

TWA = Time-Weighted Average

vPvB = very Persistent and very Bioaccumulative

Further information

Other information

: The eSDS(s) received to date have been reviewed for the registered components in this mixture. The advice provided in the body of this SDS covers all necessary Risk Management Measures.

For Industry guidance and tools on REACH please visit the CEFIC website at http://cefic.org/Industry-support. The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

A vertical bar (|) in the left margin indicates an amendment from the previous version.

This product is classified as H304 (May be fatal if swallowed and enters airways). The risk relates to potential for aspiration. The risk arising from aspiration hazard is solely related to the physico-chemical properties of the substance. The risk can therefore be controlled by implementing risk management measures tailored to this specific hazard and included within Chapter 8 of the SDS. An exposure scenario is not presented.

This product is classified as R66 / EUH066 (Repeated exposure may cause skin dryness or cracking). The risk relates to the potential for repeated or prolonged dermal contact. The risk arising from contact is solely related to the physico-chemical properties of the substance. The risk can therefore be controlled by implementing risk management measures tailored to this specific hazard and included within Chapter 8 of the SDS. An exposure scenario is not presented.

There has been a significant change in the required exposure controls/personal protection requirements in section 8.

GTL Solvent GS 2735

Version 2.0 Revision Date 27.04.2018 Print Date 05.09.2022

Sources of key data used to compile the Safety Data Sheet

: The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

Identified Uses according to the Use Descriptor System

Uses - Worker

Title - Industrial

> Manufacture of substance Distribution of substance

Formulation & (re)packing of substances and mixtures

Uses in Coatings Use in Cleaning Agents

Lubricants

Metal working fluids / rolling oils

Functional Fluids Use in laboratories

Water treatment chemicals Polymer processing Mining chemicals

Use in Oil and Gas field drilling and production operations

Uses - Worker

- Professional Title

> Uses in Coatings Use in Cleaning Agents

Lubricants

Metal working fluids / rolling oils Use as binders and release agents

Use as a fuel **Functional Fluids** Use in laboratories

Water treatment chemicals Use in Agrochemicals uses

Uses - Consumer

- Consumer Title

> **Uses in Coatings** Use in Cleaning Agents

Lubricants Use as a fuel

Use in Agrochemicals uses Other Consumer Uses

Regulation 1907/2006/EC

GTL Solvent GS 2735

Version 2.0 Revision Date 27.04.2018 Print Date 05.09.2022

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.