Prepared according to GB/T 16483, GB/T 17519

NEODOL 25-7

800001034100

Initial release date: 2005.12.05

Version 5.0 Revision Date 2025.02.28 Print Date 2025.03.07

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : NEODOL 25-7

Product code : V2453, V2668

Synonyms : Alcohols, C12-15, ethoxylated

Other means of identification : 68002-97-1 (Alcohols, C10-16, Ethoxylated)

Manufacturer or supplier's details

Supplier :

SHELL EASTERN CHEMICALS (S)

A REGISTERED BUSINESS OF SHELL EASTERN

TRADING (PTE) LTD (UEN:198902087C)

9 North Buona Vista Drive, #07-01

The Metropolis Tower 1 Singapore 138588

Singapore

Telephone : +65 6384 8269 Telefax : +65 6384 8454

Contact for Safety Data : If you have any enquiries about the content of this SDS

Sheet Sheet

please email sccmsds@shell.com 如果您有关于该SDS内容的

任何质询,请发电邮联系 sccmsds@shell.com

Emergency telephone : +86-532-83889090

number

Recommended use of the chemical and restrictions on use

Recommended use : Use as a surfactant in various applications

Restrictions on use : This product must not be used in applications other than the

above without first seeking the advice of the supplier.

This product must not be used in applications other than those

listed in Section 1 without first seeking the advice of the

supplier.

Other information : NEODOL is a trademark owned by Shell Trademark

Management B.V. and Shell Brands Inc. and used by affiliates

of Royal Dutch Shell plc.

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Hazy to semi-solid liquid.
Colour	Data not available

Prepared according to GB/T 16483, GB/T 17519

NEODOL 25-7

800001034100 Initial release date: 2005.12.05

Version 5.0 Revision Date 2025.02.28 Print Date 2025.03.07

Odour	mild
Health Hazards	Harmful if swallowed. May be harmful in contact with skin. Causes serious eye damage.
Safety Hazards	Not classified as flammable but will burn.
Environmental Hazards	Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

GHS Classification

Acute toxicity (Oral) : Category 4 Acute toxicity (Dermal) : Category 5 Serious eye damage : Category 1 Short-term (acute) aquatic Category 1

ong-term (chronic) aquatic Category 2

nazard

GHS label elements

Hazard pictograms Signal word Danger

PHYSICAL HAZARDS: Hazard statements

Not classified as a physical hazard under GHS criteria.

HEALTH HAZARDS: H302 Harmful if swallowed.

H313 May be harmful in contact with skin. H318 Causes serious eye damage. **ENVIRONMENTAL HAZARDS:** H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention:

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

P273 Avoid release to the environment.

Response:

P301 + P312 IF SWALLOWED: Call a POISON

CENTER/doctor if you feel unwell.

P330 Rinse mouth.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

Prepared according to GB/T 16483, GB/T 17519

NEODOL 25-7

800001034100 Initial release date: 2005.12.05

Version 5.0

Revision Date 2025.02.28

Print Date 2025.03.07

P310 Immediately call a POISON CENTER/doctor.
P391 Collect spillage.

Storage:
No precautionary phrases.

Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

Repeated exposure may cause skin dryness or cracking.

Physical and chemical hazards	Not classified as flammable but will burn.
Health Hazards	Inhalation: No specific hazards under normal use conditions. Skin: May be harmful in contact with skin. Causes mild skin irritation. Repeated exposure may cause skin dryness or cracking. Eyes: Causes serious eye damage. Ingestion: Harmful if swallowed.
Environmental Hazards	Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

3.1 Substances

Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
C12-15 Alcohol Ethoxylate	68131-39-5	Acute Tox.4; H302 Acute Tox.5; H313 Eye Dam.1; H318 Aquatic Acute1; H400 Aquatic Chronic2; H411	100

For explanation of abbreviations see section 16.

Prepared according to GB/T 16483, GB/T 17519

NEODOL 25-7

800001034100

Initial release date: 2005.12.05

Version 5.0 Revision Date 2025.02.28 Print Date 2025.03.07

4. FIRST AID MEASURES

General advice : Not expected to be a health hazard when used under normal

conditions.

If inhaled : No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Immediately flush skin with

> large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If needed, transport

to the nearest medical facility for additional treatment.

: Immediately flush eye(s) with plenty of water. In case of eye contact

Remove contact lenses, if present and easy to do. Continue

rinsing.

Transport to the nearest medical facility for additional

treatment.

If swallowed : Do not induce vomiting. If victim is alert, rinse mouth and

drink 1/2 to 1 glass of water to help dilute the material. Do not give liquids to a drowsy, convulsing, or unconscious person. Transport to nearest medical facility for additional treatment.

Most important symptoms and effects, both acute and

delayed

: Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision. Skin irritation signs and symptoms may include a burning

sensation, redness, swelling, and/or blisters.

Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.

Not considered to be an inhalation hazard under normal

conditions of use.

Possible respiratory irritation signs and symptoms may include

a temporary burning sensation of the nose and throat,

coughing, and/or difficulty breathing.

Skin irritation signs and symptoms may include a burning

sensation, redness, swelling, and/or blisters.

Corrosive to eyes.

Contact can cause severe eye damage including chemical burns, pain, clouding of the eye surface, inflammation of the

eye, and may result in permanent loss of vision.

Swallowing of corrosive chemicals may cause immediate pain and burning in the mouth, throat, and stomach followed by

vomiting and diarrhea.

Burns and tearing of the esophagus and stomach are

possible.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

Prepared according to GB/T 16483, GB/T 17519

NEODOL 25-7

800001034100

Initial release date: 2005.12.05

Version 5.0 Revision Date 2025.02.28 Print Date 2025.03.07

appropriate personal protective equipment according to the

incident, injury and surroundings.

Notes to physician : IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!

Call a doctor or poison control center for guidance.

Treat symptomatically.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam, water spray or fog. Dry chemical

powder, carbon dioxide, sand or earth may be used for small

fires only.

Unsuitable extinguishing

media

: None

Specific hazards during

firefighting

: Carbon monoxide may be evolved if incomplete combustion

occurs.

Specific extinguishing

methods

: Standard procedure for chemical fires.

Clear fire area of all non-emergency personnel.

Keep adjacent containers cool by spraying with water.

Special protective equipment

for firefighters

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in

a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures :

Observe all relevant local and international regulations.

Notify authorities if any exposure to the general public or the

environment occurs or is likely to occur.

Local authorities should be advised if significant spillages

cannot be contained.

: Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see

Section 13 of this Safety Data Sheet. Stay upwind and keep out of low areas. Be ready for fire or possible exposure.

Environmental precautions : Prevent from spreading or entering into drains, ditches or

rivers by using sand, earth, or other appropriate barriers.
Use appropriate containment to avoid environmental

Prepared according to GB/T 16483, GB/T 17519

NEODOL 25-7

800001034100

Initial release date: 2005.12.05

Version 5.0 Revision Date 2025.02.28 Print Date 2025.03.07

contamination.

Ventilate contaminated area thoroughly.

Methods and materials for containment and cleaning up

: For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

Additional advice : For guidance on selection of personal protective equipment

see Section 8 of this Safety Data Sheet.

For guidance on disposal of spilled material see Section 13 of

this Safety Data Sheet.

7. HANDLING AND STORAGE

Handling

General Precautions : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine

appropriate controls for safe handling, storage and disposal of

this material.

Ensure that all local regulations regarding handling and

storage facilities are followed.

Advice on safe handling : Avoid contact with skin, eyes and clothing.

Do not empty into drains.

Avoidance of contact : Copper.

Copper alloys.

Strong oxidising agents.

Aluminum

Product Transfer : Keep containers closed when not in use. Refer to guidance

under Handling section.

Storage

Conditions for safe storage : Refer to section 15 for any additional specific legislation

covering the packaging and storage of this product.

Other data : Tanks should be fitted with heating coils in areas where the

ambient temperatures are below the recommended product

Prepared according to GB/T 16483, GB/T 17519

NEODOL 25-7

800001034100 Initial release date: 2005.12.05

Version 5.0	Revision Date 2025.02.28	Print Date 2025.03.07	
	not exceed 100 °C. Bulk storage tanks should be diked Vapours from tanks should not be r Breathing losses during storage sh suitable vapour treatment system. Nitrogen blanket recommended for m3 or higher). Insulation (lagging) will minimize he ambient temperature. Tanks should be fitted with heating ambient conditions can result in ha	handling temperatures. Heating coil skin temperatures should not exceed 100 °C. Bulk storage tanks should be diked (bunded). Vapours from tanks should not be released to atmosphere. Breathing losses during storage should be controlled by a suitable vapour treatment system. Nitrogen blanket recommended for large tanks (capacity 100 m3 or higher). Insulation (lagging) will minimize heat loss in areas of low	
Packaging material	: Suitable material: Stainless steel., l Unsuitable material: Aluminum, Co		
Container Advice	 Containers, even those that have be explosive vapours. Do not cut, drill, similar operations on or near contains. 	grind, weld or perform	
Specific use(s)	: Not applicable		
	Ensure that all local regulations reg storage facilities are followed.	jarding handling and	

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

GBZ 159 Specifications of air sampling for hazardous substances monitoring in the workplace.

GBZ/T 160 Determination of toxic substances in the air of workplace.

GBZ/T 192 Determination of dust in the air of workplace.

GBZ/T 300 Determination of toxic substances in the air of workplace

Engineering measures : Adequate ventilation to control airborne concentrations below

the exposure guidelines/limits.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

Prepared according to GB/T 16483, GB/T 17519

NEODOL 25-7

800001034100

Initial release date: 2005.12.05

Version 5.0 Revision Date 2025.02.28 Print Date 2025.03.07

Eye washes and showers for emergency use.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

General Information

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Do not ingest. If swallowed, then seek immediate medical assistance.

Personal protective equipment

Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection

: If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.

Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use: Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C

(149°F)].

Hand protection Remarks

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile

Prepared according to GB/T 16483, GB/T 17519

NEODOL 25-7

800001034100 Initial release date: 2005.12.05

Version 5.0 Revision Date 2025.02.28 Print Date 2025.03.07

> rubber gloves. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eve protection : Wear goggles for use against liquids and gas. Wear full face shield if splashes are likely to occur.

: Skin protection is not required under normal conditions of use. Skin and body protection

For prolonged or repeated exposures use impervious clothing

over parts of the body subject to exposure.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard,

and provide employee skin care programmes.

Thermal hazards : Not applicable

Hygiene measures : Wash hands before eating, drinking, smoking and using the

toilet.

Launder contaminated clothing before re-use.

Do not ingest. If swallowed, then seek immediate medical assistance.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.

Practice good housekeeping.

Define procedures for safe handling and maintenance of

controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this

product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective

equipment, local exhaust ventilation.

Prepared according to GB/T 16483, GB/T 17519

NEODOL 25-7

800001034100 Initial release date: 2005.12.05

Version 5.0 Revision Date 2025.02.28 Print Date 2025.03.07

Drain down system prior to equipment break-in or

maintenance.

Retain drain downs in sealed storage pending disposal or

subsequent recycle.

10

Environmental exposure controls

General advice : Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

vapour.

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local

environmental legislation.

Information on accidental release measures are to be found in

section 6.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Hazy to semi-solid liquid.

Colour : Data not available

Odour : mild

Odour Threshold : Data not available

pH : 6.8

Melting point/freezing point : 12 °C / 54 °F

Boiling point/boiling range : 260 °C / 500 °F

Flash point : 186.1 °C / 367.0 °F

Evaporation rate : Data not available

Flammability (solid, gas) : Not applicable

Upper explosion limit : Data not available
Lower explosion limit : Data not available

Vapour pressure : < 0.1 hPa (37.8 °C / 100.0 °F)

Relative vapour density : 17.0

Relative density : 0.965 (122.0 °C / 251.6 °F)

Method: ASTM D4052

Density : 970 kg/m3 (40 $^{\circ}$ C / 104 $^{\circ}$ F)

Method: ASTM D4052

Solubility(ies)

Water solubility : 100 g/l Complete, may form gel.

Prepared according to GB/T 16483, GB/T 17519

NEODOL 25-7

800001034100 Initial release date: 2005.12.05

Version 5.0 Revision Date 2025.02.28 Print Date 2025.03.07

Solubility in other solvents : Data not available

Partition coefficient: n-

octanol/water

: log Pow: 3

Auto-ignition temperature : Data not available

Decomposition temperature : Data not available

Viscosity

Viscosity, dynamic : Not applicable (20 °C / 68 °F)

Viscosity, dynamic 50 mPa.s (33 °C / 91 °F)

Viscosity, kinematic : 36 mm2/s (40 °C / 104 °F)

Method: ASTM D445

Particle characteristics

Particle size : Data not available

Explosive properties : Not applicable

Oxidizing properties : Data not available

Surface tension : Data not available

Conductivity: > 10,000 pS/m

A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be

a static accumulator.

Molecular weight : Data not available

10. STABILITY AND REACTIVITY

Reactivity : Stable at normal ambient temperature and pressure., May

oxidise in the presence of air.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: None known.

Conditions to avoid : Extremes of temperature and direct sunlight.

Product cannot ignite due to static electricity.

Incompatible materials : Copper.

Copper alloys.

Strong oxidising agents.

Prepared according to GB/T 16483, GB/T 17519

NEODOL 25-7

800001034100

Initial release date: 2005.12.05

Version 5.0 Revision Date 2025.02.28 Print Date 2025.03.07

Aluminum

Hazardous decomposition

products

: None expected under normal use conditions.

11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on product testing, and/or similar

products, and/or components.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for

individual component(s).

Exposure routes : Exposure may occur via inhalation, ingestion, skin absorption,

skin or eye contact, and accidental ingestion.

Acute toxicity

Components:

C12-15 Alcohol Ethoxylate:

Acute oral toxicity : LD50 Rat: > 300 - <= 2000 mg/kg

Remarks: Harmful if swallowed.

Acute inhalation toxicity : Remarks: Low toxicity by inhalation.

Acute dermal toxicity : LD50 Rabbit: > 2000 - <= 5000 mg/kg

Remarks: May be harmful in contact with skin.

Skin corrosion/irritation

Components:

C12-15 Alcohol Ethoxylate:

Remarks: Causes mild skin irritation., Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Components:

C12-15 Alcohol Ethoxylate:

Remarks: Causes serious eye damage.

Respiratory or skin sensitisation

Components:

C12-15 Alcohol Ethoxylate:

Remarks: Not a sensitiser.

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Components:

Prepared according to GB/T 16483, GB/T 17519

NEODOL 25-7

800001034100

Initial release date: 2005.12.05

Version 5.0 Revision Date 2025.02.28 Print Date 2025.03.07

C12-15 Alcohol Ethoxylate:

: Remarks: Non mutagenic, Based on available data, the

classification criteria are not met.

Carcinogenicity

Components:

C12-15 Alcohol Ethoxylate:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
C12-15 Alcohol Ethoxylate	No carcinogenicity classification.

Reproductive toxicity

Components:

C12-15 Alcohol Ethoxylate:

:

Remarks: Does not impair fertility., Not a developmental

toxicant.

STOT - single exposure

Components:

C12-15 Alcohol Ethoxylate:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Components:

C12-15 Alcohol Ethoxylate:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Components:

C12-15 Alcohol Ethoxylate:

Not an aspiration hazard.

Further information

Components:

C12-15 Alcohol Ethoxylate:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

Prepared according to GB/T 16483, GB/T 17519

NEODOL 25-7

800001034100

Initial release date: 2005.12.05

Version 5.0 Revision Date 2025.02.28 Print Date 2025.03.07

12. ECOLOGICAL INFORMATION

Basis for assessment : Information given is based on product testing.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for

individual component(s).

Ecotoxicity

Components:

C12-15 Alcohol Ethoxylate :

Toxicity to fish (Acute : Remarks: Toxic

toxicity) LC/EC/IC50 >1 - <=10 mg/l

Toxicity to crustacean (Acute

toxicity)

: Remarks: Very toxic. LC/EC/IC50 < 1 mg/l

Toxicity to algae/aquatic : Remarks: Very toxic. plants (Acute toxicity) : LC/EC/IC50 < 1 mg/l

M-Factor (Short-term (acute) : 1

aquatic hazard)

Toxicity to microorganisms

(Acute toxicity)

: Remarks: LC/EC/IC50 > 100 mg/l

: Remarks: NOEC/NOEL > 0.1 - <=1.0 mg/l

Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic

toxicity)
Toxicity to

Toxicity to : Remarks: NOEC/NOEL > 0.1 - <=1.0 mg/l

crustacean(Chronic toxicity)

Persistence and degradability

Components:

C12-15 Alcohol Ethoxylate:

Biodegradability : Biodegradation: 63 %

Exposure time: 28 d

Method: OECD Test Guideline 301F

GLP: yes

Remarks: Readily biodegradable.

Bioaccumulative potential

Product:

Partition coefficient: n-

: log Pow: 3

octanol/water Components:

C12-15 Alcohol Ethoxylate:

Bioaccumulation : Remarks: Bioaccumulation is unlikely to occur due to

metabolism and excretion.

Data estimated using read-across from similar substances

Mobility in soil

Prepared according to GB/T 16483, GB/T 17519

NEODOL 25-7

800001034100

Initial release date: 2005.12.05

Version 5.0 Revision Date 2025.02.28 Print Date 2025.03.07

Components:

C12-15 Alcohol Ethoxylate:

Mobility : Remarks: Dissolves in water., If the product enters soil, one or

more constituents will or may be mobile and may contaminate

groundwater.

Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses.

Waste product should not be allowed to contaminate soil or

water.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or

national requirements and must be complied with.

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Residues may cause an explosion hazard. Do not puncture, cut, or weld uncleaned drums. Send to drum recoverer or metal reclaimer.

Local legislation

Remarks : If potential for exposure exists refer to Section 8 for specific

personal protective equipment.

14. TRANSPORT INFORMATION

International Regulations

ADR

UN number : 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(C12-15 Alcohol Ethoxylate)

Class : 9
Packing group : III
Labels : 9

Prepared according to GB/T 16483, GB/T 17519

NEODOL 25-7

800001034100

Initial release date: 2005.12.05

Version 5.0 Revision Date 2025.02.28 Print Date 2025.03.07

Hazard Identification Number : 90 Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3082

Proper shipping name : Environmentally hazardous substances, liquid, n.o.s.

(C12-15 Alcohol Ethoxylate)

Class : 9
Packing group : III
Labels : 9

IMDG-Code

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(C12-15 Alcohol Ethoxylate)

Class : 9
Packing group : III
Labels : 9
Marine pollutant : yes

Maritime transport in bulk according to IMO instruments

Pollution category : Y Ship type : 2

Product name : Alcohol (C12-C16) poly (7-19) ethoxylates

Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

Additional Information: This product may be transported under nitrogen blanketing.

Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a

confined space entry.

Transport in bulk according to Annex II of Marpol and the IBC

Code

15. REGULATORY INFORMATION

National regulatory information

Rotterdam Convention (Prior Informed Consent)

Not applicable

Stockholm Convention (Persistent Organic Pollutants)

Not applicable

Law on the Prevention and Control of Occupational Diseases

The categories of occupational disease:

Not applicable

Occupational Disease Classification list:

Not applicable

Prepared according to GB/T 16483, GB/T 17519

NEODOL 25-7

800001034100

Initial release date: 2005.12.05

Version 5.0 Revision Date 2025.02.28 Print Date 2025.03.07

Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals : Not applicable

Identification of Major Hazard Installations for : Not applicable

Hazardous Chemicals (GB 18218)

Hazardous Chemicals for Priority Management under : Not applicable

SAWS

Regulations on Labour Protection in Workplaces where Toxic Substances are Used

Catalogue of Highly Toxic Chemicals : Not applicable

Regulation of Environmental Management on the First Import of Chemicals and the Import and Export of Toxic Chemicals

China Severely Restricted Toxic Chemicals for Import : Not applicable

and Export

Other international regulations

The components of this product are reported in the following inventories:

AIIC : Listed DSL : Listed : Listed **IECSC ENCS** : Listed **TSCA** : Listed KECI : Listed **PICCS** : Listed **NZIoC** : Listed TCSI : Listed

16. OTHER INFORMATION

Full text of H-Statements

H302 Harmful if swallowed.

H313 May be harmful in contact with skin.
H318 Causes serious eye damage.
H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. Acute toxicity

Aquatic Acute Short-term (acute) aquatic hazard Aquatic Chronic Long-term (chronic) aquatic hazard

Eye Dam. Serious eye damage

Abbreviations and Acronyms

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with

Prepared according to GB/T 16483, GB/T 17519

NEODOL 25-7

800001034100

Initial release date: 2005.12.05

Version 5.0 Revision Date 2025.02.28 Print Date 2025.03.07

x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System: GLP - Good Laboratory Practice: IARC - International Agency for Research on Cancer: IATA - International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC -New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG -Transportation of Dangerous Goods: TECI - Thailand Existing Chemicals Inventory: TSCA - Toxic Substances Control Act (United States): UN - United Nations: UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative: WHMIS - Workplace Hazardous Materials Information System

Further information

Training advice : Provide adequate information, instruction and training for

operators.

Other information : A vertical bar (|) in the left margin indicates an amendment

from the previous version.

Sources of key data used to compile the Safety Data

Sheet

: The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CN / EN