

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
2.0	08.10.2024	800001012715	Print Date 15.10.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name	: Pentane Blend 85/15
Product code	: Q1128
Unique Formula Identifier (UFI)	: JYY0-10UT-E00G-VTYU

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture	: Industrial Solvent. Please refer to section 16 and/or the annexes for the registered uses under REACH.
Uses advised against	: This product must not be used in applications other than the above without first seeking the advice of the supplier.  This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier	: <b>Shell Chemicals Europe B.V.</b> PO Box 2334 3000 CH Rotterdam Netherlands
Telephone	: +31 (0)10 441 5137 / +31 (0)10 441 5191
Telefax	: +31 (0)20 716 8316/ +31 (0)20 713 9230
Contact for Safety Data Sheet	: sccmsds@shell.com

#### 1.4 Emergency telephone number

Toxicological Information Center Address: Na Bojišti 1, 120 00 Prague 2, Czech Republic  
Telephone: +420 224 919 293 / +420 224 915 4  
+44 (0) 1235 239 670 (This telephone number is available 24 hours per day, 7 days per week)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 1	H224: Extremely flammable liquid and vapour.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters air-

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0	Revision Date: 08.10.2024	SDS Number: 800001012715	Date of last issue: 06.03.2023 Print Date 15.10.2024
----------------	------------------------------	-----------------------------	---

ways.

Specific target organ toxicity - single exposure, Category 3, Narcotic effects

H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard, Category 2

H411: Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word :

Danger

Hazard statements :

PHYSICAL HAZARDS:  
H224 Extremely flammable liquid and vapour.  
HEALTH HAZARDS:  
H304 May be fatal if swallowed and enters airways.  
H336 May cause drowsiness or dizziness.  
ENVIRONMENTAL HAZARDS:  
H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements :

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements :

#### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P243 Take action to prevent static discharges.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P273 Avoid release to the environment.

#### Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P312 Call a POISON CENTER/ doctor if you feel unwell.

#### Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

#### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### 2.3 Other hazards

The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0      Revision Date: 08.10.2024      SDS Number: 800001012715      Date of last issue: 06.03.2023  
Print Date 15.10.2024

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

May form flammable/explosive vapour-air mixture.

This material is a static accumulator.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
pentane	109-66-0 203-692-4 601-006-00-1 01-2119459286-30	Flam. Liq. 1; H224 Asp. Tox. 1; H304 STOT SE 3; H336 (Narcotic effects) Aquatic Chronic 2; H411 EUH066	85
isopentane	78-78-4 201-142-8 601-085-00-2 01-2119475602-38	Flam. Liq. 1; H224 Asp. Tox. 1; H304 STOT SE 3; H336 Aquatic Chronic 2; H411	15

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General advice : Not expected to be a health hazard when used under normal conditions.

Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0	Revision Date: 08.10.2024	SDS Number: 800001012715	Date of last issue: 06.03.2023 Print Date 15.10.2024
----------------	------------------------------	-----------------------------	---

---

- |                         |  |
|-------------------------|--|
| If inhaled              | : Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.   |
| In case of skin contact | : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.<br>If persistent irritation occurs, obtain medical attention.  |
| In case of eye contact  | : Flush eye with copious quantities of water.<br>Remove contact lenses, if present and easy to do. Continue rinsing.<br>If persistent irritation occurs, obtain medical attention.   |
| If swallowed            | : Call emergency number for your location / facility.<br>If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.<br>If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing. |

### 4.2 Most important symptoms and effects, both acute and delayed

- |          |   |
|----------|---|
| Symptoms | : Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination.<br>Continued inhalation may result in unconsciousness and death.   |
|          | No specific hazards under normal use conditions.<br>Skin irritation signs and symptoms may include a burning sensation, redness, or swelling.   |
|          | No specific hazards under normal use conditions.<br>Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.  |
|          | If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.<br>If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing. |

### 4.3 Indication of any immediate medical attention and special treatment needed

- |           |   |
|-----------|---|
| Treatment | : Call a doctor or poison control center for guidance.<br>Potential for chemical pneumonitis.<br>Treat symptomatically. |
|-----------|---|

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
2.0	08.10.2024	800001012715	Print Date 15.10.2024

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use water in a jet.

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Clear fire area of all non-emergency personnel.  
Hazardous combustion products may include:  
A complex mixture of airborne solid and liquid particulates and gases (smoke).  
Carbon monoxide.  
Unidentified organic and inorganic compounds.  
Flammable vapours may be present even at temperatures below the flash point.  
The vapour is heavier than air, spreads along the ground and distant ignition is possible.  
Will float and can be reignited on surface water.

#### 5.3 Advice for firefighters

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

Specific extinguishing methods : Standard procedure for chemical fires.

Further information : Keep adjacent containers cool by spraying with water.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Observe all relevant local and international regulations.  
Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.  
Local authorities should be advised if significant spillages cannot be contained.  
6.1.1 For non emergency personnel:  
Avoid contact with skin, eyes and clothing.  
Isolate hazard area and deny entry to unnecessary or unprotected personnel.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0	Revision Date: 08.10.2024	SDS Number: 800001012715	Date of last issue: 06.03.2023 Print Date 15.10.2024
----------------	------------------------------	-----------------------------	---

Do not breathe fumes, vapour.  
Do not operate electrical equipment.  
6.1.2 For emergency responders:  
Avoid contact with skin, eyes and clothing.  
Isolate hazard area and deny entry to unnecessary or unprotected personnel.  
Do not breathe fumes, vapour.  
Do not operate electrical equipment.

### 6.2 Environmental precautions

Environmental precautions : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas indicator.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.  
For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.  
  
Ventilate contaminated area thoroughly.  
If contamination of site occurs remediation may require specialist advice.

### 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.,  
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Technical measures : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.  
Use the information in this data sheet as input to a risk as-

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0	Revision Date: 08.10.2024	SDS Number: 800001012715	Date of last issue: 06.03.2023 Print Date 15.10.2024
----------------	------------------------------	-----------------------------	---

- 
- assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.  
Ensure that all local regulations regarding handling and storage facilities are followed.
- Advice on safe handling : Avoid inhaling vapour and/or mists.  
Avoid contact with skin, eyes and clothing.  
Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.  
Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.  
Bulk storage tanks should be diked (bunded).  
When using do not eat or drink.
- The vapour is heavier than air, spreads along the ground and distant ignition is possible.
- Product Transfer : Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$  m/s until fill pipe submerged to twice its diameter, then  $\leq 7$  m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.
- Refer to guidance under Handling section.
- Hygiene measures : Wash hands before eating, drinking, smoking and using the toilet. Launder contaminated clothing before re-use. Do not ingest. If swallowed, then seek immediate medical assistance.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.
- Further information on storage stability : Storage Temperature:  
Ambient.
- Bulk storage tanks should be diked (bunded).  
Locate tanks away from heat and other sources of ignition.  
Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0      Revision Date: 08.10.2024      SDS Number: 800001012715      Date of last issue: 06.03.2023  
Print Date 15.10.2024

Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat. Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products which are not harmful or toxic to man or to the environment.

Electrostatic charges will be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.

The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.

Packaging material : Suitable material: For containers, or container linings use mild steel, stainless steel., For container paints, use epoxy paint, zinc silicate paint.  
Unsuitable material: Avoid prolonged contact with natural, butyl or nitrile rubbers.

Container Advice : Do not cut, drill, grind, weld or perform similar operations on or near containers.

### 7.3 Specific end use(s)

Specific use(s) : Please refer to section 16 and/or the annexes for the registered uses under REACH.

See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).  
IEC/TS 60079-32-1: Electrostatic hazards, guidance

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
pentane	109-66-0	TWA	1.000 ppm 3.000 mg/m <sup>3</sup>	CZ OEL
pentane		STEL	1.500 ppm 4.500 mg/m <sup>3</sup>	CZ OEL
pentane		TWA	1.000 ppm 3.000 mg/m <sup>3</sup>	2006/15/EC
Further information: Indicative				
isopentane	78-78-4	TWA	1.000 ppm 3.000 mg/m <sup>3</sup>	CZ OEL
isopentane		STEL	1.500 ppm	CZ OEL



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0      Revision Date: 08.10.2024      SDS Number: 800001012715      Date of last issue: 06.03.2023  
Print Date 15.10.2024

			4.500 mg/m3	
isopentane		TWA	1.000 ppm 3.000 mg/m3	2006/15/EC
Further information: Indicative				

### Biological occupational exposure limits

No biological limit allocated.

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
pentane	Workers	Dermal	Long-term systemic effects	432 mg/kg bw/day
pentane	Workers	Inhalation	Long-term systemic effects	3000 mg/m3
pentane	Consumers	Dermal	Long-term systemic effects	214 mg/kg bw/day
pentane	Consumers	Inhalation	Long-term systemic effects	643 mg/m3
pentane	Consumers	Oral	Long-term systemic effects	214 mg/kg bw/day
isopentane	Workers	Dermal	Long-term systemic effects	432 mg/kg bw/day
isopentane	Workers	Inhalation	Long-term systemic effects	3000 mg/m3
isopentane	Consumers	Dermal	Long-term systemic effects	214 mg/kg bw/day
isopentane	Consumers	Inhalation	Long-term systemic effects	643 mg/m3
isopentane	Consumers	Oral	Long-term systemic effects	214 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
pentane	Water	0,23 mg/l
pentane	Sediment	1,2 mg/kg
pentane	Soil	0,55 mg/kg wet weight
pentane	Sewage treatment plant	3,6 mg/l
isopentane	Water	0,25 mg/l
isopentane	Sediment	1,10 mg/kg
isopentane	Soil	0,55 mg/kg
isopentane	Sewage treatment plant	3,9 mg/l

## 8.2 Exposure controls

### Engineering measures

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.  
Use sealed systems as far as possible.  
Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.  
Local exhaust ventilation is recommended.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
2.0	08.10.2024	800001012715	Print Date 15.10.2024

Eye washes and showers for emergency use.  
Firewater monitors and deluge systems are recommended.  
Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.  
The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

### General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.  
Define procedures for safe handling and maintenance of controls.  
Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.  
Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.  
Drain down system prior to equipment break-in or maintenance.  
Retain drain downs in sealed storage pending disposal or for subsequent recycle.

### Personal protective equipment

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : Wear goggles for use against liquids and gas.  
Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0	Revision Date: 08.10.2024	SDS Number: 800001012715	Date of last issue: 06.03.2023 Print Date 15.10.2024
----------------	------------------------------	-----------------------------	---

- 
- resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.
- Skin and body protection** : Skin protection is not required under normal conditions of use.  
For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure.
- If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.  
Protective clothing approved to EU Standard EN14605.
- Wear antistatic and flame-retardant clothing, if a local risk assessment deems it so.
- Respiratory protection** : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.  
Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.  
If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type AX boiling point < 65°C (149°F)] meeting EN14387.
- Thermal hazards** : Not applicable

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Physical state** : Liquid.
- Colour** : colourless
- Odour** : Paraffinic
- Odour Threshold** : Data not available
- Melting / freezing point** : < -130 °C

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0	Revision Date: 08.10.2024	SDS Number: 800001012715	Date of last issue: 06.03.2023 Print Date 15.10.2024
----------------	------------------------------	-----------------------------	---

Boiling point/boiling range : 33 - 35 °C

### Flammability

Flammability (solid, gas) : Not applicable

### Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit /  
upper flammability limit : 7,8 %(V)

Lower explosion limit /  
Lower flammability limit : 1,3 %(V)

Flash point : -50 °C  
Method: IP 170

Auto-ignition temperature : 400 °C  
Method: ASTM E-659  
  
275 °C  
Method: DIN 51794

Decomposition temperature  
Decomposition temperature : Data not available

pH : Not applicable

### Viscosity

Viscosity, dynamic : Data not available

Viscosity, kinematic : 0,32 mm<sup>2</sup>/s (25 °C)  
Method: ASTM D445

### Solubility(ies)

Water solubility : < 0,05 g/l (25 °C)

Partition coefficient: n-  
octanol/water : log Pow: 3,4

Vapour pressure : Typical 61 kPa (20 °C)  
  
Typical 167 kPa (50 °C)

Relative density : Data not available

Density : 630 kg/m<sup>3</sup> (15 °C)  
Method: ASTM D4052

Relative vapour density : 2,5 (20 °C)

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0	Revision Date: 08.10.2024	SDS Number: 800001012715	Date of last issue: 06.03.2023 Print Date 15.10.2024
----------------	------------------------------	-----------------------------	---

---

### 9.2 Other information

Explosive properties	:	Not classified
Oxidizing properties	:	Data not available
Evaporation rate	:	1 Method: DIN 53170, di-ethyl ether=1  12 Method: ASTM D 3539, nBuAc=1
Conductivity	:	0,9 pS/m at 20 °C Method: ASTM D-4308 Low conductivity: < 100 pS/m, The conductivity of this material makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m., Whether a liquid is nonconductive or semi-conductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid
Surface tension	:	Data not available
Molecular weight	:	72 g/mol

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

### 10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions  
Stable under normal conditions of use.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

### 10.4 Conditions to avoid

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.  
  
In certain circumstances product can ignite due to static electricity.

### 10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0	Revision Date: 08.10.2024	SDS Number: 800001012715	Date of last issue: 06.03.2023 Print Date 15.10.2024
----------------	------------------------------	-----------------------------	---

### 10.6 Hazardous decomposition products

Hazardous decomposition products are not expected to form during normal storage. Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

#### Acute toxicity

##### Product:

Acute oral toxicity	: LD50 (Rat): > 5000 mg/kg Remarks: Low toxicity Based on available data, the classification criteria are not met.
Acute inhalation toxicity	: LC50 (Rat): > 20 mg/l Exposure time: 4 h Remarks: Low toxicity High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea.
Acute dermal toxicity	: Remarks: Low toxicity Based on available data, the classification criteria are not met.

##### Components:

##### **pentane:**

Acute oral toxicity	: LD50 (Rat, male and female): > 5.000 mg/kg Method: OECD Test Guideline 401 Remarks: Based on available data, the classification criteria are not met.
Acute inhalation toxicity	: LC50 (Rat, male and female): > 20 mg/l Exposure time: 4 h Test atmosphere: vapour Method: OECD Test Guideline 403 Remarks: Based on available data, the classification criteria are not met.

##### **isopentane:**

Acute oral toxicity	: LD 50 (Rat, male and female): > 5.000 mg/kg Method: OECD Test Guideline 401 Remarks: Based on available data, the classification criteria are not met.
---------------------	--

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
2.0	08.10.2024	800001012715	Print Date 15.10.2024

---

Acute inhalation toxicity : LD50 (Rat, male and female): > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
Remarks: Based on available data, the classification criteria are not met.

### Skin corrosion/irritation

#### Product:

Remarks : Not irritating to skin.  
Repeated exposure may cause skin dryness or cracking.

#### Components:

##### **pentane:**

Species : Rabbit  
Method : Test(s) equivalent or similar to OECD Test Guideline 404  
Remarks : Slightly irritating to skin.  
Insufficient to classify.

##### **isopentane:**

Species : Rabbit  
Method : Test(s) equivalent or similar to OECD Test Guideline 404  
Remarks : Slightly irritating.  
Insufficient to classify.

### Serious eye damage/eye irritation

#### Product:

Remarks : Not irritating to eye.

#### Components:

##### **pentane:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Remarks : Slightly irritating.  
Insufficient to classify.

##### **isopentane:**

Species : Rabbit  
Method : Test(s) equivalent or similar to OECD Test Guideline 405  
Remarks : Slightly irritating.  
Insufficient to classify.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
2.0	08.10.2024	800001012715	Print Date 15.10.2024

### Respiratory or skin sensitisation

#### Product:

Remarks : Not a sensitiser.  
Based on available data, the classification criteria are not met.

#### Components:

##### **pentane:**

Species : Guinea pig  
Method : OECD Test Guideline 406  
Remarks : Based on available data, the classification criteria are not met.

##### **isopentane:**

Species : Guinea pig  
Method : Test(s) equivalent or similar to OECD Test Guideline 406  
Remarks : Based on available data, the classification criteria are not met.

### Germ cell mutagenicity

#### Product:

Genotoxicity in vivo : Remarks: Not mutagenic.

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

#### Components:

##### **pentane:**

Genotoxicity in vitro : Method: Test(s) equivalent or similar to OECD Guideline 471  
Remarks: Based on available data, the classification criteria are not met.

Method: Directive 67/548/EEC, Annex V, B.10.  
Remarks: Based on available data, the classification criteria are not met.

Genotoxicity in vivo : Species: Rat  
Method: Directive 67/548/EEC, Annex V, B.12.  
Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

##### **isopentane:**

Genotoxicity in vitro : Method: Test(s) equivalent or similar to OECD Guideline 471  
Remarks: Based on available data, the classification criteria are not met.



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0      Revision Date: 08.10.2024      SDS Number: 800001012715      Date of last issue: 06.03.2023  
Print Date 15.10.2024

Method: Directive 67/548/EEC, Annex V, B.10.  
Remarks: Based on available data, the classification criteria are not met.

Genotoxicity in vivo : Species: Rat  
Method: Directive 67/548/EEC, Annex V, B.12.  
Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### Carcinogenicity

#### Product:

Remarks : Not a carcinogen.  
Based on available data, the classification criteria are not met.

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

#### Components:

##### **pentane:**

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

##### **isopentane:**

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Material	GHS/CLP Carcinogenicity Classification
pentane	No carcinogenicity classification.
isopentane	No carcinogenicity classification.

### Reproductive toxicity

#### Product:

Effects on fertility :  
Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0	Revision Date: 08.10.2024	SDS Number: 800001012715	Date of last issue: 06.03.2023 Print Date 15.10.2024
----------------	------------------------------	-----------------------------	---

---

### **Components:**

#### **pentane:**

Effects on fertility : Species: Rat  
Sex: male and female  
Application Route: Inhalation  
  
Method: Equivalent or similar to OECD Test Guideline 416  
Remarks: Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

#### **isopentane:**

Effects on fertility : Species: Rat  
Sex: male and female  
Application Route: Inhalation  
  
Method: Equivalent or similar to OECD Test Guideline 416  
Remarks: Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### **STOT - single exposure**

#### **Product:**

Remarks : May cause drowsiness and dizziness.  
Inhalation of vapours or mists may cause irritation to the respiratory system.

### **Components:**

#### **pentane:**

Exposure routes : Inhalation  
Target Organs : Central nervous system  
Remarks : May cause drowsiness or dizziness.

#### **isopentane:**

Exposure routes : Inhalation  
Target Organs : Central nervous system  
Remarks : May cause drowsiness or dizziness.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
2.0	08.10.2024	800001012715	Print Date 15.10.2024

---

### STOT - repeated exposure

#### Product:

Remarks : Based on available data, the classification criteria are not met.

#### Components:

##### pentane:

Remarks : Based on available data, the classification criteria are not met.

##### isopentane:

Remarks : Based on available data, the classification criteria are not met.  
Low systemic toxicity on repeated exposure.

### Repeated dose toxicity

#### Components:

##### pentane:

Species	: Rat, male and female
Application Route	: Inhalation
Test atmosphere	: Gas
Method	: OECD Test Guideline 413
Target Organs	: No specific target organs noted

##### isopentane:

Species	: Rat, male and female
Application Route	: Inhalation
Test atmosphere	: Gas
Method	: Test(s) equivalent or similar to OECD Test Guideline 413
Target Organs	: No specific target organs noted

### Aspiration toxicity

#### Product:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

#### Components:

##### pentane:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

##### isopentane:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
2.0	08.10.2024	800001012715	Print Date 15.10.2024

### 11.2 Information on other hazards

#### Endocrine disrupting properties

##### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### Further information

##### Product:

Remarks : Exposure to very high concentrations of similar materials has been associated with irregular heart rhythms and cardiac arrest.  
Classifications by other authorities under varying regulatory frameworks may exist.

Remarks : Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

##### Components:

##### **pentane:**

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

##### **isopentane:**

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

## SECTION 12: Ecological information

### 12.1 Toxicity

##### Product:

Toxicity to fish : Remarks: LL/EL/IL50 > 1 <= 10 mg/l  
Toxic

Toxicity to daphnia and other : Remarks: Toxic  
aquatic invertebrates LL/EL/IL50 > 1 <= 10 mg/l

Toxicity to algae/aquatic plants : Remarks: LL/EL/IL50 >10 <= 100 mg/l  
Harmful

Toxicity to fish (Chronic tox- : Remarks: Data not available

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
2.0	08.10.2024	800001012715	Print Date 15.10.2024

icity)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: Data not available

Toxicity to microorganisms :  
Remarks: Data not available

### Components:

#### **pentane:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4,26 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: Toxic  
LL/EL/IL50 > 1 <= 10 mg/l

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2,7 mg/l  
Exposure time: 48 h  
Method: Test(s) equivalent or similar to OECD Guideline 202  
Remarks: Toxic  
LL/EL/IL50 > 1 <= 10 mg/l

Toxicity to algae/aquatic plants : EC50 (Scenedesmus capricornutum (fresh water algae)): 10,7 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Harmful  
LL/EL/IL50 >10 <= 100 mg/l

Toxicity to microorganisms : NOEL (Tetrahymena pyriformis): 23,7 mg/l  
Exposure time: 48 h  
Method: Based on quantitative structure-activity relationship (QSAR) modelling  
Remarks: NOEC/NOEL >100 mg/l

Toxicity to fish (Chronic toxicity) : NOELR: 6,165 mg/l  
Exposure time: 28 d  
Species: Oncorhynchus mykiss (rainbow trout)  
Method: Based on quantitative structure-activity relationship (QSAR) modelling  
Remarks: NOEC/NOEL > 1.0 - <= 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 10,76 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: Based on quantitative structure-activity relationship (QSAR) modelling  
Remarks: no data available

#### **isopentane:**

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
2.0	08.10.2024	800001012715	Print Date 15.10.2024

- 
- |  |   |
|--|---|
| Toxicity to fish   | : LC50 (Oncorhynchus mykiss (rainbow trout)): 4,26 mg/l<br>Exposure time: 96 h<br>Method: Information given is based on data obtained from similar substances.<br>Remarks: Toxic<br>LL/EL/IL50 > 1 <= 10 mg/l           |
| Toxicity to daphnia and other aquatic invertebrates                    | : EC50 (Daphnia magna (Water flea)): 4,2 mg/l<br>Exposure time: 48 h<br>Method: Test(s) equivalent or similar to OECD Guideline 301 F<br>Remarks: Toxic<br>LL/EL/IL50 > 1 <= 10 mg/l                                    |
| Toxicity to algae/aquatic plants                                       | : EL50 (Selenastrum capricornutum (green algae)): 25,12 mg/l<br>Exposure time: 72 h<br>Method: Based on quantitative structure-activity relationship (QSAR) modelling<br>Remarks: Harmful<br>LL/EL/IL50 >10 <= 100 mg/l |
| Toxicity to microorganisms   | : EL50 (Tetrahymena pyriformis): 130,9 mg/l<br>Exposure time: 48 h<br>Method: Based on quantitative structure-activity relationship (QSAR) modelling<br>Remarks: Practically non toxic:<br>LL/EL/IL50 > 100 mg/l        |
| Toxicity to fish (Chronic toxicity)                                    | : NOELR: 7,618 mg/l<br>Exposure time: 28 d<br>Species: Oncorhynchus mykiss (rainbow trout)<br>Method: Based on quantitative structure-activity relationship (QSAR) modelling<br>Remarks: NOEC/NOEL > 1.0 - <= 10 mg/l   |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : NOELR: 13,29 mg/l<br>Exposure time: 21 d<br>Species: Daphnia magna (Water flea)<br>Method: Based on quantitative structure-activity relationship (QSAR) modelling<br>Remarks: NOEC/NOEL > 10 - <=100 mg/l             |

### 12.2 Persistence and degradability

#### Product:

- |                  |   |
|------------------|---|
| Biodegradability | : Remarks: Readily biodegradable.<br>Oxidises rapidly by photo-chemical reactions in air. |
|------------------|---|

#### Components:

##### **pentane:**

- |                  |                        |
|------------------|------------------------|
| Biodegradability | : Biodegradation: 87 % |
|------------------|------------------------|

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
2.0	08.10.2024	800001012715	Print Date 15.10.2024

---

Exposure time: 28 d  
Method: Test(s) equivalent or similar to OECD Guideline 301 F  
Remarks: Readily biodegradable.  
Oxidises rapidly by photo-chemical reactions in air.

### isopentane:

Biodegradability : Biodegradation: 71 %  
Exposure time: 28 d  
Method: Test(s) equivalent or similar to OECD Guideline 301 F  
Remarks: Readily biodegradable.  
Oxidises rapidly by photo-chemical reactions in air.

## 12.3 Bioaccumulative potential

### Product:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

### Components:

#### pentane:

Bioaccumulation : Species: Pimephales promelas (fathead minnow)  
Bioconcentration factor (BCF): 171  
Method: Based on quantitative structure-activity relationship (QSAR) modelling  
Remarks: Does not bioaccumulate significantly.

#### isopentane:

Bioaccumulation : Species: Pimephales promelas (fathead minnow)  
Bioconcentration factor (BCF): 171  
Method: Information given is based on data obtained from similar substances.  
Remarks: Does not bioaccumulate significantly.

## 12.4 Mobility in soil

### Product:

Mobility : Remarks: Floats on water., If the product enters soil, one or more constituents will or may be mobile and may contaminate groundwater.

### Components:

#### pentane:

Mobility : Remarks: Floats on water., If the product enters soil, one or more constituents will or may be mobile and may contaminate groundwater.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
2.0	08.10.2024	800001012715	Print Date 15.10.2024

### isopentane:

Mobility : Remarks: Floats on water., If the product enters soil, one or more constituents will or may be mobile and may contaminate groundwater.

## 12.5 Results of PBT and vPvB assessment

### Product:

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

### Components:

#### pentane:

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

#### isopentane:

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

## 12.6 Endocrine disrupting properties

### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## 12.7 Other adverse effects

### Product:

Additional ecological information : In view of the high rate of loss from solution, the product is unlikely to pose a significant hazard to aquatic life.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

### Components:

#### pentane:

Additional ecological information : In view of the high rate of loss from solution, the product is unlikely to pose a significant hazard to aquatic life.

#### isopentane:



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0	Revision Date: 08.10.2024	SDS Number: 800001012715	Date of last issue: 06.03.2023 Print Date 15.10.2024
----------------	------------------------------	-----------------------------	---

---

Additional ecological information	: In view of the high rate of loss from solution, the product is unlikely to pose a significant hazard to aquatic life. Does not have ozone depletion potential.
-----------------------------------	---

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product	: Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Do not dispose into the environment, in drains or in water courses. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination. Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.  Waste, spills or used product is dangerous waste.  Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.  MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.
Contaminated packaging	: Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums. Send to drum recoverer or metal reclaimer. Comply with any local recovery or waste disposal regulations.

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADN	: 1265
ADR	: 1265

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
2.0	08.10.2024	800001012715	Print Date 15.10.2024

---

<b>RID</b>	:	1265
<b>IMDG</b>	:	1265
<b>IATA</b>	:	1265

### 14.2 UN proper shipping name

<b>ADN</b>	:	PENTANES (2-METHYLBUTANE)
<b>ADR</b>	:	PENTANES
<b>RID</b>	:	PENTANES
<b>IMDG</b>	:	PENTANES
<b>IATA</b>	:	PENTANES

### 14.3 Transport hazard class(es)

<b>ADN</b>	:	3
<b>ADR</b>	:	3
<b>RID</b>	:	3
<b>IMDG</b>	:	3
<b>IATA</b>	:	3

### 14.4 Packing group

<b>ADN</b>	
Packing group	: I
Classification Code	: F1
Labels	: 3 (N2)
<b>ADR</b>	
Packing group	: I
Classification Code	: F1
Hazard Identification Number	: 33
Labels	: 3
<b>RID</b>	
Packing group	: I
Classification Code	: F1
Hazard Identification Number	: 33
Labels	: 3
<b>IMDG</b>	
Packing group	: I
Labels	: 3
<b>IATA</b>	
Packing group	: I
Labels	: 3

### 14.5 Environmental hazards

<b>ADN</b>	
Environmentally hazardous	: yes
<b>ADR</b>	
Environmentally hazardous	: no

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0	Revision Date: 08.10.2024	SDS Number: 800001012715	Date of last issue: 06.03.2023 Print Date 15.10.2024
----------------	------------------------------	-----------------------------	---

### RID

Environmentally hazardous : no

### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

### 14.7 Maritime transport in bulk according to IMO instruments

Pollution category	: Y
Ship type	: 3
Product name	: Pentane (all isomers)

**Additional Information** : This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry. Transport in bulk according to Annex II of Marpol and the IBC Code

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV) : Product is not subject to Authorisation under REACH.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5a FLAMMABLE LIQUIDS

E2 ENVIRONMENTAL HAZARDS

### Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Act No. 350/2011 Coll., on chemical substances and mixtures including related regulations and

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
2.0	08.10.2024	800001012715	Print Date 15.10.2024

decrees as amended.

Act No. 201/2012 Coll., on protection of the air, including related regulations and decrees as amended.

Act No. 304/2017 Coll., on road traffic and transport, including related regulations and decrees as amended (ADR).

Act No. 319/2016 Coll., on railways and rail transport, including relating regulations and decrees as amended (RID).

Act No. 541/2020 Coll., on waste, including related regulations and decrees as amended.

Act No. 542/2020 Coll., on products with terminated lifetime period including relating regulations and decrees as amended.

Act No. 544/2020 Coll., on waters, including relating regulations and decrees as amended.

Act No. 365/2011 Coll., Labor Code, including relating regulations and decrees as amended.

Act No. 258/2000 Coll. Public Health Protection, including relating regulations and decrees as amended.

Government Regulation No. 361/2007 Coll., laying down conditions for the protection of health at work.

Product is subject to Prevention of Major Accident (No. 224/2015 Coll.) based on Seveso III directive (2012/18/EU).

### The components of this product are reported in the following inventories:

DSL : Listed

IECSC : Listed

ENCS : Listed

KECI : Listed

PICCS : Listed

TSCA : Listed

AIIC : Listed

NZIoC : Listed

TCSI : Listed

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

## SECTION 16: Other information

### Full text of H-Statements

EUH066	: Repeated exposure may cause skin dryness or cracking.
H224	: Extremely flammable liquid and vapour.
H304	: May be fatal if swallowed and enters airways.
H336	: May cause drowsiness or dizziness.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version	Revision Date:	SDS Number:	Date of last issue: 06.03.2023
2.0	08.10.2024	800001012715	Print Date 15.10.2024

H411 : Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Flam. Liq.	: Flammable liquids
STOT SE	: Specific target organ toxicity - single exposure
2006/15/EC	: Europe. Indicative occupational exposure limit values
CZ OEL	: Czech Republic. Chemical agents at work - Appendix 2: Occupational exposure limits
2006/15/EC / TWA	: Limit Value - eight hours
CZ OEL / TWA	: Time weighted average
CZ OEL / STEL	: Maximum permissible concentration

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Training advice : Provide adequate information, instruction and training for operators.

Other information : For Industry guidance and tools on REACH please visit the

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0	Revision Date: 08.10.2024	SDS Number: 800001012715	Date of last issue: 06.03.2023 Print Date 15.10.2024
----------------	------------------------------	-----------------------------	---

CEFIC website at <http://cefic.org/Industry-support>.

The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

A vertical bar (|) in the left margin indicates an amendment from the previous version.

This product is classified as H304 (May be fatal if swallowed and enters airways). The risk relates to potential for aspiration. The risk arising from aspiration hazard is solely related to the physico-chemical properties of the substance. The risk can therefore be controlled by implementing risk management measures tailored to this specific hazard and included within Section 8 of the SDS. An exposure scenario is not presented.

This product is classified as R66 / EUH066 (Repeated exposure may cause skin dryness or cracking). The risk relates to the potential for repeated or prolonged dermal contact. The risk arising from contact is solely related to the physico-chemical properties of the substance. The risk can therefore be controlled by implementing risk management measures tailored to this specific hazard and included within Section 8 of the SDS. An exposure scenario is not presented.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

### Classification of the mixture:

Flam. Liq. 1	H224
Asp. Tox. 1	H304
STOT SE 3	H336
Aquatic Chronic 2	H411

### Classification procedure:

On basis of test data.  
Expert judgement and weight of evidence determination.  
Expert judgement and weight of evidence determination.  
Expert judgement and weight of evidence determination.

### Identified Uses according to the Use Descriptor System

#### Uses - Worker

Title : Manufacture of substance  
- Industrial

#### Uses - Worker

Title : Distribution of substance  
- Industrial

#### Uses - Worker

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0	Revision Date: 08.10.2024	SDS Number: 800001012715	Date of last issue: 06.03.2023 Print Date 15.10.2024
----------------	------------------------------	-----------------------------	---

---

Title	:	Formulation & (re)packing of substances and mixtures - Industrial
-------	---	--

### Uses - Worker

Title	:	Use in coatings - Industrial
-------	---	---------------------------------

### Uses - Worker

Title	:	Use in blowing agents - Industrial
-------	---	---------------------------------------

### Uses - Worker

Title	:	Functional Fluids - Industrial
-------	---	-----------------------------------

### Uses - Worker

Title	:	Functional Fluids - Professional
-------	---	-------------------------------------

### Uses - Worker

Title	:	Use in laboratories - Industrial
-------	---	-------------------------------------

### Uses - Worker

Title	:	Use in laboratories - Professional
-------	---	---------------------------------------

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CZ / EN

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0      Revision Date: 08.10.2024      SDS Number: 800001012715      Date of last issue: 06.03.2023  
Print Date 15.10.2024

### Exposure Scenario - Worker

<b>300000000640</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Manufacture of substance- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15 <b>Environmental Release Categories:</b> ERC1, ERC4, ESVOC SpERC 1.1.v1
<b>Scope of process</b>	Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/ recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities.

SECTION 2		OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1		Control of Worker Exposure	
Product Characteristics			
Physical form of product		Liquid, vapour pressure > 10 kPa at STP	
Concentration of the Substance in Mixture/Article		Covers percentage substance in the product up to 100%., Unless stated otherwise.,	
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios		Risk Management Measures	
General exposures (closed systems)Use in closed process, no likelihood of exposureUse in closed, continuous process with occasional controlled exposureUse in closed batch process (synthesis or formulation)		No other specific measures identified.	
General exposures (open systems)Use in batch and other process (synthesis) where opportunity for exposure arises		No other specific measures identified.	
Process samplingTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large con-		No other specific measures identified.	



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version  
2.0

Revision Date:  
08.10.2024

SDS Number:  
800001012715

Date of last issue: 06.03.2023  
Print Date 15.10.2024

tainers at dedicated facilities	
Laboratory activitiesUse as laboratory reagent	No other specific measures identified.
Bulk transfers(open systems)Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities	No other specific measures identified.
Bulk transfers(closed systems)Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities	No other specific measures identified.
Equipment cleaning and maintenanceTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities	No other specific measures identified.
Storage.Use in closed process, no likelihood of exposureUse in closed, continuous process with occasional controlled exposure	Store substance within a closed system.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	2,2E+04
Fraction of Regional tonnage used locally:	1
Annual site tonnage (tonnes/year):	2,2E+04
Maximum daily site tonnage (kg/day):	7,2E+04
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	5,0E-02
Release fraction to wastewater from process (initial release prior to RMM):	3,0E-03
Release fraction to soil from process (initial release prior to RMM):	1,0E-04
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process re-	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0      Revision Date: 08.10.2024      SDS Number: 800001012715      Date of last issue: 06.03.2023  
Print Date 15.10.2024

lease estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment.	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	90
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of $\geq$ (%)	88
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%)	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	96,9
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	96,9
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	2,2E+05
Assumed domestic sewage treatment plant flow (m3/d)	1,0E+04
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
During manufacturing no waste of the substance is generated.	
<b>Conditions and measures related to external recovery of waste</b>	
During manufacturing no waste of the substance is generated.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version  
2.0

Revision Date:  
08.10.2024

SDS Number:  
800001012715

Date of last issue: 06.03.2023  
Print Date 15.10.2024

---

--

<b>Section 4.2 -Environment</b>
---------------------------------

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
--

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.
---

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.
---

Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org/en/reach-for-industries-libraries.html">http://cefic.org/en/reach-for-industries-libraries.html</a> ).
--

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version  
2.0

Revision Date:  
08.10.2024

SDS Number:  
800001012715

Date of last issue: 06.03.2023  
Print Date 15.10.2024

### Exposure Scenario - Worker

<b>300000000641</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Distribution of substance- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15 <b>Environmental Release Categories:</b> ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC6d, ERC7, ESVOC SpERC 1.1b.v1
<b>Scope of process</b>	Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure > 10 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.		
Contributing Scenarios	Risk Management Measures	
General exposures (closed systems)Use in closed process, no likelihood of exposureUse in closed, continuous process with occasional controlled exposureUse in closed batch process (synthesis or formulation)	No other specific measures identified.	
General exposures (open systems)Use in batch and other process (synthesis) where opportunity for exposure arises	No other specific measures identified.	
Process samplingUse in closed batch process (synthesis or formulation)	No other specific measures identified.	
Laboratory activitiesUse as	No other specific measures identified.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version  
2.0

Revision Date:  
08.10.2024

SDS Number:  
800001012715

Date of last issue: 06.03.2023  
Print Date 15.10.2024

laboratory reagent	
Bulk transfers(closed systems)Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities	No other specific measures identified.
Bulk transfers(open systems)Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities	No other specific measures identified.
Drum and small package fillingTransfer of substance or preparation into small containers (dedicated filling line, including weighing)	No other specific measures identified.
Equipment cleaning and maintenanceTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities	No other specific measures identified.
Storage.Use in closed process, no likelihood of exposureUse in closed, continuous process with occasional controlled exposure	Store substance within a closed system.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	3,6E+03
Fraction of Regional tonnage used locally:	2,0E-03
Annual site tonnage (tonnes/year):	7,2
Maximum daily site tonnage (kg/day):	360
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	20
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	1,0E-03
Release fraction to wastewater from process (initial release prior to RMM):	1,0E-05
Release fraction to soil from process (initial release prior to RMM):	1,0E-05

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0      Revision Date: 08.10.2024      SDS Number: 800001012715      Date of last issue: 06.03.2023  
Print Date 15.10.2024

<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment.	
No wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	90
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	0
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%)	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	96,0
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	96,0
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	2,7E+06
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version  
2.0

Revision Date:  
08.10.2024

SDS Number:  
800001012715

Date of last issue: 06.03.2023  
Print Date 15.10.2024

should ensure that risks are managed to at least equivalent levels.

### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version  
2.0

Revision Date:  
08.10.2024

SDS Number:  
800001012715

Date of last issue: 06.03.2023  
Print Date 15.10.2024

### Exposure Scenario - Worker

<b>300000000642</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Formulation & (re)packing of substances and mixtures- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15 <b>Environmental Release Categories:</b> ERC2, ESVOC SpERC 2.2.v1
<b>Scope of process</b>	Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure > 10 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.		
Contributing Scenarios		Risk Management Measures
General exposures (closed systems)Use in closed process, no likelihood of exposureUse in closed, continuous process with occasional controlled exposureUse in closed batch process (synthesis or formulation)		No other specific measures identified.
General exposures (open systems)Use in batch and other process (synthesis) where opportunity for exposure arises		No other specific measures identified.
Batch processes at elevated temperaturesOperation is carried out at elevated		Provide a good standard of controlled ventilation (10 to 15 air changes per hour).



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version  
2.0

Revision Date:  
08.10.2024

SDS Number:  
800001012715

Date of last issue: 06.03.2023  
Print Date 15.10.2024

temperature (> 20°C above ambient temperature).Use in closed batch process (synthesis or formulation)	
Process samplingUse in closed batch process (synthesis or formulation)	No other specific measures identified.
Laboratory activitiesUse as laboratory reagent	No other specific measures identified.
Bulk transfersTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities	No other specific measures identified.
Mixing operations (open systems)Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact)	No other specific measures identified.
ManualTransfer from/pouring from containersNon-dedicated facilityTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities	No other specific measures identified.
Drum/batch transfersDedicated facilityTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities	No other specific measures identified.
Production or preparation or articles by tableting, compression, extrusion or pelletisationProduction of preparations or articles by tableting, compression, extrusion, pelletisation	No other specific measures identified.
Drum and small package fillingTransfer of substance or preparation into small containers (dedicated filling line, including weighing)	No other specific measures identified.
Equipment cleaning and maintenanceTransfer of substance or preparation (charging/ discharging)	No other specific measures identified.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version  
2.0

Revision Date:  
08.10.2024

SDS Number:  
800001012715

Date of last issue: 06.03.2023  
Print Date 15.10.2024

from/ to vessels/ large containers at non-dedicated facilities	
Storage. Use in closed process, no likelihood of exposure Use in closed, continuous process with occasional controlled exposure	Store substance within a closed system.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	3,4E+03
Fraction of Regional tonnage used locally:	1
Annual site tonnage (tonnes/year):	3,4E+03
Maximum daily site tonnage (kg/day):	1,1E+04
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements):	2,5E-02
Release fraction to wastewater from process (initial release prior to RMM):	2,0E-03
Release fraction to soil from process (initial release prior to RMM):	1,0E-04
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment.	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	77,2
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%)	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0      Revision Date: 08.10.2024      SDS Number: 800001012715      Date of last issue: 06.03.2023  
Print Date 15.10.2024

Estimated substance removal from wastewater via domestic sewage treatment (%)	96,0
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	96,0
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	6,5E+04
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

<b>Section 4.2 -Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.	
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.	
Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org/en/reach-for-industries-libraries.html">http://cefic.org/en/reach-for-industries-libraries.html</a> ).	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version  
2.0

Revision Date:  
08.10.2024

SDS Number:  
800001012715

Date of last issue: 06.03.2023  
Print Date 15.10.2024

### Exposure Scenario - Worker

<b>300000000643</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use in coatings- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15 <b>Environmental Release Categories:</b> ERC4, ESVOC SpERC 4.3a.v1
<b>Scope of process</b>	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure > 10 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.		
Contributing Scenarios		Risk Management Measures
General exposures (closed systems)Use in closed process, no likelihood of exposure		No other specific measures identified.
General exposures (closed systems)with sample collectionUse in contained systemsUse in closed, continuous process with occasional controlled exposure		No other specific measures identified.
Film formation - force drying, stoving and other technologies.Operation is carried out at elevated temperature (> 20°C above		Provide a good standard of controlled ventilation (10 to 15 air changes per hour).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version  
2.0

Revision Date:  
08.10.2024

SDS Number:  
800001012715

Date of last issue: 06.03.2023  
Print Date 15.10.2024

ambient temperature).Use in closed, continuous process with occasional controlled exposure	
Mixing operations (closed systems)Use in contained batch processesUse in closed batch process (synthesis or formulation)	No other specific measures identified.
Film formation - air dryingUse in batch and other process (synthesis) where opportunity for exposure arises	No other specific measures identified.
Preparation of material for applicationMixing operations (open systems)Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact)	No other specific measures identified.
Spraying (automatic/robotic)Industrial spraying	No other specific measures identified.
ManualSprayingIndustrial spraying	No other specific measures identified.
Material transfersTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilitiesTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities	No other specific measures identified.
Roller, spreader, flow applicationRoller application or brushing	No other specific measures identified.
Dipping, immersion and pouringTreatment of articles by dipping and pouring	No other specific measures identified.
Laboratory activitiesUse as laboratory reagent	No other specific measures identified.
Material transfersDrum/batch transfersTransfer from/pouring from containersTransfer of substance or preparation into small containers (dedicated	No other specific measures identified.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version  
2.0

Revision Date:  
08.10.2024

SDS Number:  
800001012715

Date of last issue: 06.03.2023  
Print Date 15.10.2024

filling line, including weighing)	
Production or preparation of articles by tableting, compression, extrusion or pelletisation Production of preparations or articles by tableting, compression, extrusion, pelletisation	No specific measures identified.
Equipment cleaning and maintenance Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities	No other specific measures identified.
Storage. Use in closed process, no likelihood of exposure	Store substance within a closed system.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	2,1
Fraction of Regional tonnage used locally:	1
Annual site tonnage (tonnes/year):	2,1
Maximum daily site tonnage (kg/day):	110
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	20
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	9,8E-01
Release fraction to wastewater from process (initial release prior to RMM):	7,0E-03
Release fraction to soil from process (initial release prior to RMM):	0
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment.	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
No wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	90
Treat onsite wastewater (prior to receiving water discharge) to provide	0

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0      Revision Date: 08.10.2024      SDS Number: 800001012715      Date of last issue: 06.03.2023  
Print Date 15.10.2024

the required removal efficiency of $\geq$ (%)	
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%)	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	96,0
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	96,0
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	1,9E+04
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

<b>Section 4.2 -Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version  
2.0

Revision Date:  
08.10.2024

SDS Number:  
800001012715

Date of last issue: 06.03.2023  
Print Date 15.10.2024

---

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.
---

Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org/en/reach-for-industries-libraries.html">http://cefic.org/en/reach-for-industries-libraries.html</a> ).
--



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version  
2.0

Revision Date:  
08.10.2024

SDS Number:  
800001012715

Date of last issue: 06.03.2023  
Print Date 15.10.2024

### Exposure Scenario - Worker

<b>300000000666</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use in blowing agents- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC8b, PROC9, PROC12 <b>Environmental Release Categories:</b> ERC4, ESVOC SpERC 4.9.v1
<b>Scope of process</b>	Use as a blowing agent for rigid and flexible foams, including material transfers, mixing and injection, curing, cutting, storage and packing.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure > 10 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.		
Contributing Scenarios	Risk Management Measures	
Bulk transfersDedicated facilityTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities	No other specific measures identified.	
Mixing operations (closed systems)Use in closed process, no likelihood of exposure	No other specific measures identified.	
Extrusion and expansion of polymer massUse of blowing agents in manufacture of foam	No other specific measures identified.	
Cutting and shavingUse of blowing agents in manufacture of foam	No other specific measures identified.	
Collection and re-	No other specific measures identified.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version  
2.0

Revision Date:  
08.10.2024

SDS Number:  
800001012715

Date of last issue: 06.03.2023  
Print Date 15.10.2024

processing of shavings, cuttings, etc.Use of blowing agents in manufacture of foam	
Product packagingUse of blowing agents in manufacture of foam	No other specific measures identified.
Storage.Use in closed, continuous process with occasional controlled exposure	No other specific measures identified.
Mixing operations (closed systems)Operation is carried out at elevated temperature (> 20°C above ambient temperature).Use in closed batch process (synthesis or formulation)	Provide a good standard of controlled ventilation (10 to 15 air changes per hour).
Intermediate polymer storageOperation is carried out at elevated temperature (> 20°C above ambient temperature).Use in closed batch process (synthesis or formulation)	Provide a good standard of controlled ventilation (10 to 15 air changes per hour).
Centrifuging including dischargingOperation is carried out at elevated temperature (> 20°C above ambient temperature).Use in closed batch process (synthesis or formulation)	Provide a good standard of controlled ventilation (10 to 15 air changes per hour).
Drying and storageUse of blowing agents in manufacture of foam	No other specific measures identified.
Semi-bulk packagingTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities	No other specific measures identified.
Treatment by heatingOperation is carried out at elevated temperature (> 20°C above ambient temperature).Use of blowing agents in manufacture of foam	Provide a good standard of controlled ventilation (10 to 15 air changes per hour).
Article formation in mouldOperation is carried out at elevated temperature (> 20°C above ambient temperature).Use of blow-	Provide a good standard of controlled ventilation (10 to 15 air changes per hour).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version  
2.0

Revision Date:  
08.10.2024

SDS Number:  
800001012715

Date of last issue: 06.03.2023  
Print Date 15.10.2024

ing agents in manufacture of foam	
Cutting by heated wire- ManualUse of blowing agents in manufacture of foam	No other specific measures identified.
Mixing operations (closed systems)Use in closed batch process (synthesis or formulation)	No other specific measures identified.
Drum and small package fillingFilling/ preparation of equipment from drums or containers.Transfer of substance or preparation into small containers (dedicated filling line, including weighing)	No other specific measures identified.
FoamingUse of blowing agents in manufacture of foam	No other specific measures identified.
CompressionUse of blowing agents in manufacture of foam	No other specific measures identified.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	1,5E+03
Fraction of Regional tonnage used locally:	1
Annual site tonnage (tonnes/year):	1,5E+03
Maximum daily site tonnage (kg/day):	1,5E+04
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	100
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	1
Release fraction to wastewater from process (initial release prior to RMM):	3,0E-04
Release fraction to soil from process (initial release prior to RMM):	0
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by soil.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0      Revision Date: 08.10.2024      SDS Number: 800001012715      Date of last issue: 06.03.2023  
Print Date 15.10.2024

Prevent discharge of undissolved substance to or recover from onsite wastewater.	
No wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of $\geq$ (%)	0
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%)	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	96
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	96
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	4,3E+05
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

<b>Section 4.2 -Environment</b>	
---------------------------------	--

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version  
2.0

Revision Date:  
08.10.2024

SDS Number:  
800001012715

Date of last issue: 06.03.2023  
Print Date 15.10.2024

---

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
--

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.
---

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.
---

Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org/en/reach-for-industries-libraries.html">http://cefic.org/en/reach-for-industries-libraries.html</a> ).
--

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version  
2.0

Revision Date:  
08.10.2024

SDS Number:  
800001012715

Date of last issue: 06.03.2023  
Print Date 15.10.2024

### Exposure Scenario - Worker

<b>300000000667</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Functional Fluids- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9 <b>Environmental Release Categories:</b> ERC7, ESVOC SpERC 7.13a.v1
<b>Scope of process</b>	Use as functional fluids e.g. cable oils, transfer oils, coolants, insulators, refrigerants, hydraulic fluids in industrial equipment including maintenance and related material transfers.

SECTION 2		OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1		Control of Worker Exposure	
Product Characteristics			
Physical form of product		Liquid, vapour pressure > 10 kPa at STP	
Concentration of the Substance in Mixture/Article		Covers percentage substance in the product up to 100%., Unless stated otherwise.,	
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios		Risk Management Measures	
Bulk transfers(closed systems)Use in closed process, no likelihood of exposureUse in closed, continuous process with occasional controlled exposure		No other specific measures identified.	
Drum/batch transfersDedicated facilityTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities		No other specific measures identified.	
Filling of articles/equipment(closed systems)Transfer of substance or preparation into small containers (dedicated filling line, including weighing)		No other specific measures identified.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version  
2.0

Revision Date:  
08.10.2024

SDS Number:  
800001012715

Date of last issue: 06.03.2023  
Print Date 15.10.2024

Filling/ preparation of equipment from drums or containers.Non-dedicated facilityTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities	No other specific measures identified.
General exposures (closed systems)Use in closed process, no likelihood of exposureUse in closed, continuous process with occasional controlled exposureUse in closed batch process (synthesis or formulation)	No other specific measures identified.
General exposures (open systems)Use in batch and other process (synthesis) where opportunity for exposure arises	No other specific measures identified.
General exposures (open systems)elevated temperatureUse in batch and other process (synthesis) where opportunity for exposure arises	Provide a good standard of controlled ventilation (10 to 15 air changes per hour).
Remanufacture of reject articlesTransfer of substance or preparation into small containers (dedicated filling line, including weighing)	No other specific measures identified.
Equipment maintenanceTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities	No other specific measures identified.
Storage.Use in closed process, no likelihood of exposureUse in closed, continuous process with occasional controlled exposure	Store substance within a closed system.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	1,6E+02

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0      Revision Date: 08.10.2024      SDS Number: 800001012715      Date of last issue: 06.03.2023  
Print Date 15.10.2024

Fraction of Regional tonnage used locally:	6,3E-02
Annual site tonnage (tonnes/year):	10
Maximum daily site tonnage (kg/day):	5,0E+02
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	20
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	1,0E-02
Release fraction to wastewater from process (initial release prior to RMM):	3,0E-04
Release fraction to soil from process (initial release prior to RMM):	1,0E-03
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process re-release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment.	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
No wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	0
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%)	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	96
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	96
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	4,3E+05
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

### SECTION 3

### EXPOSURE ESTIMATION



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version  
2.0

Revision Date:  
08.10.2024

SDS Number:  
800001012715

Date of last issue: 06.03.2023  
Print Date 15.10.2024

### Section 3.1 - Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

### Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

## SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version  
2.0

Revision Date:  
08.10.2024

SDS Number:  
800001012715

Date of last issue: 06.03.2023  
Print Date 15.10.2024

### Exposure Scenario - Worker

<b>300000000668</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Functional Fluids- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC8a, PROC9, PROC20 <b>Environmental Release Categories:</b> ERC9a, ERC9b, ESVOC SpERC 9.13b.v1
<b>Scope of process</b>	Use as functional fluids e.g. cable oils, transfer oils, coolants, insulators, refrigerants, hydraulic fluids in professional equipment including maintenance and related material transfers.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure > 10 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.		
Contributing Scenarios	Risk Management Measures	
Drum/batch transfersNon-dedicated facilityTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities	No other specific measures identified.	
Transfer from/pouring from containersDedicated facilityTransfer of substance or preparation into small containers (dedicated filling line, including weighing)	No other specific measures identified.	
Filling/ preparation of equipment from drums or containers.Dedicated facilityTransfer of substance or preparation into small containers (dedicated filling	No other specific measures identified.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version  
2.0

Revision Date:  
08.10.2024

SDS Number:  
800001012715

Date of last issue: 06.03.2023  
Print Date 15.10.2024

line, including weighing)	
General exposures (closed systems)Use in closed process, no likelihood of exposureUse in closed, continuous process with occasional controlled exposureUse in closed batch process (synthesis or formulation)	No other specific measures identified.
Operation of equipment containing engine oils and similar.Engine lubricant service	No other specific measures identified.
Operation of equipment containing engine oils and similar.elevated temperatureEngine lubricant service	Provide a good standard of controlled ventilation (10 to 15 air changes per hour).
Remanufacture of reject articlesTransfer of substance or preparation into small containers (dedicated filling line, including weighing)	No other specific measures identified.
Equipment maintenanceTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities	No other specific measures identified.
Storage.Use in closed process, no likelihood of exposureUse in closed, continuous process with occasional controlled exposure	Store substance within a closed system.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
Readily biodegradable.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	50
Fraction of Regional tonnage used locally:	5,0E-04
Annual site tonnage (tonnes/year):	2,5E-02
Maximum daily site tonnage (kg/day):	6,8E-02
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0      Revision Date: 08.10.2024      SDS Number: 800001012715      Date of last issue: 06.03.2023  
Print Date 15.10.2024

Release fraction to air from wide dispersive use (regional only):	5,0E-02
Release fraction to wastewater from wide dispersive use:	2,5E-02
Release fraction to soil from wide dispersive use (regional only):	2,5E-02
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process re-lease estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emis-sions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater.	
No wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	0
If discharging to domestic sewage treatment plant, provide the re-quired onsite wastewater removal efficiency of (%)	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	96
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	96
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	1,0E+03
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version  
2.0

Revision Date:  
08.10.2024

SDS Number:  
800001012715

Date of last issue: 06.03.2023  
Print Date 15.10.2024

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0      Revision Date: 08.10.2024      SDS Number: 800001012715      Date of last issue: 06.03.2023  
Print Date 15.10.2024

### Exposure Scenario - Worker

<b>300000000669</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use in laboratories- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC10, PROC15 <b>Environmental Release Categories:</b> ERC2, ERC4
<b>Scope of process</b>	Use of the substance within laboratory settings, including material transfers and equipment cleaning.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure > 10 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.		
Contributing Scenarios	Risk Management Measures	
Laboratory activitiesUse as laboratory reagent	No other specific measures identified.	
CleaningRoller application or brushing	No other specific measures identified.	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB.		
Predominantly hydrophobic.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used in region:		0,1
Regional use tonnage (tonnes/year):		5
Fraction of Regional tonnage used locally:		0,4
Annual site tonnage (tonnes/year):		2
Maximum daily site tonnage (kg/day):		100
Frequency and Duration of Use		
Continuous release.		
Emission Days (days/year):		20
Environmental factors not influenced by risk management		
Local freshwater dilution factor:		10
Local marine water dilution factor:		100
Other Operational Conditions affecting Environmental Exposure		

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0      Revision Date: 08.10.2024      SDS Number: 800001012715      Date of last issue: 06.03.2023  
Print Date 15.10.2024

Release fraction to air from process (initial release prior to RMM):	2,5E-02
Release fraction to wastewater from process (initial release prior to RMM):	2,0E-02
Release fraction to soil from process (initial release prior to RMM):	1,0E-04
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process re-release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment.	
No wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	0
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%)	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	96,9
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	96,9
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	6,5E+03
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
------------------	--

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version  
2.0

Revision Date:  
08.10.2024

SDS Number:  
800001012715

Date of last issue: 06.03.2023  
Print Date 15.10.2024

---

### Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0      Revision Date: 08.10.2024      SDS Number: 800001012715      Date of last issue: 06.03.2023  
Print Date 15.10.2024

### Exposure Scenario - Worker

<b>300000000670</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use in laboratories- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC10, PROC15 <b>Environmental Release Categories:</b> ERC8a, ESVOC SpERC 8.17.v1
<b>Scope of process</b>	Use of small quantities within laboratory settings, including material transfers and equipment cleaning.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure > 10 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.		
Contributing Scenarios	Risk Management Measures	
Laboratory activitiesUse as laboratory reagent	No other specific measures identified.	
CleaningRoller application or brushing	No other specific measures identified.	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB.		
Predominantly hydrophobic.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used in region:		0,1
Regional use tonnage (tonnes/year):		5
Fraction of Regional tonnage used locally:		5,0E-04
Annual site tonnage (tonnes/year):		2,5E-03
Maximum daily site tonnage (kg/day):		6,9E-03
Frequency and Duration of Use		
Continuous release.		
Emission Days (days/year):		365
Environmental factors not influenced by risk management		
Local freshwater dilution factor:		10
Local marine water dilution factor:		100

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version 2.0      Revision Date: 08.10.2024      SDS Number: 800001012715      Date of last issue: 06.03.2023  
Print Date 15.10.2024

<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from wide dispersive use (regional only):	0,5
Release fraction to wastewater from wide dispersive use:	0,5
Release fraction to soil from wide dispersive use (regional only):	0
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process re-release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment.	
No wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	0
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%)	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	96
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	96
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	89
Assumed domestic sewage treatment plant flow (m3/d)	2,0E+03
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
------------------	--

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Pentane Blend 85/15

Version  
2.0

Revision Date:  
08.10.2024

SDS Number:  
800001012715

Date of last issue: 06.03.2023  
Print Date 15.10.2024

---

### Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).