

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.04.2021 |
| 1.6 | 06.04.2023 | 800001005738 | Print Date 12.04.2023 |

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

| | |
|-------------------------------|---|
| Trade name | : Methyl PROXITOL |
| Product code | : U5141 |
| Registration number EU | : 01-2119457435-35-0002 |
| CAS-No. | : 107-98-2 |
| Other means of identification | : 1-methoxy-2-propanol, PGME, PM, Propylene glycol monomethyl ether |

1.2 Relevant identified uses of the substance or mixture and uses advised against

| | |
|-----------------------------------|--|
| Use of the Sub- stance/Mixture | : Solvent. Please refer to section 16 and/or the annexes for the registered uses under REACH. |
| Uses advised against | : This product must not be used in applications other than the above without first seeking the advice of the supplier. |

1.3 Details of the supplier of the safety data sheet

| | |
|----------------------------------|---|
| Manufacturer/Supplier | : Shell Chemicals Europe B.V. PO Box 2334 3000 CH Rotterdam Netherlands |
| Contact person | : Shell Chemicals South East Europe |
| Telephone | : +30 210 9895 700 |
| Telefax | : +30 210 9895 744 |
| Contact for Safety Data Sheet | : sccmsds@shell.com |

1.4 Emergency telephone number

+44 (0) 1235 239 670 (This telephone number is available 24 hours per day, 7 days per week)

| | |
|-------------------|---|
| Other information | : PROXITOL is a trademark owned by Shell Trademark Management B.V. and Shell Brands Inc. and used by affiliates of Royal Dutch Shell plc. |
|-------------------|---|

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.04.2021 |
| 1.6 | 06.04.2023 | 800001005738 | Print Date 12.04.2023 |

Flammable liquids, Category 3

H226: Flammable liquid and vapour.

Specific target organ toxicity - single exposure, Category 3, Narcotic effects

H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

:



Signal word

:

Warning

Hazard statements

:

PHYSICAL HAZARDS:

H226 Flammable liquid and vapour.

HEALTH HAZARDS:

H336 May cause drowsiness or dizziness.

ENVIRONMENTAL HAZARDS:

Not classified as environmental hazard according to CLP criteria.

Precautionary statements

:

Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

P233 Keep container tightly closed.

P243 Take precautionary measures against static discharge.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P370 + P378 In case of fire: Use appropriate media to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

Vapours are heavier than air. Vapours may travel across the ground and reach remote ignition sources causing a flashback fire danger.
Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.
If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

SECTION 3: Composition/information on ingredients

3.1 Substances

Components

| Chemical name | CAS-No. EC-No. | Concentration (% w/w) |
|-----------------------|------------------------|-----------------------|
| 1-Methoxypropane-2-ol | 107-98-2 203-539-1 | >= 99,6 |
| 2-methoxypropanol | 1589-47-5 216-455-5 | < 0,1 |

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Not expected to be a health hazard when used under normal conditions.
- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- If inhaled : Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.
- In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.
If persistent irritation occurs, obtain medical attention.
- In case of eye contact : Flush eye with copious quantities of water.
Remove contact lenses, if present and easy to do. Continue rinsing.
If persistent irritation occurs, obtain medical attention.
- If swallowed : If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
Rinse mouth.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.04.2021 |
| 1.6 | 06.04.2023 | 800001005738 | Print Date 12.04.2023 |

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death.
Skin irritation signs and symptoms may include a burning sensation, redness, or swelling.
Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.
Ingestion may result in nausea, vomiting and/or diarrhoea.
Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Call a doctor or poison control center for guidance.
Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : None

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : The vapour is heavier than air, spreads along the ground and distant ignition is possible.
Carbon monoxide may be evolved if incomplete combustion occurs.

5.3 Advice for firefighters

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

Specific extinguishing methods : Standard procedure for chemical fires.

Further information : Clear fire area of all non-emergency personnel.
Keep adjacent containers cool by spraying with water.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.04.2021 |
| 1.6 | 06.04.2023 | 800001005738 | Print Date 12.04.2023 |

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Observe the relevant local and international regulations
Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.
Local authorities should be advised if significant spillages cannot be contained.
The vapour is heavier than air, spreads along the ground and distant ignition is possible.
Vapour may form an explosive mixture with air.
6.1.1 For non emergency personnel:
Avoid contact with skin, eyes and clothing.
Isolate hazard area and deny entry to unnecessary or unprotected personnel.
Stay upwind and keep out of low areas.
6.1.2 For emergency responders:
Avoid contact with skin, eyes and clothing.
Isolate hazard area and deny entry to unnecessary or unprotected personnel.
Stay upwind and keep out of low areas.

6.2 Environmental precautions

Environmental precautions : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.
Ventilate contaminated area thoroughly.
Monitor area with combustible gas indicator.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.
For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.04.2021 |
| 1.6 | 06.04.2023 | 800001005738 | Print Date 12.04.2023 |

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.,
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- | | |
|-------------------------|---|
| Technical measures | : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material. Ensure that all local regulations regarding handling and storage facilities are followed. |
| Advice on safe handling | : Avoid contact with skin, eyes and clothing. Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Bulk storage tanks should be diked (bunded). Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk. The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Do NOT use compressed air for filling, discharging, or handling operations. |
| Product Transfer | : Refer to guidance under Handling section. |

7.2 Conditions for safe storage, including any incompatibilities

- | | |
|---|--|
| Requirements for storage areas and containers | : The vapour is heavier than air. Beware of accumulation in pits and confined spaces. Refer to section 15 for any additional specific legislation covering the packaging and storage of this product. |
| Packaging material | : Suitable material: For containers, or container linings use mild steel, stainless steel. Unsuitable material: Natural, butyl, neoprene or nitrile rubbers. |
| Container Advice | : Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

7.3 Specific end use(s)

Specific use(s) : Please refer to section 16 and/or the annexes for the registered uses under REACH.

Ensure that all local regulations regarding handling and storage facilities are followed.
See additional references that provide safe handling practices: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).
IEC/TS 60079-32-1: Electrostatic hazards, guidance

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|-----------------------|---|-------------------------------|----------------------------------|--------|
| 1-Methoxypropane-2-ol | 107-98-2 | KGVI | 150 ppm 568 mg/m ³ | RS OEL |
| | Further information: This chemical substance can adversely affect the skin., Substance mentioned in indicative exposure limit values in Directive 2000/39 / EC (first list) | | | |
| 1-Methoxypropane-2-ol | | GVI | 100 ppm 375 mg/m ³ | RS OEL |
| | Further information: This chemical substance can adversely affect the skin., Substance mentioned in indicative exposure limit values in Directive 2000/39 / EC (first list) | | | |

Biological occupational exposure limits

No biological limit allocated.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|-----------------------|-----------|-----------------|----------------------------|-------------------------|
| 1-Methoxypropane-2-ol | Workers | Inhalation | Acute local effects | 553,5 mg/m ³ |
| 1-Methoxypropane-2-ol | Workers | Inhalation | Long-term systemic effects | 369 mg/m ³ |
| 1-Methoxypropane-2-ol | Workers | Dermal | Long-term systemic effects | 50,6 mg/kg bw/day |
| 1-Methoxypropane-2-ol | Consumers | Inhalation | Long-term systemic effects | 43,9 mg/m ³ |
| 1-Methoxypropane-2-ol | Consumers | Dermal | Long-term systemic effects | 18,1 mg/kg bw/day |
| 1-Methoxypropane-2-ol | Consumers | Oral | Long-term systemic | 3,3 mg/kg |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

| | | | | |
|----|--|--|---------|--------|
| ol | | | effects | bw/day |
|----|--|--|---------|--------|

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | Environmental Compartment | Value |
|-----------------------|---------------------------|------------------------------|
| 1-Methoxypropane-2-ol | Fresh water | 10 mg/l |
| 1-Methoxypropane-2-ol | Fresh water sediment | 41,6 mg/kg dry weight (d.w.) |
| 1-Methoxypropane-2-ol | Marine sediment | 4,17 mg/kg dry weight (d.w.) |
| 1-Methoxypropane-2-ol | Soil | 2,47 mg/kg dry weight (d.w.) |
| 1-Methoxypropane-2-ol | Sewage treatment plant | 100 mg/l |

8.2 Exposure controls

Engineering measures

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Eye washes and showers for emergency use.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.
Approved to EU Standard EN166.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.04.2021 |
| 1.6 | 06.04.2023 | 800001005738 | Print Date 12.04.2023 |

Hand protection

Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC, neoprene or nitrile rubber gloves For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Skin and body protection : Skin protection is not required under normal conditions of use.
For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure.
If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.

Protective clothing approved to EU Standard EN14605.

Wear antistatic and flame-retardant clothing, if a local risk assessment deems it so.

Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.
Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.04.2021 |
| 1.6 | 06.04.2023 | 800001005738 | Print Date 12.04.2023 |

If air-filtering respirators are suitable for conditions of use:
Select a filter suitable for organic gases and vapours [Type A
boiling point > 65°C (149°F)] meeting EN14387.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|------------------------------------|
| Physical state | : Liquid. |
| Colour | : clear |
| Odour | : Ethereal |
| Odour Threshold | : Data not available |
| Melting / freezing point | : -96 °C |
| Boiling point/boiling range | : 117 - 125 °C |
| Flammability | |
| Flammability (solid, gas) | : Data not available |
| Lower explosion limit and upper explosion limit / flammability limit | |
| Upper explosion limit / upper flammability limit | : 13,1 %(V) |
| Lower explosion limit / Lower flammability limit | : 1,9 %(V) |
| Flash point | : 30 °C Method: ASTM D93 (PMCC) |
| Auto-ignition temperature | : 290 °C |
| Decomposition temperature | |
| Decomposition temperature | : Data not available |
| pH | : Data not available |
| Viscosity | |
| Viscosity, dynamic | : Data not available |
| Viscosity, kinematic | : Data not available |
| Solubility(ies) | |
| Water solubility | : completely soluble (20 °C) |
| Solubility in other solvents | : Data not available |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.04.2021 |
| 1.6 | 06.04.2023 | 800001005738 | Print Date 12.04.2023 |

| | | |
|--|---|---|
| Partition coefficient: n-octanol/water | : | log Pow: 0,37 |
| Vapour pressure | : | 1,170 Pa (20 °C) |
| Relative density | : | 0,92 (20 °C) Method: ASTM D4052 |
| Density | : | 920 - 923 kg/m ³ (20 °C) Method: ASTM D4052 |
| Relative vapour density | : | 3,1 |

9.2 Other information

| | | |
|----------------------|---|--|
| Explosives | : | Not applicable |
| Oxidizing properties | : | Data not available |
| Evaporation rate | : | 0,75 Method: ASTM D 3539, nBuAc=1 |
| Conductivity | : | Electrical conductivity: > 10,000 pS/m |

A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be a static accumulator.

| | | |
|------------------|---|------------------|
| Surface tension | : | 70,7 mN/m, 20 °C |
| Molecular weight | : | 90,12 g/mol |

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions

10.3 Possibility of hazardous reactions

| | | |
|---------------------|---|--------------------------------------|
| Hazardous reactions | : | Reacts with strong oxidising agents. |
|---------------------|---|--------------------------------------|

10.4 Conditions to avoid

| | | |
|---------------------|---|--|
| Conditions to avoid | : | Avoid heat, sparks, open flames and other ignition sources. Prevent vapour accumulation. In certain circumstances product can ignite due to static elec- |
|---------------------|---|--|

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.04.2021 |
| 1.6 | 06.04.2023 | 800001005738 | Print Date 12.04.2023 |

tricity.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

10.6 Hazardous decomposition products

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

Acute toxicity

Components:

1-Methoxypropane-2-ol:

Acute oral toxicity : LD50: > 2000 - <= 5000 mg/kg
Remarks: May be harmful if swallowed.

Acute inhalation toxicity : Remarks: Low toxicity by inhalation.

Acute dermal toxicity : LD50: > 5000 mg/kg
Remarks: Low toxicity

Skin corrosion/irritation

Components:

1-Methoxypropane-2-ol:

Remarks : Not irritating to skin.
Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.

Serious eye damage/eye irritation

Components:

1-Methoxypropane-2-ol:

Remarks : Slightly irritating to the eye.
Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

Respiratory or skin sensitisation

Components:

1-Methoxypropane-2-ol:

Remarks : Not a sensitiser.
Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Components:

1-Methoxypropane-2-ol:

Genotoxicity in vivo : Remarks: No evidence of mutagenic activity.

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Carcinogenicity

Components:

1-Methoxypropane-2-ol:

Remarks : Not carcinogenic in animal studies.

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

| Material | GHS/CLP Carcinogenicity Classification |
|-----------------------|--|
| 1-Methoxypropane-2-ol | No carcinogenicity classification. |
| 2-methoxypropanol | No carcinogenicity classification. |

Reproductive toxicity

Components:

1-Methoxypropane-2-ol:

Effects on fertility :
Remarks: Does not impair fertility., Causes foetotoxicity in animals at doses which are maternally toxic., Causes adverse effects on the foetus based on animal studies.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.04.2021 |
| 1.6 | 06.04.2023 | 800001005738 | Print Date 12.04.2023 |

STOT - single exposure

Components:

1-Methoxypropane-2-ol:

Remarks : High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness.

STOT - repeated exposure

Components:

1-Methoxypropane-2-ol:

Remarks : Kidney: caused kidney effects in male rats which are not considered relevant to humans
Based on available data, the classification criteria are not met.

Aspiration toxicity

Components:

1-Methoxypropane-2-ol:

Not an aspiration hazard., Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Components:

1-Methoxypropane-2-ol:

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.04.2021 |
| 1.6 | 06.04.2023 | 800001005738 | Print Date 12.04.2023 |

SECTION 12: Ecological information

12.1 Toxicity

Components:

1-Methoxypropane-2-ol:

Toxicity to fish : Remarks: Practically non toxic:
LC/EC/IC50 > 1000 mg/l

Toxicity to daphnia and other : Remarks: Practically non toxic:
aquatic invertebrates LC/EC/IC50 > 1000 mg/l

Toxicity to algae/aquatic plants : Remarks: Practically non toxic:
LC/EC/IC50 > 1000 mg/l

Toxicity to microorganisms :
Remarks: Data not available

Toxicity to fish (Chronic tox- : Remarks: Data not available
icity)

Toxicity to daphnia and other : Remarks: Data not available
aquatic invertebrates (Chron-
ic toxicity)

12.2 Persistence and degradability

Components:

1-Methoxypropane-2-ol:

Biodegradability : Remarks: Readily biodegradable meeting the 10 day window criteri-
on.
Oxidises rapidly by photo-chemical reactions in air.

12.3 Bioaccumulative potential

Components:

1-Methoxypropane-2-ol:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

12.4 Mobility in soil

Components:

1-Methoxypropane-2-ol:

Mobility : Remarks: Dissolves in water., If product enters soil, it will be
highly mobile and may contaminate groundwater.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.04.2021 |
| 1.6 | 06.04.2023 | 800001005738 | Print Date 12.04.2023 |

12.5 Results of PBT and vPvB assessment

Components:

1-Methoxypropane-2-ol:

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
Do not dispose into the environment, in drains or in water courses.
Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.
Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local regulations may be more stringent than regional or national requirements and must be complied with.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Drain container thoroughly.
After draining, vent in a safe place away from sparks and fire.
Residues may cause an explosion hazard.
Do not, puncture, cut, or weld uncleaned drums.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.04.2021 |
| 1.6 | 06.04.2023 | 800001005738 | Print Date 12.04.2023 |

Send to drum recoverer or metal reclaimer.

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

SECTION 14: Transport information

14.1 UN number or ID number

| | |
|------|--------|
| ADN | : 3092 |
| ADR | : 3092 |
| RID | : 3092 |
| IMDG | : 3092 |
| IATA | : 3092 |

14.2 UN proper shipping name

| | |
|------|------------------------|
| ADN | : 1-METHOXY-2-PROPANOL |
| ADR | : 1-METHOXY-2-PROPANOL |
| RID | : 1-METHOXY-2-PROPANOL |
| IMDG | : 1-METHOXY-2-PROPANOL |
| IATA | : 1-METHOXY-2-PROPANOL |

14.3 Transport hazard class(es)

| | |
|------|-----|
| ADN | : 3 |
| ADR | : 3 |
| RID | : 3 |
| IMDG | : 3 |
| IATA | : 3 |

14.4 Packing group

| | |
|------------------------------|-------|
| ADN | |
| Packing group | : III |
| Classification Code | : F1 |
| Labels | : 3 |
| ADR | |
| Packing group | : III |
| Classification Code | : F1 |
| Hazard Identification Number | : 30 |
| Labels | : 3 |
| RID | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.04.2021 |
| 1.6 | 06.04.2023 | 800001005738 | Print Date 12.04.2023 |

| | | |
|------------------------------|---|-----|
| Packing group | : | III |
| Classification Code | : | F1 |
| Hazard Identification Number | : | 30 |
| Labels | : | 3 |

IMDG

| | | |
|---------------|---|-----|
| Packing group | : | III |
| Labels | : | 3 |

IATA

| | | |
|---------------|---|-----|
| Packing group | : | III |
| Labels | : | 3 |

14.5 Environmental hazards

ADN

| | | |
|---------------------------|---|----|
| Environmentally hazardous | : | no |
|---------------------------|---|----|

ADR

| | | |
|---------------------------|---|----|
| Environmentally hazardous | : | no |
|---------------------------|---|----|

RID

| | | |
|---------------------------|---|----|
| Environmentally hazardous | : | no |
|---------------------------|---|----|

IMDG

| | | |
|------------------|---|----|
| Marine pollutant | : | no |
|------------------|---|----|

14.6 Special precautions for user

| | | |
|---------|---|--|
| Remarks | : | Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport. |
|---------|---|--|

14.7 Maritime transport in bulk according to IMO instruments

| | | |
|--------------------|---|----------------------------------|
| Pollution category | : | Z |
| Ship type | : | 3 |
| Product name | : | Propylene glycol monoalkyl ether |

| | | |
|-------------------------------|---|---|
| Additional Information | : | This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry. Transport in bulk according to Annex II of Marpol and the IBC Code |
|-------------------------------|---|---|

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

| | | |
|---|---|--|
| REACH - List of substances subject to authorisation (Annex XIV) | : | Product is not subject to Authorisation under REACH. |
| REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). | : | This product does not contain substances of very high concern (Regu- |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.04.2021 |
| 1.6 | 06.04.2023 | 800001005738 | Print Date 12.04.2023 |

lation (EC) No 1907/2006 (REACH),
Article 57).

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

| | |
|-------|----------|
| AIIC | : Listed |
| DSL | : Listed |
| IECSC | : Listed |
| ENCS | : Listed |
| KECI | : Listed |
| NZIoC | : Listed |
| PICCS | : Listed |
| TSCA | : Listed |
| TCSI | : Listed |

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Full text of other abbreviations

| | |
|--------------|--|
| RS OEL | : Serbia. Occupational Exposure Limits to chemicals at working place (Annex 1) |
| RS OEL / GVI | : occupational exposure limit |
| RS OEL / KGV | : Short Term Exposure Limit |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good La-

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.04.2021 |
| 1.6 | 06.04.2023 | 800001005738 | Print Date 12.04.2023 |

boratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Training advice : Provide adequate information, instruction and training for operators.

Other information : For Industry guidance and tools on REACH please visit the CEFIC website at <http://cefic.org/Industry-support>.
The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).

Classification of the mixture:

| | |
|--------------|------|
| Flam. Liq. 3 | H226 |
| STOT SE 3 | H336 |

Classification procedure:

On basis of test data.
Expert judgement and weight of evidence determination.

Identified Uses according to the Use Descriptor System

Uses - Worker

Title : Manufacture of substance- Industrial

Uses - Worker

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.04.2021 |
| 1.6 | 06.04.2023 | 800001005738 | Print Date 12.04.2023 |

Title : Use as an intermediate- Industrial

Uses - Worker

Title : Formulation & (re)packing of substances and mixtures- Industrial

Uses - Worker

Title : Uses in Coatings- IndustrialSolvent-based process.

Uses - Worker

Title : Uses in Coatings- IndustrialWater-based process.

Uses - Worker

Title : Uses in Coatings- ProfessionalSolvent-based process.

Uses - Worker

Title : Uses in Coatings- ProfessionalWater-based process.

Uses - Worker

Title : Use in Cleaning Agents- Industrial

Uses - Worker

Title : Use in Cleaning Agents- Professional

Uses - Worker

Title : Use in Agrochemicals uses- Professional

Identified Uses according to the Use Descriptor System

Uses - Consumer

Title : Uses in Coatings
- Consumer
Water-based process.

Uses - Consumer

Title : Uses in Coatings
- Consumer
Solvent-based process.

Uses - Consumer

Title : Use in Cleaning Agents
- Consumer

Uses - Consumer

Title : De-icing and anti-icing applications
- Consumer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.04.2021 |
| 1.6 | 06.04.2023 | 800001005738 | Print Date 12.04.2023 |

to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

RS / EN

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

Exposure Scenario - Worker

| | |
|-------------------------|---|
| 300000000424 | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Manufacture of substance- Industrial |
| Use Descriptor | Sector of Use: SU3, SU8, SU9 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 15 Environmental Release Categories: ERC1, ERC4 |
| Scope of process | Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/ recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities. |

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

| | |
|--|--|
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers use of substance/product up to 100% (unless stated differently)., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

| | |
|---|--|
| Contributing Scenarios | Risk Management Measures |
| General exposures. Continuous process (closed systems) PROC1 | No other specific measures identified. |
| General exposures. Continuous process with sample collection (closed systems) PROC2 | No other specific measures identified. |
| Use in contained batch processes PROC3 | No other specific measures identified. |
| General exposures (open systems) PROC4 | No other specific measures identified. |
| Process sampling (closed systems) PROC2 | No other specific measures identified. |
| Equipment cleaning and | No other specific measures identified. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

| | |
|---|--|
| maintenancePROC8a | |
| Bulk transfersDedicated facilityPROC8b | Clear transfer lines prior to de-coupling. |
| Bulk product storage(closed systems)PROC2 | No other specific measures identified. |
| Laboratory activitiesPROC15 | No other specific measures identified. |

| Section 2.2 | Control of Environmental Exposure |
|---|-----------------------------------|
| Substance is a unique structure. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 1 |
| Regional use tonnage (tonnes/year): | 2,0E+05 |
| Fraction of Regional tonnage used locally: | 0,6 |
| Annual site tonnage (tonnes/year): | 1,2E+05 |
| Maximum daily site tonnage (kg/day): | 4,0E+05 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 300 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (initial release prior to RMM): | 1,00E-03 |
| Release fraction to wastewater from process (initial release prior to RMM): | 3,00E-03 |
| Release fraction to soil from process (initial release prior to RMM): | 1,00E-04 |
| Technical conditions and measures at process level (source) to prevent release | |
| Common practices vary across sites thus conservative process re-release estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | |
| Risk from environmental exposure is driven by freshwater. | |
| Prevent discharge of undissolved substance to or recover from onsite wastewater. | |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | |
| Treat air emission to provide a typical removal efficiency of (%) | 0 |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%) | 87,3 |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | 0 |
| Organisational measures to prevent/limit release from site | |
| Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. | |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 87,3 |
| Total efficiency of removal from wastewater after onsite and offsite | 87,3 |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

| | |
|---|---------|
| (domestic treatment plant) RMMs (%) | |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 5,3E+05 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2.000 |
| Conditions and Measures related to external treatment of waste for disposal | |
| During manufacturing no waste of the substance is generated. | |
| Conditions and measures related to external recovery of waste | |
| During manufacturing no waste of the substance is generated. | |

| | |
|---|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. | |

| | |
|---------------------------------|--|
| Section 3.2 -Environment | |
| Used EUSES model. | |

| | |
|---|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
| Section 4.1 - Health | |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. | |

| | |
|--|--|
| Section 4.2 -Environment | |
| Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. | |
| Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. | |
| Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. | |
| Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org/en/reach-for-industries-libraries.html). | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

Exposure Scenario - Worker

| | |
|-------------------------|--|
| 300000000425 | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Use as an intermediate- Industrial |
| Use Descriptor | Sector of Use: SU3, SU8, SU9 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 15 Environmental Release Categories: ERC6a |
| Scope of process | Use of substance as an intermediate (not related to Strictly Controlled Conditions). Includes recycling/ recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container). |

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

| | |
|--|---|
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers use of substance/product up to 100% (unless stated differently). |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

| | |
|---|--|
| Contributing Scenarios | Risk Management Measures |
| General exposures. Continuous process (closed systems) PROC1 | No other specific measures identified. |
| General exposures. Continuous process with sample collection (closed systems) PROC2 | No other specific measures identified. |
| Use in contained batch processes PROC3 | No other specific measures identified. |
| General exposures (open systems) PROC4 | No other specific measures identified. |
| Process sampling (closed systems) PROC2 | No other specific measures identified. |
| Equipment cleaning and | No other specific measures identified. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

| | |
|---|--|
| maintenancePROC8a | |
| Bulk transfersDedicated facilityPROC8b | Clear transfer lines prior to de-coupling. |
| Bulk product storage(closed systems)PROC2 | No other specific measures identified. |
| Laboratory activitiesPROC15 | No other specific measures identified. |

| Section 2.2 | Control of Environmental Exposure |
|---|-----------------------------------|
| Substance is a unique structure. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 1 |
| Regional use tonnage (tonnes/year): | 5,7E+04 |
| Fraction of Regional tonnage used locally: | 0,2 |
| Annual site tonnage (tonnes/year): | 1,14E+04 |
| Maximum daily site tonnage (kg/day): | 3,8E+04 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 300 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (initial release prior to RMM): | 1,00E-04 |
| Release fraction to wastewater from process (initial release prior to RMM): | 5,00E-04 |
| Release fraction to soil from process (initial release prior to RMM): | 1,00E-04 |
| Technical conditions and measures at process level (source) to prevent release | |
| Common practices vary across sites thus conservative process re-release estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | |
| Risk from environmental exposure is driven by freshwater. | |
| Prevent discharge of undissolved substance to or recover from onsite wastewater. | |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | |
| Treat air emission to provide a typical removal efficiency of (%) | 0 |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%) | 87,3 |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | 0 |
| Organisational measures to prevent/limit release from site | |
| Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. | |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 87,3 |
| Total efficiency of removal from wastewater after onsite and offsite | 87,3 |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

| | |
|---|---------|
| (domestic treatment plant) RMMs (%) | |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 2,9E+06 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2.000 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

| | |
|---|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. | |

| |
|---------------------------------|
| Section 3.2 -Environment |
| Used EUSES model. |

| | |
|---|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
| Section 4.1 - Health | |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. | |

| |
|--|
| Section 4.2 -Environment |
| Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. |
| Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. |
| Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. |
| Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org/en/reach-for-industries-libraries.html). |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version
1.6

Revision Date:
06.04.2023

SDS Number:
800001005738

Date of last issue: 07.04.2021
Print Date 12.04.2023

Exposure Scenario - Worker

| | |
|-------------------------|---|
| 300000000427 | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Formulation & (re)packing of substances and mixtures- Industrial |
| Use Descriptor | Sector of Use: SU3, SU10 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 8a, PROC 8b, PROC 9, PROC 14, PROC 15 Environmental Release Categories: ERC2 |
| Scope of process | Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities. |

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

| | |
|---|--|
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers use of substance/product up to 100% (unless stated differently)., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

| | |
|--|--|
| Contributing Scenarios | Risk Management Measures |
| General exposures. Continuous process- no sampling (closed systems) PROC1 | No other specific measures identified. |
| General exposures. Continuous process- with sample collection (closed systems) PROC2 | No other specific measures identified. |
| General exposures. Use in contained batch processes with sample collection PROC3 | No other specific measures identified. |
| General exposures (open systems) PROC4 | No other specific measures identified. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

| | |
|---|--|
| Batch processes at elevated temperatures(closed systems)PROC3 | No other specific measures identified. |
| Process sampling(closed systems)PROC3 | No other specific measures identified. |
| Bulk transfersDedicated facilityPROC8b | No other specific measures identified. |
| Mixing operations (open systems)PROC5 | No other specific measures identified. |
| Transfer from/pouring from containersManualPROC8a | No other specific measures identified. |
| Equipment cleaning and maintenancePROC8a | No other specific measures identified. |
| Drum/batch transfersDedicated facilityPROC8b | No other specific measures identified. |
| Production or preparation or articles by tableting, compression, extrusion or pelletisationPROC14 | No other specific measures identified. |
| Drum and small package fillingDedicated facilityPROC9 | No other specific measures identified. |
| Bulk product storage(closed systems)PROC2 | No other specific measures identified. |
| Laboratory activitiesPROC15 | No other specific measures identified. |

| Section 2.2 | Control of Environmental Exposure |
|--|-----------------------------------|
| Substance is a unique structure. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 1 |
| Regional use tonnage (tonnes/year): | 6,3E+04 |
| Fraction of Regional tonnage used locally: | 0,4 |
| Annual site tonnage (tonnes/year): | 3,7E+04 |
| Maximum daily site tonnage (kg/day): | 1,3E+05 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 300 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (initial release prior to RMM): | 5,00E-03 |
| Release fraction to wastewater from process (initial release prior to RMM): | 3,00E-03 |
| Release fraction to soil from process (initial release prior to RMM): | 1,00E-04 |
| Technical conditions and measures at process level (source) to prevent release | |
| Common practices vary across sites thus conservative process release estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emis- | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

| | |
|---|---------|
| sions and releases to soil | |
| Risk from environmental exposure is driven by freshwater. | |
| Prevent discharge of undissolved substance to or recover from onsite wastewater. | |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | |
| Treat air emission to provide a typical removal efficiency of (%) | 0 |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%) | 87,3 |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | 0 |
| Organisational measures to prevent/limit release from site | |
| Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. | |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 87,3 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 87,3 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 5,3E+05 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2.000 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

| | |
|---|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. | |

| | |
|---------------------------------|--|
| Section 3.2 -Environment | |
| Used EUSES model. | |

| | |
|---|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
| Section 4.1 - Health | |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version
1.6

Revision Date:
06.04.2023

SDS Number:
800001005738

Date of last issue: 07.04.2021
Print Date 12.04.2023

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version
1.6

Revision Date:
06.04.2023

SDS Number:
800001005738

Date of last issue: 07.04.2021
Print Date 12.04.2023

Exposure Scenario - Worker

| | |
|-------------------------|--|
| 300000000428 | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Uses in Coatings- IndustrialSolvent-based process. |
| Use Descriptor | Sector of Use: SU3 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 7, PROC 8a, PROC 8b, PROC 10, PROC 13, PROC 15 Environmental Release Categories: ERC4 |
| Scope of process | Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities. |

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

| | |
|---|--|
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers use of substance/product up to 100% (unless stated differently)., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

| | |
|---|--|
| Contributing Scenarios | Risk Management Measures |
| General exposures.(closed systems)PROC1 | No other specific measures identified. |
| General exposures.(closed systems)with sample collectionPROC2 | No other specific measures identified. |
| Film formation - force drying, stoving and other technologies.PROC2 | No other specific measures identified. |
| Mixing operations (closed systems)PROC3 | No other specific measures identified. |
| Film formation - air dryingPROC4 | No other specific measures identified. |
| Preparation of material for applicationMixing opera- | No other specific measures identified. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

| | |
|--|---|
| tions (open systems)PROC5 | |
| Spraying (automatic/robotic)PROC7 | Carry out in a vented booth or extracted enclosure. |
| SprayingManualPROC7 | Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Wear suitable gloves tested to EN374. |
| Material transfer-sPROC8aPROC8b | No other specific measures identified. |
| Roller, spreader, flow applicationPROC10 | Wear suitable gloves tested to EN374. |
| Dipping, immersion and pouringPROC13 | No other specific measures identified. |
| Laboratory activitiesPROC15 | No other specific measures identified. |

| Section 2.2 | Control of Environmental Exposure |
|---|-----------------------------------|
| Substance is a unique structure. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 1 |
| Regional use tonnage (tonnes/year): | 6,3E+04 |
| Fraction of Regional tonnage used locally: | 0,05 |
| Annual site tonnage (tonnes/year): | 3,2E+03 |
| Maximum daily site tonnage (kg/day): | 1,1E+04 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 300 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (initial release prior to RMM): | 0,9 |
| Release fraction to wastewater from process (initial release prior to RMM): | 0,02 |
| Release fraction to soil from process (initial release prior to RMM): | 0,001 |
| Technical conditions and measures at process level (source) to prevent release | |
| Common practices vary across sites thus conservative process release estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | |
| Risk from environmental exposure is driven by freshwater. | |
| Prevent discharge of undissolved substance to or recover from onsite wastewater. | |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | |
| Treat air emission to provide a typical removal efficiency of (%) | 70 |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%) | 87,3 |
| If discharging to domestic sewage treatment plant, no secondary | 0 |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

| | |
|---|---------|
| wastewater treatment required. | |
| Organisational measures to prevent/limit release from site | |
| Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. | |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 87,3 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 87,3 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 7,9E+04 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2.000 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

| | |
|---|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. | |

| | |
|---------------------------------|--|
| Section 3.2 -Environment | |
| Used EUSES model. | |

| | |
|---|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
| Section 4.1 - Health | |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. | |

| | |
|--|--|
| Section 4.2 -Environment | |
| Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. | |
| Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. | |
| Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. | |
| Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org/en/reach-for-industries-libraries.html). | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version
1.6

Revision Date:
06.04.2023

SDS Number:
800001005738

Date of last issue: 07.04.2021
Print Date 12.04.2023

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

Exposure Scenario - Worker

| | |
|-------------------------|--|
| 300000000429 | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Uses in Coatings- IndustrialWater-based process. |
| Use Descriptor | Sector of Use: SU3 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 7, PROC 8a, PROC 8b, PROC 10, PROC 13, PROC 15 Environmental Release Categories: ERC4 |
| Scope of process | Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities. |

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

| | |
|--|---|
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 5%., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

| | |
|---|--|
| Contributing Scenarios | Risk Management Measures |
| General exposures.(closed systems)PROC1 | No other specific measures identified. |
| General exposures.(closed systems)with sample collectionPROC2 | No other specific measures identified. |
| Film formation - force drying, stoving and other technologies.PROC2 | No other specific measures identified. |
| Mixing operations (closed systems)General exposures (closed systems)PROC3 | No other specific measures identified. |
| Film formation - air dryingPROC4 | No other specific measures identified. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

| | |
|--|--|
| Preparation of material for application Mixing operations (open systems) PROC5 | No other specific measures identified. |
| Spraying (automatic/robotic) PROC7 | Wear suitable gloves tested to EN374. |
| Spraying Manual PROC7 | Wear suitable gloves tested to EN374. |
| Material transfers Non-dedicated facility PROC8a | No other specific measures identified. |
| Material transfers Dedicated facility PROC8b | No other specific measures identified. |
| Roller, spreader, flow application PROC10 | No other specific measures identified. |
| Dipping, immersion and pouring PROC13 | No other specific measures identified. |
| Laboratory activities PROC15 | No other specific measures identified. |

| Section 2.2 Control of Environmental Exposure | |
|--|---------|
| Substance is a unique structure. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 1 |
| Regional use tonnage (tonnes/year): | 2,6E+03 |
| Fraction of Regional tonnage used locally: | 0,05 |
| Annual site tonnage (tonnes/year): | 130 |
| Maximum daily site tonnage (kg/day): | 433 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 300 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (initial release prior to RMM): | 0,8 |
| Release fraction to wastewater from process (initial release prior to RMM): | 0,1 |
| Release fraction to soil from process (initial release prior to RMM): | 0,001 |
| Technical conditions and measures at process level (source) to prevent release | |
| Common practices vary across sites thus conservative process release estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | |
| Risk from environmental exposure is driven by freshwater. | |
| Prevent discharge of undissolved substance to or recover from onsite wastewater. | |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | |
| Treat air emission to provide a typical removal efficiency of (%) | 0 |
| Treat onsite wastewater (prior to receiving water discharge) to provide | 87,3 |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

| | |
|---|---------|
| the required removal efficiency of \geq (%) | |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | 0 |
| Organisational measures to prevent/limit release from site | |
| Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. | |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 87,3 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 87,3 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 1,4E+05 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2.000 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

| | |
|---|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. | |

| |
|---------------------------------|
| Section 3.2 -Environment |
| Used EUSES model. |

| | |
|---|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
| Section 4.1 - Health | |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. | |

| |
|--|
| Section 4.2 -Environment |
| Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. |
| Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. |
| Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version
1.6

Revision Date:
06.04.2023

SDS Number:
800001005738

Date of last issue: 07.04.2021
Print Date 12.04.2023

| |
|--|
| Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org/en/reach-for-industries-libraries.html). |
|--|

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

Exposure Scenario - Worker

| | |
|-------------------------|--|
| 300000000430 | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Uses in Coatings- ProfessionalSolvent-based process. |
| Use Descriptor | Sector of Use: SU22 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 8a, PROC 8b, PROC 10, PROC 11, PROC 13, PROC 15, PROC 19 Environmental Release Categories: ERC8a, ERC8d |
| Scope of process | Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, brush, spreader by hand or similar methods, and film formation), and equipment cleaning, maintenance and associated laboratory activities. |

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

| | |
|---|--|
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers use of substance/product up to 100% (unless stated differently)., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

| | |
|---|--|
| Contributing Scenarios | Risk Management Measures |
| Filling/ preparation of equipment from drums or containers.Use in contained systemsPROC1PROC2 | No other specific measures identified. |
| General exposures.(closed systems)Use in contained systemsPROC2 | No other specific measures identified. |
| Film formation - air dryingPROC4 | No specific measures identified. |
| Preparation of material for applicationPROC3PROC5 | Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). , or: Ensure operation is undertaken outdoors. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

| | |
|--|---|
| Material transfersDrum/batch transfersNon-dedicated facilityPROC8a | Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). |
| Material transfersDedicated facilityDrum/batch transfersPROC8b | No other specific measures identified. |
| Roller, spreader, flow applicationPROC10 | Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). , or: Ensure operation is undertaken outdoors. Wear suitable gloves tested to EN374. |
| SprayingManualIndoorPROC11 | Carry out in a vented booth or extracted enclosure. Wear a respirator conforming to EN140 with Type A filter or better. |
| SprayingManualOutdoorPROC11 | Ensure operation is undertaken outdoors. Wear a respirator conforming to EN140 with Type A filter or better. Wear suitable gloves tested to EN374. |
| Dipping, immersion and pouringPROC13 | Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). , or: Ensure operation is undertaken outdoors. |
| Laboratory activitiesPROC15 | No other specific measures identified. |
| Hand application - fingerpaints, pastels, adhesivesPROC19 | Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). , or: Ensure operation is undertaken outdoors. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. |

| Section 2.2 | Control of Environmental Exposure |
|--|-----------------------------------|
| Substance is a unique structure. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 1 |
| Regional use tonnage (tonnes/year): | 6,3E+04 |
| Fraction of Regional tonnage used locally: | 0,05 |
| Annual site tonnage (tonnes/year): | 3.150 |
| Maximum daily site tonnage (kg/day): | 1,1E+04 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 300 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

| | |
|---|---------|
| Release fraction to air from process (initial release prior to RMM): | 0,9 |
| Release fraction to wastewater from process (initial release prior to RMM): | 0,02 |
| Release fraction to soil from process (initial release prior to RMM): | 0,001 |
| Technical conditions and measures at process level (source) to prevent release | |
| Common practices vary across sites thus conservative process re-release estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | |
| Risk from environmental exposure is driven by freshwater. | |
| Prevent discharge of undissolved substance to or recover from onsite wastewater. | |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | |
| Treat air emission to provide a typical removal efficiency of (%) | 0 |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%) | 87,3 |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | 0 |
| Organisational measures to prevent/limit release from site | |
| Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. | |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 87,3 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 87,3 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 8,0E+04 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2.000 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

| | |
|---|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. | |

| |
|---------------------------------|
| Section 3.2 -Environment |
| Used EUSES model. |

| | |
|------------------|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE |
|------------------|--|

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version
1.6

Revision Date:
06.04.2023

SDS Number:
800001005738

Date of last issue: 07.04.2021
Print Date 12.04.2023

| EXPOSURE SCENARIO | |
|--|--|
| Section 4.1 - Health | |
| Section 4.2 -Environment | |
| Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. | |
| Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. | |
| Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. | |
| Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org/en/reach-for-industries-libraries.html). | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version
1.6

Revision Date:
06.04.2023

SDS Number:
800001005738

Date of last issue: 07.04.2021
Print Date 12.04.2023

Exposure Scenario - Worker

| | |
|-------------------------|--|
| 300000000431 | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Uses in Coatings- Professional Water-based process. |
| Use Descriptor | Sector of Use: SU22 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 8a, PROC 8b, PROC 10, PROC 11, PROC 13, PROC 15 Environmental Release Categories: ERC8a, ERC8d |
| Scope of process | Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, brush, spreader by hand or similar methods, and film formation), and equipment cleaning, maintenance and associated laboratory activities. |

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

| | |
|---|---|
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 5%., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

| | |
|--|--|
| Contributing Scenarios | Risk Management Measures |
| Filling/ preparation of equipment from drums or containers. Use in contained systems PROC2 | No other specific measures identified. |
| General exposures (closed systems) Use in contained systems PROC1 PROC2 | No other specific measures identified. |
| Preparation of material for application PROC3 PROC5 | No specific measures identified. |
| Film formation - air drying PROC4 | No other specific measures identified. |
| Material transfers Drum/batch transfers PROC8a PROC8b | No other specific measures identified. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

| | |
|--|---|
| Roller, spreader, flow applicationPROC10 | No other specific measures identified. |
| SprayingManualPROC11 | Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). , or: Ensure operation is undertaken outdoors. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. |
| Dipping, immersion and pouringPROC13 | No other specific measures identified. |
| Laboratory activitiesPROC15 | No other specific measures identified. |
| Hand application - finger-paints, pastels, adhesivesPROC19 | Wear suitable gloves tested to EN374. |

| Section 2.2 | Control of Environmental Exposure |
|---|-----------------------------------|
| Substance is a unique structure. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 1 |
| Regional use tonnage (tonnes/year): | 2,6E+03 |
| Fraction of Regional tonnage used locally: | 0,05 |
| Annual site tonnage (tonnes/year): | 130 |
| Maximum daily site tonnage (kg/day): | 433 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 300 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (initial release prior to RMM): | 0,8 |
| Release fraction to wastewater from process (initial release prior to RMM): | 0,1 |
| Release fraction to soil from process (initial release prior to RMM): | 0,001 |
| Technical conditions and measures at process level (source) to prevent release | |
| Common practices vary across sites thus conservative process release estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | |
| Risk from environmental exposure is driven by freshwater. | |
| Prevent discharge of undissolved substance to or recover from onsite wastewater. | |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | |
| Treat air emission to provide a typical removal efficiency of (%) | 0 |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%) | 87,3 |
| If discharging to domestic sewage treatment plant, no secondary | 0 |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

| | |
|---|---------|
| wastewater treatment required. | |
| Organisational measures to prevent/limit release from site | |
| Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. | |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 87,3 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 87,3 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 1,5E+04 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2.000 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

| | |
|---|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. | |

| | |
|---------------------------------|--|
| Section 3.2 -Environment | |
| Used EUSES model. | |

| | |
|---|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
| Section 4.1 - Health | |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. | |

| | |
|--|--|
| Section 4.2 -Environment | |
| Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. | |
| Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. | |
| Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. | |
| Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org/en/reach-for-industries-libraries.html). | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version
1.6

Revision Date:
06.04.2023

SDS Number:
800001005738

Date of last issue: 07.04.2021
Print Date 12.04.2023

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version
1.6

Revision Date:
06.04.2023

SDS Number:
800001005738

Date of last issue: 07.04.2021
Print Date 12.04.2023

Exposure Scenario - Worker

| | |
|-------------------------|---|
| 300000000434 | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Use in Cleaning Agents- Industrial |
| Use Descriptor | Sector of Use: SU3 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 7, PROC 8a, PROC 8b, PROC 10, PROC 13 Environmental Release Categories: ERC4, ESVOC SpERC 4.4a.v1 |
| Scope of process | Covers the use as a component of cleaning products including transfer from storage, pouring/unloading from drums or containers. Exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, automated and by hand), related equipment cleaning and maintenance. |

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

| | |
|---|--|
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers use of substance/product up to 100% (unless stated differently)., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

| | |
|---|--|
| Contributing Scenarios | Risk Management Measures |
| Bulk transfersNon-dedicated facilityPROC8a | No specific measures identified. |
| Use in contained system-Automated process with (semi) closed systems.PROC2 | No other specific measures identified. |
| Use in contained system-Automated process with (semi) closed systems.Drum/batch transfer-sPROC3 | No other specific measures identified. |
| Application of cleaning products in closed systemsPROC2 | No other specific measures identified. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

| | |
|---|--|
| Filling/ preparation of equipment from drums or containers.Dedicated facilityPROC8b | No other specific measures identified. |
| Use in contained batch processesTreatment by heatingPROC4 | Provide extraction ventilation at points where emissions occur. |
| Degreasing small objects in cleaning stationPROC13 | No other specific measures identified. |
| Cleaning with low-pressure washersPROC10 | Wear suitable gloves tested to EN374. |
| Cleaning with high pressure washersPROC7 | Avoid carrying out activities involving exposure for more than 4 hours Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). |
| CleaningSurfacesno sprayingManualPROC10 | Wear suitable gloves tested to EN374. |
| Storage.PROC1 | Store substance within a closed system. |

| Section 2.2 | Control of Environmental Exposure |
|---|-----------------------------------|
| Substance is a unique structure. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 1 |
| Regional use tonnage (tonnes/year): | 5,2E+03 |
| Fraction of Regional tonnage used locally: | 0,02 |
| Annual site tonnage (tonnes/year): | 1,04E+02 |
| Maximum daily site tonnage (kg/day): | 5,2E+02 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 300 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (initial release prior to RMM): | 0,3 |
| Release fraction to wastewater from process (initial release prior to RMM): | 1,0E-04 |
| Release fraction to soil from process (initial release prior to RMM): | 0 |
| Technical conditions and measures at process level (source) to prevent release | |
| Common practices vary across sites thus conservative process release estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | |
| Risk from environmental exposure is driven by marine water. | |
| Prevent discharge of undissolved substance to or recover from onsite wastewater. | |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

| | |
|---|---------|
| Treat air emission to provide a typical removal efficiency of (%) | 0 |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%) | 87,3 |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | 0 |
| Organisational measures to prevent/limit release from site | |
| Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. | |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 87,3 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 87,3 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 3,1E+06 |
| Assumed domestic sewage treatment plant flow (m ³ /d) | 2.000 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

| | |
|---|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. | |

| |
|---------------------------------|
| Section 3.2 -Environment |
| Used EUSES model. |

| | |
|---|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
| Section 4.1 - Health | |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. | |

| |
|--|
| Section 4.2 -Environment |
| Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. |
| Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version
1.6

Revision Date:
06.04.2023

SDS Number:
800001005738

Date of last issue: 07.04.2021
Print Date 12.04.2023

| |
|---|
| Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. |
|---|

| |
|--|
| Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org/en/reach-for-industries-libraries.html). |
|--|

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

Exposure Scenario - Worker

| | |
|-------------------------|---|
| 300000000435 | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Use in Cleaning Agents- Professional |
| Use Descriptor | Sector of Use: SU22 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 10, PROC 11, PROC 13 Environmental Release Categories: ERC8a, ERC8d, ESVOC SpERC 8.4b.v1 |
| Scope of process | Covers the use as a component of cleaning products including pouring/unloading from drums or containers; and exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping automated and by hand). |

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

| | |
|---|--|
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers use of substance/product up to 100% (unless stated differently)., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

| | |
|--|--|
| Contributing Scenarios | Risk Management Measures |
| Filling/ preparation of equipment from drums or containers.Dedicated facilityPROC8b | No specific measures identified. |
| Use in contained systemsAutomated process with (semi) closed systems.PROC2 | No other specific measures identified. |
| Use in contained systemsAutomated process with (semi) closed systems.Drum/batch transfersPROC3 | No other specific measures identified. |
| Semi Automated process. (e.g.: Semi automatic application of floor care and maintenance products)PROC4 | No other specific measures identified. |
| Filling/ preparation of equipment from drums or containers.Non-dedicated facilityPROC8a | Ensure operation is undertaken outdoors. , or: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version
1.6

Revision Date:
06.04.2023

SDS Number:
800001005738

Date of last issue: 07.04.2021
Print Date 12.04.2023

| | |
|--|---|
| | Avoid carrying out activities involving exposure for more than 4 hours |
| CleaningSurfacesManualDipping, immersion and pouringPROC13 | Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). |
| Cleaning with low-pressure washer-sPROC10 | Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). |
| Cleaning with high pressure washersIndoorPROC11 | Limit the substance content in the product to 5 %. Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Wear suitable gloves tested to EN374. |
| Cleaning with high pressure washersOutdoorPROC11 | Limit the substance content in the product to 5 %. Ensure operation is undertaken outdoors. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. |
| CleaningSurfacesManualSprayingPROC10 | Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Wear suitable gloves tested to EN374. |
| Ad hoc manual application via trigger sprays, dipping, etc.Rolling, BrushingPROC10 | Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Wear suitable gloves tested to EN374. |
| Application of cleaning products in closed systemsPROC4 | No other specific measures identified. |
| Cleaning of medical devicesPROC4 | No other specific measures identified. |
| Storage.PROC1 | Store substance within a closed system. |

| Section 2.2 | Control of Environmental Exposure |
|--|-----------------------------------|
| Substance is a unique structure. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 0,1 |
| Regional use tonnage (tonnes/year): | 520 |
| Fraction of Regional tonnage used locally: | 5,0E-04 |
| Annual site tonnage (tonnes/year): | 0,26 |
| Maximum daily site tonnage (kg/day): | 0,712 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 365 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (initial release prior to RMM): | 2,00E-02 |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

| | |
|---|----------|
| Release fraction to wastewater from process (initial release prior to RMM): | 1,00E-06 |
| Release fraction to soil from process (initial release prior to RMM): | 0 |
| Technical conditions and measures at process level (source) to prevent release | |
| Common practices vary across sites thus conservative process re-release estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | |
| Risk from environmental exposure is driven by marine water. | |
| Prevent discharge of undissolved substance to or recover from onsite wastewater. | |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | |
| Treat air emission to provide a typical removal efficiency of (%) | 0 |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%) | 87,3 |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | 0 |
| Organisational measures to prevent/limit release from site | |
| Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. | |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 87,3 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 87,3 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 550 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2.000 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

| | |
|---|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. | |

| | |
|---------------------------------|--|
| Section 3.2 -Environment | |
| Used EUSES model. | |

| | |
|------------------|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|------------------|--|

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.04.2021 |
| 1.6 | 06.04.2023 | 800001005738 | Print Date 12.04.2023 |

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

Exposure Scenario - Worker

| | |
|-------------------------|--|
| 300000000440 | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Use in Agrochemicals uses- Professional |
| Use Descriptor | Sector of Use: SU22 Process Categories: PROC 1, PROC 2, PROC 4, PROC 8a, PROC 8b, PROC 11, PROC 13 Environmental Release Categories: ERC8a, ERC8d |
| Scope of process | Use as an agrochemical excipient for application by manual or machine spraying, smokes and fogging; including equipment clean-downs and disposal. |

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

| | |
|---|---|
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers percentage substance in the product up to 25%. |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

| | |
|---|--|
| Contributing Scenarios | Risk Management Measures |
| Transfer from/pouring from containersDedicated facilityPROC8b | No specific measures identified. |
| Mixing operations (open systems)OutdoorPROC4 | No other specific measures identified. |
| Spraying/ fogging by manual applicationOutdoorPROC11 | Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140 with Type A filter or better. |
| Spraying/ fogging by machine applicationPROC11 | Carry out in a vented booth or extracted enclosure. |
| Ad hoc manual application via trigger sprays, dipping, etc.PROC13 | No other specific measures identified. |
| Equipment cleaning and maintenancePROC8a | No other specific measures identified. |
| Disposal of wastesOutdoorPROC8a | No other specific measures identified. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

| | |
|---------------------------|--|
| Storage.OutdoorPROC1PROC2 | No other specific measures identified. |
|---------------------------|--|

| Section 2.2 | Control of Environmental Exposure |
|---|-----------------------------------|
| Substance is a unique structure. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 1 |
| Regional use tonnage (tonnes/year): | 650 |
| Fraction of Regional tonnage used locally: | 0,001 |
| Annual site tonnage (tonnes/year): | 0,65 |
| Maximum daily site tonnage (kg/day): | 325 |
| Frequency and Duration of Use | |
| Intermittent release. | |
| Emission Days (days/year): | 2 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (initial release prior to RMM): | 0,05 |
| Release fraction to wastewater from process (initial release prior to RMM): | 0,1 |
| Release fraction to soil from process (initial release prior to RMM): | 0,8 |
| Technical conditions and measures at process level (source) to prevent release | |
| Common practices vary across sites thus conservative process re-release estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | |
| Risk from environmental exposure is driven by marine water. | |
| Prevent discharge of undissolved substance to or recover from onsite wastewater. | |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | |
| Treat air emission to provide a typical removal efficiency of (%) | 0 |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%) | 87,3 |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | 0 |
| Organisational measures to prevent/limit release from site | |
| Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. | |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 87,3 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 87,3 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2.000 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

Conditions and measures related to external recovery of waste

External recovery and recycling of waste should comply with applicable local and/or regional regulations.

SECTION 3

EXPOSURE ESTIMATION

Section 3.1 - Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 -Environment

Used EUSES model.

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version
1.6

Revision Date:
06.04.2023

SDS Number:
800001005738

Date of last issue: 07.04.2021
Print Date 12.04.2023

Exposure Scenario - Consumer

| | |
|-------------------------|---|
| 300000001041 | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Uses in Coatings - Consumer Water-based process. |
| Use Descriptor | Sector of Use: SU21 Product Categories: PC9a Environmental Release Categories: ERC8a, ERC8d |
| Scope of process | Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including product transfer and preparation, application by brush, spray by hand or similar methods) and equipment cleaning. |

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

| | |
|--|-------------------------------------|
| Section 2.1 | Control of Consumer Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure > 10 Pa |
| Concentration of the Substance in Mixture/Article | Covers concentration up to (%): 5 % |
| Amounts Used | |
| for each use event, covers amount up to (g): | 1.880 |
| Frequency and Duration of Use | |
| covers use up to (times/day of use): | 1 |
| Covers use up to (hours/event): | 3 |
| Other Operational Conditions affecting Exposure | |
| Covers use at ambient temperatures. | |
| Covers use in room size of 20m ³ | |

| | |
|--|---|
| Product Categories | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
| Coatings and paints, thinners, paint removers Waterborne latex wall paint. Solvent rich, high solid, water borne paint. Aerosol spray can. Removers (paint-, glue-, wall paper-, sealant-remover). | Avoid using in room with closed doors. Avoid using when windows closed. |

| | |
|----------------------------------|--|
| Section 2.2 | Control of Environmental Exposure |
| Substance is a unique structure. | |
| Readily biodegradable. | |
| Amounts Used | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

| | |
|---|---------|
| Fraction of EU tonnage used in region: | 0,1 |
| Regional use tonnage (tonnes/year): | 260 |
| Fraction of Regional tonnage used locally: | 1,0E-04 |
| Annual site tonnage (tonnes/year): | 2,6E-02 |
| Maximum daily site tonnage (kg/day): | 8,7E-02 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 300 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (initial release prior to RMM): | 0,8 |
| Release fraction to wastewater from process (initial release prior to RMM): | 0,15 |
| Release fraction to soil from process (initial release prior to RMM): | 0,01 |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 87,3 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 87,3 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 1,5E+04 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2.000 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

| | |
|---|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated. The Consexpo model has been used to estimate consumer exposures unless otherwise indicated. | |

| |
|---------------------------------|
| Section 3.2 -Environment |
| Used EUSES model. |

| | |
|---|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
| Section 4.1 - Health | |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

| | | | |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.04.2021 |
| 1.6 | 06.04.2023 | 800001005738 | Print Date 12.04.2023 |

should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

Exposure Scenario - Consumer

| | |
|-------------------------|---|
| 300000001044 | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Uses in Coatings - Consumer Solvent-based process. |
| Use Descriptor | Sector of Use: SU21 Product Categories: PC9a Environmental Release Categories: ERC8a, ERC8d |
| Scope of process | Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including product transfer and preparation, application by brush, spray by hand or similar methods) and equipment cleaning. |

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

| | |
|--|--------------------------------------|
| Section 2.1 | Control of Consumer Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure > 10 Pa |
| Concentration of the Substance in Mixture/Article | Covers concentration up to (%): 10 % |
| Amounts Used | |
| for each use event, covers amount up to (g): | 500 |
| Frequency and Duration of Use | |
| covers use up to (times/day of use): | 1 |
| Covers use up to (hours/event): | 1,1 |
| Other Operational Conditions affecting Exposure | |
| Covers use in room size of 20m ³ | |

| | |
|--|--|
| Product Categories | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
| Coatings and paints, thinners, paint removers Solvent rich, high solid, water borne paint. | Avoid using in room with closed doors. |
| | Avoid using when windows closed. |

| | |
|--|--|
| Section 2.2 | Control of Environmental Exposure |
| Substance is a unique structure. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 1 |
| Regional use tonnage (tonnes/year): | 6,3E+04 |
| Fraction of Regional tonnage used locally: | 0,0001 |
| Annual site tonnage (tonnes/year): | 6,3 |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

| | |
|---|---------|
| Maximum daily site tonnage (kg/day): | 3,2E+03 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 2 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (initial release prior to RMM): | 0,8 |
| Release fraction to wastewater from process (initial release prior to RMM): | 0,15 |
| Release fraction to soil from process (initial release prior to RMM): | 0,01 |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 87,3 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 87,3 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2.000 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

| | |
|---|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated. The Consexpo model has been used to estimate consumer exposures unless otherwise indicated. | |

| |
|---------------------------------|
| Section 3.2 -Environment |
| Used EUSES model. |

| | |
|---|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
| Section 4.1 - Health | |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. | |

| |
|--|
| Section 4.2 -Environment |
| Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version
1.6

Revision Date:
06.04.2023

SDS Number:
800001005738

Date of last issue: 07.04.2021
Print Date 12.04.2023

| |
|--|
| measures. |
| Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. |
| Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. |
| Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org/en/reach-for-industries-libraries.html). |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

Exposure Scenario - Consumer

| | |
|-------------------------|---|
| 300000001043 | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Use in Cleaning Agents - Consumer |
| Use Descriptor | Sector of Use: SU21 Product Categories: PC35 Environmental Release Categories: ERC8a, ERC8d, ESVOC SpERC 8.4c.v1 |
| Scope of process | Covers general exposures to consumers arising from the use of household products sold as washing and cleaning products, aerosols, coatings, de-icers, lubricants and air care products. |

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

| | |
|--|--------------------------------------|
| Section 2.1 | Control of Consumer Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure > 10 Pa |
| Concentration of the Substance in Mixture/Article | Covers concentration up to (%): 10 % |
| Amounts Used | |
| for each use event, covers amount up to (g): | 16 |
| Frequency and Duration of Use | |
| Unless stated otherwise. | |
| Covers use up to (hours/event): | 1 |
| covers use up to (times/day of use): | 3 |
| Covers use up to (days/year): | 365 |
| Other Operational Conditions affecting Exposure | |
| Covers use at ambient temperatures. Covers use under typical household ventilation. | |

| | |
|--|--|
| Product Categories | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
| Washing and cleaning products (including solvent based products) Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners). | Covers use up to 1 times/day of use |
| | Covers use in room size of 15 m ³ |
| Washing and cleaning products (including solvent based products) Cleaners, liquids (all purpose clean- | Covers use up to 3 times/day of use |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

| | |
|---|----------------------------------|
| ers, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners). | |
| | Covers use in room size of 15 m3 |

| | |
|---|--|
| Section 2.2 | Control of Environmental Exposure |
| Substance is a unique structure. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 0,1 |
| Regional use tonnage (tonnes/year): | 26 |
| Fraction of Regional tonnage used locally: | 5,0E-04 |
| Annual site tonnage (tonnes/year): | 0,01 |
| Maximum daily site tonnage (kg/day): | 0,027 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 365 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (initial release prior to RMM): | 0,95 |
| Release fraction to wastewater from process (initial release prior to RMM): | 0,025 |
| Release fraction to soil from process (initial release prior to RMM): | 0,025 |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 87,3 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 87,3 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2.000 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

| | |
|---|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated. The Consexpo model has been used to estimate consumer exposures unless otherwise indicated. | |

| | |
|---------------------------------|--|
| Section 3.2 -Environment | |
| Used EUSES model. | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version
1.6

Revision Date:
06.04.2023

SDS Number:
800001005738

Date of last issue: 07.04.2021
Print Date 12.04.2023

| |
|--|
| |
|--|

| | |
|------------------|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|------------------|--|

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version
1.6

Revision Date:
06.04.2023

SDS Number:
800001005738

Date of last issue: 07.04.2021
Print Date 12.04.2023

Exposure Scenario - Consumer

| | |
|-------------------------|--|
| 300000001045 | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | De-icing and anti-icing applications - Consumer |
| Use Descriptor | Sector of Use: SU21 Product Categories: PC4 Environmental Release Categories: ERC8d |
| Scope of process | De-icing of vehicles and similar equipment by spraying. |

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

| | |
|--|--------------------------------------|
| Section 2.1 | Control of Consumer Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure > 10 Pa |
| Concentration of the Sub-stance in Mixture/Article | Covers concentration up to (%): 30 % |
| Amounts Used | |
| for each use event, covers amount up to (g): | 500 |
| Frequency and Duration of Use | |
| Covers use up to (hours/event): | 0,5 |
| covers use up to (times/day of use): | 1 |
| Other Operational Conditions affecting Exposure | |
| Covers outdoor use. | |

| | |
|-----------------------------------|--|
| Product Categories | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
| Anti-Freeze and de-icing products | No specific risk management measure identified beyond those operational conditions stated. |

| | |
|--|--|
| Section 2.2 | Control of Environmental Exposure |
| Substance is a unique structure. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 0,1 |
| Regional use tonnage (tonnes/year): | 260 |
| Fraction of Regional tonnage used locally: | 0,002 |
| Annual site tonnage (tonnes/year): | 0,52 |
| Maximum daily site tonnage (kg/day): | 260 |
| Frequency and Duration of Use | |
| Continuous release. | |
| Emission Days (days/year): | 2 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version 1.6 Revision Date: 06.04.2023 SDS Number: 800001005738 Date of last issue: 07.04.2021
Print Date 12.04.2023

| | |
|---|-------|
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (initial release prior to RMM): | 0,9 |
| Release fraction to wastewater from process (initial release prior to RMM): | 0,05 |
| Release fraction to soil from process (initial release prior to RMM): | 0,05 |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 87,3 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 87,3 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2.000 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

| | |
|---|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated. The Consexpo model has been used to estimate consumer exposures unless otherwise indicated. | |

| |
|---------------------------------|
| Section 3.2 -Environment |
| Used EUSES model. |

| | |
|---|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
| Section 4.1 - Health | |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. | |

| |
|--|
| Section 4.2 -Environment |
| Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. |
| Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. |
| Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. |
| Further details on scaling and control technologies are provided in SpERC factsheet |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Methyl PROXITOL

Version
1.6

Revision Date:
06.04.2023

SDS Number:
800001005738

Date of last issue: 07.04.2021
Print Date 12.04.2023

(<http://cefic.org/en/reach-for-industries-libraries.html>).