

# SAFETY DATA SHEET

## IPA

Version 1.1

Revision Date 09.10.2024

Print Date 16.10.2024

### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product name : IPA

Product code : S1111, ZA07A

CAS-No. : 67-63-0

Other means of identification : IPA, Isopropanol, Propan-2-ol, Propanol, sec-, Propyl alcohol, sec-, Dimethyl carbinol

#### Manufacturer or supplier's details

Manufacturer/Supplier : **Shell Chemicals Europe B.V.**  
PO Box 2334  
3000 CH Rotterdam  
Netherlands

Telephone : +31 (0)10 231 7000

Telefax : +31 (0)10 231 7180

Emergency telephone number : +31 (0)10 231 7393  
UAT for SPS2020 - New ER number

#### Recommended use of the chemical and restrictions on use

Recommended use : Industrial Solvent.

Restrictions on use : Advice in this document relates only to product as originally supplied. Other derivative chemicals will have different properties and hazards. Advice should be sought on their safe handling and use.  
This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

### 2. HAZARDS IDENTIFICATION

#### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids : Category 2

Eye irritation : Category 2

Specific target organ toxicity - single exposure (Inhalation, Oral) : Category 3 (Narcotic effects)

#### Label elements

# SAFETY DATA SHEET

## IPA

Version 1.1

Revision Date 09.10.2024

Print Date 16.10.2024

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: **PHYSICAL HAZARDS:**  
H225 Highly flammable liquid and vapour.  
**HEALTH HAZARDS:**  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
**ENVIRONMENTAL HAZARDS:**  
Not classified as environmental hazard according to CLP criteria.

Precautionary statements

: **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P243 Take action to prevent static discharges.  
**Response:**  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 If eye irritation persists: Get medical advice/attention.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
**Storage:**  
No precautionary phrases.  
**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

Vapours are heavier than air. Vapours may travel across the ground and reach remote ignition sources causing a flashback fire danger. Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Slightly irritating to respiratory system.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Substance

### Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (% w/w%)
Isopropyl alcohol	67-63-0	Flam. Liq. 2; H225 Eye Irrit. 2; H319	<= 100

# SAFETY DATA SHEET

## IPA

Version 1.1

Revision Date 09.10.2024

Print Date 16.10.2024

		STOT SE 3; H336	
--	--	-----------------	--

For explanation of abbreviations see section 16.

### 4. FIRST-AID MEASURES

General advice	: Not expected to be a health hazard when used under normal conditions.
If inhaled	: Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.
In case of skin contact	: Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
In case of eye contact	: Immediately flush eye(s) with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Transport to the nearest medical facility for additional treatment.
If swallowed	: If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.
Most important symptoms and effects, both acute and delayed	: Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death. No specific hazards under normal use conditions. Skin irritation signs and symptoms may include a burning sensation, redness, or swelling. Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision. If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.
Protection of first-aiders	: When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
Notes to physician	: IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!

# SAFETY DATA SHEET

## IPA

Version 1.1

Revision Date 09.10.2024

Print Date 16.10.2024

Call a doctor or poison control center for guidance.  
Potential for chemical pneumonitis.  
Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
- Unsuitable extinguishing media : None
- Specific hazards during firefighting : The vapour is heavier than air, spreads along the ground and distant ignition is possible.  
Carbon monoxide may be evolved if incomplete combustion occurs.
- Specific extinguishing methods : Standard procedure for chemical fires.  
Clear fire area of all non-emergency personnel.  
Keep adjacent containers cool by spraying with water.
- Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

### 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Observe the relevant local and international regulations  
Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.  
Local authorities should be advised if significant spillages cannot be contained.  
The vapour is heavier than air, spreads along the ground and distant ignition is possible.  
Vapour may form an explosive mixture with air.
- : Avoid contact with skin, eyes and clothing.  
Isolate hazard area and deny entry to unnecessary or unprotected personnel.  
Stay upwind and keep out of low areas.
- Environmental precautions : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take

# SAFETY DATA SHEET

## IPA

Version 1.1

Revision Date 09.10.2024

Print Date 16.10.2024

precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.

Ventilate contaminated area thoroughly.

Monitor area with combustible gas indicator.

Methods and materials for containment and cleaning up : For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

Additional advice : For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.  
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

## 7. HANDLING AND STORAGE

General Precautions : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.  
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.  
Ensure that all local regulations regarding handling and storage facilities are followed.

Advice on safe handling : Avoid contact with skin, eyes and clothing.  
Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.  
Bulk storage tanks should be diked (bunded).  
Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.  
Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.  
The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.  
Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.  
Do NOT use compressed air for filling, discharging, or handling operations.

Avoidance of contact : Strong oxidising agents.

# SAFETY DATA SHEET

## IPA

Version 1.1

Revision Date 09.10.2024

Print Date 16.10.2024

Product Transfer : Refer to guidance under Handling section.

### Storage

Conditions for safe storage : The vapour is heavier than air. Beware of accumulation in pits and confined spaces.  
Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Packaging material : Suitable material: For containers, or container linings use mild steel, stainless steel.  
Unsuitable material: Natural, butyl, neoprene or nitrile rubbers.

Container Advice : Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers.

Specific use(s) : Not applicable

Ensure that all local regulations regarding handling and storage facilities are followed.  
See additional references that provide safe handling practices: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).  
IEC/TS 60079-32-1: Electrostatic hazards, guidance

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Isopropyl alcohol	67-63-0	TWA	200 ppm	ACGIH
Isopropyl alcohol		STEL	400 ppm	ACGIH
Isopropyl alcohol		TWA	400 ppm 980 mg/m <sup>3</sup>	OSHA Z-1

### Biological occupational exposure limits

No biological limit allocated.

### Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

# SAFETY DATA SHEET

## IPA

Version 1.1

Revision Date 09.10.2024

Print Date 16.10.2024

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods  
<http://www.cdc.gov/niosh/>  
Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods  
<http://www.osha.gov/>  
Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances  
<http://www.hse.gov.uk/>  
Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany  
<http://www.dguv.de/inhalt/index.jsp>  
L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

### Engineering measures

: Use sealed systems as far as possible.  
Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.  
Local exhaust ventilation is recommended.  
Firewater monitors and deluge systems are recommended.  
Eye washes and showers for emergency use.  
Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.  
The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.  
Appropriate measures include:

#### General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.  
Practice good housekeeping.  
Define procedures for safe handling and maintenance of controls.  
Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.  
Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.  
Drain down system prior to equipment break-in or maintenance.  
Retain drain downs in sealed storage pending disposal or subsequent recycle.

### Personal protective equipment

#### Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

#### Respiratory protection

: If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.  
Check with respiratory protective equipment suppliers.  
Where air-filtering respirators are unsuitable (e.g. airborne

# SAFETY DATA SHEET

## IPA

Version 1.1

Revision Date 09.10.2024

Print Date 16.10.2024

concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type A boiling point >65°C (149°F)].

### Hand protection Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Butyl rubber. Nitrile rubber. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

### Eye protection

: Wear goggles for use against liquids and gas.  
Wear full face shield if splashes are likely to occur.

### Skin and body protection

: Wear antistatic and flame-retardant clothing, if a local risk assessment deems it so.  
Skin protection is not required under normal conditions of use. For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure.  
If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.

### Thermal hazards

: Not applicable

## Environmental exposure controls

### General advice

: Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.  
Minimise release to the environment. An environmental



# SAFETY DATA SHEET

## IPA

Version 1.1

Revision Date 09.10.2024

Print Date 16.10.2024

assessment must be made to ensure compliance with local environmental legislation.  
Information on accidental release measures are to be found in section 6.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Liquid.
Colour	: clear
Odour	: characteristic
Odour Threshold	: Data not available
pH	: Not applicable
Melting point/freezing point	: -88 °C / -126 °F
Boiling point/boiling range	: 82 - 83 °C / 180 - 181 °F
Flash point	: 12 °C / 54 °F Method: closed cup
Evaporation rate	: 1,5 Method: ASTM D 3539, nBuAc=1
Flammability (solid, gas)	: Not applicable
Upper explosion limit	: 12 %(V)
Lower explosion limit	: 2 %(V)
Vapour pressure	: 4,1 kPa (20 °C / 68 °F)
Relative vapour density	: 2 (20 °C / 68 °F)
Relative density	: 0,78 - 0,79 (20 °C / 68 °F) Method: ASTM D4052
Density	: 785 - 786 kg/m3 (20 °C / 68 °F) Method: ASTM D4052
Solubility(ies)	
Water solubility	: completely miscible
Solubility in other solvents	: Readily soluble in various organic solvents.
Partition coefficient: n-octanol/water	: log Pow: 0,05
Auto-ignition temperature	: 425 °C / 797 °F Method: ASTM D-2155

# SAFETY DATA SHEET

## IPA

Version 1.1

Revision Date 09.10.2024

Print Date 16.10.2024

Decomposition temperature	: Data not available
Viscosity	
Viscosity, dynamic	: 2,43 mPa.sMethod: ASTM D445
Viscosity, kinematic	: Data not available
Explosive properties	: Not classified
Oxidizing properties	: Not applicable
Surface tension	: 22,7 mN/m, 20 °C / 68 °F
Conductivity	: Electrical conductivity: > 10,000 pS/m A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be a static accumulator.
Particle size	: Data not available
Molecular weight	: 60,1 g/mol

### 10. STABILITY AND REACTIVITY

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: No hazardous reaction is expected when handled and stored according to provisions
Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Avoid heat, sparks, open flames and other ignition sources. Prevent vapour accumulation. In certain circumstances product can ignite due to static electricity.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

# SAFETY DATA SHEET

## IPA

Version 1.1

Revision Date 09.10.2024

Print Date 16.10.2024

### 11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on product testing.  
Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Information on likely routes of exposure : Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

#### Acute toxicity

##### Components:

##### **Isopropyl alcohol:**

Acute oral toxicity : LD50 Rat: > 5000 mg/kg  
Remarks: Low toxicity

Acute inhalation toxicity : LC50 Rat, male and female: > 10000 ppm  
Exposure time: 6 h  
Method: Test(s) equivalent or similar to OECD Test Guideline 403  
Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.  
Remarks: Low toxicity by inhalation.

Acute dermal toxicity : LD50 Rabbit: > 5000 mg/kg  
Remarks: Low toxicity

#### Skin corrosion/irritation

##### Components:

##### **Isopropyl alcohol:**

Remarks: Not irritating to skin.

#### Serious eye damage/eye irritation

##### Components:

##### **Isopropyl alcohol:**

Species: Rabbit  
Exposure time: 24 h  
Method: Test(s) equivalent or similar to OECD Test Guideline 405  
Remarks: Irritating to eyes.

Species: Rabbit  
Exposure time: 48 h  
Method: Test(s) equivalent or similar to OECD Test Guideline 405  
Remarks: Irritating to eyes.

Species: Rabbit  
Exposure time: 72 h  
Method: Test(s) equivalent or similar to OECD Test Guideline 405

# SAFETY DATA SHEET

## IPA

Version 1.1

Revision Date 09.10.2024

Print Date 16.10.2024

Remarks: Irritating to eyes.

### Respiratory or skin sensitisation

#### Components:

##### **Isopropyl alcohol:**

Species: Guinea pig

Result: negative

Method: Buehler Test

Remarks: Not a sensitiser.

Based on available data, the classification criteria are not met.

### Germ cell mutagenicity

#### Components:

##### **Isopropyl alcohol:**

Remarks: Based on available data, the classification criteria are not met.

Remarks: Not mutagenic.

### Carcinogenicity

#### Components:

##### **Isopropyl alcohol:**

Remarks: Not a carcinogen.

Material	GHS/CLP Carcinogenicity Classification
Isopropyl alcohol	No carcinogenicity classification.

Material	Other Carcinogenicity Classification
Isopropyl alcohol	IARC: Group 3: Not classifiable as to its carcinogenicity to humans

### Reproductive toxicity

#### **Components:**

##### **Isopropyl alcohol:**

Remarks: Does not impair fertility., Not a developmental toxicant., Based on available data, the classification criteria are not met.

### STOT - single exposure

#### Components:

##### **Isopropyl alcohol:**

Remarks: May cause drowsiness and dizziness.

# SAFETY DATA SHEET

## IPA

Version 1.1

Revision Date 09.10.2024

Print Date 16.10.2024

### STOT - repeated exposure

#### Components:

##### **Isopropyl alcohol:**

Remarks: Kidney: caused kidney effects in male rats which are not considered relevant to humans

### Aspiration toxicity

#### Components:

##### **Isopropyl alcohol:**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

### Further information

#### Components:

##### **Isopropyl alcohol:**

Remarks: Exposure may enhance the toxicity of other materials., Classifications by other authorities under varying regulatory frameworks may exist.

---

## 12. ECOLOGICAL INFORMATION

Basis for assessment : Information given is based on product testing.  
Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

### Ecotoxicity

#### Components:

##### **Isopropyl alcohol :**

Toxicity to fish (Acute toxicity) : Remarks: Practically non toxic:  
LL/EL/IL50 > 100 mg/l

Toxicity to crustacean (Acute toxicity) : Remarks: Practically non toxic:  
LL/EL/IL50 > 100 mg/l

Toxicity to algae/aquatic plants (Acute toxicity) : Remarks: Practically non toxic:  
LL/EL/IL50 > 100 mg/l

Toxicity to microorganisms (Acute toxicity) : Remarks: Practically non toxic:  
LL/EL/IL50 > 100 mg/l

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to crustacean(Chronic toxicity) : Remarks: Data not available

### Persistence and degradability

#### Components:

# SAFETY DATA SHEET

## IPA

Version 1.1

Revision Date 09.10.2024

Print Date 16.10.2024

### Isopropyl alcohol :

Biodegradability : Remarks: Readily biodegradable.  
Oxidises rapidly by photo-chemical reactions in air.

### Bioaccumulative potential

#### Product:

Partition coefficient: n-octanol/water : log Pow: 0,05

#### Components:

**Isopropyl alcohol :**  
Bioaccumulation : Remarks: Does not bioaccumulate significantly.

### Mobility in soil

#### Components:

**Isopropyl alcohol :**  
Mobility : Remarks: Dissolves in water., If the product enters soil, one or more constituents will or may be mobile and may contaminate groundwater.

### Other adverse effects

no data available

#### Components:

**Isopropyl alcohol :**  
Additional ecological information : Does not have ozone depletion potential.

---

## 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Recover or recycle if possible.  
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.  
Do not dispose into the environment, in drains or in water courses.  
Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.  
Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.  
Local regulations may be more stringent than regional or national requirements and must be complied with.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Drain container thoroughly.

# SAFETY DATA SHEET

## IPA

Version 1.1

Revision Date 09.10.2024

Print Date 16.10.2024

After draining, vent in a safe place away from sparks and fire.  
Residues may cause an explosion hazard.  
Do not, puncture, cut, or weld uncleaned drums.  
Send to drum recoverer or metal reclaimer.

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

---

### 14. TRANSPORT INFORMATION

#### International Regulations

##### ADR

UN number : 1219  
Proper shipping name : ISOPROPANOL  
Class : 3  
Packing group : II  
Labels : 3  
Hazard Identification Number : 33  
Environmentally hazardous : no

##### IATA-DGR

UN/ID No. : UN 1219  
Proper shipping name : ISOPROPANOL  
Class : 3  
Packing group : II  
Labels : 3

##### IMDG-Code

UN number : UN 1219  
Proper shipping name : ISOPROPANOL  
Class : 3  
Packing group : II  
Labels : 3  
Marine pollutant : no

#### Maritime transport in bulk according to IMO instruments

Pollution category : Z  
Ship type : IBC Chapter 18 cargo, must be double hulled

#### Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

**Additional Information** : This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a

# SAFETY DATA SHEET

## IPA

Version 1.1

Revision Date 09.10.2024

Print Date 16.10.2024

confined space entry.  
Transport in bulk according to Annex II of Marpol and the IBC Code

### 15. REGULATORY INFORMATION

#### **Safety, health and environmental regulations/legislation specific for the substance or mixture**

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

#### **Other international regulations**

**The components of this product are reported in the following inventories:**

AIIC	: Listed
DSL	: Listed
IECSC	: Listed
ENCS	: Listed
KECI	: Listed
NZIoC	: Listed
PICCS	: Listed
TSCA	: Listed
TCSI	: Listed

### 16. OTHER INFORMATION

#### **Full text of H-Statements**

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

#### **Full text of other abbreviations**

Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids
STOT SE	Specific target organ toxicity - single exposure

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

SDS Regulation :

#### **Further information**

Training advice : Provide adequate information, instruction and training for operators.

Other information : A vertical bar (|) in the left margin indicates an amendment from the previous version.



# SAFETY DATA SHEET

## IPA

Version 1.1

Revision Date 09.10.2024

Print Date 16.10.2024

---

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.