According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl DIPROXITOL

Version Revision Date: SDS Number: Print Date: 11/08/2023

3.1 11/01/2023 800010021072 Date of last issue: 04/26/2018

SECTION 1. IDENTIFICATION

Product name : Ethyl DIPROXITOL

Product code : U5151

Synonyms : Propanol, (2-ethoxymethylethoxy)-, EDP, ethoxypropoxy pro-

panol

CAS-No. : 30025-38-8

Manufacturer or supplier's details

Company : Shell Chemical LP

PO Box 576

HOUSTON TX 77001

USA

SDS Request : 1-800-240-6737

Customer Service : 1-855-697-4355

Emergency telephone number

Chemtrec Domestic (24 hr) : 1-800-424-9300

Chemtrec International (24

hr)

: 1-703-527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Speciality solvent.

Restrictions on use : This product must not be used in applications other than the

above without first seeking the advice of the supplier.

Other information : DIPROXITOL is a registered trademark of Shell trademark

Management BV.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR

1910.1200)

Flammable liquids : Category 4

GHS label elements

Hazard pictograms : No Hazard Symbol required

Signal word : Warning

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl DIPROXITOL

Version Revision Date: SDS Number: Print Date: 11/08/2023
3.1 11/01/2023 800010021072 Date of last issue: 04/26/2018

Hazard statements : PHYSICAL HAZARDS:

H227 Combustible liquid. HEALTH HAZARDS:

Not classified as a health hazard under GHS criteria.

ENVIRONMENTAL HAZARDS:

Not classified as an environmental hazard under GHS criteria.

Precautionary statements : **Prevention:**

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P370 + P378 In case of fire: Use appropriate media to extin-

guish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents and container to appropriate waste

site or reclaimer in accordance with local and national regula-

tions.

Other hazards which do not result in classification

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable airvapour mixtures can occur.

The classification of this material is based on OSHA HCS 2012 criteria.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Hazardous components

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
Propanol, (2-	Propanol, (2-	30025-38-8	> 80
ethoxymethylethoxy)-	ethoxymeth-		
	ylethoxy)-		

SECTION 4. FIRST-AID MEASURES

General advice : Not expected to be a health hazard when used under normal

conditions.

If inhaled : No treatment necessary under normal conditions of use. If

symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Flush exposed area with wa-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl DIPROXITOL

Version Revision Date: SDS Number: Print Date: 11/08/2023 3.1 11/01/2023 800010021072 Date of last issue: 04/26/2018

ter and follow by washing with soap if available.

If persistent irritation occurs, obtain medical attention.

In case of eye contact : Flush eye with copious quantities of water.

Remove contact lenses, if present and easy to do. Continue

rinsing.

If persistent irritation occurs, obtain medical attention.

If swallowed : If swallowed, do not induce vomiting: transport to nearest

medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Rinse mouth.

Most important symptoms and effects, both acute and delayed

Not considered to be an inhalation hazard under normal con-

ditions of use.

Possible respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.

No specific hazards under normal use conditions.

Skin irritation signs and symptoms may include a burning sen-

sation, redness, or swelling.

No specific hazards under normal use conditions.

Eye irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blurred vision.

Ingestion may result in nausea, vomiting and/or diarrhoea. Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, lightheadedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and

death.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

Indication of any immediate medical attention and special

treatment needed

Call a doctor or poison control center for guidance.

Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam, water spray or fog. Dry chemical pow-

der, carbon dioxide, sand or earth may be used for small fires

only.

Unsuitable extinguishing

media

None

Specific hazards during fire-

fighting

: The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Carbon monoxide may be evolved if incomplete combustion

occurs.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl DIPROXITOL

Version Revision Date: SDS Number: Print Date: 11/08/2023 11/01/2023 800010021072 Date of last issue: 04/26/2018 3.1

Specific extinguishing meth-

Standard procedure for chemical fires.

Further information Clear fire area of all non-emergency personnel.

Keep adjacent containers cool by spraying with water.

Special protective equipment:

for firefighters

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec: : tive equipment and emergency procedures

Observe the relevant local and international regulations Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

Local authorities should be advised if significant spillages

cannot be contained.

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Vapour may form an explosive mixture with air. Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or unpro-

tected personnel.

Stay upwind and keep out of low areas.

Environmental precautions

Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bond-

ing and grounding (earthing) all equipment. Ventilate contaminated area thoroughly. Monitor area with combustible gas indicator.

Methods and materials for containment and cleaning up For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove

contaminated soil and dispose of safely.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl DIPROXITOL

Version Revision Date: SDS Number: Print Date: 11/08/2023
3.1 11/01/2023 800010021072 Date of last issue: 04/26/2018

Additional advice : For guidance on selection of personal protective equipment

see Section 8 of this Safety Data Sheet.

For guidance on disposal of spilled material see Section 13 of

this Safety Data Sheet.

U.S. regulations may require reporting releases of this material to the environment which exceed the reportable quantity (refer to Section 15) to the National Response Center at (800)

424-8802.

SECTION 7. HANDLING AND STORAGE

Technical measures : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this

material.

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

Advice on safe handling : Avoid contact with skin, eyes and clothing.

Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Bulk storage tanks should be diked (bunded).

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to

reduce the risk.

The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flamma-

ble

Properly dispose of any contaminated rags or cleaning mate-

rials in order to prevent fires.

Do NOT use compressed air for filling, discharging, or han-

dling operations.

Avoidance of contact : Strong oxidising agents.

Product Transfer : Refer to guidance under Handling section.

Conditions for safe storage : The vapour is heavier than air. Beware of accumulation in pits

and confined spaces.

Refer to section 15 for any additional specific legislation cov-

ering the packaging and storage of this product.

Packaging material : Suitable material: For containers, or container linings use mild

steel, stainless steel.

Unsuitable material: Natural, butyl, neoprene or nitrile rubbers.

Container Advice : Containers, even those that have been emptied, can contain

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl DIPROXITOL

 Version
 Revision Date:
 SDS Number:
 Print Date: 11/08/2023

 3.1
 11/01/2023
 800010021072
 Date of last issue: 04/26/2018

explosive vapours. Do not cut, drill, grind, weld or perform

similar operations on or near containers.

Specific use(s) : Not applicable

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

See additional references that provide safe handling practices: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices

on Static Electricity).

IEC/TS 60079-32-1: Electrostatic hazards, guidance

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures : Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne con-

centrations below the exposure guidelines/limits. Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Eye washes and showers for emergency use.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl DIPROXITOL

Version Revision Date: 3.1 11/01/2023

SDS Number: 800010021072

Print Date: 11/08/2023
Date of last issue: 04/26/2018

Appropriate measures include:

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.

Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type A boiling point >65°C (149°F)].

Respirator selection, use and maintenance should be in accordance with the requirements of the OSHA Respiratory Protection Standard, 29 CFR 1910.134.

Hand protection Remarks

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC, neoprene or nitrile rubber gloves For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves of-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl DIPROXITOL

Version Revision Date: SDS Number: Print Date: 11/08/2023
3.1 11/01/2023 800010021072 Date of last issue: 04/26/2018

fering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended.

Skin and body protection : Skin protection is not required under normal conditions of

use.

For prolonged or repeated exposures use impervious clothing

over parts of the body subject to exposure.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Stand-

ard, and provide employee skin care programmes.

Wear antistatic and flame-retardant clothing, if a local risk

assessment deems it so.

Protective measures : Personal protective equipment (PPE) should meet recom-

mended national standards. Check with PPE suppliers.

Thermal hazards : Not applicable

Environmental exposure controls

General advice : Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

vapour

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local envi-

ronmental legislation.

Information on accidental release measures are to be found in

section 6.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : clear

Odour : Ethereal

Odour Threshold : Data not available

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl DIPROXITOL

Version **Revision Date:** SDS Number: Print Date: 11/08/2023

11/01/2023 800010021072 Date of last issue: 04/26/2018 3.1

рΗ Not applicable

Melting / freezing point -50 °C / -58 °F

Boiling point/boiling range : 194 °C / 381 °F

82 °C / 180 °F Flash point

Method: ASTM D-93 / PMCC

Evaporation rate Data not available

Flammability

Flammability (solid, gas) Data not available

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit / up- : Data not available

per flammability limit

Lower explosion limit /

Lower flammability limit

Data not available

56.7 Pa (25 °C / 77 °F) Vapour pressure

Relative vapour density Data not available

Relative density 0.9317

Method: ASTM D4052

931.7 kg/m3 (20 °C / 68 °F) Density

Method: ASTM D4052

Solubility(ies)

Water solubility completely soluble (20 °C / 68 °F

Partition coefficient: n-

octanol/water

log Pow: 0.16

Auto-ignition temperature 199 °C / 390 °F

Decomposition temperature Data not available

Viscosity

Viscosity, dynamic Data not available

: 4.2 mm2/s (20 °C / 68 °F) Viscosity, kinematic

Method: ASTM D445

Explosive properties Not applicable

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl DIPROXITOL

 Version
 Revision Date:
 SDS Number:
 Print Date: 11/08/2023

 3.1
 11/01/2023
 800010021072
 Date of last issue: 04/26/2018

Oxidizing properties : Data not available

Surface tension : 61 mN/m, 20 °C / 68 °F

Conductivity: > 10,000 pS/m, A number of factors,

for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be a static accumu-

lator.

Molecular weight : 162 g/mol

Particle size : Data not available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : The product does not pose any further reactivity hazards in

addition to those listed in the following sub-paragraph.

Chemical stability : No hazardous reaction is expected when handled and stored

according to provisions

Possibility of hazardous reac-

tions

Reacts with strong oxidising agents.

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.

Prevent vapour accumulation.

In certain circumstances product can ignite due to static elec-

tricity.

Incompatible materials : Strong oxidising agents.

Hazardous decomposition

products

: Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and

ing carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degra-

dation.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment : Unless indicated otherwise, the data presented is representa-

tive of the product as a whole, rather than for individual com-

ponent(s).

Information given is based on product testing, and/or similar

products, and/or components.

Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Components:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl DIPROXITOL

Version Revision Date: SDS Number: Print Date: 11/08/2023
3.1 11/01/2023 800010021072 Date of last issue: 04/26/2018

Propanol, (2-ethoxymethylethoxy)-:

Acute oral toxicity : LD50 : > 2000 - <= 5000 mg/kg

Remarks: May be harmful if swallowed.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria

are not met.

Acute dermal toxicity : LD50 : > 5000 mg/kg

Remarks: Low toxicity

Skin corrosion/irritation

Components:

Propanol, (2-ethoxymethylethoxy)-:

Remarks: Not irritating to skin.

Serious eye damage/eye irritation

Components:

Propanol, (2-ethoxymethylethoxy)-:

Remarks: Not irritating to eye.

Respiratory or skin sensitisation

Components:

Propanol, (2-ethoxymethylethoxy)-:

Remarks: Not a skin sensitiser.

Germ cell mutagenicity

Components:

Propanol, (2-ethoxymethylethoxy)-:

Genotoxicity in vivo : Remarks: Non mutagenic, Based on available data, the classi-

fication criteria are not met.

Carcinogenicity

Components:

Propanol, (2-ethoxymethylethoxy)-:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl DIPROXITOL

Version Revision Date: SDS Number: Print Date: 11/08/2023

3.1 11/01/2023 800010021072 Date of last issue: 04/26/2018

NTP No component of this product present at levels greater than or

egual to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Components:

Propanol, (2-ethoxymethylethoxy)-:

Effects on fertility :

Remarks: Not a developmental toxicant.

Based on available data, the classification criteria are not met.

Does not impair fertility.

STOT - single exposure

Components:

Propanol, (2-ethoxymethylethoxy)-:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Components:

Propanol, (2-ethoxymethylethoxy)-:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Components:

Propanol, (2-ethoxymethylethoxy)-:

Not an aspiration hazard.

Further information

Components:

Propanol, (2-ethoxymethylethoxy)-:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment : Unless indicated otherwise, the data presented is representa-

tive of the product as a whole, rather than for individual com-

ponent(s).

Incomplete ecotoxicological data are available for this product. The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl DIPROXITOL

Version Revision Date: SDS Number: Print Date: 11/08/2023

3.1 11/01/2023 800010021072 Date of last issue: 04/26/2018

Ecotoxicity

Components:

Propanol, (2-ethoxymethylethoxy)-:

Toxicity to fish (Acute toxici: Remarks: Practically non toxic:

ty) LL/EL/IL50 > 100 mg/l

Toxicity to daphnia and other : Remarks: Practically non toxic: aquatic invertebrates (Acute LL/EL/IL50 > 100 mg/l

aquatic invertebrates (Acute toxicity)

T. 1.9. (c. al. . . /A . (c. (c.

Toxicity to algae (Acute tox- : Remarks: Practically non toxic:

icity) LL/EL/IL50 > 100 mg/l

Toxicity to fish (Chronic tox-

icity)

Remarks: NOEC/NOEL > 100 mg/l

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

Remarks: NOEC/NOEL > 100 mg/l

Toxicity to microorganisms

(Acute toxicity)

Remarks: LL/EL/IL50 > 100 mg/l

Practically non toxic:

Based on available data, the classification criteria are not met.

Persistence and degradability

Components:

Propanol, (2-ethoxymethylethoxy)-:

Biodegradability : Remarks: Readily biodegradable.

Bioaccumulative potential

Components:

Propanol, (2-ethoxymethylethoxy)-:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

Mobility in soil

Components:

Propanol, (2-ethoxymethylethoxy)-:

Mobility : Remarks: If product enters soil, one or more constituents will

be mobile and may contaminate groundwater.

Other adverse effects

Components:

Propanol, (2-ethoxymethylethoxy)-:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl DIPROXITOL

Version Revision Date: SDS Number: Print Date: 11/08/2023

3.1 11/01/2023 800010021072 Date of last issue: 04/26/2018

Additional ecological infor-

mation

: None known.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth-

ods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses.

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or na-

tional requirements and must be complied with.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides tech-

nical aspects at controlling pollutions from ships.

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Residues may cause an explosion hazard. Do not, puncture, cut, or weld uncleaned drums. Send to drum recoverer or metal reclaimer.

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

SECTION 14. TRANSPORT INFORMATION

National Regulations

US Department of Transportation Classification (49 CFR Parts 171-180)

UN/ID/NA number : NA 1993

Proper shipping name : Combustible liquid, n.o.s.

(Ethyldiproxitol)

Class : CBL
Packing group : III
Labels : NON
ERG Code : 128
Marine pollutant : no

International Regulations

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl DIPROXITOL

Version Revision Date: SDS Number: Print Date: 11/08/2023

3.1 11/01/2023 800010021072 Date of last issue: 04/26/2018

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Maritime transport in bulk according to IMO instruments

Pollution category : Z Ship type : 3

Product name : Poly (2-8) alkylene glycol monoalkyl (C1-C6) ether

Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

Additional Information : Transport in bulk according to Annex II of Marpol and the IBC

Code

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

*: This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Water Act

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

US State Regulations

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl DIPROXITOL

Version Revision Date: SDS Number: Print Date: 11/08/2023 3.1 11/01/2023 800010021072 Date of last issue: 04/26/2018

The components of this product are reported in the following inventories:

AIIC : Listed

IECSC : Listed

KECI : Listed

PICCS : Listed

TSCA : Listed

TCSI : Listed

SECTION 16. OTHER INFORMATION

Further information

NFPA Rating (Health, Fire, Reac- 0, 1, 0

tivity)

Full text of other abbreviations

2000/39/EC / TWA : Gränsvärden - åtta timmar

SE AFS / NGV : Nivågränsvärde

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this docu-

ment can be looked up in reference literature (e.g. scientific

dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial

Hygienists

ADR = European Agreement concerning the International

Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut fur Normung DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and Toxicolo-

gy Of Chemicals

ECHA = European Chemicals Agency

EINECS = The European Inventory of Existing Commercial

Chemical Substances

EL50 = Effective Loading fifty

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl DIPROXITOL

 Version
 Revision Date:
 SDS Number:
 Print Date: 11/08/2023

 3.1
 11/01/2023
 800010021072
 Date of last issue: 04/26/2018

ENCS = Japanese Existing and New Chemical Substances Inventory

EWC = European Waste Code

GHS = Globally Harmonised System of Classification and

Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IC50 = Inhibitory Concentration fifty

IL50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous Goods

INV = Chinese Chemicals Inventory

IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables

KECI = Korea Existing Chemicals Inventory

LC50 = Lethal Concentration fifty LD50 = Lethal Dose fifty per cent.

LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading

LL50 = Lethal Loading fifty

MARPOL = International Convention for the Prevention of

Pollution From Ships

NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level

OE_HPV = Occupational Exposure - High Production Volume

PBT = Persistent, Bioaccumulative and Toxic

PICCS = Philippine Inventory of Chemicals and Chemical

Substances

PNEC = Predicted No Effect Concentration

REACH = Registration Evaluation And Authorisation Of

Chemicals

RID = Regulations Relating to International Carriage of Dangerous Goods by Rail

SKIN DES = Skin Designation

STEL = Short term exposure limit

TRA = Targeted Risk Assessment

TSCA = US Toxic Substances Control Act

TWA = Time-Weighted Average

vPvB = very Persistent and very Bioaccumulative

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data

Sheet

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

Revision Date : 11/01/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Ethyl DIPROXITOL

Version Revision Date: SDS Number: Print Date: 11/08/2023

3.1 11/01/2023 800010021072 Date of last issue: 04/26/2018

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN