

SAFETY DATA SHEET

According to the Hazardous Products Regulations

NGL Butane/Butylene Mix - NonOdorized

Version
3.0

Revision Date:
2024-09-26

SDS Number:
800010025825

Print Date: 2024-10-03
Date of last issue: 22.09.2021
Date of first issue: 23.11.2015

SECTION 1. IDENTIFICATION

Product name : NGL Butane/Butylene Mix - NonOdorized

Product code : X3524

Manufacturer or supplier's details

Manufacturer/Supplier : **Shell Chemicals Canada**
PO Box 4280 STN C
CALGARY AB T2T 5Z5
Canada

Telephone : 1-855-697-4355

Telefax : 1-866-213-7508

Emergency telephone number

CHEMTREC (24 hr) : 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Chemical intermediate.

Restrictions on use : This product must not be used in applications other than the above without first seeking the advice of the supplier.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable gases : Category 1

Gases under pressure : Liquefied gas

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : PHYSICAL HAZARDS:
H220 Extremely flammable gas.
H280 Contains gas under pressure; may explode if heated.
HEALTH HAZARDS:

SAFETY DATA SHEET

According to the Hazardous Products Regulations

NGL Butane/Butylene Mix - NonOdorized

Version
3.0

Revision Date:
2024-09-26

SDS Number:
800010025825

Print Date: 2024-10-03
Date of last issue: 22.09.2021
Date of first issue: 23.11.2015

Not classified as a health hazard under GHS criteria.

ENVIRONMENTAL HAZARDS:

Not classified as an environmental hazard under GHS criteria.

Precautionary statements

: Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.
No smoking.

P243 Take precautionary measures against static discharge.

Response:

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 Eliminate all ignition sources if safe to do so.

Storage:

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

Disposal:

No precautionary phrases.

Other hazards which do not result in classification

Vapours are heavier than air. Vapours may travel across the ground and reach remote ignition sources causing a flashback fire danger.

May form flammable/explosive vapour-air mixture.

This material is a static accumulator.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

This material is shipped under pressure.

High gas concentrations will displace available air; unconsciousness and death may occur suddenly from lack of oxygen.

Exposure to rapidly expanding gases may cause frost burns to eyes and/or skin.

Inhalation of vapours or mists may cause irritation to the respiratory system.

Vapours may cause drowsiness and dizziness.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance name : NGL Butane/Butylene Mix - NonOdorized

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
butane	106-97-8	20 - 80
but-1-ene	106-98-9	20 - 80

SECTION 4. FIRST-AID MEASURES

General advice : Not expected to be a health hazard when used under normal conditions.

SAFETY DATA SHEET

According to the Hazardous Products Regulations

NGL Butane/Butylene Mix - NonOdorized

Version
3.0

Revision Date:
2024-09-26

SDS Number:
800010025825

Print Date: 2024-10-03
Date of last issue: 22.09.2021
Date of first issue: 23.11.2015

If inhaled	: Call emergency number for your location / facility. Remove to fresh air. Do not attempt to rescue the victim unless proper respiratory protection is worn. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting, or unresponsive, give 100% oxygen with rescue breathing or Cardio-Pulmonary Resuscitation as required and transport to the nearest medical facility.
In case of skin contact	: Slowly warm the exposed area by rinsing with warm water. Transport to the nearest medical facility for additional treatment.
In case of eye contact	: Slowly warm the exposed area by rinsing with warm water. Transport to the nearest medical facility for additional treatment.
If swallowed	: In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Most important symptoms and effects, both acute and delayed	: Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing. Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, lightheadedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death. Rapid release of gases which are liquids under pressure may cause frost burns of exposed tissues (skin, eye) due to evaporative cooling. No specific hazards under normal use conditions. Ingestion may result in nausea, vomiting and/or diarrhoea.
Protection of first-aiders	: When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
Notes to physician	: IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT! Artificial respiration and/or oxygen may be necessary. Call a doctor or poison control center for guidance. Treat symptomatically. Potential for cardiac sensitisation, particularly in abuse situations. Hypoxia or negative inotropes may enhance these effects. Consider: oxygen therapy. Narcotic at high vapour concentrations.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Shut off supply. If not possible and no risk to surroundings, let

SAFETY DATA SHEET

According to the Hazardous Products Regulations

NGL Butane/Butylene Mix - NonOdorized

Version	Revision Date:	SDS Number:	Print Date: 2024-10-03
3.0	2024-09-26	800010025825	Date of last issue: 22.09.2021
			Date of first issue: 23.11.2015

-
- the fire burn itself out.
- Unsuitable extinguishing media : Do not use water in a jet.
- Specific hazards during fire-fighting : Sustained fire attack on vessels may result in a Boiling Liquid Expanding Vapor Explosion (BLEVE).
The vapour is heavier than air, spreads along the ground and distant ignition is possible.
Contents are under pressure and can explode when exposed to heat or flames.
As the vapours become lighter than air, the vapours may reach ignition sources at ground or elevated locations.
- Specific extinguishing methods : Standard procedure for chemical fires.
- Further information : Clear fire area of all non-emergency personnel.
Keep adjacent containers cool by spraying with water.
- Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Observe the relevant local and international regulations
Risk of explosion. Inform the emergency services if liquid enters surface water drains.
Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.
Local authorities should be advised if significant spillages cannot be contained.
Avoid contact with skin, eyes and clothing.
Isolate hazard area and deny entry to unnecessary or unprotected personnel.
Do not breathe fumes, vapour.
Do not operate electrical equipment.
- Environmental precautions : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area and evacuate all personnel. Attempt to disperse the gas or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas meter.

SAFETY DATA SHEET

According to the Hazardous Products Regulations

NGL Butane/Butylene Mix - NonOdorized

Version
3.0

Revision Date:
2024-09-26

SDS Number:
800010025825

Print Date: 2024-10-03
Date of last issue: 22.09.2021
Date of first issue: 23.11.2015

Methods and materials for containment and cleaning up : Allow to evaporate.
Attempt to disperse the vapour or to direct its flow to a safe location, for example by using fog sprays. Otherwise treat as for small spillage.

Additional advice : For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.
Risk of explosion. Inform the emergency services if liquid enters surface water drains.
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.
Vapour may form an explosive mixture with air.

SECTION 7. HANDLING AND STORAGE

General Precautions : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

Advice on safe handling : Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.
Avoid inhaling vapour and/or mists.
Avoid contact with skin, eyes and clothing.
Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.
Bulk storage tanks should be diked (bunded).
Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.
If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.
Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges.
These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements.
These activities may lead to static discharge e.g. spark formation.
Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/s until fill pipe submerged

SAFETY DATA SHEET

According to the Hazardous Products Regulations

NGL Butane/Butylene Mix - NonOdorized

Version
3.0

Revision Date:
2024-09-26

SDS Number:
800010025825

Print Date: 2024-10-03
Date of last issue: 22.09.2021
Date of first issue: 23.11.2015

to twice its diameter, then ≤ 7 m/s). Avoid splash filling.
Do NOT use compressed air for filling, discharging, or handling operations.
The vapour is heavier than air. Beware of accumulation in pits and confined spaces.

Avoidance of contact : Strong oxidising agents.

Product Transfer : Refer to guidance under Handling section.

Storage

Other data : Keep away from aerosols, flammables, oxidizing agents, corrosives and from products harmful or toxic to man or to the environment.
Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat.
Vapours from tanks should not be released to atmosphere.
Breathing losses during storage should be controlled by a suitable vapour treatment system.
Electrostatic charges will be generated during pumping.
Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.
The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.

Packaging material : Suitable material: For containers, or container linings use mild steel, stainless steel.

Container Advice : Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers.

Specific use(s) : Ensure that all local regulations regarding handling and storage facilities are followed.
See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).
IEC/TS 60079-32-1: Electrostatic hazards, guidance

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

SAFETY DATA SHEET

According to the Hazardous Products Regulations

NGL Butane/Butylene Mix - NonOdorized

Version
3.0

Revision Date:
2024-09-26

SDS Number:
800010025825

Print Date: 2024-10-03
Date of last issue: 22.09.2021
Date of first issue: 23.11.2015

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
butane	106-97-8	STEL	1,000 ppm	ACGIH
but-1-ene	106-98-9	TWA	250 ppm	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods <http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods <http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances <http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany <http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

Engineering measures

: The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.

Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of

SAFETY DATA SHEET

According to the Hazardous Products Regulations

NGL Butane/Butylene Mix - NonOdorized

Version
3.0

Revision Date:
2024-09-26

SDS Number:
800010025825

Print Date: 2024-10-03
Date of last issue: 22.09.2021
Date of first issue: 23.11.2015

equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.
Purge system prior to equipment break-in or maintenance.

Personal protective equipment

Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. If air-filtering respirators are suitable for conditions of use:

Select a filter suitable for organic gases and vapours [Type AX boiling point $\leq 65^{\circ}\text{C}$ (149°F)].

Hand protection
Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Neoprene rubber. If contact with liquefied product is possible or anticipated, gloves should be thermally insulated to prevent cold burns. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye protection

: Wear goggles for use against liquids and gas, combined with

SAFETY DATA SHEET

According to the Hazardous Products Regulations

NGL Butane/Butylene Mix - NonOdorized

Version
3.0

Revision Date:
2024-09-26

SDS Number:
800010025825

Print Date: 2024-10-03
Date of last issue: 22.09.2021
Date of first issue: 23.11.2015

	face shield with chin guard.
Skin and body protection	: Chemical and cryogenic gloves/gauntlets, boots, and apron. Wear antistatic and flame-retardant clothing.
Thermal hazards	: When handling cold material that can cause frost burns, wear cryogenic gloves, safety hat and visor, cold resistant overalls (with cuffs over gloves and legs over boots) and heavy duty boots e.g. leather for cold resistance.
Protective measures	: Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers. The following information, while appropriate for the product is general in nature. The selection of Personal Protective Equipment will vary depending on the conditions of use.
Hygiene measures	: Wash hands before eating, drinking, smoking and using the toilet. Launder contaminated clothing before re-use.

Environmental exposure controls

General advice	: Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour. Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation. Information on accidental release measures are to be found in section 6.
----------------	--

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: compressed liquefied gas
Colour	: colourless
Odour	: odourless
Odour Threshold	: Data not available
pH	: Not applicable
Freezing point	: estimated value(s) -140 - 21.1 °C / -220 - 70.0 °F
Initial boiling point and boiling range	: -162 - -0.5 °C / -260 - 31.1 °F
Flash point	: Typical -56 °C / -69 °F

SAFETY DATA SHEET

According to the Hazardous Products Regulations

NGL Butane/Butylene Mix - NonOdorized

Version
3.0

Revision Date:
2024-09-26

SDS Number:
800010025825

Print Date: 2024-10-03
Date of last issue: 22.09.2021
Date of first issue: 23.11.2015

Evaporation rate : Data not available

Flammability

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit : 8.5 %(V)

Lower explosion limit : 1.9 %(V)

Vapour pressure : estimated value(s) 2,500 hPa (25 °C / 77 °F)

Relative vapour density : < 1
(Air = 1.0)

Relative density : 0.6

Density : estimated value(s) 600 - 630 kg/m³ (25 °C / 77 °F)

Solubility(ies)

Water solubility : slight

Solubility in other solvents : Data not available

Partition coefficient: n-octanol/water : log Pow: 2.3

Auto-ignition temperature : 385 - 405 °C / 725 - 761 °F

Decomposition temperature : Data not available

Viscosity

Viscosity, dynamic : Data not available

Viscosity, kinematic : Data not available

Explosive properties : Classification Code: Not classified

Oxidizing properties : Data not available

Surface tension : Data not available

Conductivity : Low conductivity: < 100 pS/m, The conductivity of this material makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m., Whether a liquid is nonconductive or semiconductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liq-

SAFETY DATA SHEET

According to the Hazardous Products Regulations

NGL Butane/Butylene Mix - NonOdorized

Version
3.0

Revision Date:
2024-09-26

SDS Number:
800010025825

Print Date: 2024-10-03
Date of last issue: 22.09.2021
Date of first issue: 23.11.2015

Molecular weight : 56 - 58 g/mol

SECTION 10. STABILITY AND REACTIVITY

Reactivity : The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

Chemical stability : Stable under normal conditions of use.

Possibility of hazardous reactions : Reacts violently with strong oxidising agents. Polymerisation may occur at elevated temperatures.

Conditions to avoid : Heat, flames, and sparks.
Exposure to air.
In certain circumstances product can ignite due to static electricity.

Incompatible materials : Strong oxidising agents.

Hazardous decomposition products : Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on product data and on data on the components and the toxicology of similar products.

Information on likely routes of exposure

Inhalation is the primary route of exposure.

Acute toxicity

Product:

Acute inhalation toxicity : LC 50 (Rat, male): > 2500 - <= 20000 ppm
Exposure time: 4 h
Test atmosphere: gas
Method: OECD Test Guideline 403
Remarks: Information given is based on data obtained from similar substances.
Based on available data, the classification criteria are not met.

Components:

but-1-ene:

SAFETY DATA SHEET

According to the Hazardous Products Regulations

NGL Butane/Butylene Mix - NonOdorized

Version
3.0

Revision Date:
2024-09-26

SDS Number:
800010025825

Print Date: 2024-10-03
Date of last issue: 22.09.2021
Date of first issue: 23.11.2015

Acute inhalation toxicity : LC 50 (Rat, male): > 2500 - <= 20000 ppm
Exposure time: 4 h
Test atmosphere: gas
Method: OECD Test Guideline 403
Remarks: Information given is based on data obtained from similar substances.
Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Components:

but-1-ene:

Remarks: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Components:

but-1-ene:

Remarks: Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Components:

but-1-ene:

Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Method: Literature data
Remarks: Based on available data, the classification criteria are not met.

: Method: OECD Test Guideline 473
Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Components:

but-1-ene:

Genotoxicity in vitro : Method: Literature data
Remarks: Based on available data, the classification criteria are not met.

: Method: OECD Test Guideline 473
Remarks: Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

According to the Hazardous Products Regulations

NGL Butane/Butylene Mix - NonOdorized

Version
3.0

Revision Date:
2024-09-26

SDS Number:
800010025825

Print Date: 2024-10-03
Date of last issue: 22.09.2021
Date of first issue: 23.11.2015

Germ cell mutagenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Carcinogenicity

Product:

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Components:

but-1-ene:

Remarks: Based on available data, the classification criteria are not met.

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Product:

Effects on fertility : Species: Rat
Sex: male and female
Application Route: Inhalation

Method: OECD Test Guideline 422
Remarks: Based on available data, the classification criteria are not met.

Effects on foetal development : Species: Rat, female
Application Route: Inhalation
Method: OECD Test Guideline 414
Remarks: Information given is based on data obtained from similar substances.
Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

SAFETY DATA SHEET

According to the Hazardous Products Regulations

NGL Butane/Butylene Mix - NonOdorized

Version
3.0

Revision Date:
2024-09-26

SDS Number:
800010025825

Print Date: 2024-10-03
Date of last issue: 22.09.2021
Date of first issue: 23.11.2015

Components:

but-1-ene:

Effects on fertility

:

Species: Rat
Sex: male and female
Application Route: Inhalation

Method: OECD Test Guideline 422

Remarks: Based on available data, the classification criteria are not met.

Effects on foetal development

:

Species: Rat, female
Application Route: Inhalation
Method: OECD Test Guideline 414
Remarks: Information given is based on data obtained from similar substances.
Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment

:

This product does not meet the criteria for classification in categories 1A/1B.

STOT - single exposure

Product:

Remarks: Inhalation of vapours or mists may cause irritation to the respiratory system.
Based on available data, the classification criteria are not met.

Components:

but-1-ene:

Remarks: Inhalation of vapours or mists may cause irritation to the respiratory system.
Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Components:

but-1-ene:

Remarks: Based on available data, the classification criteria are not met.

Repeated dose toxicity

Product:

Species: rat, male and female
Application Route: Inhalation
Test atmosphere: Gas
Method: OECD Test Guideline 422

SAFETY DATA SHEET

According to the Hazardous Products Regulations

NGL Butane/Butylene Mix - NonOdorized

Version
3.0

Revision Date:
2024-09-26

SDS Number:
800010025825

Print Date: 2024-10-03
Date of last issue: 22.09.2021
Date of first issue: 23.11.2015

Target Organs: No specific target organs noted

Components:

but-1-ene:

Species: rat, male and female

Application Route: Inhalation

Test atmosphere: Gas

Method: OECD Test Guideline 422

Target Organs: No specific target organs noted

Aspiration toxicity

Product:

Based on available data, the classification criteria are not met.

Components:

but-1-ene:

Based on available data, the classification criteria are not met.

Further information

Product:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

Components:

but-1-ene:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment : Incomplete ecotoxicological data are available for this product.
The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.

Ecotoxicity

Product:

Toxicity to fish (Acute toxicity) : LC50: 19 mg/l
Exposure time: 96 h
Method: Based on quantitative structure-activity relationship (QSAR) modelling
Remarks: LL/EL/IL50 10-100 mg/l

Toxicity to crustacean (Acute toxicity) : LC50 (Daphnia (water flea)): 16 mg/l
Exposure time: 48 h
Method: Based on quantitative structure-activity relationship

SAFETY DATA SHEET

According to the Hazardous Products Regulations

NGL Butane/Butylene Mix - NonOdorized

Version
3.0

Revision Date:
2024-09-26

SDS Number:
800010025825

Print Date: 2024-10-03
Date of last issue: 22.09.2021
Date of first issue: 23.11.2015

	(QSAR) modelling Remarks: LL/EL/IL50 10-100 mg/l
Toxicity to algae/aquatic plants (Acute toxicity)	: EC50 (green algae): 6.9 mg/l Exposure time: 96 h Method: Based on quantitative structure-activity relationship (QSAR) modelling Remarks: LL/EL/IL50 1-10 mg/l
Toxicity to fish (Chronic toxicity)	: Chronic Toxicity Value: 2 mg/l Exposure time: 30 d Method: Based on quantitative structure-activity relationship (QSAR) modelling
Toxicity to crustacean (Chronic toxicity)	: Chronic Toxicity Value (Daphnia (water flea)): 1.6 mg/l Method: Based on quantitative structure-activity relationship (QSAR) modelling
Toxicity to microorganisms (Acute toxicity)	: Remarks: Data not available
<u>Components:</u>	
but-1-ene:	
Toxicity to fish (Acute toxicity)	: LC50: 19 mg/l Exposure time: 96 h Method: Based on quantitative structure-activity relationship (QSAR) modelling Remarks: LL/EL/IL50 10-100 mg/l
Toxicity to crustacean (Acute toxicity)	: LC50 (Daphnia (water flea)): 16 mg/l Exposure time: 48 h Method: Based on quantitative structure-activity relationship (QSAR) modelling Remarks: LL/EL/IL50 10-100 mg/l
Toxicity to algae/aquatic plants (Acute toxicity)	: EC50 (green algae): 6.9 mg/l Exposure time: 96 h Method: Based on quantitative structure-activity relationship (QSAR) modelling Remarks: LL/EL/IL50 1-10 mg/l
Toxicity to fish (Chronic toxicity)	: Chronic Toxicity Value: 2 mg/l Exposure time: 30 d Method: Based on quantitative structure-activity relationship (QSAR) modelling
Toxicity to crustacean (Chronic toxicity)	: Chronic Toxicity Value (Daphnia (water flea)): 1.6 mg/l Method: Based on quantitative structure-activity relationship (QSAR) modelling
Toxicity to bacteria	: Remarks: Data not available

SAFETY DATA SHEET

According to the Hazardous Products Regulations

NGL Butane/Butylene Mix - NonOdorized

Version
3.0

Revision Date:
2024-09-26

SDS Number:
800010025825

Print Date: 2024-10-03
Date of last issue: 22.09.2021
Date of first issue: 23.11.2015

Persistence and degradability

Product:

Biodegradability : Method: Based on quantitative structure-activity relationship (QSAR) modelling
Remarks: Readily biodegradable.
Oxidises rapidly by photo-chemical reactions in air.

Components:

but-1-ene:

Biodegradability : Method: Based on quantitative structure-activity relationship (QSAR) modelling
Remarks: Readily biodegradable.
Oxidises rapidly by photo-chemical reactions in air.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

Partition coefficient: n-octanol/water : log Pow: 2.3

Components:

but-1-ene:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

Mobility in soil

Product:

Mobility : Remarks: Because of their extreme volatility, air is the only environmental compartment that hydrocarbon gases will be found.

Components:

but-1-ene:

Mobility : Remarks: Because of their extreme volatility, air is the only environmental compartment that hydrocarbon gases will be found.

Other adverse effects

Product:

Results of PBT and vPvB assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

Additional ecological information : In view of the high rate of loss from solution, the product is

SAFETY DATA SHEET

According to the Hazardous Products Regulations

NGL Butane/Butylene Mix - NonOdorized

Version
3.0

Revision Date:
2024-09-26

SDS Number:
800010025825

Print Date: 2024-10-03
Date of last issue: 22.09.2021
Date of first issue: 23.11.2015

mation

unlikely to pose a significant hazard to aquatic life.

Components:

but-1-ene:

Results of PBT and vPvB
assessment

: The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

Additional ecological information

: In view of the high rate of loss from solution, the product is unlikely to pose a significant hazard to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

: Recover or recycle if possible.
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water courses.

Waste product should not be allowed to contaminate soil or water.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local regulations may be more stringent than regional or national requirements and must be complied with.

Contaminated packaging

: Data not available

SECTION 14. TRANSPORT INFORMATION

TDG

UN number

: 1965

Proper shipping name

: HYDROCARBON GAS MIXTURE, LIQUEFIED, N.O.S.
(Butane, Butylene)

Class

: 2.1

Packing group

: Not Assigned

Labels

: 2.1

Marine pollutant

: no

International Regulations

IATA-DGR

SAFETY DATA SHEET

According to the Hazardous Products Regulations

NGL Butane/Butylene Mix - NonOdorized

Version
3.0

Revision Date:
2024-09-26

SDS Number:
800010025825

Print Date: 2024-10-03
Date of last issue: 22.09.2021
Date of first issue: 23.11.2015

UN/ID No. : UN 1965
Proper shipping name : HYDROCARBON GAS MIXTURE, LIQUEFIED, N.O.S.
(Butane, Butylene)

Class : 2.1
Packing group : Not Assigned
Labels : 2.1

IMDG-Code

UN number : UN 1965
Proper shipping name : HYDROCARBON GAS MIXTURE, LIQUEFIED, N.O.S.
(Butane, Butylene)

Class : 2.1
Packing group : Not Assigned
Labels : 2.1
Marine pollutant : no

Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.
The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

DSL : Listed

TSCA : Listed

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -

SAFETY DATA SHEET

According to the Hazardous Products Regulations

NGL Butane/Butylene Mix - NonOdorized

Version
3.0

Revision Date:
2024-09-26

SDS Number:
800010025825

Print Date: 2024-10-03
Date of last issue: 22.09.2021
Date of first issue: 23.11.2015

Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

Revision Date : 2024-09-26

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN