Version 3.0 Revision Date 24.01.2024 Print Date 31.01.2024

## 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product name : NEODOL 91-8

Product code : V2462, V2666

CAS-No. : 68439-46-3

Synonyms : Alcohols C9-11, ethoxylated

Manufacturer or supplier's details

Manufacturer/Supplier : Shell Chemicals Europe B.V.

PO Box 2334

3000 CH Rotterdam

Netherlands

Telephone : +31 (0)10 441 5137 / +31 (0)10 441 5191 Telefax : +31 (0)20 716 8316 /+31 (0)20 713 9230

Emergency telephone : +31 (0)10 231 7393

number +44 (0) 1235 239 670 (This telephone number is available 24

hours per day, 7 days per week) UAT for SPS2020 - New ER number

Recommended use of the chemical and restrictions on use

Recommended use : Use as a surfactant in various applications

Restrictions on use : This product must not be used in applications other than the

above without first seeking the advice of the supplier.

Other information : NEODOL is a trademark owned by Shell Trademark

Management B.V. and Shell Brands Inc. and used by affiliates

of Royal Dutch Shell plc.

#### 2. HAZARDS IDENTIFICATION

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity (Oral) : Category 4 Serious eye damage : Category 1

Label elements

Hazard pictograms



Signal word : Danger

Hazard statements : PHYSICAL HAZARDS:

Version 3.0 Revision Date 24.01.2024 Print Date 31.01.2024

Not classified as a physical hazard according to CLP criteria.

HEALTH HAZARDS: H302 Harmful if swallowed.

H318 Causes serious eye damage. ENVIRONMENTAL HAZARDS:

Not classified as environmental hazard according to CLP

criteria.

Precautionary statements : **Prevention:** 

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P301 + P312 IF SWALLOWED: Call a POISON CENTER/

doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/ doctor.

Storage:

No precautionary phrases.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

#### Other hazards

None known.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

# **Hazardous components**

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (% w/w)
Alcohols, C9-11, ethoxylated	68439-46-3	Acute Tox. 4; H302 Eye Dam. 1; H318	<= 100

For explanation of abbreviations see section 16.

#### 4. FIRST-AID MEASURES

General advice : Not expected to be a health hazard when used under normal

conditions.

Version 3.0		Revision Date 24.01.2024	Print Date 31.01.2024
If inhaled	:	No treatment necessary under norm If symptoms persist, obtain medical	
In case of skin contact	:	Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If needed, transport to the nearest medical facility for additional treatment.	
In case of eye contact	:	Immediately flush eye(s) with plenty Remove contact lenses, if present a rinsing. Transport to the nearest medical fa treatment.	and easy to do. Continue
If swallowed	:	Do not induce vomiting. If victim is drink 1/2 to 1 glass of water to help give liquids to a drowsy, convulsing Transport to nearest medical facility	dilute the material. Do not , or unconscious person.
Most important symptoms and effects, both acute and delayed	:	Not considered to be an inhalation conditions of use.  Possible respiratory irritation signs a temporary burning sensation of the coughing, and/or difficulty breathing.	and symptoms may include ne nose and throat,
		Skin irritation signs and symptoms sensation, redness, swelling, and/o	
		Corrosive to eyes. Contact can cause severe eye dam burns, pain, clouding of the eye sur eye, and may result in permanent lo	face, inflammation of the
		Swallowing of corrosive chemicals and burning in the mouth, throat, ar vomiting and diarrhea.	
		Burns and tearing of the esophagus possible.	s and stomach are
		Defatting dermatitis signs and symp burning sensation and/or a dried/cra	
Protection of first-aiders	:	When administering first aid, ensure appropriate personal protective equincident, injury and surroundings.	
Notes to physician	:	IMMEDIATE TREATMENT IS EXTENDED IN CORRECT I	

Version 3.0 Revision Date 24.01.2024 Print Date 31.01.2024

#### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam, water spray or fog. Dry chemical

powder, carbon dioxide, sand or earth may be used for small

fires only.

Unsuitable extinguishing

media

: None

Specific hazards during

firefighting

: Carbon monoxide may be evolved if incomplete combustion

occurs.

Specific extinguishing

methods

Standard procedure for chemical fires.

Clear fire area of all non-emergency personnel.

Keep adjacent containers cool by spraying with water.

Special protective equipment

for firefighters

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Observe all relevant local and international regulations. Notify authorities if any exposure to the general public or the

environment occurs or is likely to occur.

Local authorities should be advised if significant spillages

cannot be contained.

: Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see

Section 13 of this Safety Data Sheet. Stay upwind and keep out of low areas. Be ready for fire or possible exposure.

**Environmental precautions** 

: Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers. Use appropriate containment to avoid environmental

contamination.

Ventilate contaminated area thoroughly.

Methods and materials for containment and cleaning up

: For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or

Version 3.0 Revision Date 24.01.2024 Print Date 31.01.2024

safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove

contaminated soil and dispose of safely.

Additional advice : For guidance on selection of personal protective equipment

see Section 8 of this Safety Data Sheet.

For guidance on disposal of spilled material see Section 13 of

this Safety Data Sheet.

#### 7. HANDLING AND STORAGE

General Precautions : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine

appropriate controls for safe handling, storage and disposal of

this material.

Ensure that all local regulations regarding handling and

storage facilities are followed.

Advice on safe handling : Avoid contact with skin, eyes and clothing.

Do not empty into drains.

Avoidance of contact : Copper.

Copper alloys.

Strong oxidising agents.

Aluminum

Product Transfer : Keep containers closed when not in use. Refer to guidance

under Handling section.

**Storage** 

Conditions for safe storage : Refer to section 15 for any additional specific legislation

covering the packaging and storage of this product.

Other data : Tanks should be fitted with heating coils in areas where the

ambient temperatures are below the recommended product handling temperatures. Heating coil skin temperatures should

not exceed 100 °C.

Bulk storage tanks should be diked (bunded).

Vapours from tanks should not be released to atmosphere. Breathing losses during storage should be controlled by a

suitable vapour treatment system.

Nitrogen blanket recommended for large tanks (capacity 100

m3 or higher).

Insulation (lagging) will minimize heat loss in areas of low

ambient temperature.

Tanks should be fitted with heating coils in areas where ambient conditions can result in handling temperatures below

the freezing point/pour point of the product.

Version 3.0	Revision Date 24.01.2024	Print Date 31.01.2024	
Packaging material		Suitable material: Stainless steel., Epoxy resins, Polyester. Unsuitable material: Aluminum, Copper., Copper alloys.	
Container Advice	explosive vapours. Do not cut, dri	Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers.	
Specific use(s)	: Not applicable		
	Ensure that all local regulations restorage facilities are followed.	egarding handling and	

#### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

# Components with workplace control parameters

## **Biological occupational exposure limits**

No biological limit allocated.

# **Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

#### **Engineering measures**

: Adequate ventilation to control airborne concentrations below the exposure guidelines/limits.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. Eye washes and showers for emergency use.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.

Appropriate measures include:

# General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and

Version 3.0 Revision Date 24.01.2024 Print Date 31.01.2024

> protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Do not ingest. If swallowed, then seek immediate medical assistance.

#### Personal protective equipment

#### **Protective measures**

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection

: If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use: Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].

Hand protection Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact

Version 3.0 Revision Date 24.01.2024 Print Date 31.01.2024

composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye protection : Wear goggles for use against liquids and gas.

Wear full face shield if splashes are likely to occur.

Skin and body protection : Skin protection is not required under normal conditions of use.

For prolonged or repeated exposures use impervious clothing

over parts of the body subject to exposure.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard,

and provide employee skin care programmes.

Thermal hazards : Not applicable

Hygiene measures : Wash hands before eating, drinking, smoking and using the

toilet.

Launder contaminated clothing before re-use.

#### **Environmental exposure controls**

General advice : Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

vapour.

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local

environmental legislation.

Information on accidental release measures are to be found in

section 6.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Slightly viscous liquid.

Colour : Data not available

Odour : mild

Odour Threshold : Data not available pH : Data not available

pour point :  $15 \,^{\circ}\text{C} / 59 \,^{\circ}\text{F}$ 

Method: ASTM D97

Melting point/range ca. 15 °C / 59 °F

Initial boiling point and boiling : > 232 °C / 450 °F

# **NEODOL 91-8**

Version 3.0 Revision Date 24.01.2024 Print Date 31.01.2024

range

Flash point :  $159 \, ^{\circ}\text{C} / 318 \, ^{\circ}\text{F}$ 

Evaporation rate : Data not available

Flammability (solid, gas) : Not applicable

Upper explosion limit : Data not available
Lower explosion limit : Data not available

Vapour pressure : < 0.1 hPa (37 °C / 99 °F)

Relative vapour density : 18,0

Relative density : 1,008 (25 °C / 77 °F)

Method: ASTM D4052

Density : 996 kg/m3 (40 °C / 104 °F)

Method: ASTM D4052

Solubility(ies)

Water solubility : 100 g/l Complete, may form gel.

Partition coefficient: n-

octanol/water

: Data not available

Auto-ignition temperature : Data not available

Decomposition temperature : Data not available

Viscosity

Viscosity, dynamic : 98 mPa.s (20 °C / 68 °F)

Method: ASTM D445

Viscosity, dynamic 50 mPa.s (28 °C / 82 °F)

Method: ASTM D445

Viscosity, kinematic : 39,0 mm2/s (37 °C / 99 °F)

Method: ASTM D445

27 mm2/s (40 °C / 104 °F) Method: ASTM D445

Explosive properties : Not applicable

Oxidizing properties : Data not available

Surface tension :  $0,03 \text{ mN/m}, 24 ^{\circ}\text{C} / 75 ^{\circ}\text{F}$ 

Conductivity: > 10,000 pS/m

A number of factors, for example liquid temperature, presence

# **NEODOL 91-8**

Version 3.0 Revision Date 24.01.2024 Print Date 31.01.2024

> of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be

a static accumulator.

Particle size : Data not available

Data not available

Molecular weight : 510 g/mol

#### 10. STABILITY AND REACTIVITY

: Stable at normal ambient temperature and pressure., May Reactivity

oxidise in the presence of air.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: None known.

Conditions to avoid : Extremes of temperature and direct sunlight.

Product cannot ignite due to static electricity.

Incompatible materials : Copper.

Copper alloys.

Strong oxidising agents.

Aluminum

Hazardous decomposition

products

: None expected under normal use conditions.

#### 11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on product testing, and/or similar

products, and/or components.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for

individual component(s).

exposure

Information on likely routes of : Exposure may occur via inhalation, ingestion, skin absorption,

skin or eye contact, and accidental ingestion.

#### **Acute toxicity**

# **Components:**

Alcohols, C9-11, ethoxylated:

Acute oral toxicity : LD50: > 300 - <= 2000 mg/kg

Remarks: Harmful if swallowed.

Acute inhalation toxicity : Remarks: Low toxicity if inhaled.

# **NEODOL 91-8**

Version 3.0 Revision Date 24.01.2024 Print Date 31.01.2024

Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 : > 2000 mg/kg

Remarks: Low toxicity

Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation

## **Components:**

# Alcohols, C9-11, ethoxylated:

Remarks: Causes mild skin irritation., Repeated exposure may cause skin dryness or cracking.

#### Serious eye damage/eye irritation

## **Components:**

# Alcohols, C9-11, ethoxylated:

Remarks: Causes serious eye damage.

## Respiratory or skin sensitisation

#### Components:

#### Alcohols, C9-11, ethoxylated:

Remarks: Not a sensitiser.

Based on available data, the classification criteria are not met.

# Germ cell mutagenicity

#### **Components:**

Alcohols, C9-11, ethoxylated:

Remarks: Non mutagenic

## Carcinogenicity

# **Components:**

## Alcohols, C9-11, ethoxylated:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
Alcohols, C9-11, ethoxylated	No carcinogenicity classification.

# Reproductive toxicity

## Components:

## Alcohols, C9-11, ethoxylated:

Remarks: Does not impair fertility., Not a developmental toxicant., Based on available data, the classification criteria

are not met.

Version 3.0 Revision Date 24.01.2024 Print Date 31.01.2024

# STOT - single exposure

#### **Components:**

## Alcohols, C9-11, ethoxylated:

Remarks: Based on available data, the classification criteria are not met.

# STOT - repeated exposure

# **Components:**

## Alcohols, C9-11, ethoxylated:

Remarks: Based on available data, the classification criteria are not met.

## **Aspiration toxicity**

# Components:

## Alcohols, C9-11, ethoxylated:

Not an aspiration hazard.

#### **Further information**

#### Components:

# Alcohols, C9-11, ethoxylated:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

#### 12. ECOLOGICAL INFORMATION

Basis for assessment Incomplete ecotoxicological data are available for this product.

The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.

Unless indicated otherwise, the data presented is

representative of the product as a whole, rather than for

individual component(s).

## **Ecotoxicity**

# Components:

#### Alcohols, C9-11, ethoxylated:

Toxicity to fish (Acute : Remarks: Harmful

toxicity) LC/EC/IC50 >10 - <=100 mg/l

Toxicity to crustacean (Acute

: Remarks: Toxic

toxicity) LC/EC/IC50 >1 - <=10 mg/l

Toxicity to algae/aquatic : Remarks: Harmful

plants (Acute toxicity) LC/EC/IC50 >10 - <=100 mg/l

Toxicity to microorganisms : Remarks: LC/EC/IC50 > 100 mg/l

(Acute toxicity) Practically non toxic:

Based on available data, the classification criteria are not met.

# **NEODOL 91-8**

Version 3.0 Revision Date 24.01.2024 Print Date 31.01.2024

Toxicity to fish (Chronic : Remarks: NOEC/NOEL > 1.0 - <= 10 mg/l

toxicity)

Toxicity to : Remarks: NOEC/NOEL > 1.0 - <= 10 mg/l

crustacean(Chronic toxicity)

Persistence and degradability

**Components:** 

Alcohols, C9-11, ethoxylated:

Biodegradability : Remarks: Readily biodegradable.

**Bioaccumulative potential** 

**Product:** 

Partition coefficient: n-

octanol/water Components:

: Remarks: Data not available

Alcohols, C9-11, ethoxylated :

Bioaccumulation : Remarks: Bioaccumulation is unlikely to occur due to

metabolism and excretion.

Mobility in soil

**Components:** 

Alcohols, C9-11, ethoxylated:

Mobility : Remarks: Dissolves in water., If the product enters soil, one or

more constituents will or may be mobile and may contaminate

groundwater.

Other adverse effects

no data available

# 13. DISPOSAL CONSIDERATIONS

# Disposal methods

Waste from residues : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses.

Waste product should not be allowed to contaminate soil or

water.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be complied with.

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Residues may cause an explosion hazard. Do not puncture, cut, or weld uncleaned drums.

Version 3.0 Revision Date 24.01.2024 Print Date 31.01.2024

Send to drum recoverer or metal reclaimer.

#### 14. TRANSPORT INFORMATION

# **International Regulations**

## **ADR**

Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

#### **IMDG-Code**

Not regulated as a dangerous good

#### Maritime transport in bulk according to IMO instruments

Pollution category : Y Ship type : 3

Product name : Alcohol (C9-11) poly (2.5-9) ethoxylate

#### Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

**Additional Information**: This product may be transported under nitrogen blanketing.

Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a

confined space entry.

Transport in bulk according to Annex II of Marpol and the IBC

Code

#### 15. REGULATORY INFORMATION

# Safety, health and environmental regulations/legislation specific for the substance or mixture

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

# Other international regulations

## The components of this product are reported in the following inventories:

AIIC Listed DSL Listed **IECSC** Listed KECI Listed **NZIoC** Listed **PICCS** Listed **TSCA** Listed **ENCS** Listed

# **NEODOL 91-8**

Version 3.0 Revision Date 24.01.2024 Print Date 31.01.2024

TCSI : Listed

#### 16. OTHER INFORMATION

#### **Full text of H-Statements**

H302 Harmful if swallowed.

H318 Causes serious eye damage.

#### Full text of other abbreviations

Acute Tox. Acute toxicity

Eye Dam. Serious eye damage

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this

document can be looked up in reference literature (e.g.

scientific dictionaries) and/or websites.

SDS Regulation : Regulation 1907/2006/EC

**Further information** 

Training advice : Provide adequate information, instruction and training for

operators.

Other information : A vertical bar (|) in the left margin indicates an amendment

from the previous version.

Sources of key data used to

compile the Safety Data

Sheet

: The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell

Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.