

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

| | |
|---------------------|---|
| Trade name | : Para-xylene |
| Product code | : Q9161, Q9302, Q9267, Q9272 |
| Registration number | : 01-2119484661-33-0004, 01-2119484661-33-0005, 01-2119484661-33-0007 |
| Synonyms | : 1,4-dimethylbenzene, p-Xylene |
| CAS-No. | : 106-42-3 |

1.2 Relevant identified uses of the substance or mixture and uses advised against

| | |
|------------------------------|--|
| Use of the Substance/Mixture | : Raw material for use in the chemical industry. Please refer to Ch16 and/or the annexes for the registered uses under REACH. |
| Uses advised against | : This product must not be used in applications other than the above without first seeking the advice of the supplier. |

1.3 Details of the supplier of the safety data sheet

| | |
|-------------------------------------|---|
| Manufacturer/Supplier | : Shell Chemicals Europe B.V. PO Box 2334 3000 CH Rotterdam Netherlands |
| Telephone | : +31 (0)10 441 5137 / +31 (0)10 441 5191 |
| Telefax | : +31 (0)20 716 8316 / +31 (0)20 713 9230 |
| Email Contact for Safety Data Sheet | : sccmsds@shell.com |

1.4 Emergency telephone number

+44 (0) 1235 239 670 (This telephone number is available 24 hours per day, 7 days per week)
+44 (0) 1235 239 670 (Questo numero di telefono è disponibile 24 ore al giorno, 7 giorni la settimana)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| | |
|-------------------------------|--|
| Flammable liquids, Category 3 | H226: Flammable liquid and vapour. |
| Aspiration hazard, Category 1 | H304: May be fatal if swallowed and enters |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

Acute toxicity, Category 4, Dermal
Skin irritation, Category 2
Eye irritation, Category 2
Acute toxicity, Category 4, Inhalation
Specific target organ toxicity - single exposure, Category 3
Long-term (chronic) aquatic hazard, Category 3

airways.
H312: Harmful in contact with skin.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H332: Harmful if inhaled.
H335: May cause respiratory irritation.

H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

| | |
|------|--|
| H226 | PHYSICAL HAZARDS: Flammable liquid and vapour. |
| H304 | HEALTH HAZARDS: May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H335 | May cause respiratory irritation. |
| H412 | ENVIRONMENTAL HAZARDS: Harmful to aquatic life with long lasting effects. |

Precautionary statements :

| | |
|--------------------|--|
| Prevention: | |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P243 | Take action to prevent static discharges. |
| P280 | Wear protective gloves/ protective clothing/ eye protection/ face protection. |
| P261 | Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. |
| P273 | Avoid release to the environment. |
| Response: | |
| P303 + P361 + P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. |
| P370 + P378 | In case of fire: Use appropriate media to extinguish. |
| P301 + P310 | IF SWALLOWED: Immediately call a POISON CENTER/ doctor. |
| P331 | Do NOT induce vomiting. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

P332 + P313 If skin irritation occurs: Get medical advice/attention.

Storage: No precautionary phrases.

Disposal: No precautionary phrases.

2.3 Other hazards

Vapours may cause drowsiness and dizziness.
May form flammable/explosive vapour-air mixture.
This material is a static accumulator.
Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.
If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

SECTION 3: Composition/information on ingredients

3.1 Substances

Hazardous components

| Chemical name | CAS-No. EC-No. | Concentration (% w/w) |
|---------------|-----------------------|-----------------------|
| p-xylene | 106-42-3 203-396-5 | >= 99,7 |

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Not expected to be a health hazard when used under normal conditions.
- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- If inhaled : Call emergency number for your location / facility.
Remove to fresh air. Do not attempt to rescue the victim unless proper respiratory protection is worn. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting, or unresponsive, give 100% oxygen with rescue breathing or Cardio-Pulmonary Resuscitation as required and transport to the nearest medical facility.
- In case of skin contact : Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If needed, transport to the nearest medical facility for additional treatment.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses, if present and easy to do. Continue rinsing.
Transport to the nearest medical facility for additional treatment.
- If swallowed : Call emergency number for your location / facility.
If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.
Skin irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blisters.
Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.
Ingestion may result in nausea, vomiting and/or diarrhoea.
If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.
If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.
Auditory system effects may include temporary hearing loss and/or ringing in the ears.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!
Call a doctor or poison control center for guidance.
Potential for chemical pneumonitis.
Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
- Unsuitable extinguishing media : Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

Specific hazards during firefighting : Clear fire area of all non-emergency personnel. Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Flammable vapours may be present even at temperatures below the flash point. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Will float and can be reignited on surface water.

5.3 Advice for firefighters

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

Specific extinguishing methods : Standard procedure for chemical fires.

Further information : Keep adjacent containers cool by spraying with water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Observe all relevant local and international regulations. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Local authorities should be advised if significant spillages cannot be contained.

6.1.1 For non emergency personnel:
Avoid contact with skin, eyes and clothing.
Isolate hazard area and deny entry to unnecessary or unprotected personnel.
Do not breathe fumes, vapour.
Do not operate electrical equipment.

6.1.2 For emergency responders:
Avoid contact with skin, eyes and clothing.
Isolate hazard area and deny entry to unnecessary or unprotected personnel.
Do not breathe fumes, vapour.
Do not operate electrical equipment.

6.2 Environmental precautions

Environmental precautions : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.

Monitor area with combustible gas indicator.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. Ventilate contaminated area thoroughly.

If contamination of site occurs remediation may require specialist advice.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.,
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

General Precautions : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

Ensure that all local regulations regarding handling and storage facilities are followed.

7.1 Precautions for safe handling

Advice on safe handling : Avoid inhaling vapour and/or mists.

Avoid contact with skin, eyes and clothing.

Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.

Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.

Bulk storage tanks should be diked (bunded).

When using do not eat or drink.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

The vapour is heavier than air, spreads along the ground and distant ignition is possible.

Product Transfer : Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/s until fill pipe submerged to twice its diameter, then ≤ 7 m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.

Refer to guidance under Handling section.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Other data : Storage Temperature: Ambient.

Bulk storage tanks should be diked (bunded). Locate tanks away from heat and other sources of ignition. Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions. Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat. Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products which are not harmful or toxic to man or to the environment. Electrostatic charges will be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk. The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.

Packaging material : Suitable material: For containers, or container linings use mild steel, stainless steel., For container paints, use epoxy paint, zinc silicate paint.
Unsuitable material: Avoid prolonged contact with natural, butyl or nitrile rubbers.

Container Advice : Do not cut, drill, grind, weld or perform similar operations on or near containers.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

7.3 Specific end use(s)

Specific use(s) : Please refer to Ch16 and/or the annexes for the registered uses under REACH.

See additional references that provide safe handling practices for liquids that are determined to be static accumulators:
American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or
National Fire Protection Agency 77 (Recommended Practices on Static Electricity).
IEC/TS 60079-32-1: Electrostatic hazards, guidance

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|---------------------|---|-------------------------------|----------------------|--------|
| p-xylene | 106-42-3 | TWA | 50 ppm 221 mg/m3 | IT OEL |
| Further information | The notation 'Skin' attributes to the exposure limit values and indicates the possibility of absorption through the skin. | | | |
| p-xylene | 106-42-3 | STEL | 100 ppm 442 mg/m3 | IT OEL |
| Further information | The notation 'Skin' attributes to the exposure limit values and indicates the possibility of absorption through the skin. | | | |

Biological occupational exposure limits

No biological limit allocated.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

p-xylene : End Use: Workers
Exposure routes: Inhalation
Potential health effects: Acute systemic effects
Value: 442 mg/m3
End Use: Workers
Exposure routes: Dermal
Potential health effects: Long-term systemic effects
Value: 3182 mg/kg bw/day
End Use: Workers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 221 mg/m3

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| | |
|----------|--|
| p-xylene | : Fresh water Value: 0,25 mg/l |
| | Sediment Value: 14,33 mg/kg dry weight (d.w.) |
| | Soil Value: 2,41 mg/kg dry weight (d.w.) |
| | Sewage treatment plant Value: 5 mg/l |

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods
<http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods
<http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances
<http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany
<http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

8.2 Exposure controls

Engineering measures Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

Eye washes and showers for emergency use.

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.

Practice good housekeeping.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

Define procedures for safe handling and maintenance of controls.
Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.
Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.
Drain down system prior to equipment break-in or maintenance.
Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : Wear goggles for use against liquids and gas.
Wear full face shield if splashes are likely to occur.
Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Viton. Incidental contact/Splash protection: Nitrile rubber. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced.

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

- Skin and body protection : Wear chemical resistant gloves/gauntlets and boots. Where risk of splashing, also wear an apron.
Wear antistatic and flame-retardant clothing.
- Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type A boiling point > 65°C (149°F)] meeting EN14387.
- Hygiene measures : Wash hands before eating, drinking, smoking and using the toilet. Launder contaminated clothing before re-use. Do not ingest. If swallowed, then seek immediate medical assistance.

Environmental exposure controls

- General advice : Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour. Information on accidental release measures are to be found in section 6. Take appropriate measures to fulfil the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : Liquid.
- Colour : colourless
- Odour : aromatic
- Odour Threshold : Data not available
- pH : Not applicable

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

| | |
|--|---|
| Melting point/freezing point | : 13,2 °C |
| Boiling point/boiling range | : 138 °C |
| Flash point | : > 23 - 29 °C Method: Abel |
| Evaporation rate | : Data not available |
| Flammability (solid, gas) | : Not applicable |
| Upper explosion limit | : 7 %(V) |
| Lower explosion limit | : 1 %(V) |
| Vapour pressure | : 1,167 kPa (25 °C) |
| Relative vapour density | : Data not available |
| Relative density | : Data not available |
| Density | : Typical 865 kg/m ³ (15 °C) Method: ASTM D4052 |
| Solubility(ies) | |
| Water solubility | : Data not available |
| Partition coefficient: n-octanol/water | : log Pow: 3,15 |
| Auto-ignition temperature | : > 500 °C |
| Decomposition temperature | : Data not available |
| Viscosity | |
| Viscosity, dynamic | : 0,65 mPa.s (20 °C) |
| Viscosity, kinematic | : 0,7 mm ² /s (25 °C) |
| Explosive properties | : Classification Code: Not classified |
| Oxidizing properties | : Not applicable |

9.2 Other information

| | |
|-----------------|---|
| Surface tension | : Data not available |
| Conductivity | : Low conductivity: < 100 pS/m, The conductivity of this material makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

considered semi-conductive if its conductivity is below 10,000 pS/m., Whether a liquid is nonconductive or semiconductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid

Molecular weight : 106 g/mol

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions, Stable under normal conditions of use.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.

In certain circumstances product can ignite due to static electricity.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

10.6 Hazardous decomposition products

Hazardous decomposition products : Hazardous decomposition products are not expected to form during normal storage.
Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Basis for assessment : Information given is based on product testing, and/or similar

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

products, and/or components.

Information on likely routes of exposure : Inhalation is the primary route of exposure although absorption may occur through skin contact or following accidental ingestion.

Acute toxicity

Components:

p-xylene:

Acute oral toxicity : LD 50 Rat, male and female: > 2.000 mg/kg
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)
Test substance: Mixed xylenes
Remarks: May be harmful if swallowed.

Acute inhalation toxicity : LC 50 Rat, male and female: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Other guideline method.
Test substance: Mixed xylenes
Remarks: Harmful if inhaled.

Acute dermal toxicity : LD 50 Rabbit, male: > 2.000 mg/kg
Method: Literature data
Test substance: C8 aromatics
Remarks: Harmful in contact with skin.

Skin corrosion/irritation

Components:

p-xylene:

Species: Rabbit
Method: Tested according to Annex V of Directive 67/548/EEC.
Remarks: Causes skin irritation., Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.

Serious eye damage/eye irritation

Components:

p-xylene:

Species: Rabbit
Method: Literature data
Test substance: C8 aromatics
Remarks: Causes serious eye irritation.

Respiratory or skin sensitisation

Components:

p-xylene:

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

Species: Mouse

Method: Test(s) equivalent or similar to OECD Test Guideline 429

Test substance: Mixed xylenes

Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Components:

p-xylene:

- : Method: Test(s) equivalent or similar to OECD Guideline 471
Remarks: Based on available data, the classification criteria are not met.
- : Method: Test(s) equivalent or similar to Directive 67/548/EEC, Annex V, B.10
Test substance: Mixed xylenes
Remarks: Based on available data, the classification criteria are not met.
- : Test species: MouseMethod: Test(s) equivalent or similar to OECD Test Guideline 474
Remarks: Based on available data, the classification criteria are not met.
- : Test species: MouseMethod: Test(s) equivalent or similar to OECD Test guideline 478
Test substance: Mixed xylenes
Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity-
Assessment

- : This product does not meet the criteria for classification in categories 1A/1B.

Carcinogenicity

Components:

p-xylene:

Species: Rat, (male and female)

Application Route: Oral

Method: Test(s) equivalent or similar to Directive 67/548/EEC, Annex V, B.32

Test substance: Mixed xylenes

Remarks: Based on available data, the classification criteria are not met.

Carcinogenicity -
Assessment

- : This product does not meet the criteria for classification in categories 1A/1B.

| Material | GHS/CLP Carcinogenicity Classification |
|----------|--|
| p-xylene | No carcinogenicity classification. |

| Material | Other Carcinogenicity Classification |
|----------|--------------------------------------|
|----------|--------------------------------------|

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

| | |
|----------|---|
| p-xylene | IARC: Group 3: Not classifiable as to its carcinogenicity to humans |
|----------|---|

Reproductive toxicity

Components:

p-xylene:

Effects on fertility

: Species: Rat
Sex: male and female
Application Route: Inhalation

Method: Acceptable non-standard method.
Test substance: Mixed xylenes
Remarks: Based on available data, the classification criteria are not met.

Effects on foetal development

: Species: Rat, female
Application Route: Inhalation
Method: Test(s) equivalent or similar to OECD Test Guideline 414
Remarks: Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment

: This product does not meet the criteria for classification in categories 1A/1B.

STOT - single exposure

Components:

p-xylene:

Exposure routes: Inhalation

Target Organs: Respiratory Tract

Remarks: May cause respiratory irritation.

STOT - repeated exposure

Components:

p-xylene:

Remarks: Based on available data, the classification criteria are not met., Central nervous system: repeated exposure affects the nervous system., Effects were seen at high doses only., Auditory system: prolonged and repeated exposures to high concentrations have resulted in hearing loss in rats. Solvent abuse and noise interaction in the work environment may cause hearing loss., Based on data from similar materials

Repeated dose toxicity

Components:

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

p-xylene:

Rat, male and female:

Application Route: Oral

Method: Test(s) equivalent or similar to OECD Test Guideline 408

Test substance: Mixed xylenes

Target Organs: No specific target organs noted

Rat, male:

Application Route: Inhalation

Test atmosphere: vapour

Method: Literature data

Test substance: Mixed xylenes

Target Organs: No specific target organs noted

Aspiration toxicity

Components:

p-xylene:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Further information

Components:

p-xylene:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

SECTION 12: Ecological information

12.1 Toxicity

Components:

p-xylene :

Toxicity to fish (Acute toxicity) : LC50 (Oncorhynchus mykiss (rainbow trout)): 2,6 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Toxic
LL/EL/IL50 > 1 <= 10 mg/l

Toxicity to crustacean (Acute toxicity) : IC50 (Daphnia magna (Water flea)): 3,6 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202
Remarks: Toxic
LL/EL/IL50 > 1 <= 10 mg/l

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

| | |
|---|--|
| Toxicity to algae/aquatic plants (Acute toxicity) | : EC50 (Selenastrum capricornutum (green algae)): 2,2 mg/l Exposure time: 73 h Method: OECD Test Guideline 201 Remarks: Toxic LL/EL/IL50 > 1 <= 10 mg/l |
| Toxicity to microorganisms (Acute toxicity) | : EC50 (Activated sludge, domestic waste): > 198 mg/l Exposure time: 0,5 h Method: Test(s) equivalent or similar to OECD Guideline 209 Remarks: Practically non toxic: LL/EL/IL50 > 100 mg/l |
| Toxicity to fish (Chronic toxicity) | : NOEC: > 1,3 mg/l Exposure time: 56 d Species: Oncorhynchus mykiss (rainbow trout) Method: Other guideline method. Remarks: NOEC/NOEL > 1.0 - <= 10 mg/l |
| Toxicity to crustacean (Chronic toxicity) | : NOEC: 1,57 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211 Remarks: NOEC/NOEL > 1.0 - <= 10 mg/l |

12.2 Persistence and degradability

Components:

p-xylene :

| | |
|------------------|--|
| Biodegradability | : Biodegradation: 87,8 % Exposure time: 28 d Method: OECD Test Guideline 301F Remarks: Readily biodegradable., Oxidises rapidly by photo-chemical reactions in air. |
|------------------|--|

Remarks: Not Persistent per IMO criteria., International Oil Pollution Compensation (IOPC) Fund definition: "A non-persistent oil is oil, which, at the time of shipment, consists of hydrocarbon fractions, (a) at least 50% of which, by volume, distills at a temperature of 340°C (645°F) and (b) at least 95% of which, by volume, distills at a temperature of 370°C (700°F) when tested by the ASTM Method D-86/78 or any subsequent revision thereof."

12.3 Bioaccumulative potential

Product:

| | |
|--|-----------------|
| Partition coefficient: n-octanol/water | : log Pow: 3,15 |
|--|-----------------|

Components:

p-xylene :

| | |
|-----------------|---|
| Bioaccumulation | : Species: Oncorhynchus mykiss (rainbow trout) Exposure time: 56 d |
|-----------------|---|

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

Bioconcentration factor (BCF): 25,9
Method: Other guideline method.
Remarks: Does not bioaccumulate significantly.

12.4 Mobility in soil

Components:

p-xylene :

Mobility : Remarks: Floats on water., If it enters soil, it will adsorb to soil particles and will not be mobile.

12.5 Results of PBT and vPvB assessment

Components:

p-xylene :

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

12.6 Other adverse effects

no data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.
Do not dispose into the environment, in drains or in water courses
Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.
Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local regulations may be more stringent than regional or national requirements and must be complied with.

MARPOL - see International Convention for the Prevention of

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Drain container thoroughly.
After draining, vent in a safe place away from sparks and fire.
Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums.
Send to drum recoverer or metal reclaimer.
Comply with any local recovery or waste disposal regulations.

Local legislation
Remarks : For the disposal of waste arising from the product, including empty containers not cleared, follow the Legislative Decree 152/06 and subsequent amendments.

SECTION 14: Transport information

14.1 UN number

ADN : 1307
ADR : 1307
RID : 1307
IMDG : 1307
IATA : 1307

14.2 Proper shipping name

ADN : XYLENES
ADR : XYLENES
RID : XYLENES
IMDG : XYLENES
IATA : XYLENES

14.3 Transport hazard class

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADN
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3 (N2)
ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
RID

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG

Packing group : III
Labels : 3

IATA

Packing group : III
Labels : 3

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category : Y
Ship type : 2
Product name : Xylenes

Additional Information : This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV) : Product is not subject to Authorisation under REACH.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

Other regulations : The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Classification, packaging and labeling of dangerous substances (D.Lgs.52/1997 and subsequent amendments).
Classification, packaging and labeling of dangerous preparations (D.Lgs.65/2003). Safeguard of health and safety in the workplaces (D.Lgs.81/2008 and subsequent amendments). For waste disposal refer to D.Lgs.152/06 and subsequent amendments.

Product is subject to Decreto Legislativo 26 Giugno 2015, N°105 covering among others the requirements of the Seveso III directive (2012/18/EU).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), annex XIV.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), annex XVII.

Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work and its amendments.

Directive 1994/33/EC on the protection of young people at work and its amendments.

Council Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding and its amendments.

The components of this product are reported in the following inventories:

| | |
|-------|----------|
| AICS | : Listed |
| DSL | : Listed |
| IECSC | : Listed |
| ENCS | : Listed |
| KECI | : Listed |
| NZIoC | : Listed |
| PICCS | : Listed |
| TSCA | : Listed |
| TCSI | : Listed |

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

SECTION 16: Other information

Full text of other abbreviations

| | |
|----------------------------|--|
| Acute Tox. | Acute toxicity |
| Aquatic Chronic | Long-term (chronic) aquatic hazard |
| Asp. Tox. | Aspiration hazard |
| Eye Irrit. | Eye irritation |
| Flam. Liq. | Flammable liquids |
| Skin Irrit. | Skin irritation |
| STOT SE | Specific target organ toxicity - single exposure |
| Abbreviations and Acronyms | : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites. |

ACGIH = American Conference of Governmental Industrial Hygienists

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances

ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council

CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut für Normung

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission

EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and Toxicology Of Chemicals

ECHA = European Chemicals Agency

EINECS = The European Inventory of Existing Commercial Chemical Substances

EL50 = Effective Loading fifty

ENCS = Japanese Existing and New Chemical Substances Inventory

EWC = European Waste Code

GHS = Globally Harmonised System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IC50 = Inhibitory Concentration fifty

IL50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous Goods

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

INV = Chinese Chemicals Inventory
IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables
KECI = Korea Existing Chemicals Inventory
LC50 = Lethal Concentration fifty
LD50 = Lethal Dose fifty per cent.
LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading
LL50 = Lethal Loading fifty
MARPOL = International Convention for the Prevention of Pollution From Ships
NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level
OE_HP = Occupational Exposure - High Production Volume
PBT = Persistent, Bioaccumulative and Toxic
PICCS = Philippine Inventory of Chemicals and Chemical Substances
PNEC = Predicted No Effect Concentration
REACH = Registration Evaluation And Authorisation Of Chemicals
RID = Regulations Relating to International Carriage of Dangerous Goods by Rail
SKIN_DES = Skin Designation
STEL = Short term exposure limit
TRA = Targeted Risk Assessment
TSCA = US Toxic Substances Control Act
TWA = Time-Weighted Average
vPvB = very Persistent and very Bioaccumulative

Further information

Training advice : Provide adequate information, instruction and training for operators.

Other information : For Industry guidance and tools on REACH please visit the CEFIC website at <http://cefic.org/Industry-support>.
The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

A vertical bar (|) in the left margin indicates an amendment from the previous version.

This product is classified as H304 (May be fatal if swallowed and enters airways). The risk relates to potential for aspiration. The risk arising from aspiration hazard is solely related to the physico-chemical properties of the substance. The risk can therefore be controlled by implementing risk management measures tailored to this specific hazard and included within

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

Section 8 of the SDS. An exposure scenario is not presented.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

Identified Uses according to the Use Descriptor System

Uses - Worker

Title : Manufacture of substance- Industrial

Uses - Worker

Title : Use as an intermediate- Industrial

Uses - Worker

Title : Distribution of substance- Industrial

Uses - Worker

Title : Formulation & (re)packing of substances and mixtures- Industrial

Uses - Worker

Title : Uses in Coatings- Industrial

Uses - Worker

Title : Uses in Coatings- Professional

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

Exposure Scenario - Worker

300000000469

| SECTION 1 | EXPOSURE SCENARIO TITLE |
|------------------|---|
| Title | Manufacture of substance- Industrial |
| Use Descriptor | Sector of Use: SU3, SU8, SU9 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 15 Environmental Release Categories: ERC1, ERC4, ESVOC SpERC 1.1.v1 |
| Scope of process | Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/ recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities. |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|-----------|---|
|-----------|---|

| Section 2.1 | Control of Worker Exposure |
|---|--|
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers use of substance/product up to 100% (unless stated differently)., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

| Contributing Scenarios | Risk Management Measures |
|------------------------------------|--|
| General measures (skin irritants). | Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying. |
| General measures (eye irritants). | Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

| | |
|--|---|
| General exposures (closed systems) | No other specific measures identified. |
| General exposures (closed systems)with sample collectionGeneral measures (skin irritants). | No other specific measures identified. |
| General exposures (closed systems)Use in contained batch processes | No other specific measures identified. |
| General exposures (open systems)Batch processwith sample collection | No other specific measures identified. |
| Process sampling | Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). , or: Avoid carrying out activities involving exposure for more than 1 hour. |
| Laboratory activities | No other specific measures identified. |
| Bulk transfers(open systems)with potential for aerosol generation. | Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). , or: Avoid carrying out activities involving exposure for more than 1 hour. |
| Bulk transfers(closed systems) | Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). , or: Avoid carrying out activities involving exposure for more than 1 hour. |
| Equipment cleaning and maintenance | Drain down system prior to equipment opening or maintenance. |
| Storage.General measures (skin irritants). | No other specific measures identified. |

| Section 2.2 Control of Environmental Exposure | |
|---|---------|
| Substance is a unique structure. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 0,142 |
| Regional use tonnage (tonnes/year): | 6,0E+05 |
| Fraction of Regional tonnage used locally: | 1 |
| Annual site tonnage (tonnes/year): | 6,0E+05 |
| Maximum daily site tonnage (kg/day): | 2,0E+06 |
| Frequency and Duration of Use | |
| Emission Days (days/year): | 300 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 40 |
| Local marine water dilution factor: | 100 |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

| | |
|---|---------|
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (initial release prior to RMM): | 5,0E-03 |
| Release fraction to wastewater from process (initial release prior to RMM): | 3,0E-03 |
| Release fraction to soil from process (initial release prior to RMM): | 1,0E-04 |
| Technical conditions and measures at process level (source) to prevent release | |
| Common practices vary across sites thus conservative process release estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | |
| Risk from environmental exposure is driven by wastewater treatment plant microbes. | |
| Prevent discharge of undissolved substance to or recover from onsite wastewater. | |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | |
| Treat air emission to provide a typical removal efficiency of (%) | 90 |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%) | 93,6 |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | 0 |
| Organisational measures to prevent/limit release from site | |
| Do not apply industrial sludge to natural soils. | |
| Sludge should be incinerated, contained or reclaimed. | |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 93,6 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 93,6 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 6,4E+06 |
| Assumed domestic sewage treatment plant flow (m3/d) | 10.000 |
| Conditions and Measures related to external treatment of waste for disposal | |
| During manufacturing no waste of the substance is generated. | |
| Conditions and measures related to external recovery of waste | |
| During manufacturing no waste of the substance is generated. | |

| | |
|---|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. | |

| | |
|---------------------------------|--|
| Section 3.2 -Environment | |
| Used EUSES model. | |

| | |
|------------------|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE |
|------------------|--|

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

| EXPOSURE SCENARIO | |
|---|--|
| Section 4.1 - Health | |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. | |
| Section 4.2 -Environment | |
| Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. | |
| Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. | |
| Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. | |
| Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org). | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

Exposure Scenario - Worker

300000000470

| SECTION 1 | EXPOSURE SCENARIO TITLE |
|------------------|--|
| Title | Use as an intermediate- Industrial |
| Use Descriptor | Sector of Use: SU3, SU8, SU9 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 15 Environmental Release Categories: ERC1, ERC4, ESVOC SpERC 6.1a.v1 |
| Scope of process | Use of substance as an intermediate (not related to Strictly Controlled Conditions). Includes recycling/ recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container). |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|-----------|---|
|-----------|---|

| Section 2.1 | Control of Worker Exposure |
|---|--|
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers use of substance/product up to 100% (unless stated differently)., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

| Contributing Scenarios | Risk Management Measures |
|------------------------------------|--|
| General measures (skin irritants). | Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying. |
| General measures (eye irritants). | Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

| | |
|--|---|
| General exposures (closed systems) | No other specific measures identified. |
| General exposures (closed systems)with sample collectionGeneral measures (skin irritants). | No other specific measures identified. |
| General exposures (closed systems)Use in contained batch processes | No other specific measures identified. |
| General exposures (open systems)Batch processwith sample collection | No other specific measures identified. |
| Process sampling | Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). , or: Avoid carrying out activities involving exposure for more than 1 hour. |
| Laboratory activities | No other specific measures identified. |
| Bulk transfers(open systems)with potential for aerosol generation. | Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). , or: Avoid carrying out activities involving exposure for more than 1 hour. |
| Bulk transfers(closed systems) | Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). , or: Avoid carrying out activities involving exposure for more than 1 hour. |
| Equipment cleaning and maintenance | Drain down system prior to equipment opening or maintenance. |
| Storage.General measures (skin irritants). | No other specific measures identified. |

| Section 2.2 Control of Environmental Exposure | |
|---|----------|
| Substance is a unique structure. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 0,1 |
| Regional use tonnage (tonnes/year): | 3,57E+05 |
| Fraction of Regional tonnage used locally: | 0,01 |
| Annual site tonnage (tonnes/year): | 3,57E+03 |
| Maximum daily site tonnage (kg/day): | 1,19E+04 |
| Frequency and Duration of Use | |
| Emission Days (days/year): | 300 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

| | |
|---|----------|
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (initial release prior to RMM): | 5,0E-03 |
| Release fraction to wastewater from process (initial release prior to RMM): | 3,0E-03 |
| Release fraction to soil from wide dispersive use (regional only): | 1,0E-04 |
| Technical conditions and measures at process level (source) to prevent release | |
| Common practices vary across sites thus conservative process release estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | |
| Risk from environmental exposure is driven by soil. | |
| Prevent discharge of undissolved substance to or recover from onsite wastewater. | |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | |
| Treat air emission to provide a typical removal efficiency of (%) | 80 |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%) | 93,6 |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | 0 |
| Organisational measures to prevent/limit release from site | |
| Do not apply industrial sludge to natural soils. | |
| Sludge should be incinerated, contained or reclaimed. | |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 93,6 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 93,6 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 1,76E+04 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2.000 |
| Conditions and Measures related to external treatment of waste for disposal | |
| This substance is consumed during use and no waste of substance is generated. | |
| Conditions and measures related to external recovery of waste | |
| This substance is consumed during use and no waste of substance is generated. | |

| | |
|---|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. | |

| | |
|---------------------------------|--|
| Section 3.2 -Environment | |
| Used EUSES model. | |

| | |
|------------------|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|------------------|--|

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

Exposure Scenario - Worker

300000000471

| SECTION 1 | EXPOSURE SCENARIO TITLE |
|------------------|---|
| Title | Distribution of substance- Industrial |
| Use Descriptor | Sector of Use: SU3, SU8, SU9 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 9, PROC 15 Environmental Release Categories: ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC 6C,, ERC7, ESVOC SpERC 1.1b.v1 |
| Scope of process | Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities. |

| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|-----------|---|
|-----------|---|

| Section 2.1 | Control of Worker Exposure |
|---|--|
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers use of substance/product up to 100% (unless stated differently)., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

| Contributing Scenarios | Risk Management Measures |
|------------------------------------|--|
| General measures (skin irritants). | Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying. |
| General measures (eye irritants). | Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

| | |
|--|--|
| General exposures (closed systems) | No other specific measures identified. |
| General exposures (closed systems)with sample collectionGeneral measures (skin irritants). | No other specific measures identified. |
| General exposures (closed systems)Use in contained batch processes | No other specific measures identified. |
| General exposures (open systems)Batch processwith sample collection | No other specific measures identified. |
| Process sampling | No other specific measures identified. |
| Laboratory activities | No other specific measures identified. |
| Bulk transfers(closed systems) | Ensure material transfers are under containment or extract ventilation. , or: Operate activity away from sources of substance emission or release. |
| Bulk transfers(open systems) | Ensure material transfers are under containment or extract ventilation. , or: Operate activity away from sources of substance emission or release. |
| Drum and small package filling | Fill containers/cans at dedicated filling points supplied with local extract ventilation. Ensure material transfers are under containment or extract ventilation. |
| Equipment cleaning and maintenance | Drain down and flush system prior to equipment opening or maintenance. |
| Storage.General measures (skin irritants). | Store substance within a closed system. No other specific measures identified. |

| Section 2.2 | | Control of Environmental Exposure |
|---|--|-----------------------------------|
| Substance is a unique structure. | | |
| Readily biodegradable. | | |
| Amounts Used | | |
| Fraction of EU tonnage used in region: | | 0,142 |
| Regional use tonnage (tonnes/year): | | 6,0E+05 |
| Fraction of Regional tonnage used locally: | | 1 |
| Annual site tonnage (tonnes/year): | | 6,0E+05 |
| Maximum daily site tonnage (kg/day): | | 2,0E+06 |
| Frequency and Duration of Use | | |
| Emission Days (days/year): | | 300 |
| Environmental factors not influenced by risk management | | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

| | |
|---|----------|
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (initial release prior to RMM): | 1,0E-04 |
| Release fraction to wastewater from process (initial release prior to RMM): | 1,0E-05 |
| Release fraction to soil from process (initial release prior to RMM): | 1,0E-05 |
| Technical conditions and measures at process level (source) to prevent release | |
| Common practices vary across sites thus conservative process release estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | |
| Risk from environmental exposure is driven by soil. | |
| Prevent discharge of undissolved substance to or recover from onsite wastewater. | |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | |
| Treat air emission to provide a typical removal efficiency of (%) | 90 |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%) | 93,6 |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | 0 |
| Organisational measures to prevent/limit release from site | |
| Do not apply industrial sludge to natural soils. | |
| Sludge should be incinerated, contained or reclaimed. | |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 93,6 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 93,6 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 5,25E+06 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2.000 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

| | |
|---|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. | |
| Section 3.2 -Environment | |
| Used EUSES model. | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

| |
|--|
| |
|--|

| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|-----------|---|
|-----------|---|

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

Exposure Scenario - Worker

| | |
|-------------------------|---|
| 300000000472 | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Formulation & (re)packing of substances and mixtures-Industrial |
| Use Descriptor | Sector of Use: SU3, SU10 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 8a, PROC 8b, PROC 9, PROC 14, PROC 15 Environmental Release Categories: ERC2, ESVOC SpERC 2.2.v1 |
| Scope of process | Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities. |

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

| | |
|---|--|
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers use of substance/product up to 100% (unless stated differently)., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

| | |
|------------------------------------|--|
| Contributing Scenarios | Risk Management Measures |
| General measures (skin irritants). | Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying. |
| General measures (eye irritants). | Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

| | |
|---|--|
| General exposures (closed systems) | No other specific measures identified. |
| General exposures (closed systems)with sample collectionGeneral measures (skin irritants). | No other specific measures identified. |
| General exposures (closed systems)Use in contained batch processes | No other specific measures identified. |
| General exposures (open systems)Batch processwith sample collectionwith potential for aerosol generation. | No other specific measures identified. |
| Batch processes at elevated temperatures | Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). |
| Process sampling | No other specific measures identified. |
| Laboratory activities | No other specific measures identified. |
| Bulk transfers | Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). |
| Mixing operations (open systems)with potential for aerosol generation. | Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). |
| ManualTransfer from/pouring from containers | Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). |
| Drum/batch transfers | Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). |
| Production or preparation or articles by tableting, compression, extrusion or pelletisation | Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). |
| Drum and small package filling | Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). |
| Equipment cleaning and maintenance | Drain down and flush system prior to equipment opening or maintenance. |
| Storage.General measures (skin irritants). | No other specific measures identified. |

| | |
|--|--|
| Section 2.2 | Control of Environmental Exposure |
| Substance is a unique structure. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 0,1 |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

| | |
|---|----------|
| Regional use tonnage (tonnes/year): | 7,0E+03 |
| Fraction of Regional tonnage used locally: | 1 |
| Annual site tonnage (tonnes/year): | 7,0E+03 |
| Maximum daily site tonnage (kg/day): | 2,3E+04 |
| Frequency and Duration of Use | |
| Emission Days (days/year): | 300 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (initial release prior to RMM): | 2,5E-02 |
| Release fraction to wastewater from process (initial release prior to RMM): | 2,0E-03 |
| Release fraction to soil from process (initial release prior to RMM): | 1,0E-04 |
| Technical conditions and measures at process level (source) to prevent release | |
| Common practices vary across sites thus conservative process release estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | |
| Risk from environmental exposure is driven by soil. | |
| Prevent discharge of undissolved substance to or recover from onsite wastewater. | |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | |
| Treat air emission to provide a typical removal efficiency of (%) | 0 |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%) | 93,6 |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | 0 |
| Organisational measures to prevent/limit release from site | |
| Do not apply industrial sludge to natural soils. | |
| Sludge should be incinerated, contained or reclaimed. | |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 93,6 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 93,6 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 2,16E+04 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2.000 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

| | |
|---|--|
| SECTION 3 | EXPOSURE ESTIMATION |
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. | |
| Section 3.2 -Environment | |
| Used EUSES model. | |
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
| Section 4.1 - Health | |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. | |
| Section 4.2 -Environment | |
| Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. | |
| Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. | |
| Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. | |
| Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org). | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

Exposure Scenario - Worker

| | |
|-------------------------|--|
| 300000000473 | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Uses in Coatings- Industrial |
| Use Descriptor | Sector of Use: SU3 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 7, PROC 8a, PROC 8b, PROC 10, PROC 13, PROC 15 Environmental Release Categories: ERC4, ESVOC SpERC 4.3a.v1 |
| Scope of process | Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities. |

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

| | |
|---|--|
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers use of substance/product up to 100% (unless stated differently)., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

| | |
|------------------------------------|--|
| Contributing Scenarios | Risk Management Measures |
| General measures (skin irritants). | Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying. |
| General measures (eye irritants). | Use suitable eye protection. Avoid direct eye contact with product, also via contamination |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

| | |
|---|--|
| | on hands. |
| General exposures (closed systems) | No other specific measures identified. |
| General exposures (closed systems)with sample collectionUse in contained systems | No other specific measures identified. |
| Film formation - force drying, stoving and other technologies. | No other specific measures identified. |
| Mixing operations (closed systems)General exposures (closed systems) | No other specific measures identified. |
| Film formation - air drying | No other specific measures identified. |
| Preparation of material for applicationMixing operations (open systems) | Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). |
| Spraying (automatic/robotic) | Carry out in a vented booth provided with laminar airflow. |
| ManualSpraying | Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Wear a respirator conforming to EN140 with Type A filter or better. |
| Material transfers | Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). |
| Roller, spreader, flow application | Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). |
| Dipping, immersion and pouring | Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). |
| Laboratory activities | No other specific measures identified. |
| Drum/batch transfersTransfer from/pouring from containers | Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). |
| Production or preparation of articles by tableting, compression, extrusion or pelletisation | Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). |
| Equipment cleaning and maintenance | Drain down system prior to equipment opening or maintenance. |
| Storage.General measures (skin irritants). | Store substance within a closed system. No other specific measures identified. |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

| Section 2.2 | | Control of Environmental Exposure |
|---|--|-----------------------------------|
| Substance is a unique structure. | | |
| Readily biodegradable. | | |
| Amounts Used | | |
| Fraction of EU tonnage used in region: | | 0,1 |
| Regional use tonnage (tonnes/year): | | 7,0E+03 |
| Fraction of Regional tonnage used locally: | | 0,3 |
| Annual site tonnage (tonnes/year): | | 2,1E+03 |
| Maximum daily site tonnage (kg/day): | | 7,0E+04 |
| Frequency and Duration of Use | | |
| Emission Days (days/year): | | 300 |
| Environmental factors not influenced by risk management | | |
| Local freshwater dilution factor: | | 10 |
| Local marine water dilution factor: | | 100 |
| Other Operational Conditions affecting Environmental Exposure | | |
| Release fraction to air from process (initial release prior to RMM): | | 9,8E-02 |
| Release fraction to wastewater from process (initial release prior to RMM): | | 7,0E-03 |
| Release fraction to soil from process (initial release prior to RMM): | | 0 |
| Technical conditions and measures at process level (source) to prevent release | | |
| Common practices vary across sites thus conservative process release estimates used. | | |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | | |
| Risk from environmental exposure is driven by soil. | | |
| Prevent discharge of undissolved substance to or recover from onsite wastewater. | | |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | | |
| Treat air emission to provide a typical removal efficiency of (%) | | 90 |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%) | | 93,6 |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | | 0 |
| Organisational measures to prevent/limit release from site | | |
| Do not apply industrial sludge to natural soils. | | |
| Sludge should be incinerated, contained or reclaimed. | | |
| Conditions and Measures related to municipal sewage treatment plant | | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | | 93,6 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | | 93,6 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | | 2,57E+04 |
| Assumed domestic sewage treatment plant flow (m3/d) | | 2.000 |
| Conditions and Measures related to external treatment of waste for disposal | | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

Conditions and measures related to external recovery of waste

External recovery and recycling of waste should comply with applicable local and/or regional regulations.

SECTION 3

EXPOSURE ESTIMATION

Section 3.1 - Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 -Environment

Used EUSES model.

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

Exposure Scenario - Worker

| | |
|-------------------------|--|
| 300000000474 | |
| SECTION 1 | EXPOSURE SCENARIO TITLE |
| Title | Uses in Coatings- Professional |
| Use Descriptor | Sector of Use: SU22 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 8a, PROC 8b, PROC 10, PROC 11, PROC 13, PROC 15, PROC 19 Environmental Release Categories: ERC8a, ERC8d, ESVOC SpERC 8.3b.v1 |
| Scope of process | Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, brush, spreader by hand or similar methods, and film formation), and equipment cleaning, maintenance and associated laboratory activities. |

| | |
|------------------|--|
| SECTION 2 | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES |
|------------------|--|

| | |
|---|--|
| Section 2.1 | Control of Worker Exposure |
| Product Characteristics | |
| Physical form of product | Liquid, vapour pressure 0.5 - 10 kPa at STP |
| Concentration of the Substance in Mixture/Article | Covers use of substance/product up to 100% (unless stated differently)., |
| Frequency and Duration of Use | |
| Covers daily exposures up to 8 hours (unless stated differently). | |
| Other Operational Conditions affecting Exposure | |
| Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. | |

| | |
|------------------------------------|--|
| Contributing Scenarios | Risk Management Measures |
| General measures (skin irritants). | Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying. |
| General measures (eye irritants). | Use suitable eye protection. Avoid direct eye contact with product, also via contamination |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

| | |
|--|---|
| | on hands. |
| General exposures (closed systems) | No other specific measures identified. |
| Filling/ preparation of equipment from drums or containers. | No other specific measures identified. |
| General exposures (closed systems)Use in contained systems | No other specific measures identified. |
| Preparation of material for application | No other specific measures identified. |
| Film formation - air dryingOutdoor | Ensure operation is undertaken outdoors. |
| Film formation - air dryingIndoor | Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. |
| Preparation of material for applicationIndoor | Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Avoid carrying out operation for more than 4 hours. |
| Preparation of material for applicationOutdoor | Avoid carrying out operation for more than 4 hours. |
| Material transfersDrum/batch transfersDedicated facility | Ensure material transfers are under containment or extract ventilation. |
| Material transfersDrum/batch transfersNon-dedicated facility | Use drum pumps or carefully pour from container. |
| Roller, spreader, flow applicationIndoor | Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). |
| Roller, spreader, flow applicationOutdoor | Ensure operation is undertaken outdoors. Wear a respirator conforming to EN140 with Type A filter or better. |
| ManualSprayingIndoor | Carry out in a vented booth or extracted enclosure. Wear a respirator conforming to EN140 with Type A filter or better. |
| ManualSprayingOutdoor | Ensure operation is undertaken outdoors. Wear a respirator conforming to EN140 with Type A filter or better. |
| Dipping, immersion and pouringIndoor | Provide extraction ventilation at points where emissions occur. |
| Dipping, immersion and pouringOutdoor | Ensure operation is undertaken outdoors. Wear a respirator conforming to EN140 with Type A filter or |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

| | |
|--|---|
| | better. |
| Laboratory activities | No other specific measures identified. |
| Hand application - fingerpaints, pastels, adhesivesIndoor | Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). |
| Hand application - fingerpaints, pastels, adhesivesOutdoor | Ensure operation is undertaken outdoors. Avoid carrying out operation for more than 4 hours. |
| Equipment cleaning and maintenance | Drain down system prior to equipment opening or maintenance. |
| Storage.General measures (skin irritants). | Store substance within a closed system. |

| | |
|---|--|
| Section 2.2 | Control of Environmental Exposure |
| Substance is a unique structure. | |
| Readily biodegradable. | |
| Amounts Used | |
| Fraction of EU tonnage used in region: | 0,1 |
| Regional use tonnage (tonnes/year): | 7,0E+03 |
| Fraction of Regional tonnage used locally: | 2,0E-03 |
| Annual site tonnage (tonnes/year): | 14 |
| Maximum daily site tonnage (kg/day): | 38,3 |
| Frequency and Duration of Use | |
| Emission Days (days/year): | 365 |
| Environmental factors not influenced by risk management | |
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |
| Other Operational Conditions affecting Environmental Exposure | |
| Release fraction to air from process (initial release prior to RMM): | 9,8E-01 |
| Release fraction to wastewater from process (initial release prior to RMM): | 1,0E-02 |
| Release fraction to soil from process (initial release prior to RMM): | 1,0E-02 |
| Technical conditions and measures at process level (source) to prevent release | |
| Common practices vary across sites thus conservative process release estimates used. | |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | |
| Risk from environmental exposure is driven by freshwater. | |
| Prevent discharge of undissolved substance to or recover from onsite wastewater. | |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | |
| Treat air emission to provide a typical removal efficiency of (%) | 0 |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%) | 93,6 |
| If discharging to domestic sewage treatment plant, no secondary wastewater treatment required. | 0 |
| Organisational measures to prevent/limit release from site | |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022

| | |
|---|-------|
| Do not apply industrial sludge to natural soils. | |
| Sludge should be incinerated, contained or reclaimed. | |
| Conditions and Measures related to municipal sewage treatment plant | |
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 93,6 |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 93,6 |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 2,11 |
| Assumed domestic sewage treatment plant flow (m3/d) | 2.000 |
| Conditions and Measures related to external treatment of waste for disposal | |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. | |
| Conditions and measures related to external recovery of waste | |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. | |

| | |
|---|----------------------------|
| SECTION 3 | EXPOSURE ESTIMATION |
| Section 3.1 - Health | |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. | |

| |
|---------------------------------|
| Section 3.2 -Environment |
| Used EUSES model. |

| | |
|---|--|
| SECTION 4 | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
| Section 4.1 - Health | |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. | |

| |
|--|
| Section 4.2 -Environment |
| Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. |
| Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. |
| Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. |
| Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org). |

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Para-xylene

Version 1.1

Revision Date 26.04.2021

Print Date 29.08.2022