LINEVOL 11

Version 1.0 Revision Date Print Date 13.07.2025

11.07.2025

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : LINEVOL 11

Product code : V9335

Synonyms : Undecanol, 1-CAS-No. : 112-42-5

Manufacturer or supplier's details

Supplier :

SHELL EASTERN CHEMICALS (S)

A REGISTERED BUSINESS OF SHELL EASTERN

TRADING (PTE) LTD (UEN:198902087C)

9 North Buona Vista Drive, #07-01

The Metropolis Tower 1 Singapore 138588

Singapore 138 Singapore

Telephone : +65 6384 8269 Telefax : +65 6384 8454

Contact for Safety Data

Emergency telephone

Sheet

: +800 2537 8747 (ALERT SGS- toll Free) or +65 6542 9595

number (ALERT SGS)

Recommended use of the chemical and restrictions on use

Recommended use : Feedstock for plasticiser or other alcohol derivative.

Restrictions on use

This product must not be used in applications other than those

listed in Section 1 without first seeking the advice of the

supplier.

Other information : LINEVOL is a trademark owned by Shell Trademark

Management B.V. and Shell Brands Inc. and used by affiliates

of Royal Dutch Shell plc.

2. HAZARDS IDENTIFICATION

GHS Classification

Skin irritation : Category 3 Eye irritation : Category 2A

LINEVOL 11

Version 1.0 Revision Date Print Date 13.07.2025

Aspiration hazard 11.07.2025 Category 2

Short-term (acute) aquatic hazard

Long-term (chronic) aquatic

hazard

: Category 1: Category 2

GHS label elements

Hazard pictograms







Signal word : Warning

Hazard statements : PHYSICAL HAZARDS:

Not classified as a physical hazard under GHS criteria.

HEALTH HAZARDS:

H316 Causes mild skin irritation. H319 Causes serious eye irritation.

H305 May be harmful if swallowed and enters airways.

ENVIRONMENTAL HAZARDS: H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention:

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

P273 Avoid release to the environment.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P332 + P313 If skin irritation occurs: Get medical advice/

attention.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P391 Collect spillage.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regulations.

LINEVOL 11

Version 1.0 **Revision Date** Print Date 13.07.2025 11.07.2025

Other hazards which do not result in classification

Repeated exposure may cause skin dryness or cracking. Harmful: May cause lung damage if swallowed.

3. COMPOSITION/INFORMATION ON INGREDIENTS

: Substance Substance / Mixture

3.1 Substances

Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Undecan-1-ol	112-42-5	Skin Irrit.3; H316 Eye Irrit.2A; H319 Asp. Tox.2; H305 Aquatic Acute1; H400 Aquatic Chronic2; H411	<= 100

For explanation of abbreviations see section 16.

4. FIRST-AID MEASURES

General advice : Not expected to be a health hazard when used under normal

conditions.

If inhaled : No treatment necessary under normal conditions of use. If

symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Immediately flush skin with

large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical

facility for additional treatment.

In case of eye contact Immediately flush eye(s) with plenty of water.

Remove contact lenses, if present and easy to do. Continue

rinsing.

Transport to the nearest medical facility for additional

treatment.

3 / 18 800001011474 SG

LINEVOL 11

Version 1.0	Revision Date Print Date 13.07.2025 11.07.2025	
If swallowed	: In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.	
Most important symptoms and effects, both acute and delayed	Not considered to be an inhalation hazard under normal conditions of use. Possible respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.	
	Skin irritation signs and symptoms may include a burning sensation, redness, or swelling.	
	Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.	
	No specific hazards under normal use conditions. Ingestion may result in nausea, vomiting and/or diarrhoea.	
	Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.	
Protection of first-aiders	: When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.	
Notes to physician	: IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT! Call a doctor or poison control center for guidance. Treat symptomatically.	
5. FIRE-FIGHTING MEASURES		
Suitable extinguishing media	 Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. 	
Unsuitable extinguishing media	: Do not use water in a jet.	
Specific hazards during firefighting	 Carbon monoxide may be evolved if incomplete combustion occurs. Will float and can be reignited on surface water. The vapour is heavier than air, spreads along the ground and distant ignition is possible. 	
Specific extinguishing methods	 Standard procedure for chemical fires. Clear fire area of all non-emergency personnel. Keep adjacent containers cool by spraying with water. 	
Special protective equipmer for firefighters	: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if	

LINEVOL 11

Version 1.0 Revision Date Print Date 13.07.2025 11.07.2025

large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures .

Observe all relevant local and international regulations. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

Local authorities should be advised if significant spillages

cannot be contained.

: Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see

Section 13 of this Safety Data Sheet. Stay upwind and keep out of low areas. Be ready for fire or possible exposure.

Environmental precautions

: Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers. Use appropriate containment to avoid environmental

contamination.

Ventilate contaminated area thoroughly.

Methods and materials for containment and cleaning up

: For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove

contaminated soil and dispose of safely.

Additional advice : For guidance on selection of personal protective equipment

see Section 8 of this Safety Data Sheet.

For guidance on disposal of spilled material see Section 13 of

this Safety Data Sheet.

7. HANDLING AND STORAGE

General Precautions : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

LINEVOL 11

Version 1.0	Revision Date 11.07.2025	Print Date 13.07.2025
	Section 8 of this Use the informat assessment of lo appropriate contr this material.	Safety Data Sheet. ion in this data sheet as input to a risk ical circumstances to help determine rols for safe handling, storage and disposal of cal regulations regarding handling and are followed.
Advice on safe handling	Do not empty into	ch skin, eyes and clothing. o drains. of Pressure Hazard
Avoidance of contact	Copper.Copper alloys.Strong oxidisingAluminum	agents.
Product Transfer		closed when not in use. Do not use or filling discharge or handling.
Storage		
Conditions for safe storage		15 for any additional specific legislation kaging and storage of this product.
Other data	Vapours from tar Breathing losses suitable vapour tr Nitrogen blanket m3 or higher). Insulation (laggin ambient tempera Tanks should be ambient condition	ks should be diked (bunded). nks should not be released to atmosphere. during storage should be controlled by a reatment system. recommended for large tanks (capacity 100 ng) will minimize heat loss in areas of low ture. fitted with heating coils in areas where his can result in handling temperatures below t/pour point of the product.
Packaging material		: Stainless steel., Epoxy resins, Polyester. rial: Aluminum, Copper., Copper alloys.
Container Advice	explosive vapour	those that have been emptied, can contain s. Do not cut, drill, grind, weld or perform s on or near containers.
Specific use(s)	: Not applicable	
	Ensure that all lo	cal regulations regarding handling and

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

6 / 18 800001011474

storage facilities are followed.

LINEVOL 11

Version 1.0 Revision Date Print Date 13.07.2025 11.07.2025

Contains no substances with occupational exposure limit values.

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures

: Adequate ventilation to control airborne concentrations below the exposure guidelines/limits.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. Eye washes and showers for emergency use.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

General Information

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or

7/18 800001011474

LINEVOL 11

Version 1.0

Revision Date 11.07.2025

Print Date 13.07.2025

subsequent recycle.

Do not ingest. If swallowed, then seek immediate medical assistance.

Personal protective equipment

Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection

: If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.

Where air-filtering respirators are suitable, select an

appropriate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use: Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C

(149°F)].

Hand protection Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

LINEVOL 11

Version 1.0 Revision Date Print Date 13.07.2025

11.07.2025

Eye protection : Wear goggles for use against liquids and gas.

Wear full face shield if splashes are likely to occur.

Skin and body protection : Skin protection is not required under normal conditions of use.

For prolonged or repeated exposures use impervious clothing

over parts of the body subject to exposure.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard,

and provide employee skin care programmes.

Thermal hazards : Not applicable

Hygiene measures : Wash hands before eating, drinking, smoking and using the

toilet.

Launder contaminated clothing before re-use.

Environmental exposure controls

General advice : Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

vapour.

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local

environmental legislation.

Information on accidental release measures are to be found in

section 6.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquid.

Colour : Water white

Odour : mild

Odour Threshold : Data not available pH : Not applicable Melting / freezing point : 15.6 °C / 60.1 °F

Pour point 11.1 °C / 52.0 °F

Boiling point/boiling range : $245.0 \,^{\circ}\text{C} / 473.0 \,^{\circ}\text{F}$ Flash point : $121.1 \,^{\circ}\text{C} / 250.0 \,^{\circ}\text{F}$

Evaporation rate : Data not available

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit : Data not available
Lower explosion limit : Data not available

LINEVOL 11

Version 1.0 Revision Date Print Date 13.07.2025

11.07.2025

Vapour pressure : 0.4137 Pa (25 °C / 77 °F)

Relative vapour density : 4.5

Relative density : 0.831 (25.0 °C / 77.0 °F)

Method: ASTM D4052

Density : 0.831 g/cm3Method: ASTM D4052

Solubility(ies)

Water solubility : 19.1 mg/l (25 °C / 77 °F)

Partition coefficient: n-

octanol/water

: Data not available

Auto-ignition temperature : ca. 250 °C / 482 °F

Decomposition temperature : Data not available

Viscosity

Viscosity, dynamic : Data not available

Viscosity, kinematic : 18.0 mm2/s (25.0 °C / 77.0 °F)

Method: ASTM D445

11.0 mm2/s (37.8 °C / 100.0 °F)

Method: ASTM D445

Particle characteristics

Particle size : Data not available

Oxidizing properties : Not applicable

Surface tension : Data not available

Conductivity: > 10,000 pS/m, This material is not

expected to be a static accumulator.

Molecular weight : 172 g/mol

10. STABILITY AND REACTIVITY

Reactivity : Stable at normal ambient temperature and pressure., May

oxidise in the presence of air.

LINEVOL 11

Version 1.0 Revision Date Print Date 13.07.2025

11.07.2025

Chemical stability : The product is chemically stable. Stable under normal

conditions.

Possibility of hazardous

reactions

: None known.

Conditions to avoid : Extremes of temperature and direct sunlight.

Incompatible materials : Copper.

Copper alloys.

Strong oxidising agents.

Aluminum

Hazardous decomposition

products

: None expected under normal use conditions.

11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on product testing, and/or similar

products, and/or components.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for

individual component(s).

Information on likely routes of

exposure

Exposure may occur via inhalation, ingestion, skin absorption,

skin or eye contact, and accidental ingestion.

Acute toxicity

Components:

Undecan-1-ol:

Acute oral toxicity : LD50 Rat: > 5000 mg/kg

Remarks: Low toxicity

Acute inhalation toxicity : Remarks: Low toxicity

Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 Rabbit: > 5000 mg/kg

Remarks: Low toxicity

Skin corrosion/irritation

Components:

Undecan-1-ol:

Remarks: Causes mild skin irritation.

Serious eye damage/eye irritation

Components:

Undecan-1-ol:

Remarks: Causes serious eye irritation.

11 / 18 800001011474 SG

LINEVOL 11

Version 1.0

Revision Date 11.07.2025 Print Date 13.07.2025

Respiratory or skin sensitisation

Components:

Undecan-1-ol:

Remarks: Not a sensitiser.

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Components:

Undecan-1-ol:

: Remarks: No evidence of mutagenic activity.

Carcinogenicity

Components:

Undecan-1-ol:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification	
Undecan-1-ol	No carcinogenicity classification.	

Reproductive toxicity

Components:

Undecan-1-ol:

Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair

fertility.

STOT - single exposure

Components:

Undecan-1-ol:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Components:

Undecan-1-ol:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

LINEVOL 11

Version 1.0 **Revision Date** Print Date 13.07.2025 11.07.2025

Components:

Undecan-1-ol:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Further information

Components:

Undecan-1-ol:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

12. ECOLOGICAL INFORMATION

Basis for assessment : Information given is based on product testing, and/or similar

products, and/or components.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for

individual component(s).

Ecotoxicity

Components:

Undecan-1-ol:

Toxicity to fish (Acute

toxicity)

: Remarks: LC/EC/IC50 >1 - <=10 mg/l

Toxic

Toxicity to crustacean (Acute

toxicity)

: Remarks: LC/EC/IC50 < 1 mg/l

: Remarks: LC/EC/IC50 < 1 mg/l

Very toxic.

Very toxic.

Toxicity to algae/aquatic

plants (Acute toxicity)

M-Factor (Short-term (acute)

: 1

aquatic hazard)

Toxicity to microorganisms

(Acute toxicity)

: Remarks: Data estimated using read-across from similar

substances

LC/EC/IC50 > 100 mg/l Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic

toxicity) Toxicity to : Remarks: Data not available

: Remarks: NOEC/NOEL > 0.01 - <=0.1 mg/l

crustacean(Chronic toxicity)

Persistence and degradability

Components: Undecan-1-ol:

Biodegradability : Remarks: Data estimated using read-across from similar

13 / 18 800001011474 SG

LINEVOL 11

Version 1.0 **Revision Date** Print Date 13.07.2025 11.07.2025

substances

Readily biodegradable.

Oxidises rapidly by photo-chemical reactions in air.

Bioaccumulative potential

Product:

Partition coefficient: n-

octanol/water Components: Undecan-1-ol: : Remarks: Data not available

Bioaccumulation : Bioconcentration factor (BCF): 50

Remarks: Not expected to bioaccumulate significantly.

Mobility in soil

Components: Undecan-1-ol:

Remarks: Floats on water., If product enters soil, it will be Mobility

highly mobile and may contaminate groundwater.

Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Recover or recycle if possible.

> It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water

courses.

Waste product should not be allowed to contaminate soil or

water.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or

national requirements and must be complied with.

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Residues may cause an explosion hazard. Do not puncture, cut, or weld uncleaned drums. Send to drum recoverer or metal reclaimer.

14 / 18 800001011474

LINEVOL 11

Version 1.0 Revision Date Print Date 13.07.2025 11.07.2025

14. TRANSPORT INFORMATION

International Regulations

ADR

UN number : 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Undecan-1-ol)

Class : 9
Packing group : III
Labels : 9
Hazard Identification Number : 90
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3082

Proper shipping name : Environmentally hazardous substances, liquid, n.o.s.

(Undecan-1-ol)

Class : 9
Packing group : III
Labels : 9

IMDG-Code

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Undecan-1-ol)

Class : 9
Packing group : III
Labels : 9
Marine pollutant : yes

Maritime transport in bulk according to IMO instruments

Pollution category : X Ship type : 2

Product name : Undecyl alcohol

Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

Additional Information: This product may be transported under nitrogen blanketing.

Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry. Transport in bulk according to Annex II

of Marpol and the IBC Code

LINEVOL 11

Version 1.0	Revision Date	Print Date 13.07.2025
11.07.2025		

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Local Regulations

Workplace Safety and Health Act & Workplace Safety and Health (General Provision) Regulations	This product is subject to the requirements in the Act/ Regulations.
Fire Safety Act and Fire Safety (Petroleum & Flammable Materials) Regulations	This product is not subject to the requirements in the Act/Regulations.
Maritime and Port Authority of Singapore (Dangerous Goods, Petroleum and Explosives) Regulations	This product is subject to the requirements in the Act/ Regulations.
Environmental Protection and Management Act and Environmental Protection and Management (Hazardous Substances) Regulations	This product is not subject to the requirements in the Act/Regulations.

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Other international regulations

The components of this product are reported in the following inventories:

AIIC : Listed DSL Listed **IECSC** Listed **ENCS** : Listed KECI : Listed **NZIoC** : Listed **PICCS** : Listed **TSCA** : Listed TCSI : Listed

16. OTHER INFORMATION

Full text of H-Statements

H305 May be harmful if swallowed and enters airways.

H316 Causes mild skin irritation. H319 Causes serious eye irritation. H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Acute Short-term (acute) aquatic hazard Aquatic Chronic Long-term (chronic) aquatic hazard

LINEVOL 11

Version 1.0 Revision Date Print Date 13.07.2025 11.07.2025

Asp. Tox. Aspiration hazard Eye Irrit. Eye irritation Skin Irrit. Skin irritation

Abbreviations and Acronyms

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System: GLP - Good Laboratory Practice: IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC -New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG -Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Further information

Training advice : Provide adequate information, instruction and training for

operators.

Other information : A vertical bar (|) in the left margin indicates an amendment

from the previous version.

Sources of key data used to compile the Safety Data

Sheet

: The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

LINEVOL 11

Version 1.0

Revision Date 11.07.2025 Print Date 13.07.2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SG / EN