CARADOL SA36-200

Print Date 16.09.2023 Revision Date 08.09.2023 Version 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : CARADOL SA36-200

Product code : U3206 CAS-No. : 9082-00-2

Synonyms : Polyol

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Use for the manufacture of polyurethane products.

Substance/Mixture

Uses advised against : This product must not be used in applications other than the

above without first seeking the advice of the supplier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : SHELL MARKETS (MIDDLE EAST) LIMITED

CHEMICALS PO Box 307 JEBEL ALI, DUBAI Unit.Arab Emir.

Telephone : Telefax :

Contact for Safety Data

Sheet

1.4 Emergency telephone number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification

Based on available data this substance / mixture does not meet the classification criteria.

2.2 Label elements

GHS-Labelling

Hazard pictograms : No Hazard Symbol required

Signal word : No signal word

1 / 17 800010056301 AE

CARADOL SA36-200

Print Date 16.09.2023 Revision Date 08.09.2023 Version 1.1

PHYSICAL HAZARDS: Hazard statements

Not classified as a physical hazard under GHS criteria.

HEALTH HAZARDS:

Not classified as a health hazard under GHS criteria.

ENVIRONMENTAL HAZARDS:

Not classified as an environmental hazard under GHS criteria.

Precautionary statements : Prevention:

No precautionary phrases.

Response:

No precautionary phrases.

Storage:

No precautionary phrases.

Disposal:

No precautionary phrases.

2.3 Other hazards

SECTION 3: Composition/information on ingredients

3.1 Substances

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Polyalkylene glycol	9082-00-2	<= 100

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Not expected to be a health hazard when used under normal

conditions.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

If inhaled : No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Flush exposed area with

water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.

In case of eye contact : Flush eye with copious quantities of water.

Remove contact lenses, if present and easy to do. Continue

If persistent irritation occurs, obtain medical attention.

Revision Date 08.09.2023

CARADOL SA36-200

If swallowed : In general no treatment is necessary unless large quantities

are swallowed, however, get medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Print Date 16.09.2023

: Not considered to be an inhalation hazard under normal **Symptoms**

conditions of use.

Possible respiratory irritation signs and symptoms may include

Version 1.1

a temporary burning sensation of the nose and throat,

coughing, and/or difficulty breathing.

No specific hazards under normal use conditions.

Skin irritation signs and symptoms may include a burning

sensation, redness, or swelling.

Eve irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision. Indestion may result in nausea, vomiting and/or diarrhoea.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Call a doctor or poison control center for guidance.

> Treat symptomatically. Following cases of gross overexposure, investigation of liver, kidney and eye function may be advisable. Records of such incidents should be maintained

for future reference.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Large fires should only be fought by properly trained fire

> fighters., Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used

for small fires only.

Unsuitable extinguishing

media

: Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Will only burn if enveloped in a pre-existing fire. Hazardous combustion products may include: Carbon dioxide

Unidentified organic and inorganic compounds. Toxic gases

Carbon monoxide.

5.3 Advice for firefighters

Special protective equipment

for firefighters

: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

Specific extinguishing

methods

Standard procedure for chemical fires.

Further information : Clear fire area of all non-emergency personnel.

3 / 17 800010056301 AE

	C	CARADOL SA36-200
 Print Date 16.09.2023	Revision Date 08.09.2023	Version 1.1
	All storage areas should be provifighting facilities.	ded with adequate fire

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Observe all relevant local and international regulations.

Avoid contact with skin, eyes and clothing.

Avoid inhaling vapour and/or mists.

Extinguish any naked flames. Do not smoke. Remove ignition

Keep adjacent containers cool by spraying with water.

sources. Avoid sparks.

6.2 Environmental precautions

Environmental precautions : Remove all possible sources of ignition in the surrounding

area.

Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers. Use appropriate containment to avoid environmental

contamination.

Ventilate contaminated area thoroughly.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : For large liquid spills (> 1 drum), transfer by mechanical

means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an

appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

Proper disposal should be evaluated based on regulatory status of this material (refer to Section 13), potential contamination from subsequent use and spillage, and regulations governing disposal in the local area.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

CARADOL SA36-200

Print Date 16.09.2023 Revision Date 08.09.2023 Version 1.1

SECTION 7: Handling and storage

General Precautions : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine

appropriate controls for safe handling, storage and disposal of

this material.

Ensure that all local regulations regarding handling and

storage facilities are followed.

7.1 Precautions for safe handling

Advice on safe handling : In accordance with good industrial hygiene practices,

precautions should be taken to avoid breathing of material.

Use local exhaust extraction over processing area. Avoid unintentional contact with isocyanates to prevent

uncontrolled polymerisation.

Avoid contact with skin, eyes and clothing.

Air-dry contaminated clothing in a well-ventilated area before

laundering.

Do not empty into drains. Handling Temperature:

Ambient.

When handling product in drums, safety footwear should be worn and proper handling equipment should be used.

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

Product Transfer : Lines should be purged with nitrogen before and after product

transfer. Keep containers closed when not in use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Other data : Prevent all contact with water and with moist atmosphere.

Tanks must be clean, dry and rust-free. Prevent ingress of water. Must be stored in a diked (bunded) well- ventilated area, away from sunlight, ignition sources and other sources of heat. Nitrogen blanket recommended for large tanks (capacity 100 m3 or higher). Drums should be stacked to a

maximum of 3 high.

Storage period : 24 month(s)

Storage Temperature: Ambient.

SAFFTY DATA SHFFT

	CAR	ADOL SA36-200
Print Date 16.09.2023	Revision Date 08.09.2023	Version 1.1
	Storage should be handled at temperativiscosities are less than 500 cSt; typics should be fitted with heating coils in an temperatures are below the recommer temperatures. Heating coil skin temperatures are below the recommer temperatures.	ally at 25-50 °C. Tanks eas where the ambient nded product handling
Packaging material	: Suitable material: Stainless steel.For epoxy paint, zinc silicate paint. Unsuitable material: Copper.Copper	•
7.3 Specific end use(s)		
Specific use(s)	: Not applicable	
	Ensure that all local regulations regard storage facilities are followed.	ling handling and

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

8.2 Exposure controls

Engineering measuresWhere material is heated, sprayed or mist formed, there is greater potential

CARADOL SA36-200

Print Date 16.09.2023

Revision Date 08.09.2023

Version 1.1

for airborne concentrations to be generated.

Adequate ventilation to control airborne concentrations.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended.

Hand protection

Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber. Incidental contact/Splash protection: PVC, neoprene or nitrile rubber gloves For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-

	CARAD	OL SA36-200
Print Date 16.09.2023	Revision Date 08.09.2023	Version 1.1
	perfumed moisturizer is recommended.	
Skin and body protection :	Skin protection is not ordinarily required bey work clothes. It is good practice to wear chemical resistant	
Respiratory protection :	No respiratory protection is ordinarily require conditions of use. In accordance with good industrial hygiene precautions should be taken to avoid breath	practices,
Hygiene measures :	Wash hands before eating, drinking, smokir toilet. Launder contaminated clothing before	
Environmental exposure controls		
General advice :	Local guidelines on emission limits for volat must be observed for the discharge of exhavapour. Minimise release to the environment. An enassessment must be made to ensure complenvironmental legislation. Information on accidental release measures section 6.	ust air containing vironmental liance with local

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : clear, Water white

Odour odourless

Odour Threshold : Data not available рΗ : Data not available Melting / freezing point : Data not available Boiling point/boiling range Data not available

Flash point : Typical > 227 °C Method: ASTM D93 (PMCC)

Evaporation rate : Data not available

Flammability

: Not applicable Flammability (solid, gas)

Lower explosion limit and upper explosion limit / flammability limit

		CARADOL SA36-200
Print Date 16.09.2023	Revision Date 08.09.2023	Version 1.1
Upper explosion limit	: Data not available	
Lower explosion limit	: Data not available	
Vapour pressure	: Data not available	
Relative vapour density	: Data not available	
Relative density	: Data not available	
Density	: Typical 1.090 kg/m3 (20 °C) Method: ASTM D4052	
Solubility(ies)		
Water solubility	: Miscible.	
Auto-ignition temperature	: Data not available	
Decomposition temperature	: Data not available	
Viscosity		
Viscosity, dynamic	: Typical 1.080 mPa.s (20 °C) Method: ASTM D445	
Viscosity, kinematic	: Data not available	
Explosive properties	: Not applicable	
Oxidizing properties	: Data not available	
9.2 Other information		
Surface tension	: Data not available	
Conductivity	: Electrical conductivity: > 10,00 for example liquid temperature and anti-static additives can grof a liquid, This material is not accumulator.	eatly influence the conductivity
Molecular weight	: Data not available	

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions, Hygroscopic.

10.3 Possibility of hazardous reactions

	CA	RADOL SA36-200
Print Date 16.09.2023	Revision Date 08.09.2023	Version 1.1
Hazardous reactions	 Polymerises exothermically with di-is temperatures. The reaction becomes progressively be violent at higher temperatures if the partners is good or is supported by sof solvents. Reacts with strong oxidising agents. 	more vigorous and can ne miscibility of reaction

10.4 Conditions to avoid

Conditions to avoid : Heat, flames, and sparks.

Product cannot ignite due to static electricity.

10.5 Incompatible materials

Materials to avoid : Avoid contact with isocyanates, copper and copper alloys,

zinc, strong oxidizing agents, and water.

10.6 Hazardous decomposition products

Hazardous decomposition

products

: Unknown toxic products may be formed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Basis for assessment : Information given is based on data obtained from similar

substances.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for

individual component(s).

exposure

Information on likely routes of : Exposure may occur via inhalation, ingestion, skin absorption,

skin or eye contact, and accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity : LD 50 : > 2.000 mg/kg

Remarks: Based on available data, the classification criteria

are not met.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria

are not met.

: LD 50 : > 2.000 mg/kg Acute dermal toxicity

Remarks: Low toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

CARADOL SA36-200

Print Date 16.09.2023 Revision Date 08.09.2023 Version 1.1

Product:

Remarks: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

: Remarks: Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
Polyalkylene glycol	No carcinogenicity classification.

Reproductive toxicity

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

CARADOL SA36-200

Print Date 16.09.2023 Revision Date 08.09.2023 Version 1.1

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

SECTION 12: Ecological information

12.1 Toxicity

Basis for assessment : Incomplete ecotoxicological data are available for this product.

> The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.

Unless indicated otherwise, the data presented is

representative of the product as a whole, rather than for

individual component(s).

Product:

Toxicity to fish (Acute

toxicity)

: LC50: > 100 mg/l

Remarks: Based on available data, the classification criteria

are not met.

Practically non toxic:

Toxicity to daphnia and other aquatic invertebrates (Acute

toxicity)

: EC50 : > 100 mg/l

Remarks: Based on available data, the classification criteria

are not met.

Practically non toxic:

Toxicity to algae (Acute

toxicity)

: EC50 : > 100 mg/l

Remarks: Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic

toxicity)

: Remarks: Data not available

Toxicity to daphnia and other

aquatic invertebrates

: Remarks: Data not available

(Chronic toxicity) Toxicity to bacteria (Acute

: IC50: > 100 mg/l

toxicity) Remarks: Based on available data, the classification criteria

are not met.

CARADOL SA36-200

Print Date 16.09.2023

Revision Date 08.09.2023

Version 1.1

Practically non toxic:

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: Readily biodegradable.

no data available

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

12.4 Mobility in soil

Product:

Mobility : Remarks: If the product enters soil, one or more constituents

will or may be mobile and may contaminate groundwater.

12.5 Results of PBT and vPvB assessment

no data available

12.6 Other adverse effects

no data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses.

Waste product should not be allowed to contaminate soil or

water.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or

national requirements and must be complied with.

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

CARADOL SA36-200

Print Date 16.09.2023 Revision Date 08.09.2023 Version 1.1

Send to drum recoverer or metal reclaimer.

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

Local legislation

SECTION 14: Transport information

14.1 UN number

ADR : Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good **IATA** : Not regulated as a dangerous good

14.2 Proper shipping name

ADR : Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good **IATA** : Not regulated as a dangerous good

14.3 Transport hazard class

ADR : Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good **IATA** Not regulated as a dangerous good

14.5 Environmental hazards

ADR : Not regulated as a dangerous good **IMDG** : Not regulated as a dangerous good

14.6 Special precautions for user

Remarks Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

14.7 Maritime transport in bulk according to IMO instruments

Pollution category : Z Ship type : 3

Product name : Glycerol, propoxylated and ethoxylated

Additional Information : This product may be transported under nitrogen blanketing.

> Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a

confined space entry.

Transport in bulk according to Annex II of Marpol and the IBC

Code

SAFFTY DATA SHFFT

CARADOL SA36-200

Print Date 16.09.2023 Revision Date 08.09.2023 Version 1.1

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations : The regulatory information is not intended to be

comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

IECSC : All components listed. **NZIoC** : All components listed. All components listed. **PICCS** KECI All components listed. : All components listed. **TCSI** AIIC : All components listed. DSL All components listed. All components listed. **TSCA ENCS** : All components listed.

SECTION 16: Other information

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this

document can be looked up in reference literature (e.g.

scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial

Hygienists

ADR = European Agreement concerning the International

Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut fur Normung DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and

Toxicology Of Chemicals

	CARADOL SA36-200
Print Date 16.09.2023	Revision Date 08.09.2023 Version 1.1
	ECHA = European Chemicals Agency EINECS = The European Inventory of Existing Commercial Chemical Substances EL50 = Effective Loading fifty ENCS = Japanese Existing and New Chemical Substances Inventory EWC = European Waste Code GHS = Globally Harmonised System of Classification and Labelling of Chemicals IARC = International Agency for Research on Cancer IATA = International Air Transport Association IC50 = Inhibitory Concentration fifty IL50 = Inhibitory Level fifty IMDG = International Maritime Dangerous Goods INV = Chinese Chemicals Inventory IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables KECI = Korea Existing Chemicals Inventory LC50 = Lethal Concentration fifty LD50 = Lethal Dose fifty per cent. LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading LL50 = Lethal Loading fifty MARPOL = International Convention for the Prevention of Pollution From Ships NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level OE_HPV = Occupational Exposure - High Production Volume PBT = Persistent, Bioaccumulative and Toxic PICCS = Philippine Inventory of Chemicals and Chemical Substances PNEC = Predicted No Effect Concentration REACH = Registration Evaluation And Authorisation Of Chemicals RID = Regulations Relating to International Carriage of Dangerous Goods by Rail SKIN_DES = Skin Designation STEL = Short term exposure limit TRA = Targeted Risk Assessment TSCA = US Toxic Substances Control Act TWA = Time-Weighted Average vPvB = very Persistent and very Bioaccumulative
Further information	
Training advice	: Provide adequate information, instruction and training for operators.
Other information	: A vertical bar () in the left margin indicates an amendment from the previous version.
Sources of key data used to compile the Safety Data Sheet	: The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

CARADOL SA36-200

Print Date 16.09.2023

Revision Date 08.09.2023

Version 1.1

IUCLID date base, EC 1272 regulation, etc).

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.