Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

GTL Solvent GS 2735

Initial release date: 2015/08/31 Revision Date: 11.05.2021

Version 2.1

SDS Number: 800010023138

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : GTL Solvent GS 2735

: Q6529 Product code

Synonyms : Hydrocarbons C16-C22, n-alkanes, isoalkanes, <2% aromat-

CAS-No. : 2170468-39-8

EC-No. : 942-086-0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-: Solvent.

stance/Mixture

on use

Recommended restrictions : This product must not be used in applications other than the

above without first seeking the advice of the supplier.

1.3 Details of the supplier of the safety data sheet

: Shell Chemicals Europe B.V. Company

PO Box 2334

3000 CH Rotterdam

Netherlands

Telephone : +31 (0)10 441 5137 / +31 (0)10 441 5191

Telefax : +31 (0)20 716 8316 / +31 (0)20 713 9230

E-mail address of person

responsible for the SDS

: sccmsds@shell.com

1.4 Emergency telephone number

Emergency telephone num-

ber

: +44 (0) 1235 239 670 (This telephone number is available 24

hours per day, 7 days per week)

National Poison Counselling Centre (UZEM) - 114

+44 (0) 1235 239 670 (Bu telefon numarasına haftanın 7 günü

24 saat ulaşılabilinir)

Ulusal Zehir Danişma Merkezi (UZEM) - 114

1 / 17 800010023138

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

GTL Solvent GS 2735

Initial release date: 2015/08/31 Revision Date: 11.05.2021

Version 2.1

SDS Number: 800010023138

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification T.R. SEA No 28848

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters air-

ways.

2.2 Label elements

Labelling T.R. SEA No 28848

Hazard pictograms

Signal word : Danger

Hazard statements : PHYSICAL HAZARDS:

Not classified as a physical hazard under

GHS criteria.

HEALTH HAZARDS:

H304 May be fatal if swallowed and enters air-

ways.

ENVIRONMENTAL HAZARDS:

Not classified as an environmental hazard

under GHS criteria.

Supplemental Hazard

Statements

: EUH066

Repeated exposure may cause skin dry-

ness or cracking.

Precautionary statements : Prevention:

P243 Take precautionary measures against static

discharge.

Response:

P301 + P310 IF SWALLOWED: Immediately call a

POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an ap-

proved waste disposal plant.

2.3 Other hazards

May form flammable/explosive vapour-air mixture.

This material is a static accumulator.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

2 / 17 800010023138 TR

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

GTL Solvent GS 2735

Initial release date: 2015/08/31 Revision Date: 11.05.2021

Version 2.1

SDS Number: 800010023138

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable airvapour mixtures can occur.

SECTION 3: Composition/information on ingredients

3.1 Substances

Substance name : Hydrocarbons C16-C22, n-alkanes, isoalkanes, <2% aromat-

ics, 2170468-39-8

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	T.R. SEA No 28848	Concentration (% w/w)
Alkanes, C16-C22-	2170468-39-8	Asp. Tox.1; H304	<= 100
branched and linear	942-086-0	EUH066	

SECTION 4: First aid measures

4.1 Description of first aid measures

In case of eye contact

General advice : Not expected to be a health hazard when used under normal

conditions.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

If inhaled : No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

: Flush eye with copious quantities of water.

In case of skin contact : Remove contaminated clothing. Flush exposed area with wa-

ter and follow by washing with soap if available.

If persistent irritation occurs, obtain medical attention.

... perceter milater essais, estain medical attention

Remove contact lenses, if present and easy to do. Continue

rinsina

If persistent irritation occurs, obtain medical attention.

If swallowed : Call emergency number for your location / facility.

If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath,

chest congestion or continued coughing or wheezing.

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

GTL Solvent GS 2735

Initial release date: 2015/08/31 Revision Date: 11.05.2021

Version 2.1

SDS Number: 800010023138

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

: Not considered to be an inhalation hazard under normal con-

ditions of use.

Possible respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, cough-

ing, and/or difficulty breathing.

No specific hazards under normal use conditions.

Skin irritation signs and symptoms may include a burning sen-

sation, redness, or swelling.

No specific hazards under normal use conditions.

Eye irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blurred vision.

If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest

congestion, shortness of breath, and/or fever.

If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

Defatting dermatitis signs and symptoms may include a burn-

ing sensation and/or a dried/cracked appearance.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Call a doctor or poison control center for guidance.

Potential for chemical pneumonitis.

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon diox-

ide, sand or earth may be used for small fires only.

Unsuitable extinguishing

media

: Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Clear fire area of all non-emergency personnel. Hazardous combustion products may include:

A complex mixture of airborne solid and liquid particulates and

gases (smoke). Carbon monoxide.

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

GTL Solvent GS 2735

Initial release date: 2015/08/31 Revision Date: 11.05.2021

Version 2.1

SDS Number: 800010023138

Unidentified organic and inorganic compounds.

Flammable vapours may be present even at temperatures

below the flash point.

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Will float and can be reignited on surface water.

5.3 Advice for firefighters

Special protective equipment

for firefighters

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

Specific extinguishing meth-

ods

: Standard procedure for chemical fires.

Further information : Keep adjacent containers cool by spraying with water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Observe all relevant local and international regulations.

Notify authorities if any exposure to the general public or the

environment occurs or is likely to occur.

Local authorities should be advised if significant spillages

cannot be contained.

Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or unpro-

tected personnel.

Do not breathe fumes, vapour.
Do not operate electrical equipment.

6.2 Environmental precautions

Environmental precautions

: Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bond-

ing and grounding (earthing) all equipment. Monitor area with combustible gas indicator.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : For small liquid spills (< 1 drum), transfer by mechanical

5 / 17 800010023138 TR

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

GTL Solvent GS 2735

Initial release date: 2015/08/31 Revision Date: 11.05.2021

Version 2.1

SDS Number: 800010023138

means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely

Ventilate contaminated area thoroughly.

If contamination of site occurs remediation may require specialist advice.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures

: Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

Ensure that all local regulations regarding handling and storage facilities are followed.

Advice on safe handling

: Avoid inhaling vapour and/or mists.

Avoid contact with skin, eyes and clothing.

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Bulk storage tanks should be diked (bunded).

When using do not eat or drink.

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Hygiene measures

: Wash hands before eating, drinking, smoking and using the toilet. Launder contaminated clothing before re-use. Do not ingest. If swallowed, then seek immediate medical assistance.

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

GTL Solvent GS 2735

Initial release date: 2015/08/31 Revision Date: 11.05.2021

Version 2.1

SDS Number: 800010023138

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Other data : Storage Temperature: Ambient.

> Bulk storage tanks should be diked (bunded). Locate tanks away from heat and other sources of ignition. Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions. Must be stored in a diked (bunded) well- ventilated area, away from sunlight, ignition sources and other sources of heat. Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products which are not harmful or toxic to man or to the environment. Electrostatic charges will be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk. The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.

Packaging material

Suitable material: For containers, or container linings use mild steel, stainless steel., For container paints, use epoxy paint, zinc silicate paint.

Unsuitable material: Avoid prolonged contact with natural,

butyl or nitrile rubbers.

7.3 Specific end use(s)

Specific use(s) Please refer to Ch16 and/or the annexes for the registered

uses under REACH.

See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices

on Static Electricity).

IEC/TS 60079-32-1: Electrostatic hazards, guidance

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Aliphatic dearom.		TWA	1.050 mg/m3	EU HSPA
solvents 200 - 250			S S	

7 / 17 800010023138

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

GTL Solvent GS 2735

Initial release date: 2015/08/31 Revision Date: 11.05.2021

Version 2.1

SDS Number: 800010023138

Biological occupational exposure limits

No biological limit allocated.

8.2 Exposure controls

Engineering measures

Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Eye washes and showers for emergency use.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Eye protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended.

Hand protection

Remarks : Where hand contact with the product may occur the use of

gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC, neoprene or nitrile rubber gloves For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove re-

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

GTL Solvent GS 2735

Initial release date: 2015/08/31 Revision Date: 11.05.2021

Version 2.1

SDS Number: 800010023138

sistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Skin and body protection

Skin protection is not required under normal conditions of use. For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure. If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.

Wear antistatic and flame-retardant clothing, if a local risk assessment deems it so.

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.

Check with respiratory protective equipment suppliers.

Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use: Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].

Protective measures

: Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Thermal hazards : Not applicable

Environmental exposure controls

General advice : Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

vapour.

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local envi-

ronmental legislation.

Information on accidental release measures are to be found in

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

GTL Solvent GS 2735

Initial release date: 2015/08/31 Revision Date: 11.05.2021

Version 2.1

SDS Number: 800010023138

section 6.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : Data not available

Odour : odourless

Odour Threshold : Data not available

pH : Data not available

Melting / freezing point : Data not available

Boiling point/boiling range : 283 - 360 °C

Flash point : 143 °C

Evaporation rate : Data not available

Flammability (solid, gas) : Not applicable

Upper explosion limit : 7 %(V)

Lower explosion limit : 0,5 %(V)

Vapour pressure : Data not available

Relative vapour density : Data not available

Relative density : Data not available

Density : < 0,8 g/cm3 (20 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: Data not available

Auto-ignition temperature : > 200 °C

Decomposition temperature : Data not available

Viscosity

Viscosity, dynamic : Data not available

10 / 17 800010023138 TR

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

GTL Solvent GS 2735

Initial release date: 2015/08/31 Revision Date: 11.05.2021

Version 2.1

SDS Number: 800010023138

Viscosity, kinematic : Data not available

Explosive properties : Not classified

Oxidizing properties : Data not available

9.2 Other information

Surface tension : Data not available

Conductivity: < 100 pS/m

The conductivity of this material makes it a static accumulator., A liquid is typically considered nonconductive if its con-

ductivity is below 100 pS/m and is considered semi-

conductive if its conductivity is below 10,000 pS/m., Whether a liquid is nonconductive or semiconductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can

greatly influence the conductivity of a liquid

Molecular weight : Data not available

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions Stable under normal conditions of use.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.

In certain circumstances product can ignite due to static elec-

tricity.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

10.6 Hazardous decomposition products

Hazardous decomposition products are not expected to form during normal storage., Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic com-

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

GTL Solvent GS 2735

Initial release date: 2015/08/31 Revision Date: 11.05.2021

Version 2.1

SDS Number: 800010023138

pounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of : Exposure may occur via inhalation, ingestion, skin absorption,

skin or eye contact, and accidental ingestion.

Acute toxicity

Product:

exposure

Acute oral toxicity : LD50 (Rat): > 5000 mg/kg

Remarks: Low toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Remarks: LC50 greater than near-saturated vapour concen-

tration.

Low toxicity if inhaled.

Based on available data, the classification criteria are not met.

: LD50 (Rabbit): > 2000 mg/kg Acute dermal toxicity

Remarks: Low toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Prolonged/repeated contact may cause defatting of the skin which can lead to dermati-

Not irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: Not irritating to eye.

Respiratory or skin sensitisation

Product:

Remarks: Not a sensitiser.

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

Genotoxicity in vivo : Remarks: Non mutagenic

12 / 17 800010023138

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

GTL Solvent GS 2735

Initial release date: 2015/08/31 Revision Date: 11.05.2021

Version 2.1

SDS Number: 800010023138

Carcinogenicity

Product:

Remarks: Not a carcinogen.

Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
Alkanes, C16-C22-branched and linear	No carcinogenicity classification.

Reproductive toxicity

Product:

Effects on fertility

Remarks: Not a developmental toxicant.

Based on available data, the classification criteria are not met.

Does not impair fertility.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Further information

Product:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish (Acute toxici: LL50: > 100 mg/l

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

GTL Solvent GS 2735

Initial release date: 2015/08/31 Revision Date: 11.05.2021

Version 2.1

SDS Number: 800010023138

ty) Remarks: Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to daphnia and other

aquatic invertebrates (Acute

toxicity)

EL50 : > 100 mg/l Remarks: Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to algae (Acute tox-

icity)

: EL50 : > 100 mg/l

Remarks: Practically non toxic: Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic tox-

icity)

: Remarks: NOEC/NOEL > 100 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

: Remarks: NOEC/NOEL > 100 mg/l

Toxicity to bacteria (Acute

toxicity)

: IC50 : > 100 mg/l

Remarks: Practically non toxic:

Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: Oxidises rapidly by photo-chemical reactions in air.

Readily biodegradable.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Has the potential to bioaccumulate.

12.4 Mobility in soil

Product:

Mobility : Remarks: Floats on water., If it enters soil, it will adsorb to soil

particles and will not be mobile.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : The substance does not fulfill all screening criteria for persis-

tence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB..

12.6 Other adverse effects

Product:

Additional ecological infor- : Remarks: Does not have ozone depletion potential.

14 / 17 800010023138

TR

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

GTL Solvent GS 2735

Initial release date: 2015/08/31 Revision Date: 11.05.2021

Version 2.1

SDS Number: 800010023138

mation

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in a small properties of the material generated to

ods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or na-

tional requirements and must be complied with.

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard. Do not puncture,

cut or weld uncleaned drums.

Send to drum recoverer or metal reclaimer.

Comply with any local recovery or waste disposal regulations.

SECTION 14: Transport information

14.1 UN number

ADR : Not regulated as a dangerous good RID : Not regulated as a dangerous good IMDG : Not regulated as a dangerous good IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good RID : Not regulated as a dangerous good IMDG : Not regulated as a dangerous good IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

GTL Solvent GS 2735

Initial release date: 2015/08/31 Revision Date: 11.05.2021

Version 2.1

SDS Number: 800010023138

14.4 Packing group

ADR : Not regulated as a dangerous good RID : Not regulated as a dangerous good IMDG : Not regulated as a dangerous good IATA : Not regulated as a dangerous good

14.5 Environmental hazards

ADR : Not regulated as a dangerous good RID : Not regulated as a dangerous good IMDG : Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

Additional Information: This product may be transported under nitrogen blanketing.

Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined

space entry.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations : The regulatory information is not intended to be comprehen-

sive. Other regulations may apply to this material.

Regulations on the health and safety precautions for chemicals in the workplace. Regulations on the fire protection of buildings. Regulations on the prevention of industrial acci-

dents and the reduction of their effects.

The components of this product are reported in the following inventories:

DSL : Listed

EINECS : Listed

TSCA : Not listed on TSCA

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

GTL Solvent GS 2735

Initial release date: 2015/08/31 Revision Date: 11.05.2021

Version 2.1

SDS Number: 800010023138

SECTION 16: Other information

SDS Author

Name, Surname : Orkan Akbörü

Address : The Shell Company of Turkey Ltd

Gülbahar Mh. Salih Tozan Sk.

Karamancılar İş Merkezi No:18 B Blok 34394 Esentepe – Şişli / İstanbul

Certified Qualification date : 12 April 2021

Certificate number : GBF01.52.09

Further information

Training advice : Provide adequate information, instruction and training for op-

erators.

Other information : A vertical bar (|) in the left margin indicates an amendment

from the previous version.

Revision changes: Revised according to regulation on Safety

Data Sheets (SDSs) regarding hazardous substances and

mixtures (R.G. 13/12/2014-29204)

Sources of key data used to compile the Safety Data

Sheet

: The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

TR / EN