According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# **CARADOL SP37-25V**

Version Revision Date: SDS Number: Print Date: 08/29/2022

1.2 07/06/2018 800001005691 Date of last issue: 02/22/2017

#### **SECTION 1. IDENTIFICATION**

Product name : CARADOL SP37-25V

Product code : U317P

### Manufacturer or supplier's details

Company : Shell Chemical LP

PO Box 576

HOUSTON TX 77001

USA

SDS Request : 1-800-240-6737 Customer Service : 1-855-697-4355

**Emergency telephone number** 

Chemtrec Domestic (24 hr) : 1-800-424-9300 Chemtrec International (24 : 1-703-527-3887

hr)

### Recommended use of the chemical and restrictions on use

Recommended use : Use for the manufacture of polyurethane products.

Restrictions on use : This product must not be used in applications other than the

above without first seeking the advice of the supplier.

Other information : CARADOL is a registered trademark of Shell trademark Man-

agement BV.

### **SECTION 2. HAZARDS IDENTIFICATION**

#### GHS classification in accordance with 29 CFR 1910.1200

Based on available data this substance / mixture does not meet the classification criteria.

**GHS** label elements

Hazard pictograms : No Hazard Symbol required

Signal word : No signal word

Hazard statements : PHYSICAL HAZARDS:

Not classified as a physical hazard under GHS criteria.

**HEALTH HAZARDS:** 

Not classified as a health hazard under GHS criteria.

**ENVIRONMENTAL HAZARDS:** 

Not classified as an environmental hazard under GHS criteria.

Precautionary statements : Prevention:

1 / 16

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# CARADOL SP37-25V

Version Revision Date: SDS Number: Print Date: 08/29/2022

800001005691 1.2 07/06/2018 Date of last issue: 02/22/2017

No precautionary phrases.

Response:

No precautionary phrases.

Storage:

No precautionary phrases.

Disposal:

No precautionary phrases.

### Other hazards

#### Other hazards which do not result in classification

The classification of this material is based on OSHA HCS 2012 criteria.

## **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature Suspension of a solid polymeric material in a polyether polyol.

## **Hazardous components**

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
Polyalkylene glycol	POLYGLYCOL 112-2	9082-00-2	70 - 80
Styrene-acrylonitrile polymer	2- Propenenitrile, polymer with ethenylben- zene and methyloxirane polymer with oxirane ether with 1,2,3- propanetriol (3:1)	57913-80-1	20 - 30

## **SECTION 4. FIRST-AID MEASURES**

General advice Not expected to be a health hazard when used under normal

conditions.

If inhaled No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

In case of skin contact Remove contaminated clothing. Flush exposed area with wa-

ter and follow by washing with soap if available.

If persistent irritation occurs, obtain medical attention.

Flush eye with copious quantities of water. In case of eye contact

Remove contact lenses, if present and easy to do. Continue

rinsing.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# CARADOL SP37-25V

Version Revision Date: SDS Number: Print Date: 08/29/2022

Date of last issue: 02/22/2017 1.2 07/06/2018 800001005691

If persistent irritation occurs, obtain medical attention.

If swallowed In general no treatment is necessary unless large quantities

are swallowed, however, get medical advice.

Most important symptoms and effects, both acute and

delayed

use.

Does not pose an acute hazard under normal conditions of

Protection of first-aiders When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

Indication of any immediate medical attention and special

treatment needed

Treat symptomatically. Following cases of gross overexposure, investigation of liver, kidney and eye function may be advisable. Records of such incidents should be maintained

for future reference.

### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Large fires should only be fought by properly trained fire fight-

Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires

only.

Unsuitable extinguishing

media

Do not use water in a jet.

Specific hazards during fire-

fighting

Will only burn if enveloped in a pre-existing fire. Hazardous combustion products may include:

Carbon dioxide

Unidentified organic and inorganic compounds.

Toxic gases Carbon monoxide.

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

Further information Clear fire area of all non-emergency personnel.

All storage areas should be provided with adequate fire

fighting facilities.

Keep adjacent containers cool by spraying with water.

Special protective equipment:

for firefighters

Proper protective equipment including chemical resistant

gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# CARADOL SP37-25V

Version Revision Date: SDS Number: Print Date: 08/29/2022

800001005691 1.2 07/06/2018 Date of last issue: 02/22/2017

Personal precautions, protec: : tive equipment and emer-

Avoid contact with skin, eves and clothing. gency procedures

Avoid inhaling vapour and/or mists.

Extinguish any naked flames. Do not smoke. Remove ignition

Observe all relevant local and international regulations.

sources. Avoid sparks.

Remove all possible sources of ignition in the surrounding **Environmental precautions** 

Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers.

Use appropriate containment to avoid environmental contami-

nation.

Ventilate contaminated area thoroughly.

Methods and materials for containment and cleaning up For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove

contaminated soil and dispose of safely.

Proper disposal should be evaluated based on regulatory status of this material (refer to Chapter 13), potential contamination from subsequent use and spillage, and regulations

governing disposal in the local area.

Additional advice : For guidance on selection of personal protective equipment

see Chapter 8 of this Safety Data Sheet.

For guidance on disposal of spilled material see Chapter 13 of

this Safety Data Sheet.

### **SECTION 7. HANDLING AND STORAGE**

Technical measures Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Chapter 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

Advice on safe handling In accordance with good industrial hygiene practices, precau-

> tions should be taken to avoid breathing of material. Use local exhaust extraction over processing area.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# **CARADOL SP37-25V**

Version Revision Date: SDS Number: Print Date: 08/29/2022

1.2 07/06/2018 800001005691 Date of last issue: 02/22/2017

Avoid unintentional contact with isocyanates to prevent uncon-

trolled polymerisation.

Avoid contact with skin, eyes and clothing.

Air-dry contaminated clothing in a well-ventilated area before

laundering.

Do not empty into drains. Handling Temperature:

Ambient.

When handling product in drums, safety footwear should be worn and proper handling equipment should be used.

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

Avoidance of contact : Avoid contact with isocyanates, copper and copper alloys,

zinc, strong oxidizing agents, and water.

Product Transfer : Lines should be purged with nitrogen before and after product

transfer. Keep containers closed when not in use.

Conditions for safe storage : Refer to section 15 for any additional specific legislation cov-

ering the packaging and storage of this product.

Storage period : 24 Months

Further information on stor-

age stability

Prevent all contact with water and with moist atmosphere.

Tanks must be clean, dry and rust-free.

Prevent ingress of water.

Must be stored in a diked (bunded) well- ventilated area, away from sunlight, ignition sources and other sources of heat. Nitrogen blanket recommended for large tanks (capacity 100

m3 or higher).

Drums should be stacked to a maximum of 3 high.

Storage Temperature:

Ambient.

Storage should be handled at temperatures such that viscosi-

ties are less than 500 cSt; typically at 25-50 °C.

Tanks should be fitted with heating coils in areas where the ambient temperatures are below the recommended product handling temperatures. Heating coil skin temperatures should

not exceed 100 °C.

Packaging material : Suitable material: Stainless steel., For container paints, use

epoxy paint, zinc silicate paint.

Unsuitable material: Copper., Copper alloys.

Specific use(s) : Not applicable

Ensure that all local regulations regarding handling and stor-

age facilities are followed.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# **CARADOL SP37-25V**

Version Revision Date: SDS Number: Print Date: 08/29/2022

1.2 07/06/2018 800001005691 Date of last issue: 02/22/2017

## **SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION**

## Components with workplace control parameters

Contains no substances with occupational exposure limit values.

### **Biological occupational exposure limits**

No biological limit allocated.

### **Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

## **Engineering measures**

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. Adequate ventilation to control airborne concentrations.

### General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# **CARADOL SP37-25V**

Version Revision Date: SDS Number: Print Date: 08/29/2022

1.2 07/06/2018 800001005691 Date of last issue: 02/22/2017

equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or mainte-

nance.

Retain drain downs in sealed storage pending disposal or

subsequent recycle.

## Personal protective equipment

Respiratory protection : No respiratory protection is ordinarily required under normal

conditions of use.

In accordance with good industrial hygiene practices, precau-

tions should be taken to avoid breathing of material.

Hand protection Remarks

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber. Incidental contact/Splash protection: PVC, neoprene or nitrile rubber gloves For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended.

Skin and body protection : Skin protection is not ordinarily required beyond standard

work clothes.

It is good practice to wear chemical resistant gloves.

Protective measures : Personal protective equipment (PPE) should meet recom-

mended national standards. Check with PPE suppliers.

Hygiene measures : Wash hands before eating, drinking, smoking and using the

toilet.

Launder contaminated clothing before re-use.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## CARADOL SP37-25V

Version Revision Date: SDS Number: Print Date: 08/29/2022

1.2 07/06/2018 800001005691 Date of last issue: 02/22/2017

## **Environmental exposure controls**

General advice : Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

vapour.

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local envi-

ronmental legislation.

Information on accidental release measures are to be found in

section 6.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Viscous liquid.

Colour : white

Odour : odourless

Odour Threshold : Data not available

pH : Not applicable

Melting / freezing point : -18 °C / -0.40 °F

pour point -18 °C / -0.40 °F

Boiling point/boiling range : Data not available

Flash point :  $> 200 \, ^{\circ}\text{C} \, / > 392 \, ^{\circ}\text{F}$ 

Evaporation rate : Data not available

Vapour pressure : Data not available

Relative vapour density : Data not available

Relative density : Data not available

Density : 1,020 kg/m3 (25 °C / 77 °F)

Solubility(ies)

Water solubility : negligible

Partition coefficient: n-

octanol/water

Data not available

Auto-ignition temperature : Data not available

Decomposition temperature : Data not available

Viscosity

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# **CARADOL SP37-25V**

Version Revision Date: SDS Number: Print Date: 08/29/2022

1.2 07/06/2018 800001005691 Date of last issue: 02/22/2017

Viscosity, dynamic : 2,000 mPa.s (20 °C / 68 °F)

50 mPa.s (> 100 °C / > 212 °F)

Viscosity, kinematic : Data not available

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : The product does not pose any further reactivity hazards in

addition to those listed in the following sub-paragraph.

Chemical stability : No hazardous reaction is expected when handled and stored

according to provisions

Hygroscopic.

Possibility of hazardous reac-

tions

Polymerises exothermically with di-isocyanates at ambient

temperatures.

The reaction becomes progressively more vigorous and can be violent at higher temperatures if the miscibility of reaction partners is good or is supported by stirring or by the presence

of solvents.

Reacts with strong oxidising agents.

Conditions to avoid : Heat, flames, and sparks.

Product cannot ignite due to static electricity.

Incompatible materials : Avoid contact with isocyanates, copper and copper alloys,

zinc, strong oxidizing agents, and water.

Hazardous decomposition

products

Unknown toxic products may be formed.

### **SECTION 11. TOXICOLOGICAL INFORMATION**

Basis for assessment : Information given is based on product testing, and/or similar

products, and/or components.

### Information on likely routes of exposure

Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

## **Acute toxicity**

**Product:** 

Acute oral toxicity : LD50 : > 5000 mg/kg

Remarks: Low toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria

are not met.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# CARADOL SP37-25V

Version Revision Date: SDS Number: Print Date: 08/29/2022

800001005691 1.2 07/06/2018 Date of last issue: 02/22/2017

Acute dermal toxicity : LD50 : > 5000 mg/kg

Remarks: Low toxicity:

Based on available data, the classification criteria are not met.

## Skin corrosion/irritation

**Product:** 

Remarks: Not irritating to skin.

## Serious eye damage/eye irritation

**Product:** 

Remarks: Not irritating to eye.

## Respiratory or skin sensitisation

**Product:** 

Remarks: Not a skin sensitiser.

Based on available data, the classification criteria are not met.

## Germ cell mutagenicity

**Product:** 

: Remarks: Not mutagenic.

### Carcinogenicity

**Product:** 

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

**IARC** No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

## Reproductive toxicity

**Product:** 

Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair

fertility.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# **CARADOL SP37-25V**

Version Revision Date: SDS Number: Print Date: 08/29/2022

1.2 07/06/2018 800001005691 Date of last issue: 02/22/2017

## STOT - single exposure

### **Product:**

Remarks: Based on available data, the classification criteria are not met.

## STOT - repeated exposure

### **Product:**

Remarks: Based on available data, the classification criteria are not met.

## **Aspiration toxicity**

## **Product:**

Not an aspiration hazard.

### **Further information**

### **Product:**

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

#### **SECTION 12. ECOLOGICAL INFORMATION**

Basis for assessment : Incomplete ecotoxicological data are available for this product.

The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.

### **Ecotoxicity**

**Product:** 

Toxicity to fish (Acute toxici: LC50: > 100 mg/l

y) Remarks: Practically non toxic:

Toxicity to daphnia and other :

aquatic invertebrates (Acute

toxicity)

EC50: > 100 mg/l

Remarks: Practically non toxic:

Toxicity to algae (Acute tox-

icity)

EC50: > 100 mg/l

Remarks: Practically non toxic:

Toxicity to fish (Chronic tox-

icity)

Remarks: Data not available

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

Remarks: Data not available

Toxicity to microorganisms

(Acute toxicity)

IC50: > 100 mg/l

Remarks: Practically non toxic:

Based on available data, the classification criteria are not met.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# **CARADOL SP37-25V**

Version Revision Date: SDS Number: Print Date: 08/29/2022

1.2 07/06/2018 800001005691 Date of last issue: 02/22/2017

## Persistence and degradability

**Product:** 

Biodegradability : Remarks: Not readily biodegradable.

Oxidises rapidly by photo-chemical reactions in air.

Bioaccumulative potential

**Product:** 

Bioaccumulation : Remarks: Does not have the potential to bioaccumulate signif-

icantly.

Mobility in soil

**Product:** 

Mobility : Remarks: If the product enters soil, one or more constituents

will or may be mobile and may contaminate groundwater.

Other adverse effects

no data available

## **SECTION 13. DISPOSAL CONSIDERATIONS**

### **Disposal methods**

Waste from residues : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth-

ods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses

Waste product should not be allowed to contaminate soil or

water.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or na-

tional requirements and must be complied with.

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Send to drum recoverer or metal reclaimer.

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# **CARADOL SP37-25V**

Version Revision Date: SDS Number: Print Date: 08/29/2022

1.2 07/06/2018 800001005691 Date of last issue: 02/22/2017

#### **SECTION 14. TRANSPORT INFORMATION**

### **National Regulations**

## **US Department of Transportation Classification (49 CFR Parts 171-180)**

Not regulated as a dangerous good

### **International Regulations**

#### **IATA-DGR**

Not regulated as a dangerous good

#### **IMDG-Code**

Not regulated as a dangerous good

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category : Y Ship type : 3

Product name : Acrylonitrile-Styrene Copolymer Dispersion in Polyether Polyol

### Special precautions for user

Remarks : Special Precautions: Refer to Chapter 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

**Additional Information**: This product may be transported under nitrogen blanketing.

Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space

entry.

### **SECTION 15. REGULATORY INFORMATION**

## **EPCRA - Emergency Planning and Community Right-to-Know Act**

\*: This material does not contain any components with a CERCLA RQ.

# SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# **CARADOL SP37-25V**

Version Revision Date: SDS Number: Print Date: 08/29/2022

1.2 07/06/2018 800001005691 Date of last issue: 02/22/2017

#### **Clean Water Act**

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

## **US State Regulations**

### California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

## Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

## The components of this product are reported in the following inventories:

TSCA : Listed

AIIC : Listed

DSL : Listed

IECSC : Listed

KECI : Listed

NZIoC : Listed

PICCS : Listed

## **SECTION 16. OTHER INFORMATION**

## **Further information**

NFPA Rating (Health, Fire, Reac- 0, 1, 0 tivity)

#### Full text of other abbreviations

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this docu-

ment can be looked up in reference literature (e.g. scientific

dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial

**Hygienists** 

ADR = European Agreement concerning the International

Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# **CARADOL SP37-25V**

Version Revision Date: SDS Number: Print Date: 08/29/2022

1.2 07/06/2018 800001005691 Date of last issue: 02/22/2017

CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut fur Normung DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission

EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and Toxicology Of Chemicals

ECHA = European Chemicals Agency

EINECS = The European Inventory of Existing Commercial

**Chemical Substances** 

EL50 = Effective Loading fifty

ENCS = Japanese Existing and New Chemical Substances Inventory

EWC = European Waste Code

GHS = Globally Harmonised System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IC50 = Inhibitory Concentration fifty

IL50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous Goods

INV = Chinese Chemicals Inventory

IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables

KECI = Korea Existing Chemicals Inventory

LC50 = Lethal Concentration fifty

LD50 = Lethal Dose fifty per cent.

LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading

LL50 = Lethal Loading fifty

MARPOL = International Convention for the Prevention of

Pollution From Ships

NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level

OE\_HPV = Occupational Exposure - High Production Volume

PBT = Persistent, Bioaccumulative and Toxic

PICCS = Philippine Inventory of Chemicals and Chemical Substances

PNEC = Predicted No Effect Concentration

REACH = Registration Evaluation And Authorisation Of Chemicals

RID = Regulations Relating to International Carriage of Dangerous Goods by Rail

SKIN\_DES = Skin Designation

STEL = Short term exposure limit

TRA = Targeted Risk Assessment

TSCA = US Toxic Substances Control Act

TWA = Time-Weighted Average

vPvB = very Persistent and very Bioaccumulative

A vertical bar () in the left margin indicates an amendment from the previous version.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# **CARADOL SP37-25V**

Version Revision Date: SDS Number: Print Date: 08/29/2022

1.2 07/06/2018 800001005691 Date of last issue: 02/22/2017

Sources of key data used to

compile the Safety Data

Sheet

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

Revision Date : 07/06/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN