In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

# **NEODENE 12 Alpha Olefin**

MSDS number 7150 Print Date 2022.09.03

Version 3.2 Revision Date 2022.05.26

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : NEODENE 12 Alpha Olefin

Product code V1142, V1501, V1519

CAS-No. : 112-41-4

Other means of identification : Dodec-1-ene

Recommended use of the chemical and restrictions on use

Recommended use : Use as an intermediate in industrial chemicals manufacture.

Restrictions on use This product must not be used in applications other than the

above without first seeking the advice of the supplier.

#### Manufacturer or supplier's details

Supplier

SHELL EASTERN CHEMICALS (S)

A REGISTERED BUSINESS OF SHELL EASTERN

TRADING (PTE) LTD (UEN:198902087C)

9 North Buona Vista Drive, #07-01

The Metropolis Tower 1 Singapore 138588

Singapore

Telephone + 82 2 360 1169 Telefax : +82 2 393 6196 Contact for Safety Data

Sheet

: sccmsds@shell.com

Emergency telephone

number

: + (65) 6542 9595 (Alert-SGS)

Organization that prepared

the SDS

JOIN International Ltd. (JIL) Samsung Cheil Bldg., 18th Fl, 309, Tereran-ro, Gangnam-gu, Seoul, 06151, Republic of Korea

+82 (0)2 527 4317 +82 (0)2 527 4314 (FAX)

Other information : NEODENE is a trademark owned by Shell Trademark

Management B.V. and Shell Brands Inc. and used by affiliates

of Royal Dutch Shell plc.

### 2. HAZARDS IDENTIFICATION

1/21 800001007137 KR

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

# **NEODENE 12 Alpha Olefin**

MSDS number 7150

Version 3.2 Revision Date 2022.05.26 Print Date 2022.09.03

**GHS Classification** 

Flammable liquids Category 4 Aspiration hazard : Category 1

**GHS** label elements

Hazard pictograms

Signal word

PHYSICAL HAZARDS: Hazard statements

Not classified as a physical hazard under GHS criteria.

**HEALTH HAZARDS:** 

H304 May be fatal if swallowed and enters airways.

**ENVIRONMENTAL HAZARDS:** 

Not classified as an environmental hazard under GHS criteria.

Precautionary statements

Prevention:

P243 Take precautionary measures against static discharge.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/ doctor.

P331 Do NOT induce vomiting.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

# Other hazards which do not result in classification

This material is a static accumulator. Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Vapours are heavier than air. Vapours may travel across the ground and reach remote ignition sources causing a flashback fire danger.Will float and can be reignited on surface water.Repeated exposure may cause skin dryness or cracking.

NFPA Rating (Health, Fire, : 1, 2, 0

Reactivity)

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture Substance

2/21 800001007137 KR

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

# **NEODENE 12 Alpha Olefin**

MSDS number 7150 Version 3.2 Revision Date 2022.05.26 Print Date 2022.09.03

#### Components

Chemical name	Common Name	CAS-No.	Concentration (% w/w)
dodec-1-ene	dodec-1-ene	112-41-4	<= 100

#### 4. FIRST-AID MEASURES

: Not expected to be a health hazard when used under normal General advice

conditions.

In case of eye contact : Flush eye with copious quantities of water.

Remove contact lenses, if present and easy to do. Continue

If persistent irritation occurs, obtain medical attention.

In case of skin contact : Remove contaminated clothing. Immediately flush skin with

> large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical

facility for additional treatment.

If inhaled : No treatment necessary under normal conditions of use. If

symptoms persist, obtain medical advice.

If swallowed : Call emergency number for your location / facility.

> If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

Most important symptoms and effects, both acute and delayed

: Not considered to be an inhalation hazard under normal

conditions of use.

Possible respiratory irritation signs and symptoms may include

a temporary burning sensation of the nose and throat,

coughing, and/or difficulty breathing.

Skin irritation signs and symptoms may include a burning

sensation, redness, or swelling.

No specific hazards under normal use conditions.

Eve irritation signs and symptoms may include a burning

sensation, redness, swelling, and/or blurred vision.

If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest

congestion, shortness of breath, and/or fever.

The onset of respiratory symptoms may be delayed for

several hours after exposure.

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

# **NEODENE 12 Alpha Olefin**

Version 3.2 Revision Date 2022.05.26 MSDS number 7150

Print Date 2022.09.03

If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing. Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

Notes to physician : Call a doctor or poison control center for guidance.

Potential for chemical pneumonitis.

Treat symptomatically.

Narcotic at high vapour concentrations.

#### 5. FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon

dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing

media

: Do not use water in a jet.

Specific hazards during

firefighting

: Clear fire area of all non-emergency personnel.

Hazardous combustion products may include:

A complex mixture of airborne solid and liquid particulates and

gases (smoke). Carbon monoxide.

Unidentified organic and inorganic compounds.

Flammable vapours may be present even at temperatures

below the flash point.

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Will float and can be reignited on surface water.

Specific extinguishing

methods

: Standard procedure for chemical fires.

Keep adjacent containers cool by spraying with water.

Special protective equipment

for firefighters

: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if

large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

# **NEODENE 12 Alpha Olefin**

Version 3.2 Revision Date 2022.05.26

MSDS number 7150 Print Date 2022.09.03

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Observe all relevant local and international regulations.
 Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.
 Local authorities should be advised if significant spillages

cannot be contained.

: Avoid contact with skin, eyes and clothing.
Isolate hazard area and deny entry to unnecessary or unprotected personnel.

Do not breathe fumes, vapour. Do not operate electrical equipment.

Environmental precautions

: Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.

Monitor area with combustible gas indicator.

Methods and materials for containment and cleaning up

For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely

Ventilate contaminated area thoroughly.

If contamination of site occurs remediation may require

specialist advice.

Additional advice

: For guidance on selection of personal protective equipment

see Section 8 of this Safety Data Sheet.

For guidance on disposal of spilled material see Section 13 of

this Safety Data Sheet.

#### 7. HANDLING AND STORAGE

General Precautions : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

5 / 21 800001007137 KR

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

# **NEODENE 12 Alpha Olefin**

Version 3.2 Revision Date 2022.05.26 MSDS number 7150

Revision Date 2022.05.26 Print Date 2022.09.03

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine

appropriate controls for safe handling, storage and disposal of

this material.

Ensure that all local regulations regarding handling and

storage facilities are followed.

Advice on safe handling : Avoid inhaling vapour and/or mists.

Avoid contact with skin, eyes and clothing.

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Bulk storage tanks should be diked (bunded).

When using do not eat or drink.

The vapour is heavier than air, spreads along the ground and

distant ignition is possible.

Avoidance of contact : Strong oxidising agents.

Product Transfer : Even with proper grounding and bonding, this material can still

accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/s until fill pipe submerged to twice its diameter, then ≤ 7 m/s). Avoid splash

filling. Do NOT use compressed air for filling, discharging, or

handling operations.

Refer to guidance under Handling section.

### Safe storage methods (including conditions to be avoided)

Conditions for safe storage : Refer to section 15 for any additional specific legislation

covering the packaging and storage of this product.

Other data : Storage Temperature:

Ambient.

Bulk storage tanks should be diked (bunded).

Locate tanks away from heat and other sources of ignition. Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of

strict procedures and precautions.

6 / 21 800001007137 KR

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

# **NEODENE 12 Alpha Olefin**

		MSDS number 7150	
Version 3.2	Revision Date 2022.05.26	Print Date 2022.09.03	
	from sunlight, ignition sources and othe Keep away from aerosols, flammables, corrosives and from other flammable probabilities and from other flammable probabilities and from other environ Electrostatic charges will be generated Electrostatic discharge may cause fire. continuity by bonding and grounding (eato reduce the risk.  The vapours in the head space of the statement of	The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be	
Packaging material	<ul> <li>Suitable material: For containers, or cor steel, stainless steel., For container pair zinc silicate paint.</li> <li>Unsuitable material: Avoid prolonged co butyl or nitrile rubbers.</li> </ul>	nts, use epoxy paint,	
Container Advice	: Do not cut, drill, grind, weld or perform s near containers.	similar operations on or	
Specific use(s)	: Not applicable		
	See additional references that provide s for liquids that are determined to be stated American Petroleum Institute 2003 (Prolignitions Arising out of Static, Lightning National Fire Protection Agency 77 (Recon Static Electricity).  IEC/TS 60079-32-1: Electrostatic hazard	tic accumulators: tection Against and Stray Currents) or commended Practices	

#### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### Components with workplace control parameters

# **Biological occupational exposure limits**

No biological limit allocated.

#### **Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

# **NEODENE 12 Alpha Olefin**

MSDS number 7150 Revision Date 2022.05.26 Print Date 2022.09.03

http://www.osha.gov/

Version 3.2

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.isp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

#### **Engineering measures**

: Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Eye washes and showers for emergency use.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.

Appropriate measures include:

#### General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

### Personal protective equipment

#### Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection : If engineering controls do not maintain airborne

> concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

# **NEODENE 12 Alpha Olefin**

Version 3.2 Revision Date 2022.05.26 MSDS number 7150

Revision Date 2022.05.26 Print Date 2022.09.03

space) use appropriate positive pressure breathing apparatus.

Where air-filtering respirators are suitable, select an

appropriate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type A

boiling point >65°C (149°F)].

Eye protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended.

Hand protection Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374,

US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC, neoprene or nitrile rubber gloves For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using

gloves, hands should be washed and dried thoroughly.
Application of a non-perfumed moisturizer is recommended.

Skin and body protection : Skin protection is not requ

Skin protection is not required under normal conditions of use. For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard,

and provide employee skin care programmes.

Wear antistatic and flame-retardant clothing, if a local risk

assessment deems it so.

Thermal hazards : Not applicable

Hygiene measures : Wash hands before eating, drinking, smoking and using the

toilet.

Launder contaminated clothing before re-use.

9 / 21 800001007137 KR

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

# **NEODENE 12 Alpha Olefin**

Version 3.2 Revision Date 2022.05.26 MSDS number 7150

Print Date 2022.09.03

Do not ingest. If swallowed, then seek immediate medical

assistance.

### **Environmental exposure controls**

General advice : Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

vapour.

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local

environmental legislation.

Information on accidental release measures are to be found in

section 6.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquid at room temperature.

Colour : Clear colourless
Odour : Mild hydrocarbon
Odour Threshold : Data not available
pH : Not applicable
Melting / freezing point : -36 °C / -33 °F

Boiling point/boiling range : 210 - 213 °C / 410 - 415 °F

Flash point : 83 °C / 181 °F

Method: ASTM D7236 (closed cup)

Evaporation rate : Data not available

Upper/Lower explosion limit

Upper explosion limit : Data not available

Lower explosion limit : Data not available

Vapour pressure : 21 Pa (20 °C / 68 °F)

69 Pa (38 °C / 100 °F)

Solubility(ies)

Water solubility : 0.113 mg/l (25 °C / 77 °F)

Solubility in other solvents : Data not available

Relative vapour density : Data not available Relative density : 0.76 (20 °C / 68 °F)

Method: ASTM D4052

10 / 21 800001007137 KR

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

# **NEODENE 12 Alpha Olefin**

MSDS number 7150

 Version 3.2
 Revision Date 2022.05.26
 Print Date 2022.09.03

Density : 758 kg/m3 (20 °C / 68 °F)

Method: ASTM D4052

Partition coefficient: n-

octanol/water

: log Pow: estimated value(s) 6.1

Auto-ignition temperature : 242 °C / 468 °F

Decomposition temperature : Data not available

Viscosity

Viscosity, dynamic : 1.02 mPa.s (38 °C / 100 °F)

Method: ASTM D445

Viscosity, dynamic 1.38 mPa.s (20 °C / 68 °F)

Method: ASTM D445

Viscosity, kinematic : 1.8 mm2/s (20 °C / 68 °F)

Method: ASTM D445

Explosive properties : Not applicable

Oxidizing properties : Data not available

Surface tension : Data not available

Conductivity: < 100 pS/m

The conductivity of this material makes it a static

accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semiconductive if its conductivity is below 10,000 pS/m., Whether a liquid is nonconductive or semi-conductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static

additives can greatly influence the conductivity of a liquid

Particle size : Data not available

Molecular weight : 168 g/mol

#### 10. STABILITY AND REACTIVITY

Chemical stability and possibility of hazardous reactions:

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph. No hazardous reaction is expected when handled and stored according to provisions, Stable under normal

conditions of use.

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

# **NEODENE 12 Alpha Olefin**

MSDS number 7150 Version 3.2 Revision Date 2022.05.26 Print Date 2022.09.03

Reacts with strong oxidising agents.

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.

In certain circumstances product can ignite due to static

electricity.

Incompatible materials : Strong oxidising agents.

Hazardous decomposition

products

: Hazardous decomposition products are not expected to form

during normal storage.

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this

material undergoes combustion or thermal or oxidative

degradation.

#### 11. TOXICOLOGICAL INFORMATION

: Information given is based on data obtained from similar Basis for assessment

substances.

exposure

Information on likely routes of : Exposure may occur via inhalation, ingestion, skin absorption,

skin or eye contact, and accidental ingestion.

#### **Health hazard information**

## **Acute toxicity**

### Components:

dodec-1-ene:

: LD 50 Rat, male and female: > 5,000 mg/kg Acute oral toxicity

Method: Test(s) equivalent or similar to OECD Test Guideline

Remarks: Based on available data, the classification criteria

are not met. Low toxicity: LD50 >5000 mg/kg

: LC 50 Rat, male: > 20 mg/l Acute inhalation toxicity

Exposure time: 4 h Test atmosphere: vapour

Method: Test(s) equivalent or similar to OECD Test Guideline

Remarks: Based on available data, the classification criteria

are not met.

Low toxicity if inhaled.

: LD 50 Rabbit, male and female: > 2,000 mg/kg Acute dermal toxicity

12 / 21 800001007137 KR

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

# **NEODENE 12 Alpha Olefin**

Version 3.2 Revision Date 2022.05.26 MSDS number 7150

Print Date 2022.09.03

Method: OECD Test Guideline 402

Remarks: May be harmful in contact with skin.

LD50 >2000 - <=5000 mg/kg

Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation

#### **Components:**

**dodec-1-ene:**Species: Rabbit

Method: Test(s) equivalent or similar to OECD Test Guideline 404

Remarks: Causes mild skin irritation.

#### Serious eye damage/eye irritation

#### **Components:**

dodec-1-ene: Species: Rabbit

Method: Test(s) equivalent or similar to OECD Test Guideline 405

Remarks: Based on available data, the classification criteria are not met.. Not irritating to eye.

#### Respiratory or skin sensitisation

#### **Components:**

# dodec-1-ene:

Species: Guinea pig

Method: Test(s) equivalent or similar to OECD Test Guideline 406 Remarks: Based on available data, the classification criteria are not met.

Not a sensitiser.

### Carcinogenicity

#### **Components:**

dodec-1-ene:

Carcinogenicity - : This product does not meet the criteria for classification in

Assessment categories 1A/1B.

Material	GHS/CLP Carcinogenicity Classification	
dodec-1-ene	No carcinogenicity classification.	

### Germ cell mutagenicity

#### **Components:**

dodec-1-ene:

Genotoxicity in vitro : Method: OECD Test Guideline 471

Remarks: Based on available data, the classification criteria

are not met., Non mutagenic

: Method: Test(s) equivalent or similar to OECD Test Guideline

473

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

# **NEODENE 12 Alpha Olefin**

MSDS number 7150 Revision Date 2022.05.26 Print Date 2022.09.03

Remarks: Based on available data, the classification criteria

are not met., Non mutagenic

: Test species: MouseMethod: OECD Test Guideline 471 Remarks: Based on available data, the classification criteria

are not met., Non mutagenic

Germ cell mutagenicity-

Assessment

This product does not meet the criteria for classification in

categories 1A/1B.

#### Reproductive toxicity

#### Components:

Version 3.2

dodec-1-ene:

: Species: Rat

Sex: male and female Application Route: Oral

Method: OECD Test Guideline 422

Remarks: Based on available data, the classification criteria

are not met., Does not impair fertility.

Effects on foetal development

: Species: Rat, female Application Route: Oral

Method: OECD Test Guideline 414

Remarks: Based on available data, the classification criteria

are not met., Not a developmental toxicant.

Reproductive toxicity -

Assessment

: This product does not meet the criteria for classification in

categories 1A/1B.

#### STOT - single exposure

### **Components:**

#### dodec-1-ene:

Remarks: Based on available data, the classification criteria are not met.

#### STOT - repeated exposure

#### **Components:**

#### dodec-1-ene:

Remarks: Based on available data, the classification criteria are not met., Repeated exposure may cause skin dryness or cracking.

#### Repeated dose toxicity

#### Components:

#### dodec-1-ene:

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

# **NEODENE 12 Alpha Olefin**

MSDS number 7150 Print Date 2022.09.03

Version 3.2

Rat, male and female:
Application Route: Oral

Method: OECD Test Guideline 408

Target Organs: No specific target organs noted

Rat, male and female: Application Route: Inhalation Test atmosphere: vapour

Method: Test(s) equivalent or similar to OECD Test Guideline 413

Target Organs: No specific target organs noted

### **Aspiration toxicity**

### **Components:**

dodec-1-ene:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Revision Date 2022.05.26

#### **Further information**

#### Components:

dodec-1-ene:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

# 12. ECOLOGICAL INFORMATION

Basis for assessment : Information given is based on product testing.

### **Ecotoxicity**

# Components:

dodec-1-ene:

Toxicity to fish (Acute : LC50

toxicity)

: LC50 (Oncorhynchus mykiss (rainbow trout)): > 0.0034 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility

Toxicity to crustacean (Acute

toxicity)

: EC50 (Daphnia magna (Water flea)): > 0.0028 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: No toxicity at the limit of solubility

Toxicity to algae/aquatic plants (Acute toxicity)

mg/l

: EC50 (Pseudokirchneriella subcapitata (algae)): > 0.00093

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Not toxic at limit of water solubility:

Toxicity to microorganisms

(Acute toxicity)

: NOEC (Secondary Effluent): 2 mg/l

Exposure time: 336 h

15 / 21 800001007137 KR

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

# **NEODENE 12 Alpha Olefin**

MSDS number 7150

Version 3.2 Revision Date 2022.05.26 Print Date 2022.09.03

Method: OECD Test Guideline 301D

Remarks: No toxicity at the limit of solubility

Toxicity to fish (Chronic

toxicity)

: Remarks: Data not available

Toxicity to : Remarks: Data not available

Persistence and degradability

crustacean(Chronic toxicity)

Components: dodec-1-ene :

Biodegradability : Biodegradation: 72.4 - 74.5 %

Exposure time: 28 d

Method: OECD Test Guideline 301D Remarks: Readily biodegradable.

**Bioaccumulative potential** 

**Product:** 

Partition coefficient: n-

octanol/water Components:

: log Pow: estimated value(s) 6.1

Components: dodec-1-ene :

Bioaccumulation : Remarks: Has the potential to bioaccumulate.

Mobility in soil

Components: dodec-1-ene:

Mobility : Remarks: If it enters soil, it will adsorb to soil particles and will

not be mobile., Floats on water.

Other adverse effects

Components: dodec-1-ene:

Results of PBT and vPvB

assessment

: The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not

considered to be PBT or vPvB.

Additional ecological

information

: Data not available

13. DISPOSAL CONSIDERATIONS

**Disposal methods** 

Waste from residues : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Waste product should not be allowed to contaminate soil or

ground water, or be disposed of into the environment.

16 / 21 800001007137 KR

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

# **NEODENE 12 Alpha Olefin**

MSDS number 7150 Version 3.2 Revision Date 2022.05.26 Print Date 2022.09.03

Do not dispose into the environment, in drains or in water

courses

Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.

Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations. preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be complied with.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Drain container thoroughly.

> After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard. Do not puncture,

cut or weld uncleaned drums.

Send to drum recoverer or metal reclaimer.

Comply with any local recovery or waste disposal regulations.

#### **Disposal considerations**

Dispose of in accordance with local regulations.

#### 14. TRANSPORT INFORMATION

#### **National Regulations**

Refer to section 15 for specific national regulation.

### **International Regulations**

Not regulated as a dangerous good

#### **IATA-DGR**

Not regulated as a dangerous good

### **IMDG-Code**

Not regulated as a dangerous good

# Maritime transport in bulk according to IMO instruments

Pollution category : Y Ship type : 3

17 / 21 800001007137 KR

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

# **NEODENE 12 Alpha Olefin**

MSDS number 7150

Version 3.2 Revision Date 2022.05.26 Print Date 2022.09.03

Product name : 1-dodecene

Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

**Additional Information**: This product may be transported under nitrogen blanketing.

Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry. Transport in bulk according to Annex II

of Marpol and the IBC Code

#### 15. REGULATORY INFORMATION

### **National regulatory information**

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

INDUSTRY SAFETY & HEALTH ACT:	Hazardous substances prohibited from manufacturing, etc., Not applicable	
	Hazardous substances subject to authorization, Not applicable	
	Hazardous substances subject to control, Not applicable	
	Substances established for exposure limits, Not applicable	
	Hazardous factor subject to keep below permissible limit, Not applicable	
	Hazardous Factors Subject to Working Environment Monitoring, Not applicable	
	Hazardous Factors Subject to Special Medical Examination, Not applicable	
CHEMICALS CONTROL ACT:	Toxic chemical substances, Not applicable	
	Authorization chemical substances, Not applicable	
	Restricted chemical substances, Not applicable	

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

# **NEODENE 12 Alpha Olefin**

			MSDS number 7150	
Version 3.2	Revision D	ate 2022.05.26	Print Date 2022.09.03	
		Prohibited chemical substances, Not app		
		Accident precaution chemical substance, Not applicable		
		Гарріісавіе		
DANGEROUS GOODS SAFE CONTROL ACT:	Category 4 Dange	ation of dangerous material:, rous Goods (Flammable		
	Liquids), Grade 3	petroleum chemicals		
WASTES MANAGEM	WASTES MANAGEMENT ACT:		4/5/24/25 of Disposal	
	Considerations Se	ection.		

# Other requirements in domestic and other countries

The components of this product are reported in the following inventories:

AIIC : Listed

DSL : Listed

IECSC : Listed

ENCS : Listed

KECI : Listed

NZIoC : Listed

PICCS : Listed

TSCA : Listed

TCSI : Listed

#### 16. OTHER INFORMATION

### Full text of other abbreviations

Asp. Tox. Aspiration hazard Flam. Liq. Flammable liquids

### **Abbreviations and Acronyms**

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

# **NEODENE 12 Alpha Olefin**

MSDS number 7150

Version 3.2 Revision Date 2022.05.26

Print Date 2022.09.03 x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration: ICAO - International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC -New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG -Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very

#### **Further information**

Training advice : Provide adequate information, instruction and training for

operators.

Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to

compile the Safety Data

Sheet

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

: 2013.06.14 Issuing date

#### Revision number and date

Number of Revision 3.2

Revision Date 2022.05.26

: A vertical bar (|) in the left margin indicates an amendment Other information

from the previous version.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

KR / EN

In accordance with Occupational Safety and Health Act's Standard of Classification and Labelling of Chemical Substances and MSDS

# **NEODENE 12 Alpha Olefin**

Version 3.2 Revision Date 2022.05.26

MSDS number 7150 Print Date 2022.09.03