

# SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

## Shell Paraffinic Fluid GS215C

800010030019

Initial release date: 2017.05.18

Version 2.2

Revision Date 2020.10.21

Print Date 2022.09.06

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Shell Paraffinic Fluid GS215C

Product code : Q6574

CAS-No. : 90622-53-0

#### Manufacturer or supplier's details

Supplier : SHELL EASTERN CHEMICALS (S)  
A REGISTERED BUSINESS OF SHELL EASTERN  
TRADING (PTE) LTD (UEN:198902087C)  
9 North Buona Vista Drive , #07-01  
The Metropolis Tower 1  
Singapore 138588  
Singapore

Telephone : +65 6384 8737  
Telefax : +65 6384 8454  
Email Contact for Safety Data Sheet : If you have any enquiries about the content of this SDS  
please email sccmsds@shell.com

Emergency telephone number : +86-532-83889090

#### Recommended use of the chemical and restrictions on use

Recommended use : Solvent.

Restrictions on use : This product must not be used in applications other than the  
above without first seeking the advice of the supplier.

### 2. HAZARDS IDENTIFICATION

#### Emergency Overview

Appearance	liquid
Colour	Data not available
Odour	Hydrocarbon
Health Hazards	Aspiration into the lungs may cause chemical pneumonitis which can be fatal.
Safety Hazards	Combustible liquid and vapour.
Environmental Hazards	Not classified as dangerous for the environment.

#### GHS Classification

Flammable liquids : Category 4  
Aspiration hazard : Category 1

#### GHS label elements

# SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

## Shell Paraffinic Fluid GS215C

800010030019

Initial release date: 2017.05.18

Version 2.2

Revision Date 2020.10.21

Print Date 2022.09.06

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: PHYSICAL HAZARDS:  
H227 Combustible liquid.  
HEALTH HAZARDS:  
H304 May be fatal if swallowed and enters airways.  
ENVIRONMENTAL HAZARDS:  
Not classified as an environmental hazard under GHS criteria.

Precautionary statements

:

### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P243 Take precautionary measures against static discharge.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

### Response:

P370 + P378 In case of fire: Use appropriate media to extinguish.  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
P331 Do NOT induce vomiting.

### Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

### Disposal:

P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regulations.

### Other hazards which do not result in classification

May form flammable/explosive vapour-air mixture. This material is a static accumulator. Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Repeated exposure may cause skin dryness or cracking.

Physical and chemical hazards	Combustible liquid.
Health Hazards	Inhalation: Under normal conditions of use, this is not expected to be a primary route of exposure. Skin: No specific hazards under normal use conditions. Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis. Eyes: No specific hazards under normal use conditions.

# SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

## Shell Paraffinic Fluid GS215C

800010030019

Initial release date: 2017.05.18

Version 2.2

Revision Date 2020.10.21

Print Date 2022.09.06

	Ingestion: May be fatal if swallowed and enters airways.
Environmental Hazards	Not classified as dangerous for the environment.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

#### Hazardous components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Alkanes, C12-26 branched	90622-53-0	Flam. Liq.4; H227 Asp. Tox.1; H304	100

For explanation of abbreviations see section 16.

### 4. FIRST-AID MEASURES

- General advice : Not expected to be a health hazard when used under normal conditions.
- If inhaled : No treatment necessary under normal conditions of use.  
If symptoms persist, obtain medical advice.
- In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.  
If persistent irritation occurs, obtain medical attention.
- In case of eye contact : Flush eye with copious quantities of water.  
Remove contact lenses, if present and easy to do. Continue rinsing.  
If persistent irritation occurs, obtain medical attention.
- If swallowed : Call emergency number for your location / facility.  
If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.  
If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.
- Most important symptoms and effects, both acute and delayed : Not considered to be an inhalation hazard under normal conditions of use.  
Possible respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.
- No specific hazards under normal use conditions.  
Skin irritation signs and symptoms may include a burning sensation, redness, or swelling.
- No specific hazards under normal use conditions.

# SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

## Shell Paraffinic Fluid GS215C

800010030019

Initial release date: 2017.05.18

Version 2.2

Revision Date 2020.10.21

Print Date 2022.09.06

Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.

If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.

If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.

Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.

Notes to physician : Call a doctor or poison control center for guidance.  
Potential for chemical pneumonitis.  
Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use water in a jet.

Specific hazards during firefighting : Clear fire area of all non-emergency personnel.  
Hazardous combustion products may include:  
A complex mixture of airborne solid and liquid particulates and gases (smoke).  
Carbon monoxide.  
Unidentified organic and inorganic compounds.  
Flammable vapours may be present even at temperatures below the flash point.  
The vapour is heavier than air, spreads along the ground and distant ignition is possible.  
Will float and can be reignited on surface water.

Specific extinguishing methods : Standard procedure for chemical fires.  
Keep adjacent containers cool by spraying with water.

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

# SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

## Shell Paraffinic Fluid GS215C

800010030019

Initial release date: 2017.05.18

Version 2.2

Revision Date 2020.10.21

Print Date 2022.09.06

### 6. ACCIDENTAL RELEASE MEASURES

- |   |   |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Observe all relevant local and international regulations. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Local authorities should be advised if significant spillages cannot be contained.   |
|   | : Avoid contact with skin, eyes and clothing. Isolate hazard area and deny entry to unnecessary or unprotected personnel. Do not breathe fumes, vapour. Do not operate electrical equipment.  |
| Environmental precautions   | : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas indicator.  |
| Methods and materials for containment and cleaning up               | : For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. Ventilate contaminated area thoroughly. If contamination of site occurs remediation may require specialist advice. |
| Additional advice   | : For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.  |

### 7. HANDLING AND STORAGE

#### Handling

- |                     |   |
|---------------------|---|
| General Precautions | : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see |
|---------------------|---|

# SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

## Shell Paraffinic Fluid GS215C

800010030019

Initial release date: 2017.05.18

Version 2.2

Revision Date 2020.10.21

Print Date 2022.09.06

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

Ensure that all local regulations regarding handling and storage facilities are followed.

Advice on safe handling : Avoid inhaling vapour and/or mists.  
Avoid contact with skin, eyes and clothing.  
Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.  
Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.  
Bulk storage tanks should be diked (bunded).  
When using do not eat or drink.

The vapour is heavier than air, spreads along the ground and distant ignition is possible.

Avoidance of contact : Strong oxidising agents.

Product Transfer : Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$  m/s until fill pipe submerged to twice its diameter, then  $\leq 7$  m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.

Refer to guidance under Handling section.

### Storage

Conditions for safe storage : Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Other data : Storage Temperature:  
Ambient.

Bulk storage tanks should be diked (bunded).  
Locate tanks away from heat and other sources of ignition.  
Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions.  
Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat.

# SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

## Shell Paraffinic Fluid GS215C

800010030019

Initial release date: 2017.05.18

Version 2.2

Revision Date 2020.10.21

Print Date 2022.09.06

Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products which are not harmful or toxic to man or to the environment.

Electrostatic charges will be generated during pumping.

Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.

The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.

Packaging material : Suitable material: For containers, or container linings use mild steel, stainless steel., For container paints, use epoxy paint, zinc silicate paint.  
Unsuitable material: Avoid prolonged contact with natural, butyl or nitrile rubbers.

Container Advice : Do not cut, drill, grind, weld or perform similar operations on or near containers.

Specific use(s) : Not applicable

See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).  
IEC/TS 60079-32-1: Electrostatic hazards, guidance

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Aliphatic dearom. solvents 200 - 250	Not Assigned	TWA	1,050 mg/m <sup>3</sup>	OEL based on European Hydrocarbon Solvents Producers (CEFIC-HSPA) methodology.

### Biological occupational exposure limits

No biological limit allocated.

### Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure

# SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

## Shell Paraffinic Fluid GS215C

800010030019

Initial release date: 2017.05.18

Version 2.2

Revision Date 2020.10.21

Print Date 2022.09.06

controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods <http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods <http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances <http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany <http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

### Engineering measures

- : Use sealed systems as far as possible.
- Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.
- Local exhaust ventilation is recommended.
- Firewater monitors and deluge systems are recommended.
- Eye washes and showers for emergency use.
- Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
- The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.
- Appropriate measures include:

#### General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping. Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle.

### Personal protective equipment

#### Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection : If engineering controls do not maintain airborne



# SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

## Shell Paraffinic Fluid GS215C

800010030019

Initial release date: 2017.05.18

Version 2.2

Revision Date 2020.10.21

Print Date 2022.09.06

concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. If air-filtering respirators are suitable for conditions of use: Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].

Hand protection  
Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC, neoprene or nitrile rubber gloves For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye protection

: If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

Skin and body protection

: Skin protection is not required under normal conditions of use. For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure. If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.

Wear antistatic and flame-retardant clothing, if a local risk assessment deems it so.

Thermal hazards

: Not applicable

# SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

## Shell Paraffinic Fluid GS215C

800010030019

Initial release date: 2017.05.18

Version 2.2

Revision Date 2020.10.21

Print Date 2022.09.06

Hygiene measures : Wash hands before eating, drinking, smoking and using the toilet.  
Laundry contaminated clothing before re-use.  
Do not ingest. If swallowed, then seek immediate medical assistance.

### Environmental exposure controls

General advice : Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.  
Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.  
Information on accidental release measures are to be found in section 6.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : Data not available

Odour : Hydrocarbon

Odour Threshold : Data not available

pH : Not applicable

Melting / freezing point : Data not available

Boiling point/boiling range : 210 - 260 °C / 410 - 500 °F

Flash point : 83.5 °C / 182.3 °F

Evaporation rate : Data not available

Flammability (solid, gas) : Not applicable

Upper explosion limit : 7 %(V)

Lower explosion limit : 0.5 %(V)

Vapour pressure : Data not available

Relative vapour density : Data not available

Relative density : < 0.8

Density : < 800 kg/m<sup>3</sup> (15 °C / 59 °F)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : log Pow: > 5.5

# SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

## Shell Paraffinic Fluid GS215C

800010030019

Initial release date: 2017.05.18

Version 2.2	Revision Date 2020.10.21	Print Date 2022.09.06
Auto-ignition temperature	: > 200 °C / > 392 °F	
Decomposition temperature	: Data not available	
Viscosity		
Viscosity, dynamic	: Data not available	
Viscosity, kinematic	: < 2 mm <sup>2</sup> /s (25 °C / 77 °F)	
Explosive properties	: Not classified	
Oxidizing properties	: Not applicable	
Surface tension	: Data not available	
Conductivity	: Low conductivity: < 100 pS/m The conductivity of this material makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m., Whether a liquid is nonconductive or semi-conductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid	
Particle size	: Data not available	
Molecular weight	: Data not available	

### 10. STABILITY AND REACTIVITY

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: No hazardous reaction is expected when handled and stored according to provisions Stable under normal conditions of use.
Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Avoid heat, sparks, open flames and other ignition sources.  In certain circumstances product can ignite due to static electricity.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: Hazardous decomposition products are not expected to form during normal storage. Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides

# SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

## Shell Paraffinic Fluid GS215C

800010030019

Initial release date: 2017.05.18

Version 2.2

Revision Date 2020.10.21

Print Date 2022.09.06

and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

### 11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on data obtained from similar substances.

Exposure routes : Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

#### Acute toxicity

##### Product:

Acute oral toxicity : LD 50 Rat, male and female: > 5,000 mg/kg  
Method: OECD Test Guideline 401  
Remarks: Based on available data, the classification criteria are not met.

Acute inhalation toxicity : LC 50 Rat, male and female: > 2 -<= 10 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Test(s) equivalent or similar to OECD Test Guideline 403  
Remarks: LC50 greater than near-saturated vapour concentration.  
Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD 50 Rat, male and female: > 2,000 mg/kg  
Method: Test(s) equivalent or similar to OECD Test Guideline 402  
Remarks: Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation

##### Product:

Species: Rabbit  
Method: Test(s) equivalent or similar to OECD Test Guideline 404  
Remarks: Moderately irritating to skin (but insufficient to classify)., Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.

#### Serious eye damage/eye irritation

##### Product:

Species: Rabbit  
Method: OECD Test Guideline 405  
Remarks: Based on available data, the classification criteria are not met.

#### Respiratory or skin sensitisation

# SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

## Shell Paraffinic Fluid GS215C

800010030019

Initial release date: 2017.05.18

Version 2.2

Revision Date 2020.10.21

Print Date 2022.09.06

### Product:

Species: Guinea pig

Method: OECD Test Guideline 406

Remarks: Based on available data, the classification criteria are not met.

### Germ cell mutagenicity

#### Product:

Genotoxicity in vitro

: Method: Test(s) equivalent or similar to OECD Guideline 471  
Remarks: Based on available data, the classification criteria are not met.

: Method: Test(s) equivalent or similar to OECD Test Guideline 473  
Remarks: Based on available data, the classification criteria are not met.

: Method: Test(s) equivalent or similar to OECD Test Guideline 476  
Remarks: Based on available data, the classification criteria are not met.

: Test species: Mouse  
Method: Test(s) equivalent or similar to OECD Test Guideline 474  
Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity-  
Assessment

: This product does not meet the criteria for classification in categories 1A/1B.

### Carcinogenicity

#### Product:

Species: Rat, (male and female)

Application Route: Inhalation

Method: Test(s) equivalent or similar to OECD Test Guideline 453

Remarks: Weight of evidence does not support classification as a carcinogen

Species: Mouse, (male and female)

Application Route: Inhalation

Method: Test(s) equivalent or similar to OECD Test Guideline 453

Remarks: Weight of evidence does not support classification as a carcinogen

Carcinogenicity -  
Assessment

: This product does not meet the criteria for classification in categories 1A/1B.

Material	GHS/CLP Carcinogenicity Classification
Alkanes, C12-26 branched	No carcinogenicity classification.

### Reproductive toxicity

#### Product:

# SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

## Shell Paraffinic Fluid GS215C

800010030019

Initial release date: 2017.05.18

Version 2.2

Revision Date 2020.10.21

Print Date 2022.09.06

: Species: Rat  
Sex: male and female  
Application Route: Oral

Method: OECD Test Guideline 416

Remarks: Based on available data, the classification criteria are not met.

Effects on foetal development

: Species: Rat, female  
Application Route: Oral  
Method: Test(s) equivalent or similar to OECD Test Guideline 414  
Remarks: Based on available data, the classification criteria are not met.

Species: Rat, female  
Application Route: Inhalation  
Method: Test(s) equivalent or similar to OECD Test Guideline 414  
Remarks: Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment

: This product does not meet the criteria for classification in categories 1A/1B.

### STOT - single exposure

#### Product:

Remarks: Based on available data, the classification criteria are not met.

### STOT - repeated exposure

#### Product:

Remarks: Based on available data, the classification criteria are not met.

### Repeated dose toxicity

#### Product:

Rat, male and female:  
Application Route: Oral  
Method: Test(s) equivalent or similar to OECD Test Guideline 408  
Target Organs: No specific target organs noted

Rat, male and female:  
Application Route: Inhalation  
Test atmosphere: vapour  
Method: Test(s) equivalent or similar to OECD Test Guideline 413  
Target Organs: No specific target organs noted

### Aspiration toxicity

#### Product:

# SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

## Shell Paraffinic Fluid GS215C

800010030019

Initial release date: 2017.05.18

Version 2.2

Revision Date 2020.10.21

Print Date 2022.09.06

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

### Further information

#### Product:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

## 12. ECOLOGICAL INFORMATION

Basis for assessment : Incomplete ecotoxicological data are available for this product.  
The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.

### Ecotoxicity

#### Product:

Toxicity to fish (Acute toxicity) : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: Practically non toxic:  
LL/EL/IL50 > 100 mg/l

Toxicity to crustacean (Acute toxicity) : EL50 (Daphnia magna (Water flea)): > 1,000 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: Practically non toxic:  
LL/EL/IL50 > 100 mg/l

Toxicity to algae/aquatic plants (Acute toxicity) : EL50 (Pseudokirchneriella subcapitata (algae)): > 1,000 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Practically non toxic:  
LL/EL/IL50 > 100 mg/l

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to crustacean (Chronic toxicity) : Remarks: Data not available

Toxicity to microorganisms (Acute toxicity) : Remarks: Data not available

### Persistence and degradability

#### Product:

Biodegradability : Biodegradation: 80 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F  
Remarks: Product is not persistent.

### Bioaccumulative potential

#### Product:

# SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

## Shell Paraffinic Fluid GS215C

800010030019

Initial release date: 2017.05.18

Version 2.2      Revision Date 2020.10.21      Print Date 2022.09.06

Bioaccumulation : Remarks: Has the potential to bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: > 5.5

### Mobility in soil

#### Product:

Mobility : Remarks: Floats on water., If it enters soil, it will adsorb to soil particles and will not be mobile.

### Other adverse effects

#### Product:

Results of PBT and vPvB assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

---

## 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Recover or recycle if possible.  
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water courses

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.

Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be complied with.

Contaminated packaging : Drain container thoroughly.  
After draining, vent in a safe place away from sparks and fire.  
Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums.  
Send to drum recoverer or metal reclaimer.  
Comply with any local recovery or waste disposal regulations.

Local legislation  
Remarks : If potential for exposure exists refer to Section 8 for specific personal protective equipment.

---

## 14. TRANSPORT INFORMATION



# SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

## Shell Paraffinic Fluid GS215C

800010030019

Initial release date: 2017.05.18

Version 2.2

Revision Date 2020.10.21

Print Date 2022.09.06

### National Regulations

### International Regulations

#### ADR

Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

### Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

**Additional Information** : This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry.

## 15. REGULATORY INFORMATION

### National regulatory information

Rotterdam Convention (Prior Informed Consent)

Not applicable

Stockholm Convention (Persistent Organic Pollutants)

Not applicable

### Law on the Prevention and Control of Occupational Diseases

The categories of occupational disease:

Not applicable

Occupational Disease Classification list:

Not applicable

### Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals : Not applicable

Identification of Major Hazard Installations for Hazardous Chemicals (GB 18218) : Not applicable

Hazardous Chemicals for Priority Management under SAWS : Not applicable

### Regulations on Labour Protection in Workplaces where Toxic Substances are Used

Catalogue of Highly Toxic Chemicals : Not applicable

# SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

## Shell Paraffinic Fluid GS215C

800010030019

Initial release date: 2017.05.18

Version 2.2

Revision Date 2020.10.21

Print Date 2022.09.06

### Regulation of Environmental Management on the First Import of Chemicals and the Import and Export of Toxic Chemicals

China Severely Restricted Toxic Chemicals for Import : Not applicable  
and Export

### Other international regulations

The components of this product are reported in the following inventories:

IECSC	: Listed
ENCS	: Listed
KECI	: Listed
TCSI	: Listed
EINECS	: Listed

## 16. OTHER INFORMATION

### Full text of H-Statements

H227	Combustible liquid.
H304	May be fatal if swallowed and enters airways.

### Full text of other abbreviations

Asp. Tox.	Aspiration hazard
Flam. Liq.	Flammable liquids

### Abbreviations and Acronyms

AICS - Australian Inventory of Chemical Substances; AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic

# SAFETY DATA SHEET

Prepared according to GB/T 16483, GB/T 17519

## Shell Paraffinic Fluid GS215C

800010030019

Initial release date: 2017.05.18

Version 2.2

Revision Date 2020.10.21

Print Date 2022.09.06

Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

### Further information

Training advice : Provide adequate information, instruction and training for operators.

Other information : A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CN / EN