

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
3.0	23.01.2025	800001001080	Print Date 30.01.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	: NEODOL 25
Product code	: V2451, V2493, V2745
Registration number EU	: 01-2119490230-48-0002
CAS-No.	: 90604-40-3

EC-No.	: 292-334-0
--------	-------------

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- stance/Mixture	: Use in detergent manufacture. Please refer to section 16 and/or the annexes for the registered uses under REACH.
-----------------------------------	---

Uses advised against	: This product must not be used in applications other than the above without first seeking the advice of the supplier.
----------------------	--

This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier	: Shell Chemicals Europe B.V. PO Box 2334 3000 CH Rotterdam Netherlands
Telephone	: +31 (0)10 441 5137 / +31 (0)10 441 5191
Telefax	: +31 (0)20 716 8316 / +31 (0)20 713 9230
Contact for Safety Data Sheet	: sccmsds@shell.com

1.4 Emergency telephone number

+44 (0) 1235 239 670 (This telephone number is available 24 hours per day, 7 days per week)

Numéro ORFILA (INRS): + 33 (0)1 45 42 59 59

Other information	: NEODOL is a trademark owned by Shell Trademark Management B.V. and Shell Brands Inc. and used by affiliates of Royal Dutch Shell plc.
-------------------	---

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Short-term (acute) aquatic hazard, Cate-	H400: Very toxic to aquatic life.
--	-----------------------------------

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
3.0	23.01.2025	800001001080	Print Date 30.01.2025

gory 1

Long-term (chronic) aquatic hazard, Category 1

H410: Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

:



Signal word

:

Warning

Hazard statements

:

PHYSICAL HAZARDS:

Not classified as a physical hazard according to CLP criteria.

HEALTH HAZARDS:

Not classified as a health hazard under CLP criteria.

ENVIRONMENTAL HAZARDS:

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

:

Prevention:

P273 Avoid release to the environment.

Response:

P391 Collect spillage.

Storage:

No precautionary phrases.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Repeated exposure may cause skin dryness or cracking.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version 3.0 Revision Date: 23.01.2025 SDS Number: 800001001080 Date of last issue: 21.11.2023
Print Date 30.01.2025

SECTION 3: Composition/information on ingredients

3.1 Substances

Components

Chemical name	CAS-No. EC-No.	Concentration (% w/w)
Alcohols, C12-15-branched and linear	90604-40-3 292-334-0	<= 100

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Not expected to be a health hazard when used under normal conditions.
- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- If inhaled : No treatment necessary under normal conditions of use.
If symptoms persist, obtain medical advice.
- In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.
If persistent irritation occurs, obtain medical attention.
- In case of eye contact : Flush eye with copious quantities of water.
Remove contact lenses, if present and easy to do. Continue rinsing.
If persistent irritation occurs, obtain medical attention.
- If swallowed : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Not considered to be an inhalation hazard under normal conditions of use.
Possible respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.
- No specific hazards under normal use conditions.
Skin irritation signs and symptoms may include a burning sensation, redness, or swelling.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version 3.0	Revision Date: 23.01.2025	SDS Number: 800001001080	Date of last issue: 21.11.2023 Print Date 30.01.2025
----------------	------------------------------	-----------------------------	---

No specific hazards under normal use conditions.
Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.

No specific hazards under normal use conditions.
Ingestion may result in nausea, vomiting and/or diarrhoea.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Call a doctor or poison control center for guidance.
Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Carbon monoxide may be evolved if incomplete combustion occurs.
Will float and can be reignited on surface water.
The vapour is heavier than air, spreads along the ground and distant ignition is possible.

5.3 Advice for firefighters

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

Specific extinguishing methods : Standard procedure for chemical fires.

Further information : Clear fire area of all non-emergency personnel.
Keep adjacent containers cool by spraying with water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Observe all relevant local and international regulations.
Notify authorities if any exposure to the general public or the

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
3.0	23.01.2025	800001001080	Print Date 30.01.2025

environment occurs or is likely to occur.
Local authorities should be advised if significant spillages cannot be contained.

6.1.1 For non emergency personnel:
Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.
Stay upwind and keep out of low areas.
Be ready for fire or possible exposure.

6.1.2 For emergency responders:
Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.
Stay upwind and keep out of low areas.
Be ready for fire or possible exposure.

6.2 Environmental precautions

Environmental precautions : Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers.
Use appropriate containment to avoid environmental contamination.
Ventilate contaminated area thoroughly.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.
For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.,
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
3.0	23.01.2025	800001001080	Print Date 30.01.2025

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

Ensure that all local regulations regarding handling and storage facilities are followed.

- | | |
|-------------------------|--|
| Advice on safe handling | : Avoid contact with skin, eyes and clothing.
Do not empty into drains.
Sudden Release of Pressure Hazard |
| Product Transfer | : Keep containers closed when not in use. Do not use compressed air for filling discharge or handling. |
| Hygiene measures | : Wash hands before eating, drinking, smoking and using the toilet. Launder contaminated clothing before re-use. |

7.2 Conditions for safe storage, including any incompatibilities

- | | |
|---|--|
| Requirements for storage areas and containers | : Refer to section 15 for any additional specific legislation covering the packaging and storage of this product. |
| Further information on storage stability | : Bulk storage tanks should be diked (bunded).
Vapours from tanks should not be released to atmosphere.
Breathing losses during storage should be controlled by a suitable vapour treatment system.
Nitrogen blanket recommended for large tanks (capacity 100 m ³ or higher).
Insulation (lagging) will minimize heat loss in areas of low ambient temperature.
Tanks should be fitted with heating coils in areas where ambient conditions can result in handling temperatures below the freezing point/pour point of the product. |
| Packaging material | : Suitable material: Stainless steel., Epoxy resins, Polyester.
Unsuitable material: Aluminum, Copper., Copper alloys. |
| Container Advice | : Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers. |

7.3 Specific end use(s)

- | | |
|-----------------|---|
| Specific use(s) | : Please refer to section 16 and/or the annexes for the registered uses under REACH.

Ensure that all local regulations regarding handling and storage facilities are followed. |
|-----------------|---|

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
3.0	23.01.2025	800001001080	Print Date 30.01.2025

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Biological occupational exposure limits

No biological limit allocated.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Alcohols, C12-15-branched and linear		
Remarks:	Substance is a hydrocarbon with a complex, unknown or variable composition. Conventional methods of deriving PNECs are not appropriate and it is not possible to identify a single representative PNEC for such substances.	

8.2 Exposure controls

Engineering measures

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.
Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

Eye washes and showers for emergency use.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version 3.0	Revision Date: 23.01.2025	SDS Number: 800001001080	Date of last issue: 21.11.2023 Print Date 30.01.2025
----------------	------------------------------	-----------------------------	---

Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. When prolonged or frequent repeated contact occurs. Nitrile rubber gloves. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Skin and body protection : Skin protection is not ordinarily required beyond standard work clothes.
It is good practice to wear chemical resistant gloves.
Protective clothing approved to EU Standard EN14605.

Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. If air-filtering respirators are suitable for conditions of use: Select a filter suitable for the combination of organic gases and vapours and particles meeting EN14387 and EN143 [Filter type A/P for use against certain organic gases and vapours with a boiling point >65°C (149°F) and for use against particles].

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
3.0	23.01.2025	800001001080	Print Date 30.01.2025

Thermal hazards : Not applicable

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: Liquid.
Colour	: Water white
Odour	: mild
Odour Threshold	: Data not available
Melting point/ range	: Data not available
pour point	22 °C
Boiling point/boiling range	: 260 - 290 °C
Flammability	
Flammability (solid, gas)	: Not applicable
Lower explosion limit and upper explosion limit / flammability limit	
Upper explosion limit / upper flammability limit	: Data not available
Lower explosion limit / Lower flammability limit	: Data not available
Flash point	: 149 °C Method: ASTM D93 (PMCC)
Auto-ignition temperature	: Data not available
Decomposition temperature	
Decomposition temperature	: Data not available
pH	: Data not available
Viscosity	
Viscosity, dynamic	: solid @20°C 50 mPa.s (22 °C) 12 mPa.s (40 °C)

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version 3.0	Revision Date: 23.01.2025	SDS Number: 800001001080	Date of last issue: 21.11.2023 Print Date 30.01.2025
----------------	------------------------------	-----------------------------	---

Viscosity, kinematic	: 14 mm ² /s (40 °C) Method: ASTM D445
Solubility(ies) Water solubility	: ca. 5 mg/l (25 °C)
Partition coefficient: n-octanol/water	: log Pow: 5,9 - 6,66
Vapour pressure	: < 0,01 hPa (25 °C)
Relative density	: 0,834 (25 °C) Method: ASTM D4052
Density	: 0,834 g/cm ³ (25 °C) Method: ASTM D4052 0,822 g/cm ³ (40 °C) Method: ASTM D4052
Relative vapour density	: 7,0
Particle characteristics Particle size	: Data not available

9.2 Other information

Explosive properties	: Not classified
Oxidizing properties	: Data not available
Evaporation rate	: Data not available
Conductivity	: Electrical conductivity: > 10,000 pS/m

A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be a static accumulator.

Surface tension	: Data not available
Molecular weight	: 203 - 210 g/mol

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable at normal ambient temperature and pressure.
May oxidise in the presence of air.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
3.0	23.01.2025	800001001080	Print Date 30.01.2025

10.2 Chemical stability

The product is chemically stable.
Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : None known.

10.4 Conditions to avoid

Conditions to avoid : Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Materials to avoid : Copper.
Copper alloys.
Strong oxidising agents.
Aluminum

10.6 Hazardous decomposition products

None expected under normal use conditions.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

Acute toxicity

Components:

Alcohols, C12-15-branched and linear:

Acute oral toxicity : LD50 (Rat): > 5000 mg/kg
Remarks: Low toxicity

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria are not met.
Low toxicity if inhaled.

Acute dermal toxicity : LD50 (Rabbit): > 5000 mg/kg
Remarks: Low toxicity

Skin corrosion/irritation

Components:

Alcohols, C12-15-branched and linear:

Remarks : Causes mild skin irritation.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version 3.0 Revision Date: 23.01.2025 SDS Number: 800001001080 Date of last issue: 21.11.2023
Print Date 30.01.2025

Serious eye damage/eye irritation

Components:

Alcohols, C12-15-branched and linear:

Remarks : Not irritating to eye.

Respiratory or skin sensitisation

Components:

Alcohols, C12-15-branched and linear:

Remarks : Based on available data, the classification criteria are not met.
Not a sensitiser.

Germ cell mutagenicity

Components:

Alcohols, C12-15-branched and linear:

Genotoxicity in vivo : Remarks: Non mutagenic

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Carcinogenicity

Components:

Alcohols, C12-15-branched and linear:

Remarks : Based on available data, the classification criteria are not met.
Not a carcinogen.

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Material	GHS/CLP Carcinogenicity Classification
Alcohols, C12-15-branched and linear	No carcinogenicity classification.

Reproductive toxicity

Components:

Alcohols, C12-15-branched and linear:

Effects on fertility :
Remarks: Based on available data, the classification criteria are not met., Not a developmental toxicant., Does not impair

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version 3.0	Revision Date: 23.01.2025	SDS Number: 800001001080	Date of last issue: 21.11.2023 Print Date 30.01.2025
----------------	------------------------------	-----------------------------	---

fertility.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

STOT - single exposure

Components:

Alcohols, C12-15-branched and linear:

Remarks : Based on available data, the classification criteria are not met.

STOT - repeated exposure

Components:

Alcohols, C12-15-branched and linear:

Remarks : Based on available data, the classification criteria are not met.

Aspiration toxicity

Components:

Alcohols, C12-15-branched and linear:

Based on available data, the classification criteria are not met., Not an aspiration hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Components:

Alcohols, C12-15-branched and linear:

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
3.0	23.01.2025	800001001080	Print Date 30.01.2025

SECTION 12: Ecological information

12.1 Toxicity

Components:

Alcohols, C12-15-branched and linear:

Toxicity to fish	:	Remarks: Toxic LL/EL/IL50 > 1 <= 10 mg/l
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: Very toxic. LC/EC/IC50 < 1 mg/l
Toxicity to algae/aquatic plants	:	Remarks: Very toxic. LL/EL/IL50 < 1 mg/l
M-Factor (Acute aquatic toxicity)	:	1
Toxicity to microorganisms	:	Remarks: Practically non toxic: LL/EL/IL50 > 100 mg/l
Toxicity to fish (Chronic toxicity)	:	Remarks: Data not available
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	Remarks: NOEC/NOEL <= 0.01 mg/l

12.2 Persistence and degradability

Components:

Alcohols, C12-15-branched and linear:

Biodegradability	:	Remarks: Readily biodegradable. Oxidises rapidly by photo-chemical reactions in air.
------------------	---	---

12.3 Bioaccumulative potential

Components:

Alcohols, C12-15-branched and linear:

Bioaccumulation	:	Remarks: Bioaccumulation is unlikely to occur due to metabolism and excretion.
-----------------	---	--

12.4 Mobility in soil

Components:

Alcohols, C12-15-branched and linear:

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
3.0	23.01.2025	800001001080	Print Date 30.01.2025

Mobility : Remarks: Floats on water., Adsorption to solid soil phase is possible., If the product enters soil, one or more constituents will or may be mobile and may contaminate groundwater.

12.5 Results of PBT and vPvB assessment

Components:

Alcohols, C12-15-branched and linear:

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
Do not dispose into the environment, in drains or in water courses.
Waste product should not be allowed to contaminate soil or water.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local regulations may be more stringent than regional or national requirements and must be complied with.

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
3.0	23.01.2025	800001001080	Print Date 30.01.2025

Contaminated packaging : Drain container thoroughly.
After draining, vent in a safe place away from sparks and fire.
Residues may cause an explosion hazard.
Do not puncture, cut, or weld uncleaned drums.
Send to drum recoverer or metal reclaimer.

SECTION 14: Transport information

14.1 UN number or ID number

ADN	: 3082
ADR	: 3082
RID	: 3082
IMDG	: 3082
IATA	: 3082

14.2 UN proper shipping name

ADN	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (C12-C15 ALCOHOL)
ADR	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (C12-C15 ALCOHOL)
RID	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (C12-C15 ALCOHOL)
IMDG	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (C12-C15 ALCOHOL)
IATA	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (C12-C15 ALCOHOL)

14.3 Transport hazard class(es)

ADN	: 9
ADR	: 9
RID	: 9
IMDG	: 9
IATA	: 9

14.4 Packing group

ADN	
Packing group	: III
Classification Code	: M6
Labels	: 9 (N1, F)
CDNI Inland Water Waste	: NST 8969 Chemicals

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
3.0	23.01.2025	800001001080	Print Date 30.01.2025

Agreement

ADR

Packing group	:	III
Classification Code	:	M6
Hazard Identification Number	:	90
Labels	:	9

RID

Packing group	:	III
Classification Code	:	M6
Hazard Identification Number	:	90
Labels	:	9

IMDG

Packing group	:	III
Labels	:	9

IATA

Packing group	:	III
Labels	:	9

14.5 Environmental hazards

ADN

Environmentally hazardous	:	yes
---------------------------	---	-----

ADR

Environmentally hazardous	:	yes
---------------------------	---	-----

RID

Environmentally hazardous	:	yes
---------------------------	---	-----

IMDG

Marine pollutant	:	yes
------------------	---	-----

14.6 Special precautions for user

Remarks	:	Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.
---------	---	--

14.7 Maritime transport in bulk according to IMO instruments

Pollution category	:	Y
Ship type	:	2
Product name	:	NEODOL 25 (contains Alcohols (C14 – C18), primary, linear and essentially linear; Alcohols (C13 +))

Additional Information

: This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry. Transport in bulk according to Annex II of Marpol and the IBC Code

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
3.0	23.01.2025	800001001080	Print Date 30.01.2025

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV)	:	Product is not subject to Authorisation under REACH.
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Volatile organic compounds : Volatile organic compounds (VOC) content: 98,66 %

Other regulations:

The following regulatory information is not intended to be comprehensive and does not exempt the end user of the product to refer to all official documents to determine its obligations.

Labour code : Exposure forbidden to certain works/products to:

- Young people at least 15 years old and under 18 years old: art. D4153-17

- Pregnant or breast-feeding women : art. D4152-10, D4152-11

According type of product and quantity stored, check for applicability of Code of environment: art. R511-9 - Nomenclature of classified facilities.

Social security code - Article L.461-6, Appendix A, no. 601-15.

Labour code - Intensified medical supervision: Articles R.4624-18 and R.4624-19, decree 2012-135 of 30.01.2012.

The product is subject to the DDADUE (Provisions for Adaptation of Legislation to European Union Law in the Field of Sustainable Development) from 16 July 2013 of Articles 10 and 11, the transposition of the Seveso III directive (2012/18/EU).

According type of product and quantity stored, check for applicability of Code of environment: art. R511-9 - Nomenclature of classified facilities.

The components of this product are reported in the following inventories:

DSL : Listed

IECSC : Listed

KECI : Listed

NZIoC : Listed

PICCS : Listed

TSCA : Listed

TCSI : Listed

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
3.0	23.01.2025	800001001080	Print Date 30.01.2025

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

- | | | |
|-------------------|---|--|
| Training advice | : | Provide adequate information, instruction and training for operators. |
| Other information | : | For Industry guidance and tools on REACH please visit the CEFIC website at http://cefic.org/Industry-support .
The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB. |

A vertical bar (|) in the left margin indicates an amendment

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version 3.0	Revision Date: 23.01.2025	SDS Number: 800001001080	Date of last issue: 21.11.2023 Print Date 30.01.2025
----------------	------------------------------	-----------------------------	---

from the previous version.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

Classification of the mixture:

Aquatic Acute 1 H400

Aquatic Chronic 1 H410

Classification procedure:

Expert judgement and weight of evidence determination.

Expert judgement and weight of evidence determination.

Identified Uses according to the Use Descriptor System

Uses - Worker

Title : Manufacture of substance
- Industrial

Uses - Worker

Title : Use as an intermediate
- Industrial

Uses - Worker

Title : Formulation & (re)packing of substances and mixtures
- Industrial

Uses - Worker

Title : Uses in Coatings
- Industrial

Uses - Worker

Title : Uses in Coatings
- Professional

Uses - Worker

Title : Use in Cleaning Agents
- Industrial

Uses - Worker

Title : Use in Cleaning Agents
- Professional

Uses - Worker

Title : Metal working fluids / rolling oils
- Industrial

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
3.0	23.01.2025	800001001080	Print Date 30.01.2025

Uses - Worker

Title : Metal working fluids / rolling oils
- Professional

Identified Uses according to the Use Descriptor System

Uses - Consumer

Title : Uses in Coatings
- Consumer

Uses - Consumer

Title : Use in Cleaning Agents
- Consumer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

FR / EN

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version
3.0

Revision Date:
23.01.2025

SDS Number:
800001001080

Date of last issue: 21.11.2023
Print Date 30.01.2025

Exposure Scenario - Worker

300000000613	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Manufacture of substance- Industrial
Use Descriptor	Sector of Use: SU3, SU8, SU9 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 15 Environmental Release Categories: ERC1
Scope of process	Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/ recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for human health.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Contributing Scenarios	Risk Management Measures	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB.		
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used in region:		
Regional use tonnage (tonnes/year):		
Fraction of Regional tonnage used locally:		
Annual site tonnage (tonnes/year):		26,600
Maximum daily site tonnage (kg/day):		8,87E+04
Frequency and Duration of Use		
Continuous release.		
Emission Days (days/year):		300
Environmental factors not influenced by risk management		
Local freshwater dilution factor:		10
Local marine water dilution factor:		100
Other Operational Conditions affecting Environmental Exposure		
Release fraction to air from process (initial release prior to RMM):		
Release fraction to wastewater from process (initial release prior to RMM):		
Release fraction to soil from process (initial release prior to RMM):		
Technical conditions and measures at process level (source) to prevent release		
Common practices vary across sites thus conservative process release estimates used.		
Technical onsite conditions and measures to reduce or limit discharges, air emis-		

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version
3.0

Revision Date:
23.01.2025

SDS Number:
800001001080

Date of last issue: 21.11.2023
Print Date 30.01.2025

sions and releases to soil	
Risk from environmental exposure is driven by soil.	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%)	99
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%)	99
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	99
Assumed domestic sewage treatment plant flow (m ³ /d)	10.000
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	
Conditions and Measures related to external treatment of waste for disposal	
During manufacturing no waste of the substance is generated.	
Conditions and measures related to external recovery of waste	
During manufacturing no waste of the substance is generated.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
No exposure assessment presented for human health.	

Section 3.2 -Environment
Used EUSES model.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
No exposure assessment presented for human health.	

Section 4.2 -Environment
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version
3.0

Revision Date:
23.01.2025

SDS Number:
800001001080

Date of last issue: 21.11.2023
Print Date 30.01.2025

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version
3.0

Revision Date:
23.01.2025

SDS Number:
800001001080

Date of last issue: 21.11.2023
Print Date 30.01.2025

Exposure Scenario - Worker

300000000614	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use as an intermediate- Industrial
Use Descriptor	Sector of Use: SU3, SU8, SU9 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 15 Environmental Release Categories: ERC6a
Scope of process	Use of substance as an intermediate (not related to Strictly Controlled Conditions). Includes recycling/ recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for human health.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Contributing Scenarios	Risk Management Measures	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB.		
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used in region:		
Regional use tonnage (tonnes/year):		
Fraction of Regional tonnage used locally:		
Annual site tonnage (tonnes/year):		1,870
Maximum daily site tonnage (kg/day):		6,233
Frequency and Duration of Use		
Continuous release.		
Emission Days (days/year):		300
Environmental factors not influenced by risk management		
Local freshwater dilution factor:		10
Local marine water dilution factor:		100
Other Operational Conditions affecting Environmental Exposure		
Release fraction to air from process (initial release prior to RMM):		3,85E-05
Release fraction to wastewater from process (initial release prior to RMM):		0,007
Release fraction to soil from process (initial release prior to RMM):		
Technical conditions and measures at process level (source) to prevent release		
Common practices vary across sites thus conservative process release estimates used.		
Technical onsite conditions and measures to reduce or limit discharges, air emis-		

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version
3.0

Revision Date:
23.01.2025

SDS Number:
800001001080

Date of last issue: 21.11.2023
Print Date 30.01.2025

sions and releases to soil	
Risk from environmental exposure is driven by marine water.	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%)	99
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%)	99
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	99
Assumed domestic sewage treatment plant flow (m ³ /d)	10.000
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	
Conditions and Measures related to external treatment of waste for disposal	
External treatment and disposal of waste should comply with applicable local and/or regional regulations. This substance is consumed during use and no waste of substance is generated.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable local and/or regional regulations. This substance is consumed during use and no waste of substance is generated.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
No exposure assessment presented for human health.	

Section 3.2 -Environment
Used EUSES model.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
No exposure assessment presented for human health.	

Section 4.2 -Environment
Guidance is based on assumed operating conditions which may not be applicable to all

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version
3.0

Revision Date:
23.01.2025

SDS Number:
800001001080

Date of last issue: 21.11.2023
Print Date 30.01.2025

sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.
If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version
3.0

Revision Date:
23.01.2025

SDS Number:
800001001080

Date of last issue: 21.11.2023
Print Date 30.01.2025

Exposure Scenario - Worker

300000000615	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Formulation & (re)packing of substances and mixtures- Industrial
Use Descriptor	Sector of Use: SU3, SU10 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 8a, PROC 8b, PROC 9, PROC 14, PROC 15 Environmental Release Categories: ERC2
Scope of process	Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for human health.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Contributing Scenarios	Risk Management Measures	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB.		
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used in region:		
Regional use tonnage (tonnes/year):		
Fraction of Regional tonnage used locally:		
Annual site tonnage (tonnes/year):		200
Maximum daily site tonnage (kg/day):		666,7
Frequency and Duration of Use		
Continuous release.		
Emission Days (days/year):		300
Environmental factors not influenced by risk management		
Local freshwater dilution factor:		10
Local marine water dilution factor:		100
Other Operational Conditions affecting Environmental Exposure		
Release fraction to air from process (initial release prior to RMM):		3,60E-04
Release fraction to wastewater from process (initial release prior to RMM):		2,00E-05
Release fraction to soil from process (initial release prior to RMM):		
Technical conditions and measures at process level (source) to prevent release		
Common practices vary across sites thus conservative process release estimates used.		

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version 3.0 Revision Date: 23.01.2025 SDS Number: 800001001080 Date of last issue: 21.11.2023
Print Date 30.01.2025

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Risk from environmental exposure is driven by marine water.	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	99
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
Organisational measures to prevent/limit release from site	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%)	99
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	99
Assumed domestic sewage treatment plant flow (m3/d)	10.000
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	
Conditions and Measures related to external treatment of waste for disposal	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
No exposure assessment presented for human health.	

Section 3.2 -Environment
Used EUSES model.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
No exposure assessment presented for human health.	

Section 4.2 -Environment
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version
3.0

Revision Date:
23.01.2025

SDS Number:
800001001080

Date of last issue: 21.11.2023
Print Date 30.01.2025

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version
3.0

Revision Date:
23.01.2025

SDS Number:
800001001080

Date of last issue: 21.11.2023
Print Date 30.01.2025

Exposure Scenario - Worker

300000000616	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Uses in Coatings- Industrial
Use Descriptor	Sector of Use: SU3 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 7, PROC 8a, PROC 8b, PROC 10, PROC 13, PROC 15 Environmental Release Categories: ERC4
Scope of process	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for human health.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Contributing Scenarios	Risk Management Measures	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB.		
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used in region:		7,500
Regional use tonnage (tonnes/year):		
Fraction of Regional tonnage used locally:		
Annual site tonnage (tonnes/year):		0,029
Maximum daily site tonnage (kg/day):		0,1
Frequency and Duration of Use		
Continuous release.		
Emission Days (days/year):		300
Environmental factors not influenced by risk management		
Local freshwater dilution factor:		10
Local marine water dilution factor:		100
Other Operational Conditions affecting Environmental Exposure		
Release fraction to air from process (initial release prior to RMM):		0,03
Release fraction to wastewater from process (initial release prior to RMM):		0,03
Release fraction to soil from process (initial release prior to RMM):		
Technical conditions and measures at process level (source) to prevent release		
Common practices vary across sites thus conservative process re-		

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version
3.0

Revision Date:
23.01.2025

SDS Number:
800001001080

Date of last issue: 21.11.2023
Print Date 30.01.2025

lease estimates used.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Risk from environmental exposure is driven by marine water.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%)	99
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
Organisational measures to prevent/limit release from site	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%)	99
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	99
Assumed domestic sewage treatment plant flow (m3/d)	2.000
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	
Conditions and Measures related to external treatment of waste for disposal	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
No exposure assessment presented for human health.	

Section 3.2 -Environment
Used EUSES model.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
No exposure assessment presented for human health.	

Section 4.2 -Environment
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Required removal efficiency for wastewater can be achieved using onsite/offsite technolo-

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version
3.0

Revision Date:
23.01.2025

SDS Number:
800001001080

Date of last issue: 21.11.2023
Print Date 30.01.2025

gies, either alone or in combination.
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.
If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version
3.0

Revision Date:
23.01.2025

SDS Number:
800001001080

Date of last issue: 21.11.2023
Print Date 30.01.2025

Exposure Scenario - Worker

300000000617	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Uses in Coatings- Professional
Use Descriptor	Sector of Use: SU22 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 8a, PROC 8b, PROC 10, PROC 11, PROC 13, PROC 15, PROC 19 Environmental Release Categories: ERC8a, ERC8d
Scope of process	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, brush, spreader by hand or similar methods, and film formation), and equipment cleaning, maintenance and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for human health.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Contributing Scenarios	Risk Management Measures	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB.		
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used in region:		
Regional use tonnage (tonnes/year):		
Fraction of Regional tonnage used locally:		
Annual site tonnage (tonnes/year):		0,87
Maximum daily site tonnage (kg/day):		2,9
Frequency and Duration of Use		
Continuous release.		
Emission Days (days/year):		300
Environmental factors not influenced by risk management		
Local freshwater dilution factor:		10
Local marine water dilution factor:		100
Other Operational Conditions affecting Environmental Exposure		
Release fraction to air from process (initial release prior to RMM):		0,01
Release fraction to wastewater from process (initial release prior to RMM):		0,01
Release fraction to soil from process (initial release prior to RMM):		
Technical conditions and measures at process level (source) to prevent release		
Common practices vary across sites thus conservative process re-		

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version 3.0 Revision Date: 23.01.2025 SDS Number: 800001001080 Date of last issue: 21.11.2023
Print Date 30.01.2025

lease estimates used.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Risk from environmental exposure is driven by marine water.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%)	99
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
Organisational measures to prevent/limit release from site	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%)	99
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	99
Assumed domestic sewage treatment plant flow (m ³ /d)	2.000
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	
Conditions and Measures related to external treatment of waste for disposal	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
No exposure assessment presented for human health.	

Section 3.2 -Environment	
Used EUSES model.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
No exposure assessment presented for human health.	

Section 4.2 -Environment	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technolo-	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version
3.0

Revision Date:
23.01.2025

SDS Number:
800001001080

Date of last issue: 21.11.2023
Print Date 30.01.2025

gies, either alone or in combination.
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.
If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version
3.0

Revision Date:
23.01.2025

SDS Number:
800001001080

Date of last issue: 21.11.2023
Print Date 30.01.2025

Exposure Scenario - Worker

300000000618	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in Cleaning Agents- Industrial
Use Descriptor	Sector of Use: SU3 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 7, PROC 8a, PROC 8b, PROC 10, PROC 13 Environmental Release Categories: ERC4
Scope of process	Covers the use as a component of cleaning products including transfer from storage, pouring/unloading from drums or containers. Exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, automated and by hand), related equipment cleaning and maintenance.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for human health.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Contributing Scenarios	Risk Management Measures	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB.		
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used in region:		
Regional use tonnage (tonnes/year):		
Fraction of Regional tonnage used locally:		
Annual site tonnage (tonnes/year):		0,96
Maximum daily site tonnage (kg/day):		4,36
Frequency and Duration of Use		
Continuous release.		
Emission Days (days/year):		220
Environmental factors not influenced by risk management		
Local freshwater dilution factor:		10
Local marine water dilution factor:		100
Other Operational Conditions affecting Environmental Exposure		
Release fraction to air from process (initial release prior to RMM):		0
Release fraction to wastewater from process (initial release prior to RMM):		1
Release fraction to soil from process (initial release prior to RMM):		
Technical conditions and measures at process level (source) to prevent release		
Common practices vary across sites thus conservative process release estimates used.		

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version 3.0 Revision Date: 23.01.2025 SDS Number: 800001001080 Date of last issue: 21.11.2023
Print Date 30.01.2025

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Risk from environmental exposure is driven by marine water.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%)	99
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
Organisational measures to prevent/limit release from site	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%)	99
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	99
Assumed domestic sewage treatment plant flow (m ³ /d)	2.000
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	
Conditions and Measures related to external treatment of waste for disposal	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
No exposure assessment presented for human health.	

Section 3.2 -Environment	
Used EUSES model.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
No exposure assessment presented for human health.	

Section 4.2 -Environment	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version
3.0

Revision Date:
23.01.2025

SDS Number:
800001001080

Date of last issue: 21.11.2023
Print Date 30.01.2025

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version
3.0

Revision Date:
23.01.2025

SDS Number:
800001001080

Date of last issue: 21.11.2023
Print Date 30.01.2025

Exposure Scenario - Worker

300000000619	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in Cleaning Agents- Professional
Use Descriptor	Sector of Use: SU22 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 10, PROC 11, PROC 13 Environmental Release Categories: ERC8a, ERC8d
Scope of process	Covers the use as a component of cleaning products including pouring/unloading from drums or containers; and exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping automated and by hand).

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for human health.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Contributing Scenarios	Risk Management Measures	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB.		
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used in region:		
Regional use tonnage (tonnes/year):		
Fraction of Regional tonnage used locally:		
Annual site tonnage (tonnes/year):		0,52
Maximum daily site tonnage (kg/day):		1,42
Frequency and Duration of Use		
Continuous release.		
Emission Days (days/year):		365
Environmental factors not influenced by risk management		
Local freshwater dilution factor:		10
Local marine water dilution factor:		100
Other Operational Conditions affecting Environmental Exposure		
Release fraction to air from process (initial release prior to RMM):		0
Release fraction to wastewater from process (initial release prior to RMM):		1
Release fraction to soil from process (initial release prior to RMM):		
Technical conditions and measures at process level (source) to prevent release		
Common practices vary across sites thus conservative process release estimates used.		
Technical onsite conditions and measures to reduce or limit discharges, air emis-		

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version
3.0

Revision Date:
23.01.2025

SDS Number:
800001001080

Date of last issue: 21.11.2023
Print Date 30.01.2025

sions and releases to soil	
Risk from environmental exposure is driven by freshwater.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%)	99
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
Organisational measures to prevent/limit release from site	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%)	99
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	99
Assumed domestic sewage treatment plant flow (m3/d)	2.000
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	
Conditions and Measures related to external treatment of waste for disposal	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
No exposure assessment presented for human health.	

Section 3.2 -Environment	
Used EUSES model.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
No exposure assessment presented for human health.	

Section 4.2 -Environment	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.	
Required removal efficiency for air can be achieved using on-site technologies, either alone	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version
3.0

Revision Date:
23.01.2025

SDS Number:
800001001080

Date of last issue: 21.11.2023
Print Date 30.01.2025

or in combination.
If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version
3.0

Revision Date:
23.01.2025

SDS Number:
800001001080

Date of last issue: 21.11.2023
Print Date 30.01.2025

Exposure Scenario - Worker

300000000620	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Metal working fluids / rolling oils- Industrial
Use Descriptor	Sector of Use: SU3 Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 5, PROC 7, PROC 8a, PROC 8b, PROC 9, PROC 10, PROC 13, PROC 17 Environmental Release Categories: ERC4
Scope of process	Covers the use in formulated MWFs/rolling oils including transfer operations, rolling and annealing activities, cutting/machining activities, automated and manual application of corrosion protections (including brushing, dipping and spraying), equipment maintenance, draining and disposal of waste oils.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for human health.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Contributing Scenarios	Risk Management Measures	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB.		
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used in region:		
Regional use tonnage (tonnes/year):		
Fraction of Regional tonnage used locally:		
Annual site tonnage (tonnes/year):		7,5
Maximum daily site tonnage (kg/day):		25
Frequency and Duration of Use		
Continuous release.		
Emission Days (days/year):		300
Environmental factors not influenced by risk management		
Local freshwater dilution factor:		10
Local marine water dilution factor:		100
Other Operational Conditions affecting Environmental Exposure		
Release fraction to air from process (initial release prior to RMM):		9,60E-03
Release fraction to wastewater from process (initial release prior to RMM):		2,10E-07
Release fraction to soil from process (initial release prior to RMM):		
Technical conditions and measures at process level (source) to prevent release		
Common practices vary across sites thus conservative process re-		

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version 3.0 Revision Date: 23.01.2025 SDS Number: 800001001080 Date of last issue: 21.11.2023
Print Date 30.01.2025

lease estimates used.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Risk from environmental exposure is driven by marine water.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%)	99
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
Organisational measures to prevent/limit release from site	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%)	99
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	99
Assumed domestic sewage treatment plant flow (m ³ /d)	2.000
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	
Conditions and Measures related to external treatment of waste for disposal	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
No exposure assessment presented for human health.	

Section 3.2 -Environment	
Used EUSES model.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
No exposure assessment presented for human health.	

Section 4.2 -Environment	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technolo-	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version
3.0

Revision Date:
23.01.2025

SDS Number:
800001001080

Date of last issue: 21.11.2023
Print Date 30.01.2025

gies, either alone or in combination.
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.
If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version
3.0

Revision Date:
23.01.2025

SDS Number:
800001001080

Date of last issue: 21.11.2023
Print Date 30.01.2025

Exposure Scenario - Worker

300000000621	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Metal working fluids / rolling oils- Professional
Use Descriptor	Sector of Use: SU22 Process Categories: PROC 1, PROC 2, PROC 3, PROC 5, PROC 8a, PROC 8b, PROC 9, PROC 10, PROC 11, PROC 13, PROC 17 Environmental Release Categories: ERC8a, ERC8d
Scope of process	Covers the use in formulated MWFs including transfer operations, open and contained cutting/machining activities, automated and manual application of corrosion protections, draining and working on contaminated/ reject articles, and disposal of waste oils.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for human health.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Contributing Scenarios	Risk Management Measures	
Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB.		
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used in region:		
Regional use tonnage (tonnes/year):		
Fraction of Regional tonnage used locally:		
Annual site tonnage (tonnes/year):		7,5
Maximum daily site tonnage (kg/day):		25
Frequency and Duration of Use		
Continuous release.		
Emission Days (days/year):		365
Environmental factors not influenced by risk management		
Local freshwater dilution factor:		10
Local marine water dilution factor:		100
Other Operational Conditions affecting Environmental Exposure		
Release fraction to air from process (initial release prior to RMM):		9,60E-03
Release fraction to wastewater from process (initial release prior to RMM):		2,10E-07
Release fraction to soil from process (initial release prior to RMM):		
Technical conditions and measures at process level (source) to prevent release		
Common practices vary across sites thus conservative process release estimates used.		

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version 3.0 Revision Date: 23.01.2025 SDS Number: 800001001080 Date of last issue: 21.11.2023
Print Date 30.01.2025

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Risk from environmental exposure is driven by marine water.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%)	99
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
Organisational measures to prevent/limit release from site	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%)	99
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	99
Assumed domestic sewage treatment plant flow (m ³ /d)	2.000
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	
Conditions and Measures related to external treatment of waste for disposal	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
No exposure assessment presented for human health.	

Section 3.2 -Environment	
Used EUSES model.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
No exposure assessment presented for human health.	

Section 4.2 -Environment	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version
3.0

Revision Date:
23.01.2025

SDS Number:
800001001080

Date of last issue: 21.11.2023
Print Date 30.01.2025

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version
3.0

Revision Date:
23.01.2025

SDS Number:
800001001080

Date of last issue: 21.11.2023
Print Date 30.01.2025

Exposure Scenario - Consumer

300000001083	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Uses in Coatings - Consumer
Use Descriptor	Sector of Use: SU21 Product Categories: PC1, PC4, PC8 (excipient only), PC9a, PC9b, PC9c, PC15, PC18, PC23, PC24, PC31, PC34 Environmental Release Categories: ERC8a, ERC8d
Scope of process	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including product transfer and preparation, application by brush, spray by hand or similar methods) and equipment cleaning.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for human health.
Section 2.1	Control of Consumer Exposure
Product Characteristics	
Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES

Section 2.2	Control of Environmental Exposure	
Substance is complex UVCB.		
Alcohol.		
Readily biodegradable.		
Amounts Used		
Fraction of EU tonnage used in region:		
Regional use tonnage (tonnes/year):		
Fraction of Regional tonnage used locally:		
Annual site tonnage (tonnes/year):		0,87
Maximum daily site tonnage (kg/day):		2,9
Frequency and Duration of Use		
Continuous release.		
Emission Days (days/year):		300
Environmental factors not influenced by risk management		
Local freshwater dilution factor:		10
Local marine water dilution factor:		100
Other Operational Conditions affecting Environmental Exposure		
Release fraction to air from process (initial release prior to RMM):		0,01
Release fraction to wastewater from process (initial release prior to RMM):		0,01
Release fraction to soil from process (initial release prior to RMM):		
Conditions and Measures related to municipal sewage treatment plant		
Risk from environmental exposure is driven by marine water.		
Estimated substance removal from wastewater via domestic sewage		99

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version 3.0 Revision Date: 23.01.2025 SDS Number: 800001001080 Date of last issue: 21.11.2023
Print Date 30.01.2025

treatment (%)	
Assumed domestic sewage treatment plant flow (m3/d)	2.000
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	
Conditions and Measures related to external treatment of waste for disposal	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
No exposure assessment presented for human health.	

Section 3.2 -Environment	
Used EUSES model.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
No exposure assessment presented for human health.	

Section 4.2 -Environment	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version
3.0

Revision Date:
23.01.2025

SDS Number:
800001001080

Date of last issue: 21.11.2023
Print Date 30.01.2025

Exposure Scenario - Consumer

300000001084	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in Cleaning Agents - Consumer
Use Descriptor	Sector of Use: SU21 Product Categories: PC3, PC4, PC8 (excipient only), PC9a, PC24, PC35, Environmental Release Categories: ERC8a, ERC8d
Scope of process	Covers general exposures to consumers arising from the use of household products sold as washing and cleaning products, aerosols, coatings, de-icers, lubricants and air care products.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for human health.
Section 2.1	Control of Consumer Exposure
Product Characteristics	
Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES

Section 2.2	Control of Environmental Exposure
Substance is complex UVCB.	
Alcohol.	
Readily biodegradable.	
Amounts Used	
Fraction of EU tonnage used in region:	
Regional use tonnage (tonnes/year):	
Fraction of Regional tonnage used locally:	
Annual site tonnage (tonnes/year):	
Maximum daily site tonnage (kg/day):	
Frequency and Duration of Use	
Continuous release.	
Emission Days (days/year):	
Environmental factors not influenced by risk management	
Local freshwater dilution factor:	
Local marine water dilution factor:	
Other Operational Conditions affecting Environmental Exposure	
Release fraction to air from process (initial release prior to RMM):	
Release fraction to wastewater from process (initial release prior to RMM):	
Release fraction to soil from process (initial release prior to RMM):	
Conditions and Measures related to municipal sewage treatment plant	
Risk from environmental exposure is driven by freshwater.	
Estimated substance removal from wastewater via domestic sewage	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

NEODOL 25

Version 3.0 Revision Date: 23.01.2025 SDS Number: 800001001080 Date of last issue: 21.11.2023
Print Date 30.01.2025

treatment (%)	
Assumed domestic sewage treatment plant flow (m3/d)	2.000
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	
Conditions and Measures related to external treatment of waste for disposal	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
No exposure assessment presented for human health.	

Section 3.2 -Environment	
Used EUSES model.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
No exposure assessment presented for human health.	

Section 4.2 -Environment	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	