

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version	Revision Date:	SDS Number:	Date of last issue: 27.05.2024
2.0	23.01.2025	800010063771	Print Date 30.01.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	:	IP Extraction Feed Sustainable
Product code	:	Y2156
Registration number EU	:	01-2119480190-46
CAS-No.	:	68476-55-1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture	:	Please refer to section 16 and/or the annexes for the registered uses under REACH. Chemical intermediate., Raw material for use in the chemical industry., For use as a component in fuel.
Uses advised against	:	Restricted to professional users., This product must not be used in applications other than the above without first seeking the advice of the supplier. This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier	:	Shell Chemicals Europe B.V. PO Box 2334 3000 CH Rotterdam Netherlands
Telephone	:	+31 (0)10 441 5137 / +31 (0)10 441 5191
Telefax	:	+31 (0)20 716 8316 / +31 (0)20 713 9230
Contact for Safety Data Sheet	:	sccmsds@shell.com

1.4 Emergency telephone number

+44 (0) 1235 239 670
National Poison Information Centre (NVIC): Tel. nr. +31(0)88 755 8000 (24 hrs a day and 7 days a week).
Only for the purpose of informing medical personnel.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 1	H224: Extremely flammable liquid and vapour.
-------------------------------	--

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0	Revision Date: 23.01.2025	SDS Number: 800010063771	Date of last issue: 27.05.2024 Print Date 30.01.2025
----------------	------------------------------	-----------------------------	---

Acute toxicity, Category 4, Oral	H302: Harmful if swallowed.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Acute toxicity, Category 4, Dermal	H312: Harmful in contact with skin.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3	H335: May cause respiratory irritation. H336: May cause drowsiness or dizziness.
Germ cell mutagenicity, Category 2	H341: Suspected of causing genetic defects.
Carcinogenicity, Category 1B	H350: May cause cancer.
Reproductive toxicity, Category 2	H361: Suspected of damaging fertility or the unborn child.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

H224	Extremely flammable liquid and vapour.
HEALTH HAZARDS:	
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H361	Suspected of damaging fertility or the unborn child.
ENVIRONMENTAL HAZARDS:	
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version
2.0

Revision Date:
23.01.2025

SDS Number:
800010063771

Date of last issue: 27.05.2024
Print Date 30.01.2025

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243 Take action to prevent static discharges.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P302 + P352 IF ON SKIN: Wash with plenty of water and soap.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P331 Do NOT induce vomiting.

Storage:

No precautionary phrases.

Disposal:

No precautionary phrases.

2.3 Other hazards

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

This material is a static accumulator.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

The vapour is heavier than air, spreads along the ground and distant ignition is possible.

Will float and can be reignited on surface water.

SECTION 3: Composition/information on ingredients

3.1 Substances

Components

Chemical name	CAS-No. EC-No.	Concentration (% w/w)
Hydrocarbons, C5-rich	68476-55-1 270-695-5	<= 100

Further information

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version
2.0

Revision Date:
23.01.2025

SDS Number:
800010063771

Date of last issue: 27.05.2024
Print Date 30.01.2025

Contains:

Chemical name	Identification number	Classification	Concentration (% w/w)
Isoprene	78-79-5, 201-143-3	Flam. Liq.1; H224 Muta.2; H341 Carc.1B; H350 Aquatic Chronic2; H411	10 - 30
cyclopentadiene	542-92-7, 208-835-4	Flam. Liq.3; H226 Acute Tox.3; H301 Acute Tox.3; H311 Skin Irrit.2; H315 Eye Irrit.2; H319 STOT SE3; H335	5 - 12
pentane	109-66-0, 203-692-4	Flam. Liq.1; H224 Asp. Tox.1; H304 STOT SE3; H336 Aquatic Chronic2; H411 EUH066	15 - 20
penta-1,3-diene	504-60-9, 207-995-2	Flam. Liq.2; H225	10 - 20
isopentane	78-78-4, 201-142-8	Flam. Liq.1; H224 Asp. Tox.1; H304 STOT SE3; H336 Aquatic Chronic2; H411	10 - 15
Dicyclopentadiene	77-73-6, 201-052-9	Flam. Liq.2; H225 Acute Tox.4; H302 Asp. Tox.1; H304 Acute Tox.2; H330 Skin Irrit.2; H315 Eye Irrit.2; H319 STOT SE3; H335 Repr.2; H361 STOT RE2; H373 Aquatic Acute1; H400 Aquatic Chronic2; H411	2 - 5
Benzene	71-43-2, 200-753-7	Flam. Liq.2; H225 Asp. Tox.1; H304 Skin Irrit.2; H315 Eye Irrit.2; H319 Muta.1B; H340 Carc.1A; H350 STOT RE1; H372 Aquatic Chronic3; H412	>= 0 - < 0,1
1,3-butadiene	106-99-0, 203-450-8	Flam. Gas1A; H220 Press. GasLiquefied gas; H280	>= 0 - < 0,1

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0 Revision Date: 23.01.2025 SDS Number: 800010063771 Date of last issue: 27.05.2024
Print Date 30.01.2025

		Muta.1B; H340 Carc.1A; H350	
TBP (tert-butylphenol) - inhibitor	27178-34-3, 248-300-2	Acute Tox.4; H302 Acute Tox.4; H312 Acute Tox.4; H332 Skin Corr.1B; H314 Aquatic Chronic2; H411	<= 0,015

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Not expected to be a health hazard when used under normal conditions.
- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- If inhaled : Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.
- In case of skin contact : Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.
- In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Transport to the nearest medical facility for additional treatment.
- If swallowed : Call emergency number for your location / facility. If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing. Rinse mouth.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing,

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0	Revision Date: 23.01.2025	SDS Number: 800010063771	Date of last issue: 27.05.2024 Print Date 30.01.2025
----------------	------------------------------	-----------------------------	---

and/or difficulty breathing.

Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death.

Skin irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blisters.

Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.

Ingestion may result in nausea, vomiting and/or diarrhoea. If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.

If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

Damage to blood-forming organs may be evidenced by: a) fatigue and anaemia (RBC), b) decreased resistance to infection, and/or excessive bruising and bleeding (platelet effect). Heart damage may be evidenced by shortness of breath and, in severe cases, by collapse (cardiac arrest).

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	: IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT! Call a doctor or poison control center for guidance. Potential for chemical pneumonitis. Treat symptomatically. Artificial respiration and/or oxygen may be necessary.
-----------	--

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	: Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	: Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting	: Carbon monoxide may be evolved if incomplete combustion occurs. Will float and can be reignited on surface water. The vapour is heavier than air, spreads along the ground and
---------------------------------------	--

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0	Revision Date: 23.01.2025	SDS Number: 800010063771	Date of last issue: 27.05.2024 Print Date 30.01.2025
----------------	------------------------------	-----------------------------	---

distant ignition is possible.
Flammable vapours may be present even at temperatures below the flash point.

5.3 Advice for firefighters

- Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).
- Specific extinguishing methods : Standard procedure for chemical fires.
- Further information : Clear fire area of all non-emergency personnel. Keep adjacent containers cool by spraying with water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions :
Observe all relevant local and international regulations.
Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.
Local authorities should be advised if significant spillages cannot be contained.
6.1.1 For non emergency personnel:
Avoid contact with skin, eyes and clothing.
Isolate hazard area and deny entry to unnecessary or unprotected personnel.
Do not breathe fumes, vapour.
Do not operate electrical equipment.
6.1.2 For emergency responders:
Avoid contact with skin, eyes and clothing.
Isolate hazard area and deny entry to unnecessary or unprotected personnel.
Do not breathe fumes, vapour.
Do not operate electrical equipment.

6.2 Environmental precautions

- Environmental precautions : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bond-

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version	Revision Date:	SDS Number:	Date of last issue: 27.05.2024
2.0	23.01.2025	800010063771	Print Date 30.01.2025

ing and grounding (earthing) all equipment.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., Risk of explosion. Inform the emergency services if liquid enters surface water drains., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet., Vapour may form an explosive mixture with air.

Local authorities should be advised if significant spillages cannot be contained.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

Ensure that all local regulations regarding handling and storage facilities are followed.

Advice on safe handling : Avoid inhaling vapour and/or mists.

Avoid contact with skin, eyes and clothing.

Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.

The vapour is heavier than air. Beware of accumulation in pits and confined spaces.

Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.

Bulk storage tanks should be diked (bunded).

Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic dis-

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0	Revision Date: 23.01.2025	SDS Number: 800010063771	Date of last issue: 27.05.2024 Print Date 30.01.2025
----------------	------------------------------	-----------------------------	---

charge and ignition of flammable air-vapour mixtures can occur.

Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges.

These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements.

These activities may lead to static discharge e.g. spark formation.

Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/s until fill pipe submerged to twice its diameter, then ≤ 7 m/s). Avoid splash filling.

Do NOT use compressed air for filling, discharging, or handling operations.

Inhibitor levels should be maintained.

Protect against light.

- | | |
|------------------|--|
| Product Transfer | : If positive displacement pumps are used, these must be fitted with a non-integral pressure relief valve. Refer to guidance under Handling section. |
| Hygiene measures | : Wash hands before eating, drinking, smoking and using the toilet. Launder contaminated clothing before re-use. |

7.2 Conditions for safe storage, including any incompatibilities

- | | |
|--|---|
| Further information on storage stability | : <ul style="list-style-type: none">Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products which are not harmful or toxic to man or to the environment.Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat.Must be kept inhibited during storage and shipment as material can polymerise.Vapours from tanks should not be released to atmosphere.Breathing losses during storage should be controlled by a suitable vapour treatment system.Nitrogen blanket recommended.Electrostatic charges will be generated during pumping.Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.Reacts with atmospheric oxygen. Material contains a stabilizer to inhibit oxidative colour change.Prolonged storage of the product can cause the stabiliser to lose its effectiveness.The product is normally supplied in a stabilized form. If the permissible storage period and/or storage temperature is noticeably exceeded, the product may polymerise with heat evolution. |
|--|---|

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0 Revision Date: 23.01.2025 SDS Number: 800010063771 Date of last issue: 27.05.2024
Print Date 30.01.2025

Packaging material : lution.
: Suitable material: For containers, or container linings use mild steel, stainless steel.
Unsuitable material: Copper., Copper alloys.

7.3 Specific end use(s)

Specific use(s) : Please refer to section 16 and/or the annexes for the registered uses under REACH.

See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).
IEC/TS 60079-32-1: Electrostatic hazards, guidance

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Isoprene	78-79-5	TWA	3 ppm 8,4 mg/m ³	Shell Internal Standard (SIS) for 8 hour TWA.
pentane	109-66-0	TLV-8hr	600 ppm 1.800 mg/m ³	NL WG
pentane		TWA	1.000 ppm 3.000 mg/m ³	2006/15/EC
Further information: Indicative				
isopentane	78-78-4	TLV-8hr	600 ppm 1.800 mg/m ³	NL WG
isopentane		TWA	1.000 ppm 3.000 mg/m ³	2006/15/EC
Further information: Indicative				
Benzene	71-43-2	TLV-8hr	0,2 ppm 0,7 mg/m ³	NL WG
Further information: Carcinogenic substances, based on the threshold limit effect, Skin notation				
Benzene		TWA	0,25 ppm 0,8 mg/m ³	Shell Internal Standard (SIS) for 8-12 hour TWA.
Benzene		STEL	2,5 ppm 8 mg/m ³	Shell Internal Standard (SIS) for 15

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0 Revision Date: 23.01.2025 SDS Number: 800010063771 Date of last issue: 27.05.2024
Print Date 30.01.2025

1,3-butadiene	106-99-0	TLV-8hr	0,89 ppm 2 mg/m3	min (STEL) NL WG
Further information: Carcinogenic substances				

Biological occupational exposure limits

No biological limit allocated.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Isoprene	Workers	Inhalation	Long-term systemic effects	8,4 mg/m3
Isoprene	Workers	Dermal	Long-term systemic effects	23,7 mg/kg bw/day
Isoprene	Consumers	Oral	Long-term systemic effects	0,213 mg/kg bw/day
pentane	Workers	Dermal	Long-term systemic effects	432 mg/kg bw/day
pentane	Workers	Inhalation	Long-term systemic effects	3000 mg/m3
pentane	Consumers	Dermal	Long-term systemic effects	214 mg/kg bw/day
pentane	Consumers	Inhalation	Long-term systemic effects	643 mg/m3
pentane	Consumers	Oral	Long-term systemic effects	214 mg/kg bw/day
isopentane	Workers	Dermal	Long-term systemic effects	432 mg/kg bw/day
isopentane	Workers	Inhalation	Long-term systemic effects	3000 mg/m3
isopentane	Consumers	Dermal	Long-term systemic effects	214 mg/kg bw/day
isopentane	Consumers	Inhalation	Long-term systemic effects	643 mg/m3
isopentane	Consumers	Oral	Long-term systemic effects	214 mg/kg bw/day
Dicyclopentadiene	Workers	Inhalation	Acute local effects	160,23 mg/m3
Dicyclopentadiene	Workers	Dermal	Long-term systemic effects	0,3 mg/kg bw/day
Dicyclopentadiene	Workers	Inhalation	Long-term systemic effects	1,058 mg/m3
Dicyclopentadiene	Man via environment	Inhalation	Long-term systemic effects	0,26 mg/m3
Dicyclopentadiene	Man via environment	Oral	Long-term systemic effects	0,15 mg/kg bw/day
Benzene	Workers	Inhalation	Long-term systemic effects	0,8 mg/m3/ 8h
1,3-butadiene	Workers	Inhalation	Long-term systemic effects	2,21 mg/m3
1,3-butadiene	Consumers	Inhalation	Long-term systemic effects	0,0664 mg/m3

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0 Revision Date: 23.01.2025 SDS Number: 800010063771 Date of last issue: 27.05.2024
Print Date 30.01.2025

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Remarks:	Substance is a hydrocarbon with a complex, unknown or variable composition. Conventional methods of deriving PNECs are not appropriate and it is not possible to identify a single representative PNEC for such substances.	

8.2 Exposure controls

Engineering measures

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.
Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Eye washes and showers for emergency use.

Firewater monitors and deluge systems are recommended.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

General Information:

Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when there is potential for inhalation; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.

Personal protective equipment

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : Wear goggles for use against liquids and gas.
Wear full face shield if splashes are likely to occur.
Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Viton. Incidental contact/Splash protection: Nitrile rubber gloves. For continuous contact we recommend gloves with break-

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0	Revision Date: 23.01.2025	SDS Number: 800010063771	Date of last issue: 27.05.2024 Print Date 30.01.2025
----------------	------------------------------	-----------------------------	---

through time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

- Skin and body protection : Wear chemical and cold resistant gloves/gauntlets, and boots, and apron.
Protective clothing approved to EU Standard EN14605.
- Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type AX boiling point < 65°C (149°F)] meeting EN14387.
- Thermal hazards : Not applicable

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : Liquid.
- Colour : Colourless to light coloured
- Odour : strong

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0	Revision Date: 23.01.2025	SDS Number: 800010063771	Date of last issue: 27.05.2024 Print Date 30.01.2025
----------------	------------------------------	-----------------------------	---

Odour Threshold : not determined

Melting point/freezing point : Data not available

Boiling point/boiling range : 34 - 60 °C

Flammability

Flammability (solid, gas) : Data not available

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit /
upper flammability limit : 12 %(V)

Lower explosion limit /
Lower flammability limit : 1 %(V)

Flash point : < -20 °C

Auto-ignition temperature : > 200 °C

Decomposition temperature

Decomposition temperature : Data not available

pH : Data not available

Viscosity

Viscosity, dynamic : Typical 0,25 mPa.s (0 °C)
Method: ASTM D445

Typical 0,22 mPa.s (20 °C)
Method: ASTM D445

Viscosity, kinematic : Data not available

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-
octanol/water : Data not available

Vapour pressure : 58,4 kPa (20 °C)

Relative density : 0,7 (20,0 °C)
Method: ASTM D4052

Density : 678 kg/m³ (20 °C)
Method: ASTM D4052

Relative vapour density : 2,3

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version	Revision Date:	SDS Number:	Date of last issue: 27.05.2024
2.0	23.01.2025	800010063771	Print Date 30.01.2025

9.2 Other information

Explosive properties : Classification Code: Not classified

Oxidizing properties : Data not available

Conductivity : Low conductivity: < 100 pS/m

The conductivity of this material makes it a static accumulator. A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m. Whether a liquid is nonconductive or semi-conductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid

Molecular weight : Data not available

SECTION 10: Stability and reactivity

10.1 Reactivity

Prolonged exposure to air may lead to peroxide formation.
Reacts with strong oxidising agents.

10.2 Chemical stability

The product is normally supplied in a stabilized form. If the permissible storage period and/or storage temperature is noticeably exceeded, the product may polymerise with heat evolution.
Reacts violently with:
Nitric, sulphuric and chlorosulphuric acids.
Oxidises on contact with air to form unstable peroxides.
Polymerisation may occur at elevated temperatures.
Normally stable under ambient conditions and if properly inhibited.

10.3 Possibility of hazardous reactions

Hazardous reactions : Normally stable under ambient conditions and if properly inhibited.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames, and sparks.
Exposure to air.
Exposure to sunlight.
In certain circumstances product can ignite due to static electricity.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.
Strong acids.
Strong bases.
Copper alloys

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0	Revision Date: 23.01.2025	SDS Number: 800010063771	Date of last issue: 27.05.2024 Print Date 30.01.2025
----------------	------------------------------	-----------------------------	---

10.6 Hazardous decomposition products

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity	: LD50 (Rat, male and female): > 300 - 2.000 mg/kg Method: Test(s) equivalent or similar to OECD Test Guideline 401 Remarks: Harmful if swallowed.
Acute inhalation toxicity	: Remarks: May be harmful if inhaled.
Acute dermal toxicity	: LD50 (Rabbit, male): 1.183 mg/kg Method: Literature data Remarks: Harmful in contact with skin.

Components:

Hydrocarbons, C5-rich:

Acute oral toxicity	: LD 50 (Rat, male and female): >300 <=2000 mg/kg Method: Test(s) equivalent or similar to OECD Test Guideline 401 Remarks: Harmful if swallowed.
Acute inhalation toxicity	: LC 50 (Rat, male and female): > 20 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Test(s) equivalent or similar to OECD Test Guideline 403 Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity	: LD 50 (Rabbit, male): 1.183 mg/kg Method: Literature data Remarks: Harmful in contact with skin.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version	Revision Date:	SDS Number:	Date of last issue: 27.05.2024
2.0	23.01.2025	800010063771	Print Date 30.01.2025

Skin corrosion/irritation

Product:

Species	:	Rabbit
Method	:	Literature data
Remarks	:	Harmful in contact with skin.

Components:

Hydrocarbons, C5-rich:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Remarks	:	Causes skin irritation.

Serious eye damage/eye irritation

Product:

Species	:	Rabbit
Method	:	Literature data
Remarks	:	Causes serious eye irritation.

Components:

Hydrocarbons, C5-rich:

Species	:	Rabbit
Method	:	Literature data
Remarks	:	Causes serious eye irritation.

Respiratory or skin sensitisation

Product:

Species	:	Guinea pig
Method	:	Test(s) equivalent or similar to OECD Test Guideline 406
Remarks	:	Based on available data, the classification criteria are not met.

Components:

Hydrocarbons, C5-rich:

Species	:	Guinea pig
Method	:	Test(s) equivalent or similar to OECD Test Guideline 406
Remarks	:	Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

Genotoxicity in vitro	:	Method: Test(s) equivalent or similar to OECD Test Guideline 473
	:	Remarks: Suspected of causing genetic defects.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0	Revision Date: 23.01.2025	SDS Number: 800010063771	Date of last issue: 27.05.2024 Print Date 30.01.2025
----------------	------------------------------	-----------------------------	---

Mutagenic; positive in in-vivo and in-vitro assays.

Method: Literature data

Remarks: Suspected of causing genetic defects.

Mutagenic; positive in in-vivo and in-vitro assays.

Genotoxicity in vivo

: Species: Mouse

Method: OECD Test Guideline 474

Remarks: Suspected of causing genetic defects.

Mutagenic; positive in in-vivo assays.

Species: Mouse

Method: Test(s) equivalent or similar to OECD Test guideline 478

Remarks: Suspected of causing genetic defects.

Mutagenic; positive in in-vivo assays.

Germ cell mutagenicity- Assessment

: Weight of evidence does not support classification as a germ cell mutagen.

Components:

Hydrocarbons, C5-rich:

Genotoxicity in vitro

: Method: Test(s) equivalent or similar to OECD Test Guideline 473

Remarks: Suspected of causing genetic defects.

Mutagenic; positive in in-vivo and in-vitro assays.

Method: Literature data

Remarks: Suspected of causing genetic defects.

Mutagenic; positive in in-vivo and in-vitro assays.

Genotoxicity in vivo

: Species: Mouse

Method: OECD Test Guideline 474

Remarks: Suspected of causing genetic defects.

Mutagenic; positive in in-vivo assays.

Species: Mouse

Method: Test(s) equivalent or similar to OECD Test guideline 478

Remarks: Suspected of causing genetic defects.

Mutagenic; positive in in-vivo assays.

Germ cell mutagenicity- Assessment

: This product does not meet the criteria for classification in categories 1A/1B.

Carcinogenicity

Product:

Species

: Mouse, male and female

Application Route

: Inhalation

Method

: Other guideline method.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0 Revision Date: 23.01.2025 SDS Number: 800010063771 Date of last issue: 27.05.2024
Print Date 30.01.2025

Remarks : May cause cancer.
IARC Group 2B: Possibly carcinogenic to humans.

Species : Rat, male and female
Application Route : Inhalation
Method : Test(s) equivalent or similar to OECD Test Guideline 453
Remarks : May cause cancer.
IARC Group 2B: Possibly carcinogenic to humans.

Carcinogenicity - Assessment : May cause cancer.

Components:

Hydrocarbons, C5-rich:

Species : Mouse, male and female
Application Route : Inhalation
Method : Other guideline method.
Remarks : May cause cancer.
IARC Group 2B: Possibly carcinogenic to humans.

Species : Rat, male and female
Application Route : Inhalation
Method : Test(s) equivalent or similar to OECD Test Guideline 453
Remarks : May cause cancer.
IARC Group 2B: Possibly carcinogenic to humans.

Carcinogenicity - Assessment : May cause cancer.

Material	GHS/CLP Carcinogenicity Classification
Hydrocarbons, C5-rich	Carcinogenicity Category 1B
Isoprene	Carcinogenicity Category 1B
cyclopentadiene	No carcinogenicity classification.
pentane	No carcinogenicity classification.
penta-1,3-diene	No carcinogenicity classification.
isopentane	No carcinogenicity classification.
Dicyclopentadiene	No carcinogenicity classification.
Benzene	Carcinogenicity Category 1A
1,3-butadiene	Carcinogenicity Category 1A
TBP (tert-butylphenol) - inhibitor	No carcinogenicity classification.

Material	Other Carcinogenicity Classification
----------	--------------------------------------

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0 Revision Date: 23.01.2025 SDS Number: 800010063771 Date of last issue: 27.05.2024
Print Date 30.01.2025

Hydrocarbons, C5-rich	IARC: Group 2B: Possibly carcinogenic to humans
Isoprene	IARC: Group 2B: Possibly carcinogenic to humans
Benzene	IARC: Group 1: Carcinogenic to humans
1,3-butadiene	IARC: Group 1: Carcinogenic to humans

Reproductive toxicity

Product:

Effects on fertility : Remarks: Suspected of damaging fertility or the unborn child.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Components:

Hydrocarbons, C5-rich:

Effects on fertility : Species: Rat
Sex: male and female
Application Route: Inhalation

Method: OECD Test Guideline 422
Remarks: Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

STOT - single exposure

Product:

Exposure routes : Inhalation
Target Organs : Central nervous system, Respiratory Tract
Remarks : High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea.
Inhalation of vapours or mists may cause irritation to the respiratory system.
May cause drowsiness and dizziness.
May cause respiratory irritation.

Components:

Hydrocarbons, C5-rich:

Exposure routes : Inhalation
Target Organs : Central nervous system, Respiratory Tract
Remarks : Inhalation of vapours or mists may cause irritation to the respiratory system.
May cause drowsiness or dizziness.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version	Revision Date:	SDS Number:	Date of last issue: 27.05.2024
2.0	23.01.2025	800010063771	Print Date 30.01.2025

May cause respiratory irritation.
High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea.

STOT - repeated exposure

Product:

Remarks : Based on available data, the classification criteria are not met.

Components:

Hydrocarbons, C5-rich:

Remarks : Based on available data, the classification criteria are not met.

Repeated dose toxicity

Product:

Species : Rat, male and female
Application Route : Oral
Method : Test(s) equivalent or similar to OECD Test Guideline 422
Target Organs : No specific target organs noted

Species : Rat, male and female
Application Route : Inhalation
Method : Test(s) equivalent or similar to OECD Test Guideline 422
Target Organs : No specific target organs noted

Components:

Hydrocarbons, C5-rich:

Species : Rat, male and female
Application Route : Oral
Method : Test(s) equivalent or similar to OECD Test Guideline 422
Target Organs : No specific target organs noted

Species : Rat, male and female
Application Route : Inhalation
Test atmosphere : vapour
Method : Test(s) equivalent or similar to OECD Test Guideline 422
Target Organs : No specific target organs noted

Aspiration toxicity

Product:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version	Revision Date:	SDS Number:	Date of last issue: 27.05.2024
2.0	23.01.2025	800010063771	Print Date 30.01.2025

Components:

Hydrocarbons, C5-rich:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

Remarks : Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Components:

Hydrocarbons, C5-rich:

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C5-rich:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 14,1 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Harmful
LL/EL/IL50 >10 <= 100 mg/l

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 4,7 mg/l
aquatic invertebrates : Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Toxic

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version	Revision Date:	SDS Number:	Date of last issue: 27.05.2024
2.0	23.01.2025	800010063771	Print Date 30.01.2025

LL/EL/IL50 > 1 <= 10 mg/l

Toxicity to algae/aquatic plants : EC50 (*Pseudokirchneriella subcapitata* (algae)): 12,4 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Harmful
LL/EL/IL50 >10 <= 100 mg/l

Toxicity to microorganisms : NOELR (Activated sludge, domestic waste): 2 mg/l
Exposure time: 5 h
Method: OECD Test Guideline 301D
Remarks: Data not available

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: Data not available

12.2 Persistence and degradability

Components:

Hydrocarbons, C5-rich:

Biodegradability : Biodegradation: 9 %
Exposure time: 28 d
Method: OECD Test Guideline 301D
Remarks: Not readily biodegradable.

12.3 Bioaccumulative potential

Components:

Hydrocarbons, C5-rich:

Bioaccumulation : Species: *Pimephales promelas* (fathead minnow)
Bioconcentration factor (BCF): 1,2 - 2,1
Method: Based on quantitative structure-activity relationship (QSAR) modelling
Remarks: Does not bioaccumulate significantly.

12.4 Mobility in soil

Components:

Hydrocarbons, C5-rich:

Mobility : Remarks: Floats on water.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version	Revision Date:	SDS Number:	Date of last issue: 27.05.2024
2.0	23.01.2025	800010063771	Print Date 30.01.2025

12.5 Results of PBT and vPvB assessment

Components:

Hydrocarbons, C5-rich:

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water courses.
Waste product should not be allowed to contaminate soil or water.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local regulations may be more stringent than regional or national requirements and must be complied with.

SECTION 14: Transport information

14.1 UN number or ID number

ADN	: 3295
ADR	: 3295

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version	Revision Date:	SDS Number:	Date of last issue: 27.05.2024
2.0	23.01.2025	800010063771	Print Date 30.01.2025

RID : 3295

IMDG : 3295

IATA : 3295

14.2 UN proper shipping name

ADN : HYDROCARBONS, LIQUID, N.O.S.
(CONTAINING ISOPRENE AND PENTADIENE STABILIZED)

ADR : HYDROCARBONS, LIQUID, N.O.S.

RID : HYDROCARBONS, LIQUID, N.O.S.

IMDG : HYDROCARBONS, LIQUID, N.O.S.
((hydrocarbons, C5-rich)

IATA : HYDROCARBONS, LIQUID, N.O.S.

14.3 Transport hazard class(es)

ADN : 3

ADR : 3

RID : 3

IMDG : 3

IATA : 3

14.4 Packing group

ADN

Packing group : I
Classification Code : F1
Labels : 3 (INST, N2, CMR)
CDNI Inland Water Waste : NST 8963 Solvent
Agreement

ADR

Packing group : I
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

RID

Packing group : I
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

IMDG

Packing group : I
Labels : 3

IATA

Packing group : I
Labels : 3

14.5 Environmental hazards

ADN

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version	Revision Date:	SDS Number:	Date of last issue: 27.05.2024
2.0	23.01.2025	800010063771	Print Date 30.01.2025

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

14.7 Maritime transport in bulk according to IMO instruments

Pollution category : Y
Ship type : 2
Product name : IP Extraction Feed (contains Isoprene; 1,3-Cyclopentadiene dimer (molten))

Additional Information : This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry. Transport in bulk according to Annex II of Marpol and the IBC Code

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
1,3-butadiene (Number on list 29, 28)
Benzene (Number on list 72, 5, 29, 28)
Isoprene (Number on list 28)
Hydrocarbons, C5-rich (Number on list 29, 28)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5a

FLAMMABLE LIQUIDS

E1

ENVIRONMENTAL HAZARDS

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version	Revision Date:	SDS Number:	Date of last issue: 27.05.2024
2.0	23.01.2025	800010063771	Print Date 30.01.2025

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Product meets one or more criteria set for the Dutch list of 'substances of concern' (zeer zorgwekkende stoffen (ZZS)).

Product is subject to Major accident risk decision 2015 (BRZO+) based on Seveso III directive (2012/18/EU).

The components of this product are reported in the following inventories:

AIIC	: Listed
DSL	: Listed
TSCA	: Listed
IECSC	: Listed
TCSI	: Listed

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Full text of other abbreviations

2006/15/EC	: Europe. Indicative occupational exposure limit values
NL WG	: Netherlands. Law on Labour conditions - Occupational Exposure Limits
2006/15/EC / TWA	: Limit Value - eight hours
NL WG / TLV-8hr	: Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - Interna-

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version	Revision Date:	SDS Number:	Date of last issue: 27.05.2024
2.0	23.01.2025	800010063771	Print Date 30.01.2025

tional Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Training advice : Provide adequate information, instruction and training for operators.

Other information : For Industry guidance and tools on REACH please visit the CEFIC website at <http://cefic.org/Industry-support>.
The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).

Classification of the mixture:

Flam. Liq. 1	H224
Acute Tox. 4	H302
Asp. Tox. 1	H304
Acute Tox. 4	H312
Skin Irrit. 2	H315
Eye Irrit. 2	H319

Classification procedure:

On basis of test data.
Expert judgement and weight of evidence determination.
Expert judgement and weight of evidence determination.
Expert judgement and weight of evidence determination.
Expert judgement and weight of evidence determination.
Expert judgement and weight of evidence determination.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0	Revision Date: 23.01.2025	SDS Number: 800010063771	Date of last issue: 27.05.2024 Print Date 30.01.2025
----------------	------------------------------	-----------------------------	---

STOT SE 3	H335, H336	Expert judgement and weight of evidence determination.
Muta. 2	H341	Expert judgement and weight of evidence determination.
Carc. 1B	H350	Expert judgement and weight of evidence determination.
Repr. 2	H361	Expert judgement and weight of evidence determination.
Aquatic Chronic 2	H411	Expert judgement and weight of evidence determination.

Identified Uses according to the Use Descriptor System

Uses - Worker

Title : Manufacture of substance
- Industrial

Uses - Worker

Title : Use as an intermediate
- Industrial

Uses - Worker

Title : Distribution of substance
- Industrial

Uses - Worker

Title : Use as a fuel
- Industrial

Uses - Worker

Title : Polymer production
- Industrial

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NL / EN

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0 Revision Date: 23.01.2025 SDS Number: 800010063771 Date of last issue: 27.05.2024
Print Date 30.01.2025

Exposure Scenario - Worker

300000000347	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Manufacture of substance- Industrial
Use Descriptor	Sector of Use: SU3, SU8, SU9 Process Categories: PROC 1, PROC 2, PROC 3, PROC 8a, PROC 8b, PROC 15 Environmental Release Categories: ERC1, ESVOC SpERC 1.1.v1
Scope of process	Manufacture of the substance or use as a process chemical or extraction agent within closed or contained systems. Includes incidental exposures during recycling/ recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

SECTION 2		OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1		Control of Worker Exposure	
Product Characteristics			
Physical form of product		Liquid, vapour pressure > 10 kPa at STP	
Concentration of the Substance in Mixture/Article		Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios		Risk Management Measures	
General measures (carcinogens).		Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and maintain all control measures. Consider the need for risk based health surveillance.	
General measures (skin irritants).		Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0 Revision Date: 23.01.2025 SDS Number: 800010063771 Date of last issue: 27.05.2024
Print Date 30.01.2025

	hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General exposures (closed systems)	Handle substance within a closed system.
General exposures (closed systems)with sample collectionGeneral measures (skin irritants).	Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure Ensure operation is undertaken outdoors.
General exposures (closed systems)Use in contained batch processes	Handle substance within a closed system. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Provide extraction ventilation at points where emissions occur. Avoid carrying out activities involving exposure for more than 4 hours
Process sampling	Sample via a closed loop or other system to avoid exposure Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 1 hour.
Laboratory activities	Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure. Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour).
Bulk transfers(closed systems)	Ensure material transfers are under containment or extract ventilation. Clear transfer lines prior to de-coupling. Ensure operation is undertaken outdoors.
Equipment cleaning and maintenance	Drain down and flush system prior to equipment opening or maintenance. Ensure operation is undertaken outdoors. Clear spills immediately. Wear a respirator conforming to EN140 with Type A filter or better. Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Storage.General measures (skin irritants).	Store substance within a closed system. Ensure material transfers are under containment or extract ventilation. Ensure operation is undertaken outdoors.
Section 2.2	Control of Environmental Exposure
Substance is complex UVCB.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0 Revision Date: 23.01.2025 SDS Number: 800010063771 Date of last issue: 27.05.2024
Print Date 30.01.2025

Predominantly hydrophobic.	
Not readily biodegradable.	
Amounts Used	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	5E+04
Fraction of Regional tonnage used locally:	1
Annual site tonnage (tonnes/year):	5E+04
Maximum daily site tonnage (kg/day):	1,7E+05
Frequency and Duration of Use	
Continuous release.	
Emission Days (days/year):	300
Environmental factors not influenced by risk management	
Local freshwater dilution factor:	40
Local marine water dilution factor:	100
Other Operational Conditions affecting Environmental Exposure	
Release fraction to air from process (initial release prior to RMM):	5,0E-02
Release fraction to wastewater from process (initial release prior to RMM):	3,0E-03
Release fraction to soil from process (initial release prior to RMM):	1,0E-04
Technical conditions and measures at process level (source) to prevent release	
Common practices vary across sites thus conservative process re-lease estimates used.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Risk from environmental exposure is driven by wastewater treatment plant microbes.	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	90
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	75,3
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95,5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95,5
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	9,2E+05
Assumed domestic sewage treatment plant flow (m3/d)	10.000
Conditions and Measures related to external treatment of waste for disposal	
During manufacturing no waste of the substance is generated.	
Conditions and measures related to external recovery of waste	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0 Revision Date: 23.01.2025 SDS Number: 800010063771 Date of last issue: 27.05.2024
Print Date 30.01.2025

During manufacturing no waste of the substance is generated.

SECTION 3 EXPOSURE ESTIMATION

Section 3.1 - Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

SECTION 4 GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0 Revision Date: 23.01.2025 SDS Number: 800010063771 Date of last issue: 27.05.2024
Print Date 30.01.2025

Exposure Scenario - Worker

300000000352	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use as an intermediate- Industrial
Use Descriptor	Sector of Use: SU3, SU8, SU9 Process Categories: PROC 1, PROC 2, PROC 3, PROC 8a, PROC 8b, PROC 15 Environmental Release Categories: ERC6a, ESVOC SpERC 6.1a.v1
Scope of process	Use of substance as an intermediate within closed or contained systems (not related to Strictly Controlled Conditions). Includes incidental exposures during recycling/recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

SECTION 2		OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1		Control of Worker Exposure	
Product Characteristics			
Physical form of product		Liquid, vapour pressure > 10 kPa at STP	
Concentration of the Substance in Mixture/Article		Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios		Risk Management Measures	
General measures (carcinogens).		Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and maintain all control measures. Consider the need for risk based health surveillance.	
General measures (skin irritants).		Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version
2.0

Revision Date:
23.01.2025

SDS Number:
800010063771

Date of last issue: 27.05.2024
Print Date 30.01.2025

	hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General exposures (closed systems)	Handle substance within a closed system.
General exposures (closed systems)with sample collectionGeneral measures (skin irritants).	Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure Ensure operation is undertaken outdoors.
General exposures (closed systems)Use in contained batch processes	Handle substance within a closed system. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Provide extraction ventilation at points where emissions occur. Avoid carrying out activities involving exposure for more than 4 hours
Process sampling	Sample via a closed loop or other system to avoid exposure Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 1 hour.
Laboratory activities	Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure. Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour).
Bulk transfers(closed systems)	Ensure material transfers are under containment or extract ventilation. Clear transfer lines prior to de-coupling. Ensure operation is undertaken outdoors.
Equipment cleaning and maintenance	Drain down and flush system prior to equipment opening or maintenance. Ensure operation is undertaken outdoors. Clear spills immediately. Wear a respirator conforming to EN140 with Type A filter or better. Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Storage.General measures (skin irritants).	Store substance within a closed system. Ensure material transfers are under containment or extract ventilation. Ensure operation is undertaken outdoors.
Section 2.2	Control of Environmental Exposure
Substance is complex UVCB.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0 Revision Date: 23.01.2025 SDS Number: 800010063771 Date of last issue: 27.05.2024
Print Date 30.01.2025

Predominantly hydrophobic.	
Not readily biodegradable.	
Amounts Used	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	2E+04
Fraction of Regional tonnage used locally:	0,75
Annual site tonnage (tonnes/year):	1,5E+04
Maximum daily site tonnage (kg/day):	5E+04
Frequency and Duration of Use	
Continuous release.	
Emission Days (days/year):	300
Environmental factors not influenced by risk management	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
Other Operational Conditions affecting Environmental Exposure	
Release fraction to air from process (initial release prior to RMM):	2,5E-02
Release fraction to wastewater from process (initial release prior to RMM):	3E-03
Release fraction to soil from process (initial release prior to RMM):	1E-03
Technical conditions and measures at process level (source) to prevent release	
Common practices vary across sites thus conservative process re-release estimates used.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Risk from environmental exposure is driven by freshwater sediment.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	80
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	90,8
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95,5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95,5
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	1E+05
Assumed domestic sewage treatment plant flow (m3/d)	2.000
Conditions and Measures related to external treatment of waste for disposal	
This substance is consumed during use and no waste of substance is generated.	
Conditions and measures related to external recovery of waste	
This substance is consumed during use and no waste of substance is generated.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0 Revision Date: 23.01.2025 SDS Number: 800010063771 Date of last issue: 27.05.2024
Print Date 30.01.2025

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	
Section 3.2 -Environment	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	
SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	
Section 4.2 -Environment	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.	
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.	
Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org).	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0 Revision Date: 23.01.2025 SDS Number: 800010063771 Date of last issue: 27.05.2024
Print Date 30.01.2025

Exposure Scenario - Worker

300000000350	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Distribution of substance- Industrial
Use Descriptor	Sector of Use: SU3, SU8, SU9 Process Categories: PROC 1, PROC 2, PROC 3, PROC 8a, PROC 8b, PROC 15 Environmental Release Categories: ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC7, ESVOC SpERC 1.1b.v1
Scope of process	Bulk loading (including marine vessel/barge, rail/road car and IBC loading) of substance within closed or contained systems, including incidental exposures during its sampling, storage, unloading, maintenance and associated laboratory activities.

SECTION 2		OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1		Control of Worker Exposure	
Product Characteristics			
Physical form of product		Liquid, vapour pressure > 10 kPa at STP	
Concentration of the Substance in Mixture/Article		Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios		Risk Management Measures	
General measures (carcinogens).		Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and maintain all control measures. Consider the need for risk based health surveillance.	
General measures (skin irritants).		Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamina-	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version
2.0

Revision Date:
23.01.2025

SDS Number:
800010063771

Date of last issue: 27.05.2024
Print Date 30.01.2025

	tion/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General exposures (closed systems)	Handle substance within a closed system.
General exposures (closed systems)with sample collectionGeneral measures (skin irritants).	Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
General exposures (closed systems)Use in contained batch processes	Handle substance within a closed system. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Sample via a closed loop or other system to avoid exposure Avoid carrying out activities involving exposure for more than 1 hour.
Process sampling	Sample via a closed loop or other system to avoid exposure Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 1 hour.
Laboratory activities	Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure.
Bulk transfers(closed systems)	Clear transfer lines prior to de-coupling. Ensure material transfers are under containment or extract ventilation. Ensure operation is undertaken outdoors.
Drum and small package filling	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.
Equipment cleaning and maintenance	Drain down and flush system prior to equipment opening or maintenance. Ensure operation is undertaken outdoors. Wear a respirator conforming to EN140 with Type A filter or better. Clear spills immediately. Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Storage.General measures (skin irritants).	Store substance within a closed system. Ensure material transfers are under containment or extract ventilation. Ensure operation is undertaken outdoors.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0 Revision Date: 23.01.2025 SDS Number: 800010063771 Date of last issue: 27.05.2024
Print Date 30.01.2025

Section 2.2	Control of Environmental Exposure
Substance is complex UVCB.	
Predominantly hydrophobic.	
Not readily biodegradable.	
Amounts Used	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	5E+04
Fraction of Regional tonnage used locally:	2E-03
Annual site tonnage (tonnes/year):	1E+02
Maximum daily site tonnage (kg/day):	5,0E+03
Frequency and Duration of Use	
Continuous release.	
Emission Days (days/year):	20
Environmental factors not influenced by risk management	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
Other Operational Conditions affecting Environmental Exposure	
Release fraction to air from process (initial release prior to RMM):	1E-03
Release fraction to wastewater from process (initial release prior to RMM):	1E-05
Release fraction to soil from process (initial release prior to RMM):	1E-05
Technical conditions and measures at process level (source) to prevent release	
Common practices vary across sites thus conservative process re-release estimates used.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Risk from environmental exposure is driven by freshwater sediment.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	90
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	0
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95,5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95,5
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	3,1E+07
Assumed domestic sewage treatment plant flow (m3/d)	2.000
Conditions and Measures related to external treatment of waste for disposal	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
Conditions and measures related to external recovery of waste	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0 Revision Date: 23.01.2025 SDS Number: 800010063771 Date of last issue: 27.05.2024
Print Date 30.01.2025

External recovery and recycling of waste should comply with applicable local and/or regional regulations.

SECTION 3 EXPOSURE ESTIMATION

Section 3.1 - Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

SECTION 4 GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version
2.0

Revision Date:
23.01.2025

SDS Number:
800010063771

Date of last issue: 27.05.2024
Print Date 30.01.2025

Exposure Scenario - Worker

300000010376	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use as a fuel- Industrial
Use Descriptor	Sector of Use: SU3, SU10 Process Categories: PROC 1, PROC 2, PROC 3, PROC 8a, PROC 8b, PROC 16 Environmental Release Categories: ERC7, ESVOC SpERC 7.12a.v1
Scope of process	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

SECTION 2		OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1		Control of Worker Exposure	
Product Characteristics			
Physical form of product		Liquid, vapour pressure > 10 kPa	
Concentration of the Substance in Mixture/Article		Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios		Risk Management Measures	
General measures (carcinogens).		Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and maintain all control measures. Consider the need for risk based health surveillance.	
General measures (skin irritants).		Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to pre-	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0 Revision Date: 23.01.2025 SDS Number: 800010063771 Date of last issue: 27.05.2024
Print Date 30.01.2025

	vent / minimise exposures and to report any skin problems that may develop.
General exposures (closed systems)	Handle substance within a closed system.
General exposures (closed systems)with sample collectionwith occasional controlled exposure.	Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure Ensure operation is undertaken outdoors.
General exposures (closed systems)Use in contained batch processes	Handle substance within a closed system. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Provide extraction ventilation at points where emissions occur. Avoid carrying out activities involving exposure for more than 4 hours
Process sampling	Sample via a closed loop or other system to avoid exposure Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 1 hour.
Drum/batch transfers	Use drum pumps. Limit the substance content in the product to 25 %. Provide extract ventilation to material transfer points and other openings. Ensure material transfers are under containment or extract ventilation.
Bulk transfers(closed systems)	Ensure material transfers are under containment or extract ventilation. Clear transfer lines prior to de-coupling. Ensure operation is undertaken outdoors.
Equipment cleaning and maintenance	Drain down and flush system prior to equipment opening or maintenance. Ensure operation is undertaken outdoors. Clear spills immediately. Wear a respirator conforming to EN140 with Type A filter or better. Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Storage.with occasional controlled exposure.	Store substance within a closed system. Ensure material transfers are under containment or extract ventilation. Ensure operation is undertaken outdoors.
Section 2.2	Control of Environmental Exposure
Substance is complex UVCB.	
Predominantly hydrophobic.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0 Revision Date: 23.01.2025 SDS Number: 800010063771 Date of last issue: 27.05.2024
Print Date 30.01.2025

Not readily biodegradable.	
Amounts Used	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	1E+04
Fraction of Regional tonnage used locally:	1
Annual site tonnage (tonnes/year):	1E+04
Maximum daily site tonnage (kg/day):	3,3E+04
Frequency and Duration of Use	
Continuous release.	
Emission Days (days/year):	300
Environmental factors not influenced by risk management	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
Other Operational Conditions affecting Environmental Exposure	
Release fraction to air from process (initial release prior to RMM):	5E-02
Release fraction to wastewater from process (initial release prior to RMM):	1E-05
Release fraction to soil from process (initial release prior to RMM):	0E+00
Technical conditions and measures at process level (source) to prevent release	
Common practices vary across sites thus conservative process re-release estimates used.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Risk from environmental exposure is driven by freshwater sediment.	
If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.	95
Treat air emission to provide a typical removal efficiency of (%)	95
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	0
Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95,5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95,5
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	3,1E+07
Assumed domestic sewage treatment plant flow (m3/d)	2E+03
Conditions and Measures related to external treatment of waste for disposal	
This substance is consumed during use and no waste of substance is generated.	
Conditions and measures related to external recovery of waste	
This substance is consumed during use and no waste of substance is generated.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0 Revision Date: 23.01.2025 SDS Number: 800010063771 Date of last issue: 27.05.2024
Print Date 30.01.2025

indicated.

Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0 Revision Date: 23.01.2025 SDS Number: 800010063771 Date of last issue: 27.05.2024
Print Date 30.01.2025

Exposure Scenario - Worker

300000010377	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Polymer production- Industrial
Use Descriptor	Sector of Use: SU3, SU10 Process Categories: PROC 1, PROC 2, PROC 3, PROC 5, PROC 6, PROC8a, PROC8b, PROC9, PROC14, PROC21 Environmental Release Categories: ERC6a, ERC6c, ESVOC SpERC 4.20.v1
Scope of process	Manufacture of polymers from monomers in continuous and batch processes. Including production, re-cycling and recovery, degassing, discharging, reactor maintenance and immediate polymer product formation (i.e. compounding, pelletisation, product off-gassing). Professional application of coatings and inks

SECTION 2		OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1		Control of Worker Exposure	
Product Characteristics			
Physical form of product		Liquid, vapour pressure > 10 kPa	
Concentration of the Substance in Mixture/Article		Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios		Risk Management Measures	
General measures (carcinogens).		Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and maintain all control measures. Consider the need for risk based health surveillance.	
General measures (skin irritants).		Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version
2.0

Revision Date:
23.01.2025

SDS Number:
800010063771

Date of last issue: 27.05.2024
Print Date 30.01.2025

	hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
Bulk transfertransportwith sample collection	Ensure material transfers are under containment or extract ventilation. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
General exposures (closed systems)	Handle substance within a closed system.
Polymerisation (bulk and batch)Continuous processwith sample collection	Provide extract ventilation to material transfer points and other openings. Ensure operation is undertaken outdoors. , or: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
Polymerisation (bulk and batch)Batch processwith sample collection	Provide extract ventilation to material transfer points and other openings. Ensure operation is undertaken outdoors. , or: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
Finishing operationsBatch processwith sample collectionCatalyst inactivation and removal, washing and stripping / distillation to remove unreacted monomer	Provide extraction ventilation at points where emissions occur. Ensure operation is undertaken outdoors. , or: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
Intermediate polymer storage	Limit the substance content in the product to 5 %. Provide extraction ventilation at points where emissions occur. Store substance within a closed system.
Addition and stabilisation	Limit the substance content in the product to 5 %. Provide extraction ventilation at points where emissions occur. Ensure operation is undertaken outdoors. , or: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
Mixing in containers.Batch process	Limit the substance content in the product to 5 %. Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Provide extraction ventilation at points where emissions occur.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version
2.0

Revision Date:
23.01.2025

SDS Number:
800010063771

Date of last issue: 27.05.2024
Print Date 30.01.2025

PelletizingExtrusion and masterbatching	Limit the substance content in the product to 5 %. Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Provide extraction ventilation at points where emissions occur.
Pelletisation and pellet screening(open systems)	Limit the substance content in the product to 5 %. Ensure material transfers are under containment or extract ventilation.
Equipment maintenance	Drain down and flush system prior to equipment opening or maintenance. Clear spills immediately. Wear a respirator conforming to EN140 with Type A filter or better. Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Storage.with occasional controlled exposure.	Limit the substance content in the product to 5 %. Store substance within a closed system. Avoid carrying out activities involving exposure for more than 1 hour.
Section 2.2	Control of Environmental Exposure
Substance is complex UVCB.	
Predominantly hydrophobic.	
Not readily biodegradable.	
Amounts Used	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	2E+04
Fraction of Regional tonnage used locally:	0,75
Annual site tonnage (tonnes/year):	1,5E+04
Maximum daily site tonnage (kg/day):	5E+04
Frequency and Duration of Use	
Continuous release.	
Emission Days (days/year):	300
Environmental factors not influenced by risk management	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
Other Operational Conditions affecting Environmental Exposure	
Release fraction to air from process (initial release prior to RMM):	1E-02
Release fraction to wastewater from process (initial release prior to RMM):	3E-03
Release fraction to soil from process (initial release prior to RMM):	1E-04
Technical conditions and measures at process level (source) to prevent release	
Common practices vary across sites thus conservative process release estimates used.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Risk from environmental exposure is driven by freshwater sediment.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version 2.0 Revision Date: 23.01.2025 SDS Number: 800010063771 Date of last issue: 27.05.2024
Print Date 30.01.2025

Prevent discharge of undissolved substance to or recover from onsite wastewater.	
If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	80
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%)	90,8
Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95,5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95,5
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	1E+05
Assumed domestic sewage treatment plant flow (m3/d)	2E+03
Conditions and Measures related to external treatment of waste for disposal	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

Section 3.2 -Environment	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

Section 4.2 -Environment	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

IP Extraction Feed Sustainable

Version
2.0

Revision Date:
23.01.2025

SDS Number:
800010063771

Date of last issue: 27.05.2024
Print Date 30.01.2025

measures.
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.
Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org/en/reach-for-industries-libraries.html).