

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
4.0	28.01.2024	800001001021	Print Date 05.02.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	: Crude C4
Product code	: X2136, ZA17A
Registration number EU	: 01-2119485494-27-0001, 01-2119485494-27-0002, 01-2119485494-27-0003
CAS-No.	: 68955-28-2
Other means of identification	: Crude C4 (Crude BBB)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture	: Base chemical., Raw material for use in the chemical industry. The substance/product is registered with strictly controlled conditions as defined in Article 18(4) of Regulation (EC) No. 1907/2006 (REACH Regulation) and must therefore be handled as such.
Uses advised against	: This product must not be used in applications other than the above without first seeking the advice of the supplier., Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier	: Shell Chemicals Europe B.V. PO Box 2334 3000 CH Rotterdam Netherlands
Telephone	: +31 (0)10 441 5137 / +31 (0)10 441 5191
Telefax	: +31 (0)20 716 8316 / +31 (0)20 713 9230
Contact for Safety Data Sheet	: sccmsds@shell.com

1.4 Emergency telephone number

+44 (0) 1235 239 670
National Poison Information Centre (NVIC): Tel. nr. +31(0)88 755 8000 (24 hrs a day and 7 days a week).
Only for the purpose of informing medical personnel.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable gases, Category 1A	H220: Extremely flammable gas.
------------------------------	--------------------------------

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
4.0	28.01.2024	800001001021	Print Date 05.02.2024

Gases under pressure, Liquefied gas	H280: Contains gas under pressure; may explode if heated.
Germ cell mutagenicity, Category 1B	H340: May cause genetic defects.
Carcinogenicity, Category 1A	H350: May cause cancer.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

PHYSICAL HAZARDS:

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

HEALTH HAZARDS:

H340 May cause genetic defects.

H350 May cause cancer.

ENVIRONMENTAL HAZARDS:

Not classified as environmental hazard according to CLP criteria.

Precautionary statements : **Prevention:**

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243 Take action to prevent static discharges.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 In case of leakage, eliminate all ignition sources.

Storage:

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version 4.0 Revision Date: 28.01.2024 SDS Number: 800001001021 Date of last issue: 21.11.2023
Print Date 05.02.2024

2.3 Other hazards

The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Vapours may cause drowsiness and dizziness.

Slightly irritating to respiratory system.

Exposure to rapidly expanding gases may cause frost burns to eyes and/or skin.

Vapours may be irritating to the eye.

Possibility of organ or organ system damage from prolonged exposure; see Section 11 for details.

Target organ(s):

Blood forming organs

Reproductive system.

This material is a static accumulator.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

Highly reactive.

May form explosive peroxides.

The vapour is heavier than air, spreads along the ground and distant ignition is possible.

May form flammable/explosive vapour-air mixture.

SECTION 3: Composition/information on ingredients

3.1 Substances

Components

Chemical name	CAS-No. EC-No.	Concentration (% w/w)
gases (petroleum, light steam-cracked, butadiene conc.	68955-28-2 273-265-5	<= 100

Stabilised with tertiary butyl catechol.

Further information

Contains:

Chemical name	Identification number	Classification	Concentration (% w/w)
1,3-butadiene	106-99-0, 203-450-8	Flam. Gas1A; H220 Press. GasLiquefied gas; H280 Muta.1B; H340	> 40 - < 60

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version 4.0 Revision Date: 28.01.2024 SDS Number: 800001001021 Date of last issue: 21.11.2023
Print Date 05.02.2024

		Carc.1A; H350	
2-methylpropene	115-11-7, 204-066-3	Flam. Gas1A; H220 Press. GasLiquefied gas; H280	> 10 - < 30
Butene	25167-67-3, 246-689-3	Flam. Gas1A; H220 Press. GasLiquefied gas; H280	> 10 - < 40

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Not expected to be a health hazard when used under normal conditions.
- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- If inhaled : Call emergency number for your location / facility.
Remove to fresh air. Do not attempt to rescue the victim unless proper respiratory protection is worn. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting, or unresponsive, give 100% oxygen with rescue breathing or Cardio-Pulmonary Resuscitation as required and transport to the nearest medical facility.
- In case of skin contact : Slowly warm the exposed area by rinsing with warm water.
Transport to the nearest medical facility for additional treatment.
- In case of eye contact : Slowly warm the exposed area by rinsing with warm water.
Transport to the nearest medical facility for additional treatment.
- If swallowed : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.
Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination.
Continued inhalation may result in unconsciousness and

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
4.0	28.01.2024	800001001021	Print Date 05.02.2024

death.

Rapid release of gases which are liquids under pressure may cause frost burns of exposed tissues (skin, eye) due to evaporative cooling.

No specific hazards under normal use conditions.
Ingestion may result in nausea, vomiting and/or diarrhoea.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!
Artificial respiration and/or oxygen may be necessary.
Call a doctor or poison control center for guidance.
Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Shut off supply. If not possible and no risk to surroundings, let the fire burn itself out.

Unsuitable extinguishing media : Data not available

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Sustained fire attack on vessels may result in a Boiling Liquid Expanding Vapor Explosion (BLEVE).
The vapour is heavier than air, spreads along the ground and distant ignition is possible.
Contents are under pressure and can explode when exposed to heat or flames.
As the vapours become lighter than air, the vapours may reach ignition sources at ground or elevated locations.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear full protective clothing and self-contained breathing apparatus.

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

Specific extinguishing methods : Standard procedure for chemical fires.

Further information : Clear fire area of all non-emergency personnel.
Keep adjacent containers cool by spraying with water.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
4.0	28.01.2024	800001001021	Print Date 05.02.2024

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

Be ready for fire or possible exposure.

Stay upwind and keep out of low areas.

6.1.1 For non emergency personnel:

Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or unprotected personnel.

Do not breathe fumes, vapour.

Do not operate electrical equipment.

6.1.2 For emergency responders:

Avoid contact with skin, eyes and clothing.

Isolate hazard area and deny entry to unnecessary or unprotected personnel.

Do not breathe fumes, vapour.

Do not operate electrical equipment.

6.2 Environmental precautions

Environmental precautions : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area and evacuate all personnel. Attempt to disperse the gas or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas meter.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Allow to evaporate.

Attempt to disperse the vapour or to direct its flow to a safe location, for example by using fog sprays. Otherwise treat as for small spillage.

6.4 Reference to other sections

Risk of explosion. Inform the emergency services if liquid enters surface water drains., Vapour may form an explosive mixture with air.

Local authorities should be advised if significant spillages cannot be contained.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : Avoid breathing of or direct contact with material. Only use in

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version 4.0	Revision Date: 28.01.2024	SDS Number: 800001001021	Date of last issue: 21.11.2023 Print Date 05.02.2024
----------------	------------------------------	-----------------------------	---

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

Ensure that all local regulations regarding handling and storage facilities are followed.

Advice on safe handling : Avoid inhaling vapour and/or mists.
Avoid contact with skin, eyes and clothing.
Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.
The vapour is heavier than air. Beware of accumulation in pits and confined spaces.
Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.
Bulk storage tanks should be diked (bunded).
Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.
If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.
Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges.
These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements.
These activities may lead to static discharge e.g. spark formation.
Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/s until fill pipe submerged to twice its diameter, then ≤ 7 m/s). Avoid splash filling.
Do NOT use compressed air for filling, discharging, or handling operations.

Product Transfer : Refer to guidance under Handling section.

Hygiene measures : Wash hands before eating, drinking, smoking and using the toilet. Launder contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Further information on storage stability : Electrostatic charges will be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical con-

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version 4.0 Revision Date: 28.01.2024 SDS Number: 800001001021 Date of last issue: 21.11.2023
Print Date 05.02.2024

tinuity by bonding and grounding (earthing) all equipment to reduce the risk.
The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.
Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products which are not harmful or toxic to man or to the environment.
Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat.
Must be kept inhibited during storage and shipment as material can polymerise.
Vapours from tanks should not be released to atmosphere.
Breathing losses during storage should be controlled by a suitable vapour treatment system.
Storage Temperature:
Ambient.
Nitrogen blanket recommended.
The product is normally supplied in a stabilized form. If the permissible storage period and/or storage temperature is noticeably exceeded, the product may polymerise with heat evolution.
Stable under recommended storage conditions.
Packaging material : Suitable material: For containers, or container linings use mild steel, stainless steel.
Unsuitable material: Copper., Copper alloys., Magnesium., Mercury., Monel., Silver.

7.3 Specific end use(s)

Specific use(s) : The substance/product is registered with strictly controlled conditions as defined in Article 18(4) of Regulation (EC) No. 1907/2006 (REACH Regulation) and must therefore be handled as such. Refer to the industry guidance prepared by Concawe/Cefic for advice on the demonstration of strictly controlled conditions available from: <http://cefic.org>.

See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).
IEC/TS 60079-32-1: Electrostatic hazards, guidance

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parameters	Basis
------------	---------	------------------	--------------------	-------

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version 4.0 Revision Date: 28.01.2024 SDS Number: 800001001021 Date of last issue: 21.11.2023
Print Date 05.02.2024

		of exposure)		
1,3-butadiene	106-99-0	TLV-8hr	0,89 ppm 2 mg/m3	NL WG
Further information: Carcinogenic substances				

Biological occupational exposure limits

No biological limit allocated.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
1,3-butadiene	Workers	Inhalation	Long-term systemic effects	2,21 mg/m3
1,3-butadiene	Consumers	Inhalation	Long-term systemic effects	0,0664 mg/m3
2-methylpropene	Workers	Inhalation	Long-term local effects	1530 mg/m3
2-methylpropene	Consumers	Inhalation	Long-term local effects	918 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
1,3-butadiene		
Remarks:	Substance is a hydrocarbon with a complex, unknown or variable composition. Conventional methods of deriving PNECs are not appropriate and it is not possible to identify a single representative PNEC for such substances.	
2-methylpropene		
Remarks:	Substance is a hydrocarbon with a complex, unknown or variable composition. Conventional methods of deriving PNECs are not appropriate and it is not possible to identify a single representative PNEC for such substances.	

8.2 Exposure controls

Engineering measures

Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Eye washes and showers for emergency use.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

General Information:

Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when there is potential for inhalation; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
4.0	28.01.2024	800001001021	Print Date 05.02.2024

place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.

Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : Wear goggles for use against liquids and gas, combined with face shield with chin guard.

Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. When prolonged or frequent repeated contact occurs. Viton. For incidental contact/splash protection - Neoprene rubber. If contact with liquefied product is possible or anticipated, gloves should be thermally insulated to prevent cold burns. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Skin and body protection : Chemical and cryogenic gloves/gauntlets, boots, and apron. Wear antistatic and flame-retardant clothing. Protective clothing approved to EU Standard EN14605.

Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
4.0	28.01.2024	800001001021	Print Date 05.02.2024

Check with respiratory protective equipment suppliers.
Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.

Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use:

Select a filter suitable for organic gases and vapours [Type AX boiling point < 65°C (149°F)] meeting EN14387.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : Liquid under pressure.

Colour : colourless

Odour : Hydrocarbon

Odour Threshold : Data not available

Melting point/freezing point : < -50 °C

Boiling point/boiling range : -4 °C

Flammability

Flammability (solid, gas) : Extremely flammable.

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit /
upper flammability limit : 12 %(V)

Lower explosion limit /
Lower flammability limit : 2 %(V)

Flash point : -76 °C
Method: No information available.

Auto-ignition temperature : > 350 °C

Decomposition temperature
Decomposition temperature : Data not available

pH : Not applicable

Viscosity

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version 4.0	Revision Date: 28.01.2024	SDS Number: 800001001021	Date of last issue: 21.11.2023 Print Date 05.02.2024
----------------	------------------------------	-----------------------------	---

Viscosity, kinematic	:	Data not available
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	log Pow: estimated value(s) 2,4 - 2,9
Vapour pressure	:	240 kPa (20 °C)
Relative density	:	0,670 (20 °C) Method: ASTM D4052
Density	:	670 kg/m ³ (20 °C) Method: ASTM D4052
Relative vapour density	:	1,9
Particle characteristics Particle size	:	Data not available

9.2 Other information

Explosive properties	:	no data available
Oxidizing properties	:	no data available
Evaporation rate	:	Data not available
Conductivity	:	Low conductivity: < 100 pS/m

The conductivity of this material makes it a static accumulator. A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m. Whether a liquid is nonconductive or semi-conductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid

Surface tension	:	Data not available
Molecular weight	:	Data not available

SECTION 10: Stability and reactivity

10.1 Reactivity

Reacts violently with strong oxidising agents.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
4.0	28.01.2024	800001001021	Print Date 05.02.2024

10.2 Chemical stability

Oxidises on contact with air to form unstable peroxides.
Unstable at elevated temperatures.

10.3 Possibility of hazardous reactions

Hazardous reactions : Polymerisation may occur at elevated temperatures.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames, and sparks.
Exposure to air.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.
If copper, copper alloys, monel, silver, mercury or magnesium is used during construction or maintenance, the formation of explosive acetylides can occur as a result of contact with butadiene. If Teflon® or Delrin® is used, polymer formation may result.

10.6 Hazardous decomposition products

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation is the primary route of exposure although exposure may occur through skin or eye contact.

Acute toxicity

Product:

Acute oral toxicity : Remarks: Acute oral toxicity
Not applicable

Acute inhalation toxicity : LC 50 (Rat, male and female): > 2311 ppm
Exposure time: 4 h
Test atmosphere: gas
Method: Test(s) equivalent or similar to OECD Test Guideline 403
Remarks: Based on available data, the classification criteria are not met.
High concentrations may cause central nervous system de-

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
4.0	28.01.2024	800001001021	Print Date 05.02.2024

pression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

Acute dermal toxicity : Remarks: Acute dermal toxicity
Not applicable

Components:

gases (petroleum, light steam-cracked, butadiene conc.:

Acute oral toxicity : Remarks: Acute oral toxicity
Not applicable

Acute inhalation toxicity : LC 50 (Rat, male and female): > 2311 ppm
Exposure time: 4 h
Test atmosphere: gas
Method: Test(s) equivalent or similar to OECD Test Guideline 403
Remarks: Based on available data, the classification criteria are not met.
High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

Acute dermal toxicity : Remarks: Acute dermal toxicity
Not applicable

Skin corrosion/irritation

Product:

Species : Rabbit
Method : Acceptable non-standard method.
Remarks : Slightly irritating to skin.
Insufficient to classify.
Rapid release of gases which are liquids under pressure may cause frost burns of exposed tissues (skin, eye) due to evaporative cooling.

Components:

gases (petroleum, light steam-cracked, butadiene conc.:

Species : Rabbit
Method : Acceptable non-standard method.
Remarks : Slightly irritating to skin.
Insufficient to classify.
Rapid release of gases which are liquids under pressure may cause frost burns of exposed tissues (skin, eye) due to evaporative cooling.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
4.0	28.01.2024	800001001021	Print Date 05.02.2024

Serious eye damage/eye irritation

Product:

Species	:	Rabbit
Method	:	Acceptable non-standard method.
Remarks	:	Based on available data, the classification criteria are not met. Rapid release of gases which are liquids under pressure may cause frost burns of exposed tissues (skin, eye) due to evaporative cooling.

Components:

gases (petroleum, light steam-cracked, butadiene conc.:

Species	:	Rabbit
Method	:	Acceptable non-standard method.
Remarks	:	Based on available data, the classification criteria are not met. Rapid release of gases which are liquids under pressure may cause frost burns of exposed tissues (skin, eye) due to evaporative cooling.

Germ cell mutagenicity

Product:

Genotoxicity in vitro	:	Method: Test(s) equivalent or similar to OECD Guideline 471 Test substance: 1,3-Butadiene Remarks: May cause genetic defects.
-----------------------	---	---

Method: Test(s) equivalent or similar to OECD Test Guideline 476
Test substance: 1,3-Butadiene
Remarks: May cause genetic defects.

Method: Test(s) equivalent or similar to OECD Test Guideline 476
Test substance: 1,3-Butadiene
Remarks: May cause genetic defects.

Method: OECD Test Guideline 482
Test substance: 1,3-Butadiene
Remarks: May cause genetic defects.

Genotoxicity in vivo	:	Species: Mouse Method: OECD Test Guideline 474 Test substance: 1,3-Butadiene Remarks: May cause genetic defects.
----------------------	---	---

Species: Mouse
Method: Test(s) equivalent or similar to OECD Test guideline 478
Test substance: 1,3-Butadiene
Remarks: May cause genetic defects.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
4.0	28.01.2024	800001001021	Print Date 05.02.2024

Germ cell mutagenicity- Assessment : May cause genetic defects.

Components:

gases (petroleum, light steam-cracked, butadiene conc.:

Genotoxicity in vitro : Method: Test(s) equivalent or similar to OECD Guideline 471
Test substance: 1,3-Butadiene
Remarks: May cause genetic defects.

Method: Test(s) equivalent or similar to OECD Test Guideline 476
Test substance: 1,3-Butadiene
Remarks: May cause genetic defects.

Method: Test(s) equivalent or similar to OECD Test Guideline 476
Test substance: 1,3-Butadiene
Remarks: May cause genetic defects.

Method: OECD Test Guideline 482
Test substance: 1,3-Butadiene
Remarks: May cause genetic defects.

Genotoxicity in vivo : Species: Mouse
Method: OECD Test Guideline 474
Test substance: 1,3-Butadiene
Remarks: May cause genetic defects.

Species: Mouse
Method: Test(s) equivalent or similar to OECD Test guideline 478
Test substance: 1,3-Butadiene
Remarks: May cause genetic defects.

Germ cell mutagenicity- Assessment : May cause genetic defects.

Carcinogenicity

Product:

Species : Mouse, male and female
Application Route : Inhalation
Method : Test(s) equivalent or similar to OECD Test Guideline 453
Test substance : 1,3-Butadiene
Remarks : May cause cancer.

Species : Rat, male and female
Application Route : Inhalation
Method : Test(s) equivalent or similar to OECD Test Guideline 453
Test substance : 1,3-Butadiene

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version 4.0 Revision Date: 28.01.2024 SDS Number: 800001001021 Date of last issue: 21.11.2023
Print Date 05.02.2024

Remarks : May cause cancer.

Carcinogenicity - Assessment : May cause cancer.

Components:

gases (petroleum, light steam-cracked, butadiene conc.:

Species : Mouse, male and female
Application Route : Inhalation
Method : Test(s) equivalent or similar to OECD Test Guideline 453
Test substance : 1,3-Butadiene
Remarks : May cause cancer.

Species : Rat, male and female
Application Route : Inhalation
Method : Test(s) equivalent or similar to OECD Test Guideline 453
Test substance : 1,3-Butadiene
Remarks : May cause cancer.

Carcinogenicity - Assessment : May cause cancer.

Material	GHS/CLP Carcinogenicity Classification
gases (petroleum, light steam-cracked, butadiene conc.	Carcinogenicity Category 1A
1,3-butadiene	Carcinogenicity Category 1A
2-methylpropene	No carcinogenicity classification.
Butene	No carcinogenicity classification.

Material	Other Carcinogenicity Classification
1,3-butadiene	IARC: Group 1: Carcinogenic to humans

Reproductive toxicity

Product:

Effects on fertility : Species: Rat
Sex: male and female
Application Route: Inhalation

Method: OECD Test Guideline 422
Remarks: Based on available data, the classification criteria are not met.

Reproductive toxicity - As- : This product does not meet the criteria for classification in

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version 4.0	Revision Date: 28.01.2024	SDS Number: 800001001021	Date of last issue: 21.11.2023 Print Date 05.02.2024
----------------	------------------------------	-----------------------------	---

assessment categories 1A/1B.

Components:

gases (petroleum, light steam-cracked, butadiene conc.:

Effects on fertility : Species: Rat
Sex: male and female
Application Route: Inhalation

Method: OECD Test Guideline 422
Remarks: Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

STOT - single exposure

Product:

Remarks : Based on available data, the classification criteria are not met.
Inhalation of vapours or mists may cause irritation to the respiratory system.
Not classified due to data which are conclusive although insufficient for classification.

Components:

gases (petroleum, light steam-cracked, butadiene conc.:

Remarks : Based on available data, the classification criteria are not met.
Inhalation of vapours or mists may cause irritation to the respiratory system.
Not classified due to data which are conclusive although insufficient for classification.

STOT - repeated exposure

Product:

Remarks : Based on available data, the classification criteria are not met.
Contains 1,3-butadiene.
Blood-forming organs: repeated exposure affects the bone marrow.
Reproductive system: repeated exposure affects the ovaries and testes in mice.
Exposure to very high concentrations of similar materials has been associated with irregular heart rhythms and cardiac arrest.
Not classified due to data which are conclusive although insufficient for classification.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
4.0	28.01.2024	800001001021	Print Date 05.02.2024

Components:

gases (petroleum, light steam-cracked, butadiene conc.:

Remarks : Based on available data, the classification criteria are not met.
Contains 1,3-butadiene.
Blood-forming organs: repeated exposure affects the bone marrow.
Reproductive system: repeated exposure affects the ovaries and testes in mice.
Exposure to very high concentrations of similar materials has been associated with irregular heart rhythms and cardiac arrest.
Not classified due to data which are conclusive although insufficient for classification.

Repeated dose toxicity

Product:

Species : Rat, male and female
Application Route : Oral
Method : Test(s) equivalent or similar to OECD Test Guideline 407
Target Organs : No specific target organs noted

Species : Rat, male and female
Application Route : Inhalation
Test atmosphere : vapour
Method : OECD Test Guideline 422
Target Organs : No specific target organs noted

Components:

gases (petroleum, light steam-cracked, butadiene conc.:

Species : Rat, male and female
Application Route : Oral
Method : Test(s) equivalent or similar to OECD Test Guideline 407
Target Organs : No specific target organs noted

Species : Rat, male and female
Application Route : Inhalation
Test atmosphere : vapour
Method : OECD Test Guideline 422
Target Organs : No specific target organs noted

Aspiration toxicity

Product:

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
4.0	28.01.2024	800001001021	Print Date 05.02.2024

Components:

gases (petroleum, light steam-cracked, butadiene conc.:

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

Remarks : Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Components:

gases (petroleum, light steam-cracked, butadiene conc.:

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : LC50 : 19 mg/l
Exposure time: 96 h
Method: Information given is based on data obtained from similar substances.
Remarks: Data not available

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): 11 mg/l
Exposure time: 48 h
Method: Information given is based on data obtained from similar substances.
Remarks: Data not available

Toxicity to algae/aquatic plants : EC50 : 7,7 mg/l

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
4.0	28.01.2024	800001001021	Print Date 05.02.2024

Exposure time: 96 h
Method: Information given is based on data obtained from similar substances.
Remarks: Data not available

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: Data not available

Toxicity to microorganisms :
Remarks: Data not available

Components:

gases (petroleum, light steam-cracked, butadiene conc.:

Toxicity to fish : LC50 : 19 mg/l
Exposure time: 96 h
Method: Information given is based on data obtained from similar substances.
Remarks: Data not available

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): 11 mg/l
Exposure time: 48 h
Method: Information given is based on data obtained from similar substances.
Remarks: Data not available

Toxicity to algae/aquatic plants : EC50 : 7,7 mg/l
Exposure time: 96 h
Method: Information given is based on data obtained from similar substances.
Remarks: Data not available

Toxicity to microorganisms :
Remarks: Data not available

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: Data not available

12.2 Persistence and degradability

Product:

Biodegradability : Biodegradation: 50 %
Exposure time: 3,5 d
Method: Information given is based on data obtained from

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
4.0	28.01.2024	800001001021	Print Date 05.02.2024

similar substances.
Remarks: Readily biodegradable.

Components:

gases (petroleum, light steam-cracked, butadiene conc.:

Biodegradability : Biodegradation: 50 %
Exposure time: 3,5 d
Method: Information given is based on data obtained from similar substances.
Remarks: Readily biodegradable.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Does not have the potential to bioaccumulate significantly.

Components:

gases (petroleum, light steam-cracked, butadiene conc.:

Bioaccumulation : Remarks: Does not have the potential to bioaccumulate significantly.

12.4 Mobility in soil

Product:

Mobility : Remarks: Because of their extreme volatility, air is the only environmental compartment that petroleum gases will be found.

Components:

gases (petroleum, light steam-cracked, butadiene conc.:

Mobility : Remarks: Because of their extreme volatility, air is the only environmental compartment that petroleum gases will be found.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

Components:

gases (petroleum, light steam-cracked, butadiene conc.:

Assessment : The substance does not fulfill all screening criteria for persis-

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
4.0	28.01.2024	800001001021	Print Date 05.02.2024

tence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : Physical properties indicate that petroleum gases will rapidly volatilise from the aquatic environment and that acute and chronic effects would not be observed in practice.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Components:

gases (petroleum, light steam-cracked, butadiene conc.:

Additional ecological information : Physical properties indicate that petroleum gases will rapidly volatilise from the aquatic environment and that acute and chronic effects would not be observed in practice.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water courses.
Waste product should not be allowed to contaminate soil or water.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local regulations may be more stringent than regional or national requirements and must be complied with.

Contaminated packaging : Drain container thoroughly.
After draining, vent in a safe place away from sparks and fire.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
4.0	28.01.2024	800001001021	Print Date 05.02.2024

Residues may cause an explosion hazard.
Do not puncture, cut, or weld uncleaned drums.
Send to drum recoverer or metal reclaimer.

SECTION 14: Transport information

14.1 UN number or ID number

ADN	: 1010
ADR	: 1010
RID	: 1010
IMDG	: 1010
IATA	: 1010

14.2 UN proper shipping name

ADN	: BUTADIENES AND HYDROCARBON MIXTURE, STABILIZED
ADR	: BUTADIENES AND HYDROCARBON MIXTURE, STABILIZED
RID	: BUTADIENES AND HYDROCARBON MIXTURE, STABILIZED
IMDG	: BUTADIENES AND HYDROCARBON MIXTURE, STABILIZED
IATA	: BUTADIENES AND HYDROCARBON MIXTURE, STABILIZED

14.3 Transport hazard class(es)

ADN	: 2
ADR	: 2
RID	: 2
IMDG	: 2.1
IATA	: 2.1

14.4 Packing group

ADN	
Packing group	: Not Assigned
Classification Code	: 2F
Labels	: 2.1 (INST, CMR)
CDNI Inland Water Waste Agreement	: NST 3303 Refinery gasses
ADR	
Packing group	: Not assigned by regulation
Classification Code	: 2F
Hazard Identification Number	: 239
Labels	: 2.1

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
4.0	28.01.2024	800001001021	Print Date 05.02.2024

RID

Packing group	:	Not assigned by regulation
Classification Code	:	2F
Hazard Identification Number	:	239
Labels	:	2.1

IMDG

Packing group	:	Not assigned by regulation
Labels	:	2.1

IATA

Packing group	:	Not Assigned
Labels	:	2.1

14.5 Environmental hazards

ADN

Environmentally hazardous	:	no
---------------------------	---	----

ADR

Environmentally hazardous	:	no
---------------------------	---	----

RID

Environmentally hazardous	:	no
---------------------------	---	----

IMDG

Marine pollutant	:	no
------------------	---	----

14.6 Special precautions for user

Remarks	:	Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.
---------	---	--

14.7 Maritime transport in bulk according to IMO instruments

Ship type	:	2G/2PG
Product name	:	Mixed C4 cargoes

Additional Information	:	Transport in bulk according to the IGC code
-------------------------------	---	---

This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Not applicable
--	---	----------------

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version 4.0	Revision Date: 28.01.2024	SDS Number: 800001001021	Date of last issue: 21.11.2023 Print Date 05.02.2024
----------------	------------------------------	-----------------------------	---

REACH - List of substances subject to authorisation (Annex XIV)	:	Product is not subject to Authorisation under REACH.
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.	18	Liquefied flammable gases (including LPG) and natural gas

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Product is subject to Major accident risk decision 2015 (BRZO+) based on Seveso III directive (2012/18/EU).

Product meets one or more criteria set for the Dutch list of 'substances of concern' (zeer zorgwekkende stoffen (ZZS)).

The components of this product are reported in the following inventories:

AIIC	:	Listed
DSL	:	Listed
KECI	:	Listed
TSCA	:	Listed

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Full text of other abbreviations

NL WG	:	Netherlands. Law on Labour conditions - Occupational Exposure Limits
NL WG / TLV-8hr	:	Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regula-

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
4.0	28.01.2024	800001001021	Print Date 05.02.2024

tion (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

- Training advice : Provide adequate information, instruction and training for operators.
- Other information : The substance/product is registered with strictly controlled conditions as defined in Article 18(4) of Regulation (EC) No. 1907/2006 (REACH Regulation) and must therefore be handled as such. Refer to the industry guidance prepared by Concawe/Cefic for advice on the demonstration of strictly controlled conditions available from: <http://cefic.org>.
If this substance/product is sold onto third parties, confirmation that the substance/product will be handled in accordance with 'strictly controlled conditions' needs to be obtained from the third party prior to sale.
For Industry guidance and tools on REACH please visit the CEFIC website at <http://cefic.org/Industry-support>.
The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.
A vertical bar (|) in the left margin indicates an amendment from the previous version.
- Sources of key data used to compile the Safety Data : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Crude C4

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2023
4.0	28.01.2024	800001001021	Print Date 05.02.2024

Sheet	Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).
-------	--

Classification of the mixture:

Flam. Gas 1A	H220
Press. Gas Liquefied gas	H280
Muta. 1B	H340
Carc. 1A	H350

Classification procedure:

On basis of test data.
On basis of test data.
Expert judgement and weight of evidence determination.
Expert judgement and weight of evidence determination.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NL / EN