CARADOL SP37-25

Print Date 07.02.2025 Revision Date 07.02.2025 Version 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : CARADOL SP37-25

Product code : U317F

Synonyms Polyol

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Use for the manufacture of polyurethane products.

Substance/Mixture

Uses advised against : This product must not be used in applications other than the

above without first seeking the advice of the supplier.

This product must not be used in applications other than those

listed in Section 1 without first seeking the advice of the

supplier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : Shell Trading (M.E.) Pvt. Ltd.

> PO Box 16968 16968 Jebel Ali Unit.Arab Emir. : +971 4 331 6500 : +971 4 332 1597

: sccmsds@shell.com

Telefax Contact for Safety Data

Sheet

Telephone

1.4 Emergency telephone number

+ (65) 6542 9595 (Alert-SGS)

Other information : CARADOL is a trademark owned by Shell Trademark

Management B.V. and Shell Brands Inc. and used by affiliates

of Shell plc.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification

Based on available data this substance / mixture does not meet the classification criteria.

2.2 Label elements

CARADOL SP37-25

Print Date 07.02.2025 Revision Date 07.02.2025 Version 2.0

GHS-Labelling

Hazard pictograms : No Hazard Symbol required

Signal word : No signal word

Hazard statements : PHYSICAL HAZARDS:

Not classified as a physical hazard under GHS criteria.

HEALTH HAZARDS:

Not classified as a health hazard under GHS criteria.

ENVIRONMENTAL HAZARDS:

Not classified as an environmental hazard under GHS criteria.

Precautionary statements : **Prevention:**

No precautionary phrases.

Response:

No precautionary phrases.

Storage:

No precautionary phrases.

Disposal:

No precautionary phrases.

2.3 Other hazards

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

| Chemical name | CAS-No. | Classification | Concentration (% w/w) |
|-------------------------------|------------|----------------|-----------------------|
| Polyalkylene glycol | 9082-00-2 | | 70 - 80 |
| Styrene-acrylonitrile polymer | 57913-80-1 | | 20 - 30 |

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Not expected to be a health hazard when used under normal

conditions.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

If inhaled : No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

| | C | ARADOL SP37-25 |
|-------------------------|--|-------------------------|
| Print Date 07.02.2025 | Revision Date 07.02.2025 | Version 2.0 |
| | | |
| In case of skin contact | Remove contaminated clothing. Flus water and follow by washing with soa If persistent irritation occurs, obtain r | ap if available. |
| In case of eye contact | Flush eye with copious quantities of Remove contact lenses, if present arrinsing. If persistent irritation occurs, obtain r | nd easy to do. Continue |
| If swallowed | : In general no treatment is necessary | unless large quantities |

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Not considered to be an inhalation hazard under normal

conditions of use.

Possible respiratory irritation signs and symptoms may include

a temporary burning sensation of the nose and throat,

coughing, and/or difficulty breathing.

No specific hazards under normal use conditions.

are swallowed, however, get medical advice.

Skin irritation signs and symptoms may include a burning

sensation, redness, or swelling.

Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision. Ingestion may result in nausea, vomiting and/or diarrhoea.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Call a doctor or poison control center for guidance.

Treat symptomatically. Following cases of gross overexposure, investigation of liver, kidney and eye function may be advisable. Records of such incidents should be maintained

for future reference.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Large fires should only be fought by properly trained fire

fighters., Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used

for small fires only.

Unsuitable extinguishing

media

: Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Will only burn if enveloped in a pre-existing fire. Hazardous

combustion products may include: Carbon dioxide Unidentified organic and inorganic compounds. Toxic gases

Carbon monoxide.

| | C | ARADOL SP37-25 |
|---|--|-----------------------|
| Print Date 07.02.2025 | Revision Date 07.02.2025 | Version 2.0 |
| 5.3 Advice for firefighters | | |
| Special protective equipment for firefighters | : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469). | |
| Specific extinguishing methods | : Standard procedure for chemical fire | |
| Further information | Clear fire area of all non-emergency All storage areas should be provided fighting facilities. Keep adjacent containers cool by spi | with adequate fire |

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions

Observe all relevant local and international regulations.

Avoid contact with skin, eyes and clothing.

Avoid inhaling vapour and/or mists.

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

6.2 Environmental precautions

Environmental precautions : Remove all possible sources of ignition in the surrounding

area.

Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers. Use appropriate containment to avoid environmental

contamination.

Ventilate contaminated area thoroughly.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : For large liquid spills (> 1 drum), transfer by mechanical

means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an

| CARADOL SP37-25 |
|-----------------|
| |

Print Date 07.02.2025 Revision Date 07.02.2025 Version 2.0

appropriate absorbent material and dispose of safely. Remove

contaminated soil and dispose of safely.

Proper disposal should be evaluated based on regulatory status of this material (refer to Section 13), potential contamination from subsequent use and spillage, and regulations governing disposal in the local area.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

General Precautions : Avoid breathing of or direct contact with material. Only use in

well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

Section 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine

appropriate controls for safe handling, storage and disposal of

this material.

Ensure that all local regulations regarding handling and

storage facilities are followed.

7.1 Precautions for safe handling

Advice on safe handling : In accordance with good industrial hygiene practices,

precautions should be taken to avoid breathing of material.

Use local exhaust extraction over processing area.

Avoid unintentional contact with isocyanates to prevent

uncontrolled polymerisation.

Avoid contact with skin, eyes and clothing.

Air-dry contaminated clothing in a well-ventilated area before

laundering.

Do not empty into drains. Handling Temperature:

Ambient.

When handling product in drums, safety footwear should be

worn and proper handling equipment should be used.

Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

Product Transfer : Lines should be purged with nitrogen before and after product

transfer. Keep containers closed when not in use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Refer to section 15 for any additional specific legislation

covering the packaging and storage of this product.

| | CARADOL | SP37-25 |
|-------------------------|---|--|
| Print Date 07.02.2025 | Revision Date 07.02.2025 | Version 2.0 |
| Other data : | Prevent all contact with water and with moist atmotanks must be clean, dry and rust-free. Prevent in water. Must be stored in a diked (bunded) well-vearea, away from sunlight, ignition sources and oth of heat. Nitrogen blanket recommended for large (capacity 100 m3 or higher). Drums should be stamaximum of 3 high. | ngress of entilated ner sources tanks |
| Storage period : | 24 month(s) | |
| | Storage Temperature: Ambient. | |
| | Storage should be handled at temperatures such viscosities are less than 500 cSt; typically at 25-5 should be fitted with heating coils in areas where temperatures are below the recommended productemperatures. Heating coil skin temperatures sho exceed 100 °C. | 0 °C. Tanks the ambient ct handling |
| Packaging material : | Suitable material: Stainless steel. For container per epoxy paint, zinc silicate paint. Unsuitable material: Copper. Copper alloys. | oaints, use |
| 7.3 Specific end use(s) | | |
| Specific use(s) : | : Not applicable | |
| | Ensure that all local regulations regarding handlin storage facilities are followed. | ng and |

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Biological occupational exposure limits

No biological limit allocated.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Polyalkylene glycol : No DNEL value has been established.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

CARADOL SP37-25

 Print Date 07.02.2025
 Revision Date 07.02.2025
 Version 2.0

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

8.2 Exposure controls

Engineering measuresWhere material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

Adequate ventilation to control airborne concentrations.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

General Information

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended.

Hand protection

Remarks : Where hand contact with the product may occur the use of

gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber. Incidental contact/Splash protection: PVC, neoprene or nitrile rubber gloves For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the

| | CARADO | L SP37-25 |
|---------------------------------|---|---|
| Print Date 07.02.2025 | Revision Date 07.02.2025 | Version 2.0 |
| | same but recognize that suitable gloves offering a protection may not be available and in this case a breakthrough time maybe acceptable so long as maintenance and replacement regimes are follow thickness is not a good predictor of glove resistar chemical as it is dependent on the exact compos glove material. Glove thickness should be typical than 0.35 mm depending on the glove make and Suitability and durability of a glove is dependent e.g. frequency and duration of contact, chemical glove material, dexterity. Always seek advice fror suppliers. Contaminated gloves should be replace hygiene is a key element of effective hand care. Only be worn on clean hands. After using gloves, should be washed and dried thoroughly. Applicate perfumed moisturizer is recommended. | this level of a lower appropriate yed. Glove nee to a ition of the ly greater model. on usage, resistance of m glove ed. Personal Gloves must hands |
| Skin and body protection : | Skin protection is not ordinarily required beyond swork clothes. It is good practice to wear chemical resistant gloves. | |
| Respiratory protection : | No respiratory protection is ordinarily required un conditions of use. In accordance with good industrial hygiene practi precautions should be taken to avoid breathing o | ces, |
| Hygiene measures : | Wash hands before eating, drinking, smoking and toilet. Launder contaminated clothing before re-u | |
| Environmental exposure controls | | |
| General advice : | Local guidelines on emission limits for volatile su must be observed for the discharge of exhaust ai vapour. Minimise release to the environment. An environ assessment must be made to ensure compliance environmental legislation. Information on accidental release measures are t section 6. | r containing mental with local |

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Viscous liquid.

Colour : white
Odour : odourless

Odour Threshold : Data not available

CARADOL SP37-25

Print Date 07.02.2025 Revision Date 07.02.2025 Version 2.0

pH : Data not available

Melting point/freezing point : -18 °C

Boiling point/boiling range : Data not available

Flash point : Typical > 200 °C

Method: ASTM D93 (PMCC)

Evaporation rate : Data not available

Flammability

Flammability (solid, gas) : Not applicable

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit : Data not available Lower explosion limit : Data not available

Vapour pressure : Data not available (50 °C)

Relative vapour density : Data not available Relative density : Data not available

Density : Typical 1.020 kg/m3 (25 °C)

Method: ASTM D4052

Solubility(ies)

Water solubility : negligible

Solubility in other solvents : Data not available

Partition coefficient: n-

octanol/water

: Data not available

Auto-ignition temperature : Data not available

Decomposition temperature : Data not available

Viscosity

Viscosity, dynamic : Typical 2.000 mPa.s (20 °C)

Method: ASTM D445

Typical 50 mPa.s (> 100 °C) Method: ASTM D445

Viscosity, kinematic : Data not available Explosive properties : Not applicable

Oxidizing properties : Data not available

CARADOL SP37-25

Print Date 07.02.2025 Revision Date 07.02.2025 Version 2.0

9.2 Other information

Surface tension : Data not available

Conductivity: > 10,000 pS/m

A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be

a static accumulator.

Molecular weight : Data not available

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions, Hygroscopic.

10.3 Possibility of hazardous reactions

Hazardous reactions : Polymerises exothermically with di-isocyanates at ambient

temperatures.

The reaction becomes progressively more vigorous and can be violent at higher temperatures if the miscibility of reaction partners is good or is supported by stirring or by the presence

of solvents.

Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames, and sparks.

Product cannot ignite due to static electricity.

10.5 Incompatible materials

Materials to avoid : Avoid contact with isocyanates, copper and copper alloys,

zinc, strong oxidizing agents, and water.

10.6 Hazardous decomposition products

Hazardous decomposition

products

: Unknown toxic products may be formed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

CARADOL SP37-25

Print Date 07.02.2025 Revision Date 07.02.2025 Version 2.0

Basis for assessment : Information given is based on data obtained from similar

substances.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for

individual component(s).

exposure

Information on likely routes of : Exposure may occur via inhalation, ingestion, skin absorption,

skin or eye contact, and accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity : LD 50 : > 2.000 mg/kg

Remarks: Based on available data, the classification criteria

are not met.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria

are not met.

Acute dermal toxicity : LD 50 : > 2.000 mg/kg

Remarks: Low toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

: Remarks: Based on available data, the classification criteria

are not met.

Carcinogenicity

Product:

CARADOL SP37-25

Print Date 07.02.2025 Revision Date 07.02.2025 Version 2.0

Remarks: Based on available data, the classification criteria are not met.

| Material | GHS/CLP Carcinogenicity Classification |
|-------------------------------|--|
| Polyalkylene glycol | No carcinogenicity classification. |
| Styrene-acrylonitrile polymer | No carcinogenicity classification. |

Reproductive toxicity

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

CARADOL SP37-25

Print Date 07.02.2025 Revision Date 07.02.2025 Version 2.0

SECTION 12: Ecological information

12.1 Toxicity

Basis for assessment : Incomplete ecotoxicological data are available for this product.

> The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.

Unless indicated otherwise, the data presented is

representative of the product as a whole, rather than for

individual component(s).

Product:

Toxicity to fish (Acute

toxicity)

: LC50 : > 100 mg/l

Remarks: Based on available data, the classification criteria

are not met.

Practically non toxic:

Toxicity to daphnia and other

aquatic invertebrates (Acute

toxicity)

: EC50 : > 100 mg/l

Remarks: Based on available data, the classification criteria

are not met.

Practically non toxic:

Toxicity to algae (Acute

toxicity)

: EC50 : > 100 mg/l

Remarks: Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic

toxicity)

aquatic invertebrates (Chronic toxicity)

Toxicity to bacteria (Acute

toxicity)

: Remarks: Data not available

Toxicity to daphnia and other : Remarks: Data not available

: IC50 : > 100 mg/l

Remarks: Based on available data, the classification criteria

are not met.

Practically non toxic:

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: Readily biodegradable.

No data available

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

CARADOL SP37-25

Print Date 07.02.2025 Revision Date 07.02.2025 Version 2.0

Partition coefficient: n-

octanol/water

: Remarks: Data not available

12.4 Mobility in soil

Product:

Mobility : Remarks: If the product enters soil, one or more constituents

will or may be mobile and may contaminate groundwater.

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses.

Waste product should not be allowed to contaminate soil or

water.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or

national requirements and must be complied with.

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Send to drum recoverer or metal reclaimer.

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

Local legislation

SECTION 14: Transport information

14.1 UN number

ADR : Not regulated as a dangerous good

| | CARADOL | SP37-25 |
|-------------------------------------|---|---------------------------|
| Print Date 07.02.2025 | Revision Date 07.02.2025 | Version 2.0 |
| F IIII Date 07:02.2025 | Nevision Date 07.02.2025 | V 6131011 2.0 |
| IMDG | : Not regulated as a dangerous good | |
| IATA | : Not regulated as a dangerous good | |
| 14.2 Proper shipping name | | |
| ADR | : Not regulated as a dangerous good | |
| IMDG | : Not regulated as a dangerous good | |
| IATA | : Not regulated as a dangerous good | |
| 14.3 Transport hazard class | | |
| ADR | : Not regulated as a dangerous good | |
| IMDG | : Not regulated as a dangerous good | |
| IATA | : Not regulated as a dangerous good | |
| 14.4 Packing group | | |
| ADR | : Not regulated as a dangerous good | |
| IMDG | : Not regulated as a dangerous good | |
| IATA | : Not regulated as a dangerous good | |
| 14.5 Environmental hazards | | |
| ADR | : Not regulated as a dangerous good | |
| IMDG | : Not regulated as a dangerous good | |
| 14.6 Special precautions for user | | |
| Remarks | : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport. | |
| 14.7 Maritime transport in bulk acc | ording to IMO instruments | |
| Pollution category | : Y | |
| Ship type | : 3 | |
| Product name | : Acrylonitrile-Styrene Copolymer Dispersion in Polyeth | ner Polyol |
| Additional Information | : This product may be transported under nitrogen blank Nitrogen is an odourless and invisible gas. Exposure nitrogen enriched atmospheres displaces available or which may cause asphyxiation or death. Personnel mobserve strict safety precautions when involved with a confined space entry. Transport in bulk according to Annex II of Marpol and Code | eto xygen nust a |

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations : The regulatory information is not intended to be

comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

| | | CARADOL SP37-25 |
|--|--|-----------------|
| Print Date 07.02.2025 | Revision Date 07.02.2025 | Version 2.0 |
| TSCA AIIC DSL IECSC KECI NZIOC PICCS ENCS TCSI | : Listed | |

SECTION 16: Other information

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this

document can be looked up in reference literature (e.g.

scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial

Hygienists

ADR = European Agreement concerning the International

Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council

CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut fur Normung DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission

EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and

Toxicology Of Chemicals

ECHA = European Chemicals Agency

EINECS = The European Inventory of Existing Commercial

Chemical Substances

EL50 = Effective Loading fifty

ENCS = Japanese Existing and New Chemical Substances

Inventory

EWC = European Waste Code

GHS = Globally Harmonised System of Classification and

16 / 17 800001006227

CARADOL SP37-25

Print Date 07.02.2025 Revision Date 07.02.2025 Version 2.0

Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IC50 = Inhibitory Concentration fifty

IL50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous Goods

INV = Chinese Chemicals Inventory

IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables

KECI = Korea Existing Chemicals Inventory

LC50 = Lethal Concentration fifty LD50 = Lethal Dose fifty per cent.

LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading

LL50 = Lethal Loading fifty

MARPOL = International Convention for the Prevention of

Pollution From Ships

NOEC/NOEL = No Observed Effect Concentration / No

Observed Effect Level

OE_HPV = Occupational Exposure - High Production Volume

PBT = Persistent, Bioaccumulative and Toxic

PICCS = Philippine Inventory of Chemicals and Chemical

Substances

PNEC = Predicted No Effect Concentration

REACH = Registration Evaluation And Authorisation Of

Chemicals

RID = Regulations Relating to International Carriage of

Dangerous Goods by Rail SKIN_DES = Skin Designation STEL = Short term exposure limit TRA = Targeted Risk Assessment

TSCA = US Toxic Substances Control Act

TWA = Time-Weighted Average

vPvB = very Persistent and very Bioaccumulative

Further information

Training advice : Provide adequate information, instruction and training for

operators.

Other information : A vertical bar (|) in the left margin indicates an amendment

from the previous version.

Sources of key data used to

compile the Safety Data

Sheet

: The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.