

SAFETY DATA SHEET

Issuing Date January 5, 2015 **Revision Date** New **Revision Number** 0

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Kingsford® Match Light® Instant Charcoal Briquets

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended use Fuel for cooking food outdoors

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Address

The Clorox Company 1221 Broadway Oakland, CA 94612

Phone: 1-510-271-7000

Emergency telephone number

Emergency Phone Numbers For Medical Emergencies, call: 1-800-446-1014

For Transportation Emergencies, call Chemtrec: 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Carcinogenicity	Category 1A
Toxic to reproduction	Category 1B

GHS Label elements, including precautionary statements

Emergency Overview

Signal word Danger

Hazard Statements

May cause cancer (inhalation).

May damage fertility or the unborn child.



Appearance Square black briquet

Physical State Solid

Odor Petroleum solvent

Precautionary Statements - Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear eye protection such as safety glasses.

Do not breathe dust.

Precautionary Statements - Response

If exposed or concerned: Get medical advice.

Precautionary Statements - Storage

Store locked up.

Precautionary Statements - Disposal

Dispose of contents in accordance with all applicable federal, state, and local regulations.

Hazards not otherwise classified (HNOC)

CARBON MONOXIDE HAZARD. Burning charcoal inside without adequate ventilation can kill you. It gives off carbon monoxide, which has no odor. NEVER burn charcoal inside homes, vehicles, or tents.

Vapors may cause irritation to the nose, throat, and respiratory tract. Repeated or prolonged exposure to concentrations above the Worker Exposure Limit may cause central nervous system depression (e.g. dizziness, weakness, nausea, headaches and/or unconsciousness).

Solvents similar to those contained in this product have caused adverse kidney effects in male rats after prolonged and repeated inhalation exposure. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage.

Unknown Toxicity

60 - 80% of the mixture consists of ingredients of unknown toxicity.

Other information

Never barbeque indoors. Do not use lighter fluid or an electric or chimney-style starter. Never cover flaming briquets with a grill lid. Covering flaming briquets may result in a flare-up when lid is removed. Barbecue away from flammable items, overhangs, and trees. Do not add Match Light® charcoal once fire has been lit. Make sure ashes are cold before discarding.

Interactions with Other Chemicals

Reacts with strong oxidizers to catch on fire.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Trade Secret
Charcoal	16291-96-6	60 - 80	*
Limestone	1317-65-3	< 20	*
Petroleum distillates, hydrotreated light	64742-47-8	10 - 15	*
Wood dust, all soft and hard woods	RR-00514-1	< 10	*
Sodium tetraborate decahydrate	1303-96-4	0.1 - 0.9	*

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures

General Advice Show this safety data sheet to the doctor in attendance.

Eve Contact Hold eye open and rinse slowly and gently with water for 15 - 20 minutes. Remove contact

lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control

center or doctor for treatment advice.

Skin Contact Wash skin with soap and water. If irritation persists, call a doctor.

Inhalation Move to fresh air. If breathing problems develop, call a doctor.

Ingestion Drink a glassful of water. Call a doctor or poison control center.

Protection of First-aiders Avoid contact with skin, eyes, and clothing. Use personal protective equipment as

required. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and

Effects

Vapors may cause irritation to the nose, throat, and respiratory tract. Dust may cause eye

irritation. Inhalation of dust may irritate nose and throat.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

None known.

Specific Hazards Arising from the Chemical

None known.

Explosion Data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with eyes. Ensure adequate ventilation. Use personal protective

equipment as required.

Other Information Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental Precautions See Section 12 for ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further spillage if safe to do so.

Methods for Cleaning Up Remove heat and ignition sources. Vacuum sweep, if possible, to avoid generating

airborne dust. Wash residual to on-site treatment area, where appropriate. If treatment area is not available, wash down to sanitary sewer. Contact the sanitary treatment facility

in advance to assure ability to process washed-down material.

7. HANDLING AND STORAGE

Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice. Ensure adequate

ventilation. Avoid contact with skin, eyes, and clothing.

Conditions for safe storage, including any incompatibilities

Storage Store locked up in a well-ventilated and dry area away from open flames, heat sources, and

other ignition sources. Keep bag closed to avoid evaporation.

Incompatible Products Strong oxidizers.

Dama 4.14

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH	
Charcoal 16291-96-6	TWA - 0.4 mg/m ³ (dust, respirable fraction) ^a ^a based on TWA for anthracite coal dust	None	None	
Limestone 1317-65-3	None	TWA - 15 mg/m³ (total dust) TWA - 5 mg/m³ (respirable fraction)	TWA - 15 mg/m ³ (total dust) TWA - 5 mg/m ³ (respirable dust)	
Petroleum distillates, hydrotreated light 64742-47-8	TWA - 100 ppm ^b ^b Based on TWA for Stoddard solvent	TWA - 500 ppm ^d ^d Based on TWA for Stoddard solvent	IDLH ^e - 20000 mg/m ³ Ceiling ^e - 1800 mg/m ³ (15 min) TWA ^e - 350 mg/m ³ ^e Based on limits for Stoddard solvent	
Wood dust, all soft and hard woods RR-00514-1	TWA - 1 mg/m ³ (inhalable fraction)	None	TWA - 1 mg/m ³	
Sodium tetraborate decahydrate 1303-96-4 STEL - 6 mg/m³ (inhalable fraction)° STEL - 2 mg/m³ (inhalable fraction)° °Listed under borate compounds, inorganic		None	TWA - 1 mg/m³	

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH: Immediately Dangerous to Life or Health.

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Wear safety glasses.

Skin and Body Protection Wear rubber or neoprene gloves.

Respiratory ProtectionNo protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should

be worn. Respiratory protection must be provided in accordance with current local

regulations.

Handle in accordance with good industrial hygiene and safety practice. Wash hands after

handling product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical State Solid

AppearanceSquare briquetOdorPetroleum solventColorBlackOdor ThresholdNo information available

Property
pHValues
Not applicableRemarks/ Method
None known

pH Not applicable
Melting/freezing point No data available
Boiling point / boiling range No data available
Flash Point ~40°C (solvent)
Evaporation rate No data available
Flammability (solid, gas) No data available

Flammability Limits in Air

Upper flammability limit No data available Lower flammability limit No data available Vapor pressure No data available Vapor density No data available **Bulk density** ~0.7 g/cm³ Water Solubility Insoluble in water Solubility in other solvents No data available Partition coefficient: n-octanol/waterNo data available **Autoignition temperature** No data available **Decomposition temperature** No data available Kinematic viscosity No data available Dynamic viscosity No data available **Explosive Properties** Not explosive **Oxidizing Properties** No data available

Other Information

Softening PointNo data availableVOC Content (%)No data availableParticle SizeNo data availableParticle Size DistributionNo data available

None known None known None known None known None known None known

None known
None known
None known
None known
None known
None known
None known
None known
None known
None known
None known
None known
None known

Revision Date New

Reactivity

Reacts with strong oxidizers to catch on fire.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Flames, heat sources, and ignition sources.

Incompatible materials

Strong oxidizers.

Hazardous Decomposition Products

None known.

11. TOXICOLOGICAL INFORMATION

10. STABILITY AND REACTIVITY

Information on likely routes of exposure

Product Information

Inhalation Inhalation may irritate nose, throat, and respiratory tract.

Eye Contact Dust may cause temporary eye irritation.

Skin Contact Minor or no effects expected.

Ingestion Minor or no effects expected.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Petroleum distillates, hydrotreated light 64742-47-8	>5 g/kg (Rat)	>2 g/kg (Rabbit)	>5.2 mg/L (Rat, 4 h)
Sodium tetraborate decahydrate 1303-96-4	3.5 g/kg (Rat)	>10 g/kg (Rabbit)	-

Information on toxicological effects

Symptoms May cause redness and tearing of the eyes. Inhalation of dust may irritate respiratory

tract.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Wood dust,				
all soft and hard woods		Group 1	Known	X
RR-00514-1				

ACGIH: (American Conference of Governmental Industrial Hygienists)

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans NTP: (National Toxicology Program)

Known - Known Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity Contains a known or suspected reproductive toxin (sodium tetraborate decahydrate).

STOT - single exposure No information available.

STOT - repeated exposure

No information available. **Chronic Toxicity**

Contains a known or suspected carcinogen. Contains a known or suspected reproductive toxin. Possible risk of irreversible effects. Wood dust has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen (Group 1). Studies have linked wood dust to nasal cancer in furniture industry workers. Woodworkers in the building industry (e.g. carpenters) do not appear to have this increased risk. Due to the product form and typical use conditions, significant dust exposures are

unlikely, and, therefore, the potential for any chronic effects is low.

Target Organ Effects Respiratory system, reproductive system, eyes.

Aspiration Hazard Not an aspiration hazard.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Persistence and Degradability

No information available.

Bioaccumulation

No information available.

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Reclaim, if possible; otherwise dispose of in accordance with all applicable federal, state, and local regulations.

Contaminated Packaging

Dispose of in accordance with all applicable federal, state, and local regulations.

14. TRANSPORT INFORMATION

DOT Not restricted per 49 CFR 172.101(c)(12)(iv).

TDG Not restricted per TDG regulations Part 146(c)(iii).

ICAO Carbon, not activated. Not restricted. Passes self-heating carbon test.

<u>IATA</u> Carbon, not activated. Not restricted. Passes self-heating carbon test.

IMDG/IMO Carbon, not activated. Not restricted. Passes self-heating carbon test.

15. REGULATORY INFORMATION

Chemical Inventories

TSCA All components of this product are either on the TSCA 8(b) Inventory or otherwise exempt

from listing.

DSL/NDSL All components are on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute Health HazardNoChronic Health HazardYesFire HazardYesSudden Release of Pressure HazardNoReactive HazardNo

Clean Water Act

This product does not contain any substances that are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

Page 9/10

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

California Proposition 65 Warning: Combustion (burning) of this product, like other cooking methods, produces carbon monoxide and other substances known by the State of California to cause cancer, birth defects, or reproductive harm.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Limestone 1317-65-3		Х	Χ	Х	
Sodium tetraborate decahydrate 1303-96-4	Х	Х	X		
Wood dust, all soft and hard woods RR-00514-1	Х				

International Regulations

Canada WHMIS Hazard Class D2A - Very toxic material



16. OTHER INFORMATION

NFPA Health Hazard 0 Flammability 1 Instability 0 Physical and Chemical Hazards -

HMIS Health Hazard 0* Flammability 1 Physical Hazard 0 Personal Protection A

.*Indicates a chronic health hazard

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Revision Date New

Revision Note New

Reference 1015711/128727.001

General Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet