Thermo Fisher SCIENTIFIC

SAFETY DATA SHEET

Page 1/10 Creation Date 22-Aug-2013 Revision Date 07-Apr-2024 Version 5

ACR38065

Lithium (trimethylsilyl)acetylide, 0.5M solution in THF

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

产品说明: 三甲基硅烷基乙炔锂.0.5M四氢呋喃溶液

Product Description: Lithium (trimethylsilyl)acetylide, 0.5M solution in THF

Cat No.: 380650000; 380651000; 380658000 (Trimethylsilyl)ethynyl lithium **Synonyms**

Supplier UK entity/business name

Fisher Scientific UK Bishop Meadow Road,

Loughborough, Leicestershire LE11 5RG, United Kingdom

EU entity/business name Thermo Fisher Scientific

Janssen Pharmaceuticalaan 3a, 2440 Geel, Belgium

Emergency Telephone Number For information US call: 001-800-227-6701 / Europe call: +32 14 57 52 11

Emergency Number US:001-201-796-7100 / Europe: +32 14 57 52 99 CHEMTREC Tel. No. US:001-800-424-9300 / Europe:001-703-527-3887

E-mail address begel.sdsdesk@thermofisher.com

Recommended Use Laboratory chemicals. No Information available Uses advised against

SECTION 2. HAZARD IDENTIFICATION

Physical State Appearance Odor No information available Liquid

Yellow-orange

Emergency Overview

Highly flammable liquid and vapor. Suspected of causing cancer. May cause respiratory irritation. Harmful if swallowed. Causes severe skin burns and eye damage. May cause drowsiness and dizziness. May form explosive peroxides. Moisture sensitive. Air sensitive.

Classification of the substance or mixture

Flammable liquids.	Category 2
Acute Oral Toxicity	Category 4
Skin Corrosion/Irritation	Category 1 B
Serious Eye Damage/Eye Irritation	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity - (single exposure)	Category 3

Label Elements

Page 2/10

Lithium (trimethylsilyl)acetylide, 0.5M solution in THF



Signal Word

Danger

Hazard Statements

- H225 Highly flammable liquid and vapor
- H351 Suspected of causing cancer
- H335 May cause respiratory irritation
- H302 Harmful if swallowed
- H314 Causes severe skin burns and eye damage
- H336 May cause drowsiness or dizziness

Precautionary Statements

Prevention

- P201 Obtain special instructions before use
- P202 Do not handle until all safety precautions have been read and understood
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P260 Do not breathe dust/fume/gas/mist/vapors/spray
- P264 Wash face, hands and any exposed skin thoroughly after handling
- P240 Ground and bond container and receiving equipment
- P242 Use non-sparking tools
- P243 Take action to prevent static discharges
- P270 Do not eat, drink or smoke when using this product
- P271 Use only outdoors or in a well-ventilated area
- P280 Wear protective gloves/protective clothing/eye protection/face protection

Response

- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P310 Immediately call a POISON CENTER or doctor
- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
- P330 Rinse mouth
- P331 Do NOT induce vomiting
- P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
- P362 + P364 Take off contaminated clothing and wash it before reuse

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Physical and Chemical Hazards

Vapors may cause flash fire or explosion. Highly flammable. May form explosive peroxides. Water reactive.

Health Hazards

Suspected of causing cancer. May cause respiratory irritation. Harmful if swallowed. Corrosive. Causes skin and eye burns. May cause drowsiness or dizziness.

Environmental hazards

Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants. . Will likely be mobile in the environment due to its water solubility. Is not likely mobile in the environment. The product is water soluble, and may spread in water systems. Reacts with water.

Toxic to terrestrial vertebrates. This product does not contain any known or suspected endocrine disruptors.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Tetrahydrofuran	109-99-9	95

Page 3 / 10 Revision Date 07-Apr-2024

Lithium (trimethylsilyl)acetylide, 0.5M solution in THF

Lithium (trimethylsilyl)acetylide	54655-07-1	5

SECTION 4. FIRST AID MEASURES

General Advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eve Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.

Inhalation

If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately.

Ingestion

Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately.

Most important symptoms and effects

Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Causes central nervous system depression

Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

Water may be ineffective.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Page 4 / 10 Revision Date 07-Apr-2024

Lithium (trimethylsilyl)acetylide, 0.5M solution in THF

Environmental Precautions

Should not be released into the environment.

Methods for Containment and Clean Up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material.

Refer to protective measures listed in Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

Handling

Do not get in eyes, on skin, or on clothing. Wear personal protective equipment/face protection. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Shelf life 12 months. May form explosive peroxides on prolonged storage. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Keep away from heat, sparks and flame. Store under an inert atmosphere. Flammables area.

Specific Use(s)

Use in laboratories

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	China	Taiwan	Thailand	Hong Kong
Tetrahydrofuran	TWA: 300 mg/m ³	TWA: 200 ppm TWA: 590 mg/m³	TWA: 200 ppm	TWA: 200 ppm TWA: 590 mg/m³ STEL: 250 ppm STEL: 737 mg/m³

Component	ACGIH TLV	OSHA PEL	NIOSH	The United Kingdom	European Union
Tetrahydrofuran	TWA: 50 ppm	(Vacated) TWA: 200	IDLH: 2000 ppm	STEL: 100 ppm 15 min	TWA: 50 ppm (8h)
	STEL: 100 ppm	ppm	TWA: 200 ppm	STEL: 300 mg/m ³ 15	TWA: 150 mg/m ³ (8h)
	Skin	(Vacated) TWA: 590	TWA: 590 mg/m ³	min	STEL: 100 ppm
		mg/m³	STEL: 250 ppm	TWA: 50 ppm 8 hr	(15min)
		(Vacated) STEL: 250	STEL: 735 mg/m ³	TWA: 150 mg/m ³ 8 hr	STEL: 300 mg/m ³
		ppm		Skin	(15min)
		(Vacated) STEL: 735			Skin
		mg/m³			
		TWA: 200 ppm			
		TWA: 590 mg/m ³			

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. MDHS70 General methods for sampling airborne gases and vapours MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Exposure Controls

Page 5 / 10 Revision Date 07-Apr-2024

Lithium (trimethylsilyl)acetylide, 0.5M solution in THF

Engineering Measures

Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source.

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Butyl rubber	See manufacturers	-	EN 374	(minimum requirement)
Nitrile rubber	recommendations			
Viton (R)				
Neoprene gloves				

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection Long sleeved clothing

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to

EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

141

When RPE is used a face piece Fit Test should be conducted

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls No information available.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Yellow-orange

Physical State Liquid

Odor No information available

Odor Threshold No data available

pH No information available

Melting Point/Range No data available Softening Point No data available

Boiling Point/Range No information available

Flash Point No information available

Evaporation Rate

No information available

No data available

Flammability (solid,gas)

Not applicable

Liquid

Explosion Limits

No data available

Page 6 / 10 Revision Date 07-Apr-2024

Lithium (trimethylsilyl)acetylide, 0.5M solution in THF

Vapor Pressure No data available

Vapor Density No data available (Air = 1.0)

Specific Gravity / Density 0.880

Bulk Density Not applicable Liquid

Water Solubility Reacts with water
Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Componentlog PowTetrahydrofuran0.45

Autoignition Temperature

Decomposition Temperature

Viscosity

No data available

No data available

No data available

Explosive Properties Vapors may form explosive mixtures with air

Oxidizing Properties No information available

SECTION 10. STABILITY AND REACTIVITY

Stability Moisture sensitive. Air sensitive.

Hazardous Reactions None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid Excess heat. Incompatible products. Keep away from open flames, hot surfaces and

sources of ignition. Exposure to moist air or water.

Materials to avoid Bases. Strong oxidizing agents. Bromine. Oxidizing agent.

Hazardous Decomposition Products Carbon monoxide (CO). Carbon dioxide (CO2). Silicon dioxide. Thermal decomposition can

lead to release of irritating gases and vapors.

SECTION 11. TOXICOLOGICAL INFORMATION

Product Information No acute toxicity information is available for this product

(a) acute toxicity;

Toxicology data for the components

Component LD50 Oral		LD50 Dermal	LC50 Inhalation
Tetrahydrofuran	1650 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	180 mg/L (Rat) 1 h
			53.9 mg/L (Rat) 4 h

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;

Respiratory SkinNo data available

No data available

Component	Test method	Test species	Study result
Tetrahydrofuran	Local Lymph Node Assay	mouse	non-sensitising
109-99-9 (95)	OECD Test Guideline 429		

(e) germ cell mutagenicity; No data available

Page 7/10 Revision Date 07-Apr-2024

Lithium (trimethylsilyl)acetylide, 0.5M solution in THF

Component	Test method	Test species	Study result
Tetrahydrofuran	OECD Test Guideline 476	in vivo	negative
109-99-9 (95)	Gene cell mutation	Mammalian	_
	OECD Test Guideline 473		
	Chromosomal aberration assay	in vitro	negative
		Mammalian	_

(f) carcinogenicity; No data available

The table below indicates whether each agency has listed any ingredient as a carcinogen

Limited evidence of a carcinogenic effect

Component	EU	UK	Germany	IARC
Tetrahydrofuran				Group 2B

No data available (a) reproductive toxicity;

Component	Test method	Test species / Duration	Study result
Tetrahydrofuran	OECD Test Guideline 416	Rat 2 Generation	NOAEL = 3,000 ppm
109-99-9 (95)			

No data available (h) STOT-single exposure;

Respiratory system Results / Target organs

Central nervous system (CNS)

(i) STOT-repeated exposure; No data available

No information available. **Target Organs**

(j) aspiration hazard; No data available

Other Adverse Effects The toxicological properties have not been fully investigated.

delayed

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Causes central nervous system depression

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity effects Reacts with water so no ecotoxicity data for the substance is available.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Tetrahydrofuran	2160 mg/l LC50 = 96 h	EC50 48 h 3485 mg/l		
	Pimephales promelas	EC50: >10000 mg/L/24h		
	Leuciscus idus: LC50:	_		
	2820 mg/L/48h			

Persistence and Degradability

Persistence Persistence is unlikely, based on information available.

Degradability Degradation in sewage treatment plant

No information available. Water reactive.

No information available, Reacts with water.

Bioaccumulative Potential

Bioaccumulation is unlikely; Product does not bioaccumulate due to reaction with water

Component	log Pow	Bioconcentration factor (BCF)
-----------	---------	-------------------------------

Page 8 / 10 Revision Date 07-Apr-2024

Lithium (trimethylsilyl)acetylide, 0.5M solution in THF

Tetrahydrofuran 0.45 No data available
--

likely be mobile in the environment due to its water solubility Is not likely mobile in the

environment Highly mobile in soils

Endocrine Disruptor Information

Component	EU - Endocrine Disrupters Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information			
Tetrahydrofuran	Group III Chemical					
Persistent Organic Pollutant This product does not contain any known or suspected substance						
Ozone Depletion Potential This product does not contain any known or suspected substance						

SECTION 13. DISPOSAL CONSIDERATIONS

Waste from Residues/Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the

application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH

and harm aquatic organisms.

SECTION 14. TRANSPORT INFORMATION

Road and Rail Transport

UN-No UN2924

Proper Shipping Name Flammable liquid, corrosive, n.o.s.

Technical Shipping Name Tetrahydrofuran

Hazard Class 3
Subsidiary Hazard Class 8
Packing Group ||

IMDG/IMO

UN-No UN2924

Proper Shipping Name Flammable liquid, corrosive, n.o.s.

Technical Shipping Name Tetrahydrofuran

Hazard Class 3

Subsidiary Hazard Class 8
Packing Group | |

<u>IATA</u>

UN-No UN2924

Proper Shipping Name Flammable liquid, corrosive, n.o.s.

Technical Shipping Name Tetrahydrofuran

Hazard Class 3
Subsidiary Hazard Class 8

Packing Group

Special Precautions for User No special precautions required

Page 9/10

Revision Date 07-Apr-2024

Lithium (trimethylsilyl)acetylide, 0.5M solution in THF

SECTION 15. REGULATORY INFORMATION

International Inventories

X = listed, China (IECSC), Europe (EINECS/ELINCS/NLP), U.S.A. (TSCA), Canada (DSL/NDSL), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), Korea (KECL).

Component	The Inventory of Hazardous Chemicals (2015 Edition)	goods GB	TCSI	IECSC	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	AICS	KECL
Tetrahydrofuran	X	X	Χ	Χ	203-726-8	Х	Χ	Х	Χ	Χ	Χ	KE-33454
Lithium (trimethylsilyl)acetylide	-	-	Х	=	-	-	-	-	-		-	-

National Regulations

SECTION 16. OTHER INFORMATION

22-Aug-2013 **Creation Date Revision Date** 07-Apr-2024 Not applicable. **Revision Summary**

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical incident response training.

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances **ENCS** - Japanese Existing and New Chemical Substances **AICS** - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50% NOEC - No Observed Effect Concentration PBT - Persistent, Bioaccumulative, Toxic

ICAO/IATA - International Civil Aviation Organization/International Air

Transport Association ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

PNEC - Predicted No Effect Concentration

LD50 - Lethal Dose 50%

Substances List

EC50 - Effective Concentration 50% POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)

ACR38065

SAFETY DATA SHEET

Page 10 / 10 Revision Date 07-Apr-2024

Lithium (trimethylsilyl)acetylide, 0.5M solution in THF

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Physical hazards

Health Hazards

Environmental hazards

On basis of test data
Calculation method
Calculation method

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet