Thermo Fisher SCIENTIFIC

SAFETY DATA SHEET

Page 1/9 Creation Date 01-Sep-2009 Revision Date 05-Apr-2024 Version 3

ACRT03618

Isopropanol

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

产品说明: Isopropanol Product Description: Isopropanol

Cat No.: T036181000

Synonyms 2-Propanol; IPA; Isopropyl alcohol; Propan-2-ol; Isopropanol

CAS No 67-63-0 Molecular Formula C3 H8 O

Supplier UK entity/business name

Fisher Scientific UK Bishop Meadow Road,

Loughborough, Leicestershire LE11 5RG, United Kingdom

EU entity/business name Thermo Fisher Scientific

Janssen Pharmaceuticalaan 3a, 2440 Geel, Belgium

Emergency Telephone Number For information US call: 001-800-227-6701 / Europe call: +32 14 57 52 11

Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

E-mail address begel.sdsdesk@thermofisher.com

Recommended Use Laboratory chemicals.
Uses advised against No Information available

SECTION 2. HAZARD IDENTIFICATION

Physical StateAppearanceOdorLiquidColorlessAlcohol-like

Emergency Overview

Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness and dizziness.

Classification of the substance or mixture

Flammable liquids.	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Specific target organ toxicity - (single exposure)	Category 3

Label Elements



Page 2/9 Revision Date 05-Apr-2024

Isopropanol

Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

Precautionary Statements

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P240 - Ground and bond container and receiving equipment

P241 - Use explosion-proof electrical/ ventilating/ lighting equipment

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P264 - Wash face, hands and any exposed skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

Response

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P312 - Call a POISON CENTER or doctor if you feel unwell

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Physical and Chemical Hazards

Vapors may cause flash fire or explosion. Highly flammable.

Health Hazards

Causes serious eye irritation. May cause drowsiness or dizziness.

Environmental hazards

Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants. Will likely be mobile in the environment due to its volatility. The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

Other Hazards

This product does not contain any known or suspected endocrine disruptors.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Isopropyl alcohol	67-63-0	>95

SECTION 4. FIRST AID MEASURES

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if symptoms occur.

Inhalation

Remove to fresh air. Get medical attention. If not breathing, give artificial respiration.

Ingestion

Do NOT induce vomiting. Get medical attention.

Page 3/9 Revision Date 05-Apr-2024

Isopropanol

Most important symptoms and effects

Difficulty in breathing. May cause central nervous system depression: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use water jetstream. Do not use a solid water stream as it may scatter and spread fire.

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing.

Environmental Precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

Methods for Containment and Clean Up

Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. Keep in suitable, closed containers for disposal.

Refer to protective measures listed in Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

Handling

Wear personal protective equipment/face protection. Keep away from open flames, hot surfaces and sources of ignition. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Storage

Keep away from heat, sparks and flame. Flammables area. Keep container tightly closed in a dry and well-ventilated place.

Specific Use(s)

Use in laboratories

Page 4/9 Revision Date 05-Apr-2024

Isopropanol

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	China	Taiwan	Thailand	Hong Kong
Isopropyl alcohol	TWA: 350 mg/m ³	VA: 350 mg/m ³ TWA: 400 ppm TWA		TWA: 400 ppm
	STEL: 700 mg/m ³	TWA: 983 mg/m ³		TWA: 983 mg/m ³
				STEL: 500 ppm
				STEL: 1230 mg/m ³

Component	ACGIH TLV	OSHA PEL	NIOSH	The United Kingdom	European Union
Isopropyl alcohol	TWA: 200 ppm	(Vacated) TWA: 400	IDLH: 2000 ppm	STEL: 500 ppm 15 min	
	STEL: 400 ppm	ppm	TWA: 400 ppm	STEL: 1250 mg/m ³ 15	
		(Vacated) TWA: 980	TWA: 980 mg/m ³	min	
		mg/m³	STEL: 500 ppm	TWA: 400 ppm 8 hr	
			STEL: 1225 mg/m ³	TWA: 999 mg/m ³ 8 hr	
		ppm			
		(Vacated) STEL: 1225			
		mg/m³			
		TWA: 400 ppm			
		TWA: 980 mg/m ³			

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. MDHS70 General methods for sampling airborne gases and vapours MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Exposure Controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source.

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Γ	Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
	Butyl rubber	> 480 minutes	0.5 mm	EN 374	Permeation rate < 0.9 µg/cm2/min
	Nitrile rubber	> 360 - 480 minutes	0.35 - 0.55 mm		As tested under EN374-3 Determination of
	Viton (R)	> 480 minutes	0.4 mm		Resistance to Permeation by Chemicals
	Neoprene	< 40 minutes	0.7 mm		

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Page 5/9 Revision Date 05-Apr-2024

Isopropanol

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure

When workers are facing concentrations above the exposure limit they must use **Respiratory Protection**

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to

EN14387

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; Half mask: EN140; plus filter, EN 141

When RPE is used a face piece Fit Test should be conducted

Handle in accordance with good industrial hygiene and safety practice. **Hygiene Measures**

Environmental exposure controls No information available.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Colorless **Appearance** Liquid **Physical State**

Alcohol-like Odor **Odor Threshold** No data available

рΗ 1% aq. sol

Melting Point/Range -89.5 °C / -129.1 °F

Softening Point No data available

Boiling Point/Range 81 - 83 °C / 177.8 - 181.4 °F @ 760 mmHa

Flash Point 12 °C / 53.6 °F Method - Abel Closed Cup (BS 2000 Part 170, IP

170. AS/NZS 2106)

Evaporation Rate 1.7 ASTM D 3539 (Butyl acetate = 1.0)

Not applicable Flammability (solid,gas) Liquid

Explosion Limits Lower 2 Vol% Upper 12 Vol%

Vapor Pressure 43 mmHg @ 20 °C

2.1 @ 20°C / 68°F **Vapor Density** (Air = 1.0)ÀSTM D-4052 Specific Gravity / Density 0.785 **Bulk Density** Not applicable Liquid

Water Solubility Miscible

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Component log Pow Isopropyl alcohol 0.05

425 °C / 797 °F ASTM E-659 **Autoignition Temperature**

Decomposition Temperature No data available 2.27 mPa.s at 20 °C **Viscosity**

Explosive Properties Not explosive explosive air/vapour mixtures possible Vapors may

form explosive mixtures with air

Oxidizing Properties No information available

Molecular Formula C3 H8 O **Molecular Weight**

VOC Content(%) 100% (Organic Carbon (by mass) = 59.9 %) (EC/1999/13)

Refractive index 1.377 at 20 °C / 68 °F (ASTM D-1218)

Surface tension 22.7 mN/m at 20 °C / 68 °F

Coefficient of expansion 0.0009 / °C

18.6 at 20 °C / 68 °F Dielectric constant

Page 6/9 Revision Date 05-Apr-2024

Isopropanol

665 J/g Heat of vapourisation

Specific heat capacity 3 kJ/kg °C at 20 °C / 68 °F Thermal conductivity 0.137 W/m °C at 20 °C / 68 °F

SECTION 10. STABILITY AND REACTIVITY

Stability Stable under normal conditions.

Hazardous Reactions None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of

ignition.

Materials to avoid Strong oxidizing agents. Acids. Halogens. Acid anhydrides.

Hazardous Decomposition Products Carbon monoxide (CO). Carbon dioxide (CO₂), peroxides.

SECTION 11. TOXICOLOGICAL INFORMATION

Product Information

(a) acute toxicity;

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation			
Isopropyl alcohol	5045 mg/kg (Rat)	12800 mg/kg (Rat)	72.6 mg/L (Rat) 4 h			
	3600 mg/kg (Mouse)					

(b) skin corrosion/irritation; Based on available data, the classification criteria are not met

Category 2 (c) serious eye damage/irritation;

(d) respiratory or skin sensitization;

Respiratory Based on available data, the classification criteria are not met Skin

Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met (e) germ cell mutagenicity;

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

Based on available data, the classification criteria are not met (g) reproductive toxicity;

(h) STOT-single exposure; Category 3

Central nervous system (CNS) Results / Target organs

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Target Organs None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Symptoms / effects, both acute and May cause central nervous system depression: Inhalation of high vapor concentrations may

Page 7/9 Revision Date 05-Apr-2024

Isopropanol

delayed cause symptoms like headache, dizziness, tiredness, nausea and vomiting

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity effects . Do not empty into drains.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Isopropyl alcohol	LC50: = 9640 mg/L, 96h	13299 mg/L EC50 = 48	EC50: > 1000 mg/L, 72h	= 35390 mg/L EC50
	flow-through	h	(Desmodesmus	Photobacterium
	(Pimephales promelas)	9714 mg/L EC50 = 24 h	subspicatus)	phosphoreum 5 min
	LC50: > 1400000 μg/L,		EC50: > 1000 mg/L, 96h	
	96h (Lepomis		(Desmodesmus	
	macrochirus)		subspicatus)	
	LC50: = 11130 mg/L,			
	96h static (Pimephales			
	promelas)			
	$LC50$: = 10000000 μ g/L,			
	96h (Daphnia)			

Persistence and Degradability

Persistence

Expected to be biodegradable

Persistence is unlikely, based on information available.

Bioaccumulative Potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)			
Isopropyl alcohol	0.05	No data available			

The product contains volatile organic compounds (VOC) which will evaporate easily from all Mobility in soil

surfaces Will likely be mobile in the environment due to its volatility Disperses rapidly in air

Surface tension 22.7 mN/m at 20 °C / 68 °F

Endocrine Disruptor Information Persistent Organic Pollutant

Ozone Depletion Potential

This product does not contain any known or suspected endocrine disruptors

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13. DISPOSAL CONSIDERATIONS

Waste from Residues/Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

Other Information

Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with

local regulations.

SECTION 14. TRANSPORT INFORMATION

Road and Rail Transport

UN1219 **UN-No**

Proper Shipping Name Isopropanol (Isopropyl alcohol)

Hazard Class Packing Group Ш

Page 8/9 Revision Date 05-Apr-2024

Isopropanol

IMDG/IMO

UN1219 **UN-No**

Proper Shipping Name Isopropanol (Isopropyl alcohol)

Hazard Class 3 **Packing Group** Ш

IATA

UN-No UN1219 **Proper Shipping Name** Isopropanol

Hazard Class 3 **Packing Group** Ш

Special Precautions for User No special precautions required

SECTION 15. REGULATORY INFORMATION

International Inventories

X = listed, China (IECSC), Europe (EINECS/ELINCS/NLP), U.S.A. (TSCA), Canada (DSL/NDSL), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), Korea (KECL).

Component	The	List of	TCSI	IECSC	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	AICS	KECL
	Inventory of Hazardous Chemicals (2015 Edition)	•										
Isopropyl alcohol	X	X	Χ	X	200-661-7	Х	X	Х	Х	Х	Χ	KE-29363

National Regulations

SECTION 16. OTHER INFORMATION

01-Sep-2009 **Creation Date Revision Date** 05-Apr-2024 **Revision Summary** Not applicable.

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b)

Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

Substances List

PICCS - Philippines Inventory of Chemicals and Chemical Substances

ENCS - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

Page 9/9 Revision Date 05-Apr-2024

Isopropanol

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment **LC50** - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

PNEC - Predicted No Effect Concentration

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50% **POW** - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet