SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Creation Date 27-Jun-2014 **Revision Date** 09-Feb-2024 **Revision Number** 8

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description:	**Phenol/Chloroform/Isoamyl Alcohol, pH 4.3**
Cat No. :	**BP1754I-100, BP1754I-400**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use	Laboratory chemicals.
Uses advised against	No Information available

1.3. Details of the supplier of the safety data sheet

Company .

EU entity/business name
Thermo Fisher Scientific
Janssen Pharmaceuticalaan 3a, 2440 Geel,
Belgium

UK entity/business name
Fisher Scientific UK
Bishop Meadow Road,
Loughborough, Leicestershire LE11 5RG,
United Kingdom

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
e-mail - infoch@thermofisher.com

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US:**001-201-796-7100 / **Europe:** +32 14 57 52 99
CHEMTREC Tel. No.**US:**001-800-424-9300 / **Europe:**001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Based on available data, the classification criteria are not met

Health hazards

Acute oral toxicity	Category 3 (H301)
Acute dermal toxicity	Category 3 (H311)
Acute Inhalation Toxicity - Vapors	Category 3 (H331)
Skin Corrosion/Irritation	Category 1 B (H314)
Serious Eye Damage/Eye Irritation	Category 1 (H318)
Germ Cell Mutagenicity	Category 2 (H341)
Carcinogenicity	Category 2 (H351)
Reproductive Toxicity	Category 2 (H361d)
Specific target organ toxicity - (repeated exposure)	Category 1 (H372)

Environmental hazards
Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word **Danger**

Hazard Statements
H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled
H314 - Causes severe skin burns and eye damage
H341 - Suspected of causing genetic defects
H351 - Suspected of causing cancer
H361d - Suspected of damaging the unborn child
H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary Statements
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor/physician

Additional EU labelling
For use in industrial installations only

2.3. Other hazards

Toxicity to Soil Dwelling Organisms

Toxic to terrestrial vertebrates
This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Phenol	108-95-2	EEC No. 203-632-7	83-84	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Muta. 2 (H341) STOT RE 2 (H373)
1-Butanol, 3-methyl-	123-51-3	EEC No. 204-633-5	0.5-1	Flam Liq. 3 (H226) Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H335) (EUH066)
Chloroform	67-66-3	200-663-8	15-16	Acute Tox. 4 (H302) Acute Tox. 3 (H331) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H336) Carc. 2 (H351) Repr. 2 (H361d) STOT RE 1 (H372)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Phenol	Eye Irrit. 2 (H319) :: 1%<=C<3% Skin Corr. 1B (H314) :: C>=3% Skin Irrit. 2 (H315) :: 1%<=C<3%	-	-
Chloroform	STOT RE 2 : C ≥ 5 %	-	-

Components	Reach Registration Number	
Chloroform	01-2119486657-20-0015	

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

Inhalation If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh air. Immediate medical attention is required.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media
CO_2, dry chemical, dry sand, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons
No information available.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes.

Hazardous Combustion Products
Carbon monoxide (CO), Carbon dioxide (CO_2).

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance.

Hygiene Measures
Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area.

Technical Rules for Hazardous Substances (TRGS) 510 Storage Class (LGK) (Germany) Storage Class/LGK 6.1C

Switzerland - Storage of hazardous substances Storage class - SC 6.1
https://www.kvu.ch/de/themen/stoffe-und-produkte
https://www.kvu.ch/fr/themes/substances-et-produits
https://www.kvu.ch/it/temi/sostanze-e-prodotti

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits
List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE -** 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Phenol	TWA: 2 ppm (8h) TWA: 8 mg/m³ (8h) STEL: 4 ppm (15min) STEL: 16 mg/m³ (15min) Skin	STEL: 4 ppm 15 min STEL: 16 mg/m³ 15 min TWA: 2 ppm 8 hr TWA: 7.8 mg/m³ 8 hr Skin	TWA / VME: 2 ppm (8 heures). restrictive limit TWA / VME: 7.8 mg/m³ (8 heures). restrictive limit STEL / VLCT: 4 ppm. restrictive limit STEL / VLCT: 15.6 mg/m³. restrictive limit Peau	TWA: 2 ppm 8 uren TWA: 8 mg/m³ 8 uren STEL: 4 ppm 15 minuten STEL: 16 mg/m³ 15 minuten Huid	STEL / VLA-EC: 4 ppm (15 minutos). STEL / VLA-EC: 16 mg/m³ (15 minutos). TWA / VLA-ED: 2 ppm (8 horas) TWA / VLA-ED: 8 mg/m³ (8 horas) Piel
1-Butanol, 3-methyl-		STEL: 125 ppm 15 min STEL: 458 mg/m³ 15 min TWA: 100 ppm 8 hr TWA: 366 mg/m³ 8 hr	TWA / VME: 5 ppm (8 heures). restrictive limit TWA / VME: 18 mg/m³ (8 heures). restrictive limit STEL / VLCT: 10 ppm. restrictive limit STEL / VLCT: 37 mg/m³. restrictive limit	TWA: 5 ppm 8 uren TWA: 18 mg/m³ 8 uren STEL: 10 ppm 15 minuten STEL: 37 mg/m³ 15 minuten	STEL / VLA-EC: 10 ppm (15 minutos). STEL / VLA-EC: 37 mg/m³ (15 minutos). TWA / VLA-ED: 5 ppm (8 horas) TWA / VLA-ED: 18 mg/m³ (8 horas)
Chloroform	TWA: 2 ppm 8 hr TWA: 10 mg/m³ 8 hr Possibility of significant uptake through the skin	TWA: 2 ppm TWA: 9.9 mg/m³ STEL: 6 ppm STEL: 29.7 mg/m³	TWA / VME: 2 ppm (8 heures). restrictive limit TWA / VME: 10 mg/m³ (8 heures). restrictive limit STEL / VLCT: 50 ppm. STEL / VLCT: 250 mg/m³. Peau	TWA: 2 ppm 8 uren TWA: 10 mg/m³ 8 uren Huid	TWA / VLA-ED: 2 ppm (8 horas) TWA / VLA-ED: 10 mg/m³ (8 horas) Piel

Component	Italy	Germany	Portugal	The Netherlands	Finland

Phenol	TWA: 2 ppm 8 ore. Time Weighted Average TWA: 8.0 mg/m^3 8 ore. Time Weighted Average STEL: 4 ppm 15 minuti. Short-term STEL: 16 mg/m^3 15 minuti. Short-term Pelle	TWA: 2 ppm (8 Stunden). AGW - exposure factor 2 TWA: 8 mg/m^3 (8 Stunden). AGW - exposure factor 2 Haut	STEL: 4 ppm 15 minutos STEL: 16 mg/m^3 15 minutos TWA: 2 ppm 8 horas TWA: 8 mg/m^3 8 horas Pele	huid TWA: 8 mg/m^3 8 uren	TWA: 2 ppm 8 tunteina TWA: 8 mg/m^3 8 tunteina STEL: 4 ppm 15 minuutteina STEL: 16 mg/m^3 15 minuutteina Iho
1-Butanol, 3-methyl-	TWA: 18 mg/m^3 8 ore. Time Weighted Average TWA: 5 ppm 8 ore. Time Weighted Average STEL: 37 mg/m^3 15 minuti. Short-term STEL: 10 ppm 15 minuti. Short-term	TWA: 20 ppm (8 Stunden). AGW - exposure factor 2 TWA: 73 mg/m^3 (8 Stunden). AGW - exposure factor 2 TWA: 20 ppm (8 Stunden). MAK TWA: 73 mg/m^3 (8 Stunden). MAK Höhepunkt: 40 ppm Höhepunkt: 146 mg/m^3	STEL: 10 ppm 15 minutos STEL: 37 mg/m^3 15 minutos TWA: 5 ppm 8 horas TWA: 18 mg/m^3 8 horas	STEL: 37 mg/m^3 15 minuten TWA: 18 mg/m^3 8 uren	TWA: 5 ppm 8 tunteina TWA: 18 mg/m^3 8 tunteina STEL: 10 ppm 15 minuutteina STEL: 37 mg/m^3 15 minuutteina
Chloroform	TWA: 2 ppm 8 ore. Media Ponderata nel Tempo TWA: 10 mg/m^3 8 ore. Media Ponderata nel Tempo Pelle	0.5 ppm TWA MAK 2.5 mg/m^3 TWA MAK	TWA: 2 ppm 8 horas TWA: 10 mg/m^3 8 horas Pele	STEL: 25 mg/m^3 15 minuten TWA: 5 mg/m^3 8 uren	TWA: 2 ppm 8 tunteina TWA: 10 mg/m^3 8 tunteina STEL: 4 ppm 15 minuutteina STEL: 20 mg/m^3 15 minuutteina Iho

Component	Austria	Denmark	Switzerland	Poland	Norway
Phenol	Haut MAK-KZGW: 4 ppm 15 Minuten MAK-KZGW: 16 mg/m^3 15 Minuten MAK-TMW: 2 ppm 8 Stunden MAK-TMW: 8 mg/m^3 8 Stunden	TWA: 1 ppm 8 timer TWA: 4 mg/m^3 8 timer STEL: 16 mg/m^3 15 minutter STEL: 4 ppm 15 minutter Hud	Haut/Peau STEL: 5 ppm 15 Minuten STEL: 19 mg/m^3 15 Minuten TWA: 5 ppm 8 Stunden TWA: 19 mg/m^3 8 Stunden	STEL: 16 mg/m^3 15 minutach TWA: 7.8 mg/m^3 8 godzinach	TWA: 1 ppm 8 timer TWA: 4 mg/m^3 8 timer STEL: 3 ppm 15 minutter. value from the regulation STEL: 12 mg/m^3 15 minutter. value from the regulation Hud
1-Butanol, 3-methyl-	MAK-KZGW: 10 ppm 15 Minuten MAK-KZGW: 37 mg/m^3 15 Minuten MAK-TMW: 5 ppm 8 Stunden MAK-TMW: 18 mg/m^3 8 Stunden	TWA: 5 ppm 8 timer TWA: 18 mg/m^3 8 timer STEL: 37 mg/m^3 15 minutter STEL: 10 ppm 15 minutter	STEL: 40 ppm 15 Minuten STEL: 150 mg/m^3 15 Minuten TWA: 20 ppm 8 Stunden TWA: 75 mg/m^3 8 Stunden	STEL: 37 mg/m^3 15 minutach TWA: 18 mg/m^3 8 godzinach	TWA: 18 mg/m^3 8 timer TWA: 5 ppm 8 timer STEL: 37 mg/m^3 15 minutter. value from the regulation STEL: 10 ppm 15 minutter. value from the regulation Hud
Chloroform	Haut MAK-TMW: 2 ppm 8 Stunden MAK-TMW: 10 mg/m^3 8 Stunden	TWA: 2 ppm 8 timer TWA: 10 mg/m^3 8 timer Hud	Haut/Peau STEL: 1 ppm 15 Minuten STEL: 5 mg/m^3 15 Minuten TWA: 0.5 ppm 8 Stunden TWA: 2.5 mg/m^3 8 Stunden	TWA: 8 mg/m^3 8 godzinach	TWA: 2 ppm 8 timer TWA: 10 mg/m^3 8 timer 4 ppm STEL (value calculated) 15 mg/m^3 STEL (value calculated) Hud

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Phenol	TWA: 2 ppm TWA: 8 mg/m^3 STEL : 4 ppm STEL : 16 mg/m^3 Skin notation	kože TWA-GVI: 2 ppm 8 satima. TWA-GVI: 8 mg/m^3 8 satima. STEL-KGVI: 4 ppm 15 minutama. STEL-KGVI: 16 mg/m^3 15 minutama.	TWA: 2 ppm 8 hr. TWA: 8 mg/m^3 8 hr. STEL: 4 ppm 15 min STEL: 16 mg/m^3 15 min Skin	Skin-potential for cutaneous absorption STEL: 16 mg/m^3 STEL: 4 ppm TWA: 8 mg/m^3 TWA: 2 ppm	TWA: 7.5 mg/m^3 8 hodinách. Potential for cutaneous absorption Ceiling: 15 mg/m^3
1-Butanol, 3-methyl-	TWA: 18 mg/m^3 TWA: 5 ppm STEL : 37 mg/m^3	TWA-GVI: 5 ppm 8 satima. TWA-GVI: 18 mg/m^3 8	TWA: 5 ppm 8 hr. TWA: 18 mg/m^3 8 hr. STEL: 10 mg/m^3 15 min	STEL: 37 mg/m^3 STEL: 10 ppm TWA: 18 mg/m^3	TWA: 18 mg/m^3 8 hodinách. Ceiling: 37 mg/m^3

	STEL : 10 ppm	satima. TWA-GVI: 100 ppm 8 satima. regulated under 3-Methyl-1-butanol TWA-GVI: 366 mg/m³ 8 satima. regulated under 3-Methyl-1-butanol STEL-KGVI: 10 ppm 15 minutama. STEL-KGVI: 37 mg/m³ 15 minutama. STEL-KGVI: 125 ppm 15 minutama. regulated under 3-Methyl-1-butanol STEL-KGVI: 458 mg/m³ 15 minutama. regulated under 3-Methyl-1-butanol	STEL: 37 ppm 15 min	TWA: 5 ppm	
Chloroform	TWA: 2 ppm TWA: 10.0 mg/m³ Skin notation	kože TWA-GVI: 2 ppm 8 satima. TWA-GVI: 10 mg/m³ 8 satima.	TWA: 2 ppm 8 hr. TWA: 9.8 mg/m³ 8 hr. STEL: 6 ppm 15 min STEL: 29.4 mg/m³ 15 min Skin	Skin-potential for cutaneous absorption TWA: 2 ppm TWA: 10 mg/m³	TWA: 10 mg/m³ 8 hodinách. Potential for cutaneous absorption Ceiling: 20 mg/m³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Phenol	Nahk TWA: 2 ppm 8 tundides. TWA: 8 mg/m³ 8 tundides. STEL: 16 mg/m³ 15 minutites. STEL: 4 ppm 15 minutites.	Skin notation TWA: 2 ppm 8 hr TWA: 8 mg/m³ 8 hr STEL: 16 mg/m³ 15 min STEL: 4 ppm 15 min	skin - potential for cutaneous absorption STEL: 4 ppm STEL: 16 mg/m³ TWA: 2 ppm TWA: 8 mg/m³	STEL: 16 mg/m³ 15 percekben. CK TWA: 8 mg/m³ 8 órában. AK lehetséges borön keresztüli felszívódás	TWA: 1 ppm 8 klukkustundum. TWA: 4 mg/m³ 8 klukkustundum. Skin notation Ceiling: 2 ppm Ceiling: 8 mg/m³
1-Butanol, 3-methyl-	TWA: 5 ppm 8 tundides. TWA: 18 mg/m³ 8 tundides. STEL: 37 mg/m³ 15 minutites. STEL: 10 ppm 15 minutites.		STEL: 10 ppm STEL: 37 mg/m³ TWA: 5 ppm TWA: 18 mg/m³	STEL: 37 mg/m³ 15 percekben. CK TWA: 18 mg/m³ 8 órában. AK	STEL: 10 ppm STEL: 37 mg/m³ TWA: 5 ppm 8 klukkustundum. TWA: 18 mg/m³ 8 klukkustundum. Ceiling: 200 ppm Ceiling: 720 mg/m³
Chloroform	Nahk TWA: 2 ppm 8 tundides. TWA: 10 mg/m³ 8 tundides.	Skin notation TWA: 2 ppm 8 hr TWA: 10 mg/m³ 8 hr	TWA: 10 ppm TWA: 50 mg/m³	TWA: 10 mg/m³ 8 órában. AK	TWA: 2 ppm 8 klukkustundum. TWA: 10 mg/m³ 8 klukkustundum. Skin notation Ceiling: 4 ppm Ceiling: 20 mg/m³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Phenol	skin - potential for cutaneous exposure STEL: 4 ppm STEL: 16 mg/m³ TWA: 2 ppm TWA: 8 mg/m³	TWA: 2 ppm IPRD TWA: 8 mg/m³ IPRD Oda STEL: 4 ppm STEL: 16 mg/m³	Possibility of significant uptake through the skin TWA: 2 ppm 8 Stunden TWA: 8 mg/m³ 8 Stunden STEL: 16 mg/m³ 15 Minuten STEL: 4 ppm 15 Minuten	possibility of significant uptake through the skin TWA: 2 ppm TWA: 8 mg/m³ STEL: 16 mg/m³ 15 minuti STEL: 4 ppm 15 minuti	Skin notation TWA: 2 ppm 8 ore TWA: 8 mg/m³ 8 ore STEL: 4 ppm 15 minute STEL: 16 mg/m³ 15 minute
1-Butanol, 3-methyl-	STEL: 37 mg/m³ STEL: 10 ppm TWA: 18 mg/m³ TWA: 5 ppm	TWA: 18 mg/m³ IPRD TWA: 5 ppm IPRD STEL: 37 mg/m³ STEL: 10 ppm	TWA: 18 mg/m³ 8 Stunden TWA: 5 ppm 8 Stunden STEL: 37 mg/m³ 15 Minuten STEL: 10 ppm 15 Minuten		TWA: 100 mg/m³ 8 ore STEL: 200 mg/m³ 15 minute
Chloroform	skin - potential for cutaneous exposure TWA: 2 ppm TWA: 10 mg/m³	TWA: 10 mg/m³ IPRD TWA: 2 ppm IPRD Oda	Possibility of significant uptake through the skin TWA: 2 ppm 8 Stunden TWA: 10 mg/m³ 8	possibility of significant uptake through the skin TWA: 2 ppm TWA: 10 mg/m³	Skin notation TWA: 2 ppm 8 ore TWA: 10 mg/m³ 8 ore

			Stunden		

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Phenol	TWA: 0.3 mg/m³ 0539 Skin notation MAC: 1 mg/m³	Ceiling: 16 mg/m³ Potential for cutaneous absorption TWA: 2 ppm TWA: 8 mg/m³	TWA: 2 ppm 8 urah TWA: 8 mg/m³ 8 urah Koža STEL: 4 ppm 15 minutah STEL: 16 mg/m³ 15 minutah	Binding STEL: 4 ppm 15 minuter Binding STEL: 16 mg/m³ 15 minuter TLV: 1 ppm 8 timmar. NGV TLV: 4 mg/m³ 8 timmar. NGV Hud	Deri TWA: 2 ppm 8 saat TWA: 8 mg/m³ 8 saat STEL: 4 ppm 15 dakika STEL: 16 mg/m³ 15 dakika
1-Butanol, 3-methyl-	MAC: 5 mg/m³		TWA: 18 mg/m³ 8 urah TWA: 5 ppm 8 urah STEL: 10 ppm 15 minutah STEL: 37 mg/m³ 15 minutah	Binding STEL: 10 ppm 15 minuter Binding STEL: 37 mg/m³ 15 minuter TLV: 5 ppm 8 timmar. NGV TLV: 18 mg/m³ 8 timmar. NGV Hud	
Chloroform	TWA: 5 mg/m³ 2019 Skin notation STEL: 10 mg/m³ 2019	Potential for cutaneous absorption TWA: 2 ppm TWA: 10 mg/m³	TWA: 2 ppm 8 urah TWA: 10 mg/m³ 8 urah Koža	Indicative STLV: 5 ppm 15 minuter Indicative STLV: 25 mg/m³ 15 minuter LLV: 2 ppm 8 timmar. LLV: 10 mg/m³ 8 timmar. Hud	Deri TWA: 2 ppm 8 saat TWA: 10 mg/m³ 8 saat

Biological limit values
List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Phenol			Total Phenol: 250 mg/g creatinine urine end of shift	: 120 mg/g Creatinine urine end of shift	Phenol (after hydrolysis): 120 mg/g Creatinine urine (end of shift)

Component	Italy	Finland	Denmark	Bulgaria	Romania
Phenol		Total phenol: 1.3 mmol/L urine after the shift.		Phenol: 200 µg/L urine at the end of exposure or end of work shift	total Phenol: 120 mg/g Creatinine urine end of shift

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Phenol			Phenol: 200 mg/L urine end of exposure or work shift		

Monitoring methods
BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)
See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Phenol 108-95-2 (83-84)				DNEL = 1.23mg/kg bw/day
Chloroform 67-66-3 (15-16)				DNEL = 0.94mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)

Phenol 108-95-2 (83-84)	DNEL = 16mg/m^3			DNEL = 8mg/m^3
1-Butanol, 3-methyl- 123-51-3 (0.5-1)	DNEL = 292mg/m^3		DNEL = 73.16mg/m^3	
Chloroform 67-66-3 (15-16)		DNEL = 333mg/m^3	DNEL = 2.5mg/m^3	DNEL = 2.5mg/m^3

Predicted No Effect Concentration (PNEC)
See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Phenol 108-95-2 (83-84)	PNEC = 0.0077mg/L	PNEC = 0.0915mg/kg sediment dw	PNEC = 0.031mg/L	PNEC = 2.1mg/L	PNEC = 0.136mg/kg soil dw
1-Butanol, 3-methyl- 123-51-3 (0.5-1)	PNEC = 0.12mg/L	PNEC = 0.496mg/kg sediment dw	PNEC = 1.2mg/L	PNEC = 37mg/L	PNEC = 0.0287mg/kg soil dw
Chloroform 67-66-3 (15-16)	PNEC = 0.146mg/L	PNEC = 0.45mg/kg sediment dw	PNEC = 0.133mg/L	PNEC = 0.048mg/L	PNEC = 0.56mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Phenol 108-95-2 (83-84)	PNEC = 0.00077mg/L	PNEC = 0.00915mg/kg sediment dw			
1-Butanol, 3-methyl- 123-51-3 (0.5-1)	PNEC = 0.012mg/L	PNEC = 0.0496mg/kg sediment dw			
Chloroform 67-66-3 (15-16)	PNEC = 0.015mg/L	PNEC = 0.09mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures
Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Viton (R)	See manufacturers recommendations	-	EN 374	(minimum requirement)

Skin and body protection Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: low boiling organic solvent Type AX Brown conforming to

	EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387
Small scale/Laboratory use	Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. **Recommended half mask:-** Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141 When RPE is used a face piece Fit Test should be conducted
Environmental exposure controls	Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance		
Odor	No information available	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	No information available	**Method -** No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	4.3	
Viscosity	No data available	
Water Solubility	Soluble in water	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	**log Pow**	
Phenol	1.5	
1-Butanol, 3-methyl-	1.35	
Chloroform	2	
Vapor Pressure	No data available	
Density / Specific Gravity	No data available	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO_2).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral Category 3
Dermal Category 3
Inhalation Category 3

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Phenol	LD50 = 340 mg/kg (Rat)	LD50 = 630 mg/kg (Rabbit)	LC50 = 316 mg/m^3 (Rat) 4 h
1-Butanol, 3-methyl-	LD50 = 5770 mg/kg (Rat)	LD50 = 3250 mg/kg (Rabbit)	LC50 > 2000 ppm (Rat) 8 h
Chloroform	LD50 = 908 mg/kg (rat) LD50 = 695 mg/kg (Rat) LD50 = 450 mg/kg (Rat)	LD50 > 20 g/kg (Rabbit)	LC50 = 10.5 mg/L (Rat) 4 h

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory No data available
Skin No data available

(e) germ cell mutagenicity; Category 2

(f) carcinogenicity; Category 2

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Phenol			Cat. 3B	
Chloroform				Group 2B

(g) reproductive toxicity; Category 2

(h) STOT-single exposure; No data available

Results / Target organs Central nervous system (CNS).

(i) STOT-repeated exposure; Category 1

Target Organs Central nervous system (CNS), Eyes, Respiratory system, Kidney, Heart, Liver, Skin.

(j) aspiration hazard; No data available

Symptoms / effects,both acute and delayed Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects The product contains following substances which are hazardous for the environment. Contains a substance which is:. Very toxic to aquatic organisms.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Phenol	4-7 mg/L LC50 96 h 32 mg/L LC50 96 h	EC50: 10.2 - 15.5 mg/L, 48h (Daphnia magna) EC50: 4.24 - 10.7 mg/L, 48h Static (Daphnia magna)	EC50: 187 - 279 mg/L, 72h static (Desmodesmus subspicatus) EC50: 0.0188 - 0.1044 mg/L, 96h static (Pseudokirchneriella subcapitata) EC50: = 46.42 mg/L, 96h (Pseudokirchneriella subcapitata)
1-Butanol, 3-methyl-	LC50 96 h 700 mg/L (rainbow trout)	EC50: = 260 mg/L, 48h (Daphnia magna)	EC50: = 181 mg/L, 96h (Desmodesmus subspicatus) EC50: = 493 mg/L, 72h (Desmodesmus subspicatus)
Chloroform	LC50: = 300 mg/L, 96h static (Poecilia reticulata) LC50: = 18 mg/L, 96h flow-through (Lepomis macrochirus) LC50: = 18 mg/L, 96h flow-through (Oncorhynchus mykiss) LC50: = 71 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 28.9 mg/L/48h	EC50 = 560 mg/L/48h

Component	Microtox	M-Factor
Phenol	EC50 21 - 36 mg/L 30 min EC50 = 23.28 mg/L 5 min EC50 = 25.61 mg/L 15 min EC50 = 28.8 mg/L 5 min EC50 = 31.6 mg/L 15 min	
1-Butanol, 3-methyl-	EC50 = 2500 mg/L 17 h	
Chloroform	Photobacterium phosphoreum: EC50 = 520 mg/L/5 min Photobacterium phosphoreum: EC50 = 670 mg/L/15 min Photobacterium phosphoreum: EC50 = 670 mg/L/30min	

12.2. Persistence and degradability

Persistence Persistence is unlikely.

Degradation in sewage treatment plant Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Phenol	1.5	17.5 dimensionless 647 dimensionless
1-Butanol, 3-methyl-	1.35	No data available
Chloroform	2	1.4 - 13 dimensionless

12.4. Mobility in soil The product is water soluble, and may spread in water systems Will likely be mobile in the environment due to its water solubility. Highly mobile in soils

12.5. Results of PBT and vPvB assessment No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant This product does not contain any known or suspected substance

Ozone Depletion Potential This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Dispose of this container to hazardous or special waste collection point.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms.

Switzerland - Waste Ordinance Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
https://www.fedlex.admin.ch/eli/cc/2015/891/en

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN2927
14.2. UN proper shipping name Toxic liquid, corrosive, organic, n.o.s.
Technical Shipping Name (PHENOL, CHLOROFORM)
14.3. Transport hazard class(es) 6.1
Subsidiary Hazard Class 8
14.4. Packing group II

ADR

14.1. UN number	UN2927
14.2. UN proper shipping name	Toxic liquid, corrosive, organic, n.o.s.
Technical Shipping Name	(PHENOL, CHLOROFORM)
14.3. Transport hazard class(es)	6.1
Subsidiary Hazard Class	8
14.4. Packing group	II

IATA

14.1. UN number	UN2927
14.2. UN proper shipping name	TOXIC LIQUID, CORROSIVE, ORGANIC, N.O.S.
Technical Shipping Name	(PHENOL, CHLOROFORM)
14.3. Transport hazard class(es)	6.1
Subsidiary Hazard Class	8
14.4. Packing group	II

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories
Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Phenol	108-95-2	203-632-7	-	-	X	X	X	X	X
1-Butanol, 3-methyl-	123-51-3	204-633-5	-	-	X	X	KE-23575	X	X
Chloroform	67-66-3	200-663-8	-	-	X	X	X	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Phenol	108-95-2	X	ACTIVE	X	-	X	X	X
1-Butanol, 3-methyl-	123-51-3	X	ACTIVE	X	-	X	X	X
Chloroform	67-66-3	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed **KECL** - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Phenol	108-95-2	-	Use restricted. See item 75. (see link for restriction details)	-
1-Butanol, 3-methyl-	123-51-3	-	-	-
Chloroform	67-66-3	-	Use restricted. See item 32. (see *http://eur-lex.europa.eu/LexUriServ/LexUriServ.do?ur*	-

			i=CELEX:32006R1907:EN:NOT for restriction details)	

REACH links
https://echa.europa.eu/substances-restricted-under-reach

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Phenol	108-95-2	Not applicable	Not applicable
1-Butanol, 3-methyl-	123-51-3	Not applicable	Not applicable
Chloroform	67-66-3	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Component	ANNEX I - PART 1 List of chemicals subject to export notification procedure (referred to in Article 8)	ANNEX I - PART 2 List of chemicals qualifying for PIC notification (referred to in Article 11)	ANNEX I - PART 3 List of chemicals subject to the PIC procedure (referred to in Articles 13 and 14)
Chloroform 67-66-3 (15-16)	b — ban (for the category or categories concerned) b — ban (for the category or categories concerned) i(2) — industrial chemical for public	-	-

https://eur-lex.europa.eu/legal-content/EN/TXT/?uri=CELEX%3A32012R0649&qid=1604065742303.

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?
Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .
Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
Take note of Directive 94/33/EC on the protection of young people at work
Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification Water endangering class = 3 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Phenol	WGK2	Class I : 20 mg/m³ (Massenkonzentration)
1-Butanol, 3-methyl-	WGK1	
Chloroform	WGK 3	Class I : 20 mg/m³ (Massenkonzentration)

Component	France - INRS (Tables of occupational diseases)
Phenol	Tableaux des maladies professionnelles (TMP) - RG 14
1-Butanol, 3-methyl-	Tableaux des maladies professionnelles (TMP) - RG 84
Chloroform	Tableaux des maladies professionnelles (TMP) - RG 12

Swiss Regulations
Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).
Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Phenol 108-95-2 (83-84)	Prohibited and Restricted Substances		
Chloroform 67-66-3 (15-16)	Prohibited and Restricted Substances		Annex I - industrial chemical

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3
H301 - Toxic if swallowed
H311 - Toxic in contact with skin
H331 - Toxic if inhaled
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H341 - Suspected of causing genetic defects
H351 - Suspected of causing cancer
H361d - Suspected of damaging the unborn child
H372 - Causes damage to organs through prolonged or repeated exposure
H226 - Flammable liquid and vapor
H302 - Harmful if swallowed
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
EUH066 - Repeated exposure may cause skin dryness or cracking

Legend

CAS - Chemical Abstracts Service
EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
IECSC - Chinese Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
ENCS - Japanese Existing and New Chemical Substances
AICS - Australian Inventory of Chemical Substances
NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit
ACGIH - American Conference of Governmental Industrial Hygienists
DNEL - Derived No Effect Level
RPE - Respiratory Protective Equipment
LC50 - Lethal Concentration 50%
NOEC - No Observed Effect Concentration
PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average
IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)
LD50 - Lethal Dose 50%
EC50 - Effective Concentration 50%
POW - Partition coefficient Octanol:Water
vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road
IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code
OECD - Organisation for Economic Co-operation and Development
BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association
MARPOL - International Convention for the Prevention of Pollution from Ships
ATE - Acute Toxicity Estimate
VOC - (volatile organic compound)

Key literature references and sources for data
https://echa.europa.eu/information-on-chemicals
Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards	Calculation method
Environmental hazards	Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.
Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.
First aid for chemical exposure, including the use of eye wash and safety showers.
Chemical incident response training.
Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Creation Date	27-Jun-2014
Revision Date	09-Feb-2024
Revision Summary	Not applicable.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006 .

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet