# Thermo Fisher SCIENTIFIC

# **SAFETY DATA SHEET**

Page 1/9 Creation Date 27-Apr-2009 Revision Date 04-Apr-2024 Version 8

FSUM4020

# **Methanol**

# SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

产品说明: 甲醇 Product Description: 甲醇 Methanol

Cat No.: M/4020/17
Synonyms Methyl alcohol
CAS No 67-56-1
Molecular Formula C H4 O

Supplier UK entity/business name

Fisher Scientific UK

Bishop Meadow Road, Loughborough, Leicestershire LE11 5RG, United Kingdom

**EU entity/business name** Thermo Fisher Scientific Janssen Pharmaceuticalaan 3a

2440 Geel, Belgium

Emergency Telephone Number Tel: 01509 231166

Chemtrec US: (800) 424-9300 Chemtrec EU: 001-703-527-3887

E-mail address begel.sdsdesk@thermofisher.com

Recommended Use Uses advised against

Laboratory chemicals.

# **SECTION 2. HAZARD IDENTIFICATION**

Physical StateAppearanceOdorLiquidColorlessAlcohol-like

**Emergency Overview** 

Highly flammable liquid and vapor. Toxic if swallowed. Toxic in contact with skin. Toxic if inhaled. Causes damage to organs.

# Classification of the substance or mixture

Flammable liquids.	Category 2
Acute Oral Toxicity	Category 3
Acute Dermal Toxicity	Category 3
Acute Inhalation Toxicity - Vapors	Category 3
Specific target organ toxicity - (single exposure)	Category 1

# **Label Elements**

#### **Methanol**



#### Signal Word

# **Danger**

#### **Hazard Statements**

H225 - Highly flammable liquid and vapor

H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled

H370 - Causes damage to organs

#### **Precautionary Statements**

#### Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P233 - Keep container tightly closed

P240 - Ground and bond container and receiving equipment

P241 - Use explosion-proof electrical/ ventilating/ lighting equipment

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P264 - Wash face, hands and any exposed skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

#### Response

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P311 - Call a POISON CENTER or doctor

P330 - Rinse mouth

P362 + P364 - Take off contaminated clothing and wash it before reuse

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

#### Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

#### **Disposal**

P501 - Dispose of contents/ container to an approved waste disposal plant

#### **Physical and Chemical Hazards**

Highly flammable. Vapors may cause flash fire or explosion.

# **Health Hazards**

Toxic if swallowed. Toxic in contact with skin. Toxic if inhaled. Harmful if inhaled. Causes damage to organs.

# **Environmental hazards**

Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants. Will likely be mobile in the environment due to its volatility. The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

#### Other Hazards

Toxic to terrestrial vertebrates. This product does not contain any known or suspected endocrine disruptors.

# **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS No	Weight %
Methyl alcohol	67-56-1	>95

# **SECTION 4. FIRST AID MEASURES**

Page 3/9 Revision Date 04-Apr-2024

#### Methanol

\_\_\_\_\_

#### **General Advice**

Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.

#### **Eye Contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.

#### Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.

#### Inhalation

Remove to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.

# Ingestion

Do NOT induce vomiting. Call a physician or poison control center immediately.

#### Most important symptoms and effects

Difficulty in breathing. May cause blindness: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

#### Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Remove all sources of ignition. No artificial respiration, mouth-to-mouth or mouth to nose. Use suitable instruments/apparatus. Avoid contact with skin.

#### Notes to Physician

Treat symptomatically. Symptoms may be delayed.

# **SECTION 5. FIRE-FIGHTING MEASURES**

#### **Suitable Extinguishing Media**

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

# Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

# **Specific Hazards Arising from the Chemical**

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

# **Personal Precautions**

Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

# **Environmental Precautions**

Should not be released into the environment. See Section 12 for additional Ecological Information.

# Methods for Containment and Clean Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

#### **Methanol**

Refer to protective measures listed in Sections 8 and 13.

# **SECTION 7. HANDLING AND STORAGE**

#### Handling

Wear personal protective equipment/face protection. Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

#### Storage

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Flammables area.

#### Specific Use(s)

Use in laboratories

# **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### **Control Parameters**

	Component	China	Taiwan	Thailand	Hong Kong
Γ	Methyl alcohol	TWA: 25 mg/m <sup>3</sup>	TWA: 200 ppm		TWA: 200 ppm
1		STEL: 50 mg/m <sup>3</sup>	TWA: 262 mg/m <sup>3</sup>		TWA: 262 mg/m <sup>3</sup>
1		Skin			STEL: 250 ppm
1					STEL: 328 mg/m <sup>3</sup>

Component	ACGIH TLV	OSHA PEL	NIOSH	The United Kingdom	European Union
Methyl alcohol	TWA: 200 ppm	(Vacated) TWA: 200	IDLH: 6000 ppm	WEL - TWA: 200 ppm	TWA: 200 ppm 8 hr
•	STEL: 250 ppm	ppm	TWA: 200 ppm	TWA; 266 mg/m <sup>3</sup> TWA	TWA: 260 mg/m <sup>3</sup> 8 hr
	Skin	(Vacated) TWA: 260	TWA: 260 mg/m <sup>3</sup>	WEL - STEL: 250 ppm	Skin
		mg/m³	STEL: 250 ppm	STEL; 333 mg/m <sup>3</sup>	
		(Vacated) STEL: 250	STEL: 325 mg/m <sup>3</sup>	STEL	
		ppm			
		(Vacated) STEL: 325			
		mg/m³			
		Skin			
		TWA: 200 ppm			
		TWA: 260 mg/m <sup>3</sup>			

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

#### **Monitoring methods**

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. MDHS70 General methods for sampling airborne gases and vapours MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

# **Exposure Controls**

#### **Engineering Measures**

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source.

#### Personal protective equipment

Page 5/9 Revision Date 04-Apr-2024

#### Methanol

Eye Protection	Tight sealing safety goggles (European standard - EN 166)

**Hand Protection** Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Butyl rubber	> 480 minutes	0.35 mm	Level 6	As tested under EN374-3 Determination of
Viton (R)	> 480 minutes	0.70 mm	EN 374	Resistance to Permeation by Chemicals
Neoprene gloves	< 60 minutes	0.45 mm		•
Nitrile rubber	< 30 minutes	0.38 mm		

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Long sleeved clothing Skin and body protection

When workers are facing concentrations above the exposure limit they must use **Respiratory Protection** 

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits Large scale/emergency use

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to

EN371

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

When RPE is used a face piece Fit Test should be conducted

When using do not eat, drink or smoke. Provide regular cleaning of equipment, work area **Hygiene Measures** 

and clothing.

**Environmental exposure controls** No information available.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance** Colorless **Physical State** Liquid

Alcohol-like Odor **Odor Threshold** No data available Hq No information available -98 °C / -144.4 °F **Melting Point/Range Softening Point** No data available **Boiling Point/Range** 64.7 °C / 148.5 °F

Flash Point 10 °C / 50 °F Method - CC (closed cup) Abel-Pensky (DIN

51755) Directive 84/449/EEC, A.9

@ 760 mmHg

**Evaporation Rate** 5.2 (ether = 1)Flammability (solid, gas) Not applicable Liquid **Explosion Limits** Lower 6 vol%

Upper 31 vol% 128 hPa @ 20 °C **Vapor Pressure** 

(Air = 1.0)**Vapor Density** 1.11

Specific Gravity / Density 0.791

Not applicable Liquid **Bulk Density** 

Page 6/9 Revision Date 04-Apr-2024

Vapors may form explosive mixtures with air

#### Methanol

Water Solubility Miscible

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

log Pow Component Methyl alcohol -0.74

455 °C / 851 °F **Autoignition Temperature** No data available **Decomposition Temperature** 0.55 cP at 20 °C **Viscosity Explosive Properties** Not explosive

**Oxidizing Properties** No information available

C H4 O **Molecular Formula Molecular Weight** 32.04 VOC Content(%) 100

0.02255 N/m @ 20°C Surface tension

# **SECTION 10. STABILITY AND REACTIVITY**

Stability Stable under normal conditions.

**Hazardous Reactions** None under normal processing.

Hazardous polymerization does not occur. **Hazardous Polymerization** 

**Conditions to Avoid** Incompatible products. Heat, flames and sparks. Keep away from open flames, hot

surfaces and sources of ignition.

Materials to avoid Strong oxidizing agents. Strong acids. Acid anhydrides. Acid chlorides. Strong bases.

Metals. Peroxides.

Hazardous Decomposition Products Carbon monoxide (CO). Formaldehyde.

# **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Product Information**

(a) acute toxicity;

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg ( Rabbit )	LC50 = 128.2 mg/L (Rat) 4 h

(b) skin corrosion/irritation; Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met (c) serious eye damage/irritation;

(d) respiratory or skin sensitization;

Based on available data, the classification criteria are not met Respiratory Based on available data, the classification criteria are not met Skin

Component	Test method	Test species	Study result
Methyl alcohol	OECD Test Guideline 406	guinea pig	non-sensitising
67-56-1 ( >95 )	Guinea Pig Maximisation Test		
	(GPMT)		

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met (f) carcinogenicity;

There are no known carcinogenic chemicals in this product

Page 7/9 Revision Date 04-Apr-2024

#### Methanol

(g) reproductive toxicity; Based on available data, the classification criteria are not met

Component	Test method	Test species / Duration	Study result
Methyl alcohol	OECD Test Guideline 416	Rat / Inhalation 2 Generation	NOAEC = 1.3 mg/l (air)
67-56-1 (>95)			

Component substance is listed on California Proposition 65 as a developmental hazard. **Developmental Effects** 

(h) STOT-single exposure; Category 1

Results / Target organs Optic nerve

Central nervous system (CNS)

Based on available data, the classification criteria are not met (i) STOT-repeated exposure;

**Target Organs** None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

delayed

Symptoms / effects,both acute and May cause blindness: Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting

# **SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity effects** 

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Methyl alcohol	Pimephales promelas:	EC50 > 10000 mg/L 24h		EC50 = 39000 mg/L 25
	LC50 > 10000 mg/L 96h			min
				EC50 = 40000 mg/L 15
				min
				EC50 = 43000 mg/L 5
				min -

Persistence and Degradability Readily biodegradable

Persistence Persistence is unlikely based on information available

1 0101010100	i didicioned is difficulty, bacca of	information available.
	Component	Degradability
Methyl alcohol		DT50 ~ 17.2d
	67-56-1 (>95)	>94% after 20d

**Bioaccumulative Potential** Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Methyl alcohol	-0.74	<10 dimensionless

Mobility in soil The product contains volatile organic compounds (VOC) which will evaporate easily from all

surfaces Will likely be mobile in the environment due to its volatility Disperses rapidly in air

**Surface tension** 0.02255 N/m @ 20°C

**Endocrine Disruptor Information Persistent Organic Pollutant Ozone Depletion Potential** 

This product does not contain any known or suspected endocrine disruptors

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

# **SECTION 13. DISPOSAL CONSIDERATIONS**

Waste from Residues/Unused Waste is classified as hazardous. Dispose of in accordance with the European Directives

Page 8/9 Revision Date 04-Apr-2024

# Methanol

Products on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

Other Information Waste codes should be assigned by the user based on the application for which the product

was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with

local regulations.

# **SECTION 14. TRANSPORT INFORMATION**

# Road and Rail Transport

UN-No UN1230 Proper Shipping Name METHANOL

Hazard Class 3
Subsidiary Hazard Class 6.1
Packing Group ||

# IMDG/IMO

UN-No UN1230 Proper Shipping Name METHANOL

Hazard Class 3 Subsidiary Hazard Class 6.1 Packing Group II

#### IATA

UN-No UN1230 Proper Shipping Name METHANOL

Hazard Class 3
Subsidiary Hazard Class 6.1
Packing Group II

Special Precautions for User No special precautions required

# **SECTION 15. REGULATORY INFORMATION**

#### International Inventories

X = listed, China (IECSC), Europe (EINECS/ELINCS/NLP), U.S.A. (TSCA), Canada (DSL/NDSL), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), Korea (KECL).

	Component	The	List of	TCSI	IECSC	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	AICS	KECL
			dangerous										
1		Hazardous	•										
		Chemicals	12268 -										
		(2015	2012										
L		Edition)											
	Methyl alcohol	Х	Х	Х	Х	200-659-6	Х	Х	Х	Χ	Х	X	KE-23193

Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Methyl alcohol	500 tonne	5000 tonne

# **National Regulations**

**Page** 9/9 Revision Date 04-Apr-2024

#### Methanol

# **SECTION 16. OTHER INFORMATION**

**Creation Date** 27-Apr-2009 04-Apr-2024 **Revision Date Revision Summary** Not applicable.

#### **Training Advice**

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

#### Legend

**CAS** - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances IECSC - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

WEL - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration PBT - Persistent. Bioaccumulative. Toxic

ICAO/IATA - International Civil Aviation Organization/International Air **Transport Association** 

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

TSCA - United States Toxic Substances Control Act Section 8(b)

Substances List

**ENCS** - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

PNEC - Predicted No Effect Concentration

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50% POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)

#### Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

# **End of Safety Data Sheet**