ThermoFisher
SCIENTIFIC

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Creation Date 29-Jan-2015 **Revision Date** 24-Mar-2024 **Revision Number** 2

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description:	**Butyl acrylate, stabilized**
Cat No. :	**C21586**
Synonyms	2-Propenoic acid butyl ester
Index No	607-062-00-3
CAS No	141-32-2
EC No	205-480-7
Molecular Formula	C7 H12 O2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use	Laboratory chemicals.
Sector of use	SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites
Product category	PC21 - Laboratory chemicals
Process categories	PROC15 - Use as a laboratory reagent
Environmental release category	ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)
Uses advised against	No Information available

1.3. Details of the supplier of the safety data sheet

Company .

Thermo Fisher (Kandel) GmbH
Erlenbachweg 2, 76870 Kandel, Germany
Tel: +49 (0) 721 84007 280
Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US:**001-201-796-7100 / **Europe:** +32 14 57 52 99
CHEMTREC Tel. No.**US:**001-800-424-9300 / **Europe:**001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids	Category 3 (H226)

Health hazards

Acute Inhalation Toxicity - Vapors	Category 4 (H332)
Skin Corrosion/Irritation	Category 2 (H315)
Serious Eye Damage/Eye Irritation	Category 2 (H319)
Skin Sensitization	Category 1 (H317)
Specific target organ toxicity - (single exposure)	Category 3 (H335)

Environmental hazards

Chronic aquatic toxicity	Category 3 (H412)

Full text of Hazard Statements: see section 16

2.2. Label elements

Signal Word **Warning**

Hazard Statements

H226 - Flammable liquid and vapor
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H335 - May cause respiratory irritation
H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 - Call a POISON CENTER or doctor if you feel unwell

2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)
Lachrymator (substance which increases the flow of tears)
Stench
Toxic to terrestrial vertebrates
This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
n-Butyl acrylate	141-32-2	EEC No. 205-480-7	> 99	Flam. Liq. 3 (H226) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Acute Tox. 4 (H332) STOT SE 3 (H335) Aquatic Chronic 3 (H412)
4-Methoxyphenol	150-76-5	EEC No. 205-769-8	0.001-0.002	Acute Tox. 4 (H302) Skin Sens. 1 (H317) Eye Irrit. 2 (H319)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
n-Butyl acrylate	STOT SE 3 (H335) :: C>=10%	-	-

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact Get medical attention. Wash off immediately with plenty of water for at least 15 minutes.

Ingestion Do NOT induce vomiting. Get medical attention.

Inhalation Remove to fresh air. Get medical attention. If not breathing, give artificial respiration.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. May cause allergic skin reaction. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media
Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons
No information available.

5.2. Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition. Vapors may form explosive mixtures with air.

Hazardous Combustion Products
Carbon monoxide (CO), Carbon dioxide (CO_2).

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing.

6.2. Environmental precautions

Avoid release to the environment. See Section 12 for additional Ecological Information. Collect spillage. Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Use only under a chemical fume hood. Wear personal protective equipment/face protection. Use spark-proof tools and explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Use only non-sparking tools.

Hygiene Measures
Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do

not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

Technical Rules for Hazardous Substances (TRGS) 510 Storage Class (LGK) (Germany) Class 3

Switzerland - Storage of hazardous substances Storage class - SC 3
https://www.kvu.ch/de/themen/stoffe-und-produkte
https://www.kvu.ch/fr/themes/substances-et-produits
https://www.kvu.ch/it/temi/sostanze-e-prodotti

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits
List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE -** 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
n-Butyl acrylate	TWA: 2 ppm (8h) TWA: 11 mg/m³ (8h) STEL: 10 ppm (15min) STEL: 53 mg/m³ (15min)	STEL: 5 ppm 15 min STEL: 26 mg/m³ 15 min TWA: 1 ppm 8 hr TWA: 5 mg/m³ 8 hr	TWA / VME: 2 ppm (8 heures). indicative limit TWA / VME: 11 mg/m³ (8 heures). indicative limit STEL / VLCT: 10 ppm. indicative limit STEL / VLCT: 53 mg/m³. indicative limit	TWA: 2 ppm 8 uren TWA: 11 mg/m³ 8 uren STEL: 10 ppm 15 minuten STEL: 53 mg/m³ 15 minuten	STEL / VLA-EC: 10 ppm (15 minutos). STEL / VLA-EC: 53 mg/m³ (15 minutos). TWA / VLA-ED: 2 ppm (8 horas) TWA / VLA-ED: 11 mg/m³ (8 horas)
4-Methoxyphenol			TWA / VME: 5 mg/m³ (8 heures).	TWA: 5 mg/m³ 8 uren	TWA / VLA-ED: 5 mg/m³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
n-Butyl acrylate	TWA: 2 ppm 8 ore. Time Weighted Average TWA: 11 mg/m³ 8 ore. Time Weighted Average STEL: 10 ppm 15 minuti. Short-term STEL: 53 mg/m³ 15 minuti. Short-term	TWA: 2 ppm (8 Stunden). AGW - exposure factor 2 TWA: 11 mg/m³ (8 Stunden). AGW - exposure factor 2 TWA: 2 ppm (8 Stunden). MAK even if the MAK value is adhered to, "odor-associated" symptoms cannot be ruled out in individual cases TWA: 11 mg/m³ (8 Stunden). MAK even if the MAK value is adhered to,	STEL: 10 ppm 15 minutos STEL: 53 mg/m³ 15 minutos TWA: 2 ppm 8 horas TWA: 11 mg/m³ 8 horas	STEL: 53 mg/m³ 15 minuten TWA: 11 mg/m³ 8 uren	TWA: 2 ppm 8 tunteina TWA: 11 mg/m³ 8 tunteina STEL: 10 ppm 15 minuutteina STEL: 53 mg/m³ 15 minuutteina

		"odor-associated" symptoms cannot be ruled out in individual cases Höhepunkt: 4 ppm Höhepunkt: 22 mg/m³ Haut			
4-Methoxyphenol			TWA: 5 mg/m³ 8 horas		

Component	Austria	Denmark	Switzerland	Poland	Norway
n-Butyl acrylate	MAK-KZGW: 10 ppm 15 Minuten MAK-KZGW: 53 mg/m³ 15 Minuten MAK-TMW: 2 ppm 8 Stunden MAK-TMW: 11 mg/m³ 8 Stunden	TWA: 2 ppm 8 timer TWA: 11 mg/m³ 8 timer STEL: 53 mg/m³ 15 minutter STEL: 10 ppm 15 minutter	Haut/Peau STEL: 4 ppm 15 Minuten STEL: 22 mg/m³ 15 Minuten TWA: 2 ppm 8 Stunden TWA: 11 mg/m³ 8 Stunden	STEL: 30 mg/m³ 15 minutach TWA: 11 mg/m³ 8 godzinach	TWA: 2 ppm 8 timer TWA: 11 mg/m³ 8 timer STEL: 4 ppm 15 minutter. value calculated STEL: 16.5 mg/m³ 15 minutter. value calculated
4-Methoxyphenol	MAK-KZGW: 10 mg/m³ 15 Minuten MAK-TMW: 5 mg/m³ 8 Stunden	TWA: 5 mg/m³ 8 timer STEL: 10 mg/m³ 15 minutter		TWA: 5 mg/m³ 8 godzinach	TWA: 5 mg/m³ 8 timer STEL: 10 mg/m³ 15 minutter. value calculated

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
n-Butyl acrylate	TWA: 2 ppm TWA: 11 mg/m³ STEL : 10 ppm STEL : 53 mg/m³	kože TWA-GVI: 2 ppm 8 satima. TWA-GVI: 11 mg/m³ 8 satima. STEL-KGVI: 10 ppm 15 minutama. STEL-KGVI: 53 mg/m³ 15 minutama.	TWA: 2 ppm 8 hr. TWA: 11 mg/m³ 8 hr. STEL: 10 ppm 15 min STEL: 53 mg/m³ 15 min	STEL: 10 ppm STEL: 53 mg/m³ TWA: 2 ppm TWA: 11 mg/m³	TWA: 10 mg/m³ 8 hodinách. Potential for cutaneous absorption Ceiling: 20 mg/m³
4-Methoxyphenol			TWA: 5 mg/m³ 8 hr. STEL: 15 mg/m³ 15 min		

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
n-Butyl acrylate	TWA: 2 ppm 8 tundides. TWA: 11 mg/m³ 8 tundides. STEL: 10 ppm 15 minutites. STEL: 53 mg/m³ 15 minutites.	TWA: 2 ppm 8 hr TWA: 11 mg/m³ 8 hr STEL: 10 ppm 15 min STEL: 53 mg/m³ 15 min	TWA: 10 ppm TWA: 55 mg/m³	STEL: 53 mg/m³ 15 percekben. CK TWA: 11 mg/m³ 8 órában. AK	STEL: 10 ppm STEL: 53 mg/m³ TWA: 2 ppm 8 klukkustundum. TWA: 11 mg/m³ 8 klukkustundum.
4-Methoxyphenol			TWA: 5 mg/m³		TWA: 5 mg/m³ 8 klukkustundum. Ceiling: 10 mg/m³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
n-Butyl acrylate	STEL: 10 ppm STEL: 53 mg/m³ TWA: 2 ppm TWA: 11 mg/m³	TWA: 2 ppm IPRD TWA: 11 mg/m³ IPRD STEL: 10 ppm STEL: 53 mg/m³	TWA: 2 ppm 8 Stunden TWA: 11 mg/m³ 8 Stunden STEL: 10 ppm 15 Minuten STEL: 53 mg/m³ 15 Minuten	TWA: 2 ppm TWA: 11 mg/m³ STEL: 10 ppm 15 minuti STEL: 53 mg/m³ 15 minuti	TWA: 2 ppm 8 ore TWA: 11 mg/m³ 8 ore STEL: 10 ppm 15 minute STEL: 53 mg/m³ 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
n-Butyl acrylate	TWA: 10 mg/m³ 0439 MAC: 30 mg/m³	Ceiling: 53 mg/m³ TWA: 2 ppm TWA: 11 mg/m³	TWA: 2 ppm 8 urah TWA: 11 mg/m³ 8 urah Koža STEL: 10 ppm 15 minutah STEL: 53 mg/m³ 15 minutah	Binding STEL: 10 ppm 15 minuter Binding STEL: 53 mg/m³ 15 minuter TLV: 2 ppm 8 timmar. NGV TLV: 11 mg/m³ 8 timmar. NGV	TWA: 2 ppm 8 saat TWA: 11 mg/m³ 8 saat STEL: 10 ppm 15 dakika STEL: 53 mg/m³ 15 dakika
4-Methoxyphenol	MAC: 0.5 mg/m³		TWA: 5 mg/m³ 8 urah		

Biological limit values
This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Monitoring methods
BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.
MDHS70 General methods for sampling airborne gases and vapours
MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography
MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)
See table for values

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
n-Butyl acrylate 141-32-2 (> 99)			DNEL = 11mg/m³	
4-Methoxyphenol 150-76-5 (0.001-0.002)				DNEL = 3mg/m³

Predicted No Effect Concentration (PNEC)
See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
n-Butyl acrylate 141-32-2 (> 99)	PNEC = 0.00272mg/L	PNEC = 0.0338mg/kg sediment dw	PNEC = 0.011mg/L	PNEC = 3.5mg/L	PNEC = 1mg/kg soil dw
4-Methoxyphenol 150-76-5 (0.001-0.002)	PNEC = 0.0136mg/L	PNEC = 0.125mg/kg sediment dw		PNEC = 10mg/L	PNEC = 0.017mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
n-Butyl acrylate 141-32-2 (> 99)	PNEC = 0.000272mg/L	PNEC = 0.00338mg/kg sediment dw			
4-Methoxyphenol 150-76-5 (0.001-0.002)	PNEC = 0.00136mg/L	PNEC = 0.0125mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures
Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.
Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to

control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Viton (R)	See manufacturers recommendations	-	EN 374	(minimum requirement)

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water system.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Colorless	
Odor	Stench	
Odor Threshold	No data available	
Melting Point/Range	-64 °C / -83.2 °F	
Softening Point	No data available	
Boiling Point/Range	145 °C / 293 °F	@ 760 mmHg
Flammability (liquid)	Flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	**Lower** 1.5 Vol% **Upper** 7.8 Vol%	
Flash Point	39 °C / 102.2 °F	**Method -** No information available
Autoignition Temperature	297 °C / 566.6 °F	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	0.869 mPa.s at 20 °C	
Water Solubility	1.4 g/l (20°C)	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		

Component	**log Pow**	
n-Butyl acrylate	2.38	
4-Methoxyphenol	1.3	
Vapor Pressure	5 mbar @ 20 °C	
Density / Specific Gravity	0.890	
Bulk Density	Not applicable	Liquid
Vapor Density	4.4	(Air = 1.0)
Particle characteristics	(liquid) Not applicable	

9.2. Other information

Molecular Formula	C7 H12 O2
Molecular Weight	128.17
Explosive Properties	explosive air/vapour mixtures possible
Self-accelerating polymerisation temperature (SAPT)	>50°C (all packages) Inhibitor level > 131 ppm

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Light sensitive.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization may occur upon depletion of inhibitor.
Hazardous Reactions No information available.

10.4. Conditions to avoid

Temperatures above 30°C. Keep away from open flames, hot surfaces and sources of ignition. Excess heat. Exposure to light. Incompatible products.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases. Peroxides.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO_2).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral	Based on available data, the classification criteria are not met
Dermal	Based on available data, the classification criteria are not met
Inhalation	Category 4

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
n-Butyl acrylate	LD50 = 3150 mg/kg (Rat)	LD50 > 2 mg/kg (Rabbit)	LC50 = 10.3 mg/L (Rat) 4 h
4-Methoxyphenol	1600 mg/kg (Rat)	LD50 > 2000 mg/kg (Rabbit)	-

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

Respiratory Based on available data, the classification criteria are not met

Skin Category 1

May cause sensitization by skin contact

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Based on available data, the classification criteria are not met

(h) STOT-single exposure; Category 3

Results / Target organs Respiratory system.

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Target Organs None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Symptoms / effects,both acute and delayed Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects Toxic to aquatic organisms. Do not empty into drains. Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. The product contains following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
n-Butyl acrylate	LC50: = 5.2 mg/L, 96h flow-through (Oncorhynchus mykiss)	EC50: = 8.2 mg/L, 48h (Daphnia magna)	EC50: = 5.5 mg/L, 96h (Pseudokirchneriella subcapitata)
4-Methoxyphenol	LC50: = 28.5 mg/L, 96h flow-through (Oncorhynchus mykiss) LC50: = 84.3 mg/L, 96h flow-through (Pimephales		

	promelas)		

Component	Microtox	M-Factor
n-Butyl acrylate	EC50 = 31.0 mg/L 30 min EC50 = 35.0 mg/L 15 min EC50 = 37.0 mg/L 5 min	
4-Methoxyphenol	EC50 = 3.66 mg/L 5 min EC50 = 4.30 mg/L 15 min EC50 = 4.61 mg/L 30 min	

12.2. Persistence and degradability Expected to be biodegradable

Persistence Soluble in water, Persistence is unlikely, based on information available.

Degradation in sewage treatment plant Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
n-Butyl acrylate	2.38	No data available
4-Methoxyphenol	1.3	No data available

12.4. Mobility in soil The product is water soluble, and may spread in water systems . Will likely be mobile in the environment due to its water solubility. Highly mobile in soils

12.5. Results of PBT and vPvB assessment Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

12.6. Endocrine disrupting properties

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant This product does not contain any known or suspected substance

Ozone Depletion Potential This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not empty into drains.

Switzerland - Waste Ordinance Disposal should be in accordance with applicable regional, national and local laws and

regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
https://www.fedlex.admin.ch/eli/cc/2015/891/en

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number	UN2348
14.2. UN proper shipping name	BUTYL ACRYLATES, STABILIZED
14.3. Transport hazard class(es)	3
14.4. Packing group	III

ADR

14.1. UN number	UN2348
14.2. UN proper shipping name	BUTYL ACRYLATES, STABILIZED
14.3. Transport hazard class(es)	3
14.4. Packing group	III

IATA

14.1. UN number	UN2348
14.2. UN proper shipping name	BUTYL ACRYLATES, STABILIZED
14.3. Transport hazard class(es)	3
14.4. Packing group	III

14.5. Environmental hazards	No hazards identified
14.6. Special precautions for user	Inhibitors have been added to stabilize this product. Inhibitor levels should be maintained. Hazardous polymerization may occur upon depletion of inhibitor.
14.7. Maritime transport in bulk according to IMO instruments	Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories
Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
n-Butyl acrylate	141-32-2	205-480-7	-	-	X	X	KE-29450	X	X
4-Methoxyphenol	150-76-5	205-769-8	-	-	X	X	KE-23353	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
n-Butyl acrylate	141-32-2	X	ACTIVE	X	-	X	X	X
4-Methoxyphenol	150-76-5	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed **KECL** - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
n-Butyl acrylate	141-32-2	-	Use restricted. See item 75. (see link for restriction details)	-
4-Methoxyphenol	150-76-5	-	Use restricted. See item 75. (see link for restriction details)	-

REACH links
https://echa.europa.eu/substances-restricted-under-reach

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
n-Butyl acrylate	141-32-2	Not applicable	Not applicable
4-Methoxyphenol	150-76-5	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals
Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?
Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .
Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
n-Butyl acrylate	WGK1	Class I : 20 mg/m³ (Massenkonzentration)
4-Methoxyphenol	WGK1	

Component	France - INRS (Tables of occupational diseases)
n-Butyl acrylate	Tableaux des maladies professionnelles (TMP) - RG 65
4-Methoxyphenol	Tableaux des maladies professionnelles (TMP) - RG 65

Swiss Regulations
Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).
Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H226 - Flammable liquid and vapor
H302 - Harmful if swallowed
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H335 - May cause respiratory irritation
H412 - Harmful to aquatic life with long lasting effects

Legend

CAS - Chemical Abstracts Service
EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
IECSC - Chinese Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
ENCS - Japanese Existing and New Chemical Substances
AICS - Australian Inventory of Chemical Substances
NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit
ACGIH - American Conference of Governmental Industrial Hygienists
DNEL - Derived No Effect Level
RPE - Respiratory Protective Equipment
LC50 - Lethal Concentration 50%
NOEC - No Observed Effect Concentration
PBT - Persistent, Bioaccumulative, Toxic
TWA - Time Weighted Average
IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)
LD50 - Lethal Dose 50%
EC50 - Effective Concentration 50%
POW - Partition coefficient Octanol:Water
vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road
IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code
OECD - Organisation for Economic Co-operation and Development
BCF - Bioconcentration factor
ICAO/IATA - International Civil Aviation Organization/International Air Transport Association
MARPOL - International Convention for the Prevention of Pollution from Ships
ATE - Acute Toxicity Estimate
VOC - (volatile organic compound)

Key literature references and sources for data
https://echa.europa.eu/information-on-chemicals
Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Training Advice
Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.
Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.
First aid for chemical exposure, including the use of eye wash and safety showers.
Chemical incident response training.
Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Prepared By	Health, Safety and Environmental Department
Creation Date	29-Jan-2015
Revision Date	24-Mar-2024
Revision Summary	New emergency telephone response service provider.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006 .

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,

Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

End of Safety Data Sheet