

Creation Date 14-Sep-2009

Revision Date 07-Mar-2025

Revision Number 1

## Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product Description:	<b><u>n-Heptane, ACS grade, ultra dry</u></b>
Cat No. :	<b>S60486</b>
Synonyms	Normal heptane.; Heptane
Index No	601-008-00-2
CAS No	142-82-5
EC No	205-563-8
Molecular Formula	C7 H16

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use	Laboratory chemicals.
Sector of use	SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites
Product category	PC21 - Laboratory chemicals
Process categories	PROC15 - Use as a laboratory reagent
Environmental release category	ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)
Uses advised against	No Information available

### 1.3. Details of the supplier of the safety data sheet

#### Company

Thermo Fisher (Kandel) GmbH  
Erlenbachweg 2, 76870 Kandel, Germany  
Tel: +49 (0) 721 84007 280  
Fax: +49 (0) 721 84007 300

**Swiss distributor** - Fisher Scientific AG  
Neuhofstrasse 11, CH 4153 Reinach  
Tel: +41 (0) 56 618 41 11  
<https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html>

#### E-mail address

begel.sdsdesk@thermofisher.com

### 1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11  
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99  
**CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:  
Tox Info Suisse Emergency Number: **145 (24hr)**  
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)  
Chemtrec (24h) Toll-Free: 0800 564 402  
Chemtrec Local: +41-43 508 20 11 (Zurich)

## Section 2: HAZARDS IDENTIFICATION

# SAFETY DATA SHEET

n-Heptane, ACS grade, ultra dry

Revision Date 07-Mar-2025

## 2.1. Classification of the substance or mixture

### CLP Classification - Regulation (EC) No 1272/2008

#### Physical hazards

Flammable liquids

Category 2 (H225)

#### Health hazards

Aspiration Toxicity

Category 1 (H304)

Skin Corrosion/Irritation

Category 2 (H315)

Specific target organ toxicity - (single exposure)

Category 3 (H336)

#### Environmental hazards

Acute aquatic toxicity

Category 1 (H400)

Chronic aquatic toxicity

Category 1 (H410)

Full text of Hazard Statements: see section 16

## 2.2. Label elements



Signal Word

Danger

### **Hazard Statements**

H225 - Highly flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H336 - May cause drowsiness or dizziness

H410 - Very toxic to aquatic life with long lasting effects

### **Precautionary Statements**

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P331 - Do NOT induce vomiting

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P273 - Avoid release to the environment

## 2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

This product does not contain any known or suspected endocrine disruptors

# SAFETY DATA SHEET

n-Heptane, ACS grade, ultra dry

Revision Date 07-Mar-2025

## Section 3: Composition/information on ingredients

### 3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
n-Heptane	142-82-5	EEC No. 205-563-8	>95	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
n-Heptane	-	1	-

Full text of Hazard Statements: see section 16

## Section 4: First aid measures

### 4.1. Description of first aid measures

<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Get medical attention.
<b>Ingestion</b>	Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
<b>Inhalation</b>	Remove to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention. Risk of serious damage to the lungs (by aspiration). If not breathing, give artificial respiration.
<b>Self-Protection of the First Aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

### 4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes to Physician</b>	Treat symptomatically. Symptoms may be delayed.
---------------------------	---

## Section 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable Extinguishing Media

CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

# SAFETY DATA SHEET

n-Heptane, ACS grade, ultra dry

Revision Date 07-Mar-2025

## Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

## 5.2. Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Do not allow run-off from fire-fighting to enter drains or water courses.

## Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>).

## 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

## Section 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation.

### 6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

### 6.3. Methods and material for containment and cleaning up

Remove all sources of ignition. Soak up with inert absorbent material. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Keep in suitable, closed containers for disposal.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

Use only under a chemical fume hood. Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Wash hands before breaks and immediately after handling the product. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

## Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

Technical Rules for Hazardous Substances (TRGS) 510

Class 3

ALFAAS60486

# SAFETY DATA SHEET

n-Heptane, ACS grade, ultra dry

Revision Date 07-Mar-2025

## Storage Class (LGK) (Germany)

### Switzerland - Storage of hazardous substances

Storage class - SC 3

<https://www.kvu.ch/de/themen/stoffe-und-produkte>

<https://www.kvu.ch/fr/themes/substances-et-produits>

<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

### 7.3. Specific end use(s)

Use in laboratories

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
n-Heptane	TWA: 500 ppm (8h) TWA: 2085 mg/m <sup>3</sup> (8h)	STEL: 1500 ppm 15 min STEL: 6255 mg/m <sup>3</sup> 15 min TWA: 500 ppm 8 hr TWA: 2085 mg/m <sup>3</sup> 8 hr	TWA / VME: 400 ppm (8 heures). restrictive limit TWA / VME: 1668 mg/m <sup>3</sup> (8 heures). restrictive limit TWA / VME: 1000 mg/m <sup>3</sup> (8 heures). STEL / VLCT: 500 ppm. restrictive limit STEL / VLCT: 2085 mg/m <sup>3</sup> . restrictive limit STEL / VLCT: 1500 mg/m <sup>3</sup> .	TWA: 400 ppm 8 uren TWA: 1664 mg/m <sup>3</sup> 8 uren STEL: 500 ppm 15 minuten STEL: 2085 mg/m <sup>3</sup> 15 minuten	TWA / VLA-ED: 500 ppm (8 horas) TWA / VLA-ED: 2085 mg/m <sup>3</sup> (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
n-Heptane	TWA: 500 ppm 8 ore. Time Weighted Average TWA: 2085 mg/m <sup>3</sup> 8 ore. Time Weighted Average	TWA: 500 ppm (8 Stunden). AGW - exposure factor 1 TWA: 2100 mg/m <sup>3</sup> (8 Stunden). AGW - exposure factor 1 TWA: 500 ppm (8 Stunden). MAK TWA: 2100 mg/m <sup>3</sup> (8 Stunden). MAK Höhepunkt: 500 ppm Höhepunkt: 2100 mg/m <sup>3</sup>	STEL: 500 ppm 15 minutos TWA: 500 ppm 8 horas TWA: 2085 mg/m <sup>3</sup> 8 horas	STEL: 384 ppm 15 minuten STEL: 1600 mg/m <sup>3</sup> 15 minuten TWA: 288 ppm 8 uren TWA: 1200 mg/m <sup>3</sup> 8 uren	TWA: 300 ppm 8 tunteina TWA: 1200 mg/m <sup>3</sup> 8 tunteina STEL: 500 ppm 15 minuutteina STEL: 2100 mg/m <sup>3</sup> 15 minuutteina

Component	Austria	Denmark	Switzerland	Poland	Norway
n-Heptane	MAK-KZGW: 2000 ppm 15 Minuten MAK-KZGW: 8000 mg/m <sup>3</sup> 15 Minuten MAK-TMW: 500 ppm 8 Stunden MAK-TMW: 2000 mg/m <sup>3</sup> 8 Stunden	TWA: 200 ppm 8 timer TWA: 820 mg/m <sup>3</sup> 8 timer STEL: 400 ppm 15 minutter STEL: 1640 mg/m <sup>3</sup> 15 minutter	STEL: 400 ppm 15 Minuten STEL: 1600 mg/m <sup>3</sup> 15 Minuten TWA: 400 ppm 8 Stunden TWA: 1600 mg/m <sup>3</sup> 8 Stunden	STEL: 2000 mg/m <sup>3</sup> 15 minutach TWA: 1200 mg/m <sup>3</sup> 8 godzinach	TWA: 200 ppm 8 timer TWA: 800 mg/m <sup>3</sup> 8 timer TWA: 40 ppm 8 timer TWA: 275 mg/m <sup>3</sup> 8 timer STEL: 250 ppm 15 minutter. value calculated STEL: 1000 mg/m <sup>3</sup> 15 minutter. value calculated

# SAFETY DATA SHEET

n-Heptane, ACS grade, ultra dry

Revision Date 07-Mar-2025

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
n-Heptane	TWA: 1600 mg/m <sup>3</sup>	kože TWA-GVI: 500 ppm 8 satima. TWA-GVI: 2085 mg/m <sup>3</sup> 8 satima.	TWA: 500 ppm 8 hr. TWA: 2085 mg/m <sup>3</sup> 8 hr. STEL: 1500 ppm 15 min STEL: 6255 mg/m <sup>3</sup> 15 min	TWA: 500 ppm TWA: 2085 mg/m <sup>3</sup>	TWA: 1000 mg/m <sup>3</sup> 8 hodinách. Ceiling: 2000 mg/m <sup>3</sup>

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
n-Heptane	TWA: 500 ppm 8 tundides. TWA: 2085 mg/m <sup>3</sup> 8 tundides.	TWA: 500 ppm 8 hr TWA: 2085 mg/m <sup>3</sup> 8 hr	STEL: 500 ppm STEL: 2000 mg/m <sup>3</sup> TWA: 500 ppm TWA: 2000 mg/m <sup>3</sup>	TWA: 2000 mg/m <sup>3</sup> 8 órában. AK	TWA: 200 ppm 8 klukkustundum. TWA: 820 mg/m <sup>3</sup> 8 klukkustundum. Ceiling: 400 ppm Ceiling: 1640 mg/m <sup>3</sup>

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
n-Heptane	STEL: 500 ppm STEL: 2085 mg/m <sup>3</sup> TWA: 85 ppm TWA: 350 mg/m <sup>3</sup>	TWA: 500 ppm IPRD TWA: 2085 mg/m <sup>3</sup> IPRD STEL: 750 ppm STEL: 3128 mg/m <sup>3</sup>	TWA: 500 ppm 8 Stunden TWA: 2085 mg/m <sup>3</sup> 8 Stunden	TWA: 500 ppm TWA: 2085 mg/m <sup>3</sup>	TWA: 500 ppm 8 ore TWA: 2085 mg/m <sup>3</sup> 8 ore

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
n-Heptane		TWA: 500 ppm TWA: 2085 mg/m <sup>3</sup>	TWA: 500 ppm 8 urah applies to all isomers TWA: 2085 mg/m <sup>3</sup> 8 urah applies to all isomers STEL: 500 ppm 15 minutah applies to all isomers STEL: 2085 mg/m <sup>3</sup> 15 minutah applies to all isomers	Indicative STEL: 300 ppm 15 minuter Indicative STEL: 1200 mg/m <sup>3</sup> 15 minuter TLV: 200 ppm 8 timmar. NGV TLV: 800 mg/m <sup>3</sup> 8 timmar. NGV	TWA: 500 ppm 8 saat TWA: 2085 mg/m <sup>3</sup> 8 saat

## Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Component	European Union	United Kingdom	France	Spain	Germany
n-Heptane					Heptan-2,5-dione: 250 µg/L urine (end of shift )

## Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

## Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
n-Heptane 142-82-5 ( >95 )				DNEL = 300mg/kg bw/day

# SAFETY DATA SHEET

n-Heptane, ACS grade, ultra dry

Revision Date 07-Mar-2025

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
n-Heptane 142-82-5 ( >95 )				DNEL = 2085mg/m <sup>3</sup>

## Predicted No Effect Concentration (PNEC)

No information available.

## 8.2. Exposure controls

### Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

### Personal protective equipment

#### Eye Protection

Wear safety glasses with side shields (or goggles) (European standard - EN 166)

#### Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	> 480 minutes	0.38 mm	Level 6	(minimum requirement)
Neoprene gloves	> 480 minutes	0.45 mm	EN 374	
Viton (R)	> 480 minutes	0.3 mm		

#### Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

#### Respiratory Protection

No protective equipment is needed under normal use conditions.

### Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

**Recommended Filter type:** Organic gases and vapours filter Type A Brown conforming to EN14387

### Small scale/Laboratory use

Maintain adequate ventilation Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

**Recommended half mask:-** Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141

### Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

# SAFETY DATA SHEET

n-Heptane, ACS grade, ultra dry

Revision Date 07-Mar-2025

Physical State	Liquid	
Appearance	Colorless	
Odor	Petroleum distillates	
Odor Threshold	No data available	
Melting Point/Range	-91 °C / -131.8 °F	
Softening Point	No data available	
Boiling Point/Range	98 °C / 208.4 °F	
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	<b>Lower</b> 1 vol% <b>Upper</b> 7 vol%	
Flash Point	-4 °C / 24.8 °F	<b>Method -</b> No information available
Autoignition Temperature	215 °C / 419 °F	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	0.4 mPa s at 20 °C	
Water Solubility	Insoluble	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	<b>log Pow</b>	
n-Heptane	4.66	
Vapor Pressure	48 mbar @ 20 °C	
Density / Specific Gravity	0.683	
Bulk Density	Not applicable	Liquid
Vapor Density	3.5	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

## 9.2. Other information

Molecular Formula	C7 H16
Molecular Weight	100.20
Explosive Properties	Vapors may form explosive mixtures with air
Evaporation Rate	2.8 (Butyl Acetate = 1.0)

## Section 10: Stability and reactivity

### 10.1. Reactivity

None known, based on information available

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

### 10.4. Conditions to avoid

Incompatible products. Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of ignition.

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).



# SAFETY DATA SHEET

n-Heptane, ACS grade, ultra dry

Revision Date 07-Mar-2025

## Section 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
n-Heptane	>2000 mg/kg (rat)	LD50 = 3000 mg/kg ( Rabbit )	LC50 > 73.5 mg/L ( Rat ) 4 h

(b) skin corrosion/irritation;

Category 2

(c) serious eye damage/irritation;

Based on available data, the classification criteria are not met

(d) respiratory or skin sensitization;

Respiratory

Based on available data, the classification criteria are not met

Skin

Based on available data, the classification criteria are not met

(e) germ cell mutagenicity;

Based on available data, the classification criteria are not met

(f) carcinogenicity;

Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity;

Based on available data, the classification criteria are not met

(h) STOT-single exposure;

Category 3

Results / Target organs

Central nervous system (CNS).

(i) STOT-repeated exposure;

Based on available data, the classification criteria are not met

Target Organs

None known.

(j) aspiration hazard;

Category 1

Symptoms / effects, both acute and delayed

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

### 11.2. Information on other hazards

#### Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## Section 12: Ecological information

### 12.1. Toxicity

ALFAAS60486

# SAFETY DATA SHEET

n-Heptane, ACS grade, ultra dry

Revision Date 07-Mar-2025

## Ecotoxicity effects

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
n-Heptane	LC50: = 375.0 mg/L, 96h (Cichlid fish)	EC50: >10 mg/L/24h	

Component	Microtox	M-Factor
n-Heptane		1

## 12.2. Persistence and degradability

### Persistence

Persistence is unlikely.

### Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

## 12.3. Bioaccumulative potential

Product has a high potential to bioconcentrate

Component	log Pow	Bioconcentration factor (BCF)
n-Heptane	4.66	No data available

## 12.4. Mobility in soil

The product is insoluble and floats on water. Spillage unlikely to penetrate soil. The product is insoluble and floats on water. Is not likely mobile in the environment due its low water solubility. Is not likely mobile in the environment due its low water solubility and propensity to bind to soil particles.

## 12.5. Results of PBT and vPvB assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

## 12.6. Endocrine disrupting properties

### Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

## 12.7. Other adverse effects

### Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance  
This product does not contain any known or suspected substance

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

#### Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

#### Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

#### European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

#### Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not

# SAFETY DATA SHEET

n-Heptane, ACS grade, ultra dry

Revision Date 07-Mar-2025

empty into drains.

## Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600  
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

## Section 14: Transport information

### IMDG/IMO

**14.1. UN number** UN1206  
**14.2. UN proper shipping name** Heptanes  
**14.3. Transport hazard class(es)** 3  
**14.4. Packing group** II

### ADR

**14.1. UN number** UN1206  
**14.2. UN proper shipping name** Heptanes  
**14.3. Transport hazard class(es)** 3  
**14.4. Packing group** II

### IATA

**14.1. UN number** UN1206  
**14.2. UN proper shipping name** Heptanes  
**14.3. Transport hazard class(es)** 3  
**14.4. Packing group** II

**14.5. Environmental hazards** Dangerous for the environment  
Product is a marine pollutant according to the criteria set by IMDG/IMO

**14.6. Special precautions for user** No special precautions required.

**14.7. Maritime transport in bulk according to IMO instruments** Not applicable, packaged goods

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
n-Heptane	142-82-5	205-563-8	-	-	X	X	KE-18271	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
n-Heptane	142-82-5	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

### Authorisation/Restrictions according to EU REACH

ALFAAS60486

# SAFETY DATA SHEET

n-Heptane, ACS grade, ultra dry

Revision Date 07-Mar-2025

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
n-Heptane	142-82-5	-	Use restricted. See entry 75. (see link for restriction details)	-

## REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

## Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
n-Heptane	142-82-5	Not applicable	Not applicable

## Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

## Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

## National Regulations

**UK** - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

## WGK Classification

See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
n-Heptane	WGK2	

Component	France - INRS (Tables of occupational diseases)
n-Heptane	Tableaux des maladies professionnelles (TMP) - RG 84

## Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
n-Heptane 142-82-5 ( >95 )	Prohibited and Restricted Substances	Group I	

## 15.2. Chemical safety assessment

# SAFETY DATA SHEET

n-Heptane, ACS grade, ultra dry

Revision Date 07-Mar-2025

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

## Section 16: Other information

### Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H336 - May cause drowsiness or dizziness  
H400 - Very toxic to aquatic life  
H410 - Very toxic to aquatic life with long lasting effects

### Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**NOEC** - No Observed Effect Concentration

**PBT** - Persistent, Bioaccumulative, Toxic

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer  
Predicted No Effect Concentration (PNEC)

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**POW** - Partition coefficient Octanol:Water

**vPvB** - very Persistent, very Bioaccumulative

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

### Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadviser - LOLI, Merck index, RTECS

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - (volatile organic compound)

### Training Advice

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Chemical incident response training.

### Prepared By

Health, Safety and Environmental Department

### Creation Date

14-Sep-2009

### Revision Date

07-Mar-2025

### Revision Summary

Initial Release.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.  
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No  
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,  
Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and  
Preparations).**

# SAFETY DATA SHEET

n-Heptane, ACS grade, ultra dry

Revision Date 07-Mar-2025

---

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**