

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**
**Product Identifier**

Perihal Produk:

**Hydrogen chloride, ethanol solution**

Product Description:

**Hydrogen chloride, ethanol solution**

Cat No. :

S60430

**Relevant identified uses of the substance or mixture and uses advised against**

Recommended Use

Laboratory chemicals.

Uses advised against

No Information available

**Company**

 Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd  
 Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square,  
 No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,  
 Selangor Darul Ehsan, Malaysia.  
 Main line: +60 3-5525 7888

**Supplier**

E-mail address

Enquiry.my@thermofisher.com

Emergency Telephone Number

 Tel: +03-5525 7888  
 CHEMTREC Malaysia **1-800-815-308** (Malay)  
 CHEMTREC Malaysia (Kuala Lumpur) **+(60)-327884561** (Malay)

**SECTION 2: HAZARDS IDENTIFICATION**
**Classification of the substance or mixture**

Flammable liquids	Category 2 (H225)
Acute Inhalation Toxicity - Vapors	Category 3 (H331)
Skin Corrosion/Irritation	Category 1 (H314) A
Serious Eye Damage/Eye Irritation	Category 1 (H318)

**Label Elements**


Signal Word

Danger

**Hazard Statements**

H225 - Highly flammable liquid and vapor

# SAFETY DATA SHEET

Hydrogen chloride, ethanol solution

Revision Date 01-Apr-2025

H331 - Toxic if inhaled  
H314 - Causes severe skin burns and eye damage

## Precautionary Statements

### Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P240 - Ground and bond container and receiving equipment  
P242 - Use non-sparking tools  
P243 - Take action to prevent static discharges  
P264 - Wash face, hands and any exposed skin thoroughly after handling  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear protective gloves/protective clothing/eye protection/face protection

### Response

P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting  
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower  
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P310 - Immediately call a POISON CENTER or doctor  
P363 - Wash contaminated clothing before reuse  
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

### Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed  
P405 - Store locked up

### Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

## Other Hazards

This product does not contain any known or suspected endocrine disruptors  
Toxic to terrestrial vertebrates

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Ethyl alcohol	64-17-5	80
Hydrogen chloride	7647-01-0	20

## SECTION 4: FIRST AID MEASURES

### Description of first aid measures

#### General Advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

#### Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

#### Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.

#### Ingestion

Do NOT induce vomiting. Call a physician or poison control center immediately.

#### Inhalation

If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask

# SAFETY DATA SHEET

Hydrogen chloride, ethanol solution

Revision Date 01-Apr-2025

equipped with a one-way valve or other proper respiratory medical device. Remove to fresh air. Immediate medical attention is required.

## Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

## Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

## Indication of any immediate medical attention and special treatment needed

### Notes to Physician

Treat symptomatically.

## SECTION 5: FIREFIGHTING MEASURES

### Extinguishing media

#### Suitable Extinguishing Media

CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

#### Extinguishing media which must not be used for safety reasons

No information available.

### Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

### Hazardous Combustion Products

Carbon oxides, Hydrogen chloride.

### Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

### Environmental precautions

Should not be released into the environment.

### Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

### Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

# SAFETY DATA SHEET

Hydrogen chloride, ethanol solution

Revision Date 01-Apr-2025

## SECTION 7: HANDLING AND STORAGE

### Precautions for Safe Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

### Conditions for Safe Storage, Including any Incompatibilities

Corrosives area. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame.

### Specific End Uses

Use in laboratories.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

Component	Malaysia	ACGIH TLV	OSHA PEL
Ethyl alcohol		STEL: 1000 ppm	(Vacated) TWA: 1000 ppm (Vacated) TWA: 1900 mg/m <sup>3</sup> TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>
Hydrogen chloride		Ceiling: 2 ppm	Ceiling: 5 ppm Ceiling: 7 mg/m <sup>3</sup> (Vacated) Ceiling: 5 ppm (Vacated) Ceiling: 7 mg/m <sup>3</sup>

Component	European Union	The United Kingdom	Germany
Ethyl alcohol		TWA: 1000 ppm TWA: 1920 mg/m <sup>3</sup> TWA WEL - STEL: 3000 ppm STEL; 5760 mg/m <sup>3</sup> STEL	200 ppm TWA MAK; 380 mg/m <sup>3</sup> TWA MAK
Hydrogen chloride	TWA: 5 ppm (8h) TWA: 8 mg/m <sup>3</sup> (8h) STEL: 10 ppm (15min) STEL: 15 mg/m <sup>3</sup> (15min)	STEL: 5 ppm 15 min STEL: 8 mg/m <sup>3</sup> 15 min TWA: 1 ppm 8 hr TWA: 2 mg/m <sup>3</sup> 8 hr	TWA: 2 ppm (8 Stunden). AGW - exposure factor 2 TWA: 3 mg/m <sup>3</sup> (8 Stunden). AGW - exposure factor 2 TWA: 2 ppm (8 Stunden). MAK TWA: 3.0 mg/m <sup>3</sup> (8 Stunden). MAK Höhepunkt: 4 ppm Höhepunkt: 6 mg/m <sup>3</sup>

### Exposure Controls

#### Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

### Personal protective equipment

#### Eye Protection

Goggles

#### Hand Protection

Protective gloves

#### Skin and body protection

Long sleeved clothing

# SAFETY DATA SHEET

Hydrogen chloride, ethanol solution

Revision Date 01-Apr-2025

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.  
(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

## Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

## Recommended Filter type:

Organic gases and vapours filter Type A Brown conforming to EN14387

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

When RPE is used a face piece Fit Test should be conducted

## Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice

## Environmental exposure controls

No information available

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

#### Appearance

#### Physical State

Liquid

#### Odor

No information available

#### Odor Threshold

No data available

#### pH

Not applicable

#### Melting Point/Range

No data available

#### Softening Point

No data available

#### Boiling Point/Range

No information available

#### Flash Point

16 °C / 60.8 °F

Method - No information available

#### Evaporation Rate

No data available

#### Flammability (solid,gas)

Not applicable

Liquid

#### Explosion Limits

No data available

#### Vapor Pressure

No data available

#### Vapor Density

No data available

(Air = 1.0)

#### Specific Gravity / Density

0.825

#### Bulk Density

Not applicable

Liquid

#### Water Solubility

No information available

#### Solubility in other solvents

No information available

#### Partition Coefficient (n-octanol/water)

#### Component

log Pow

Ethyl alcohol

-0.32

#### Autoignition Temperature

No data available

#### Decomposition Temperature

No data available

# SAFETY DATA SHEET

Hydrogen chloride, ethanol solution

Revision Date 01-Apr-2025

Viscosity	No data available	
Explosive Properties		Vapors may form explosive mixtures with air
Oxidizing Properties	No information available	

## SECTION 10: STABILITY AND REACTIVITY

### Reactivity

None known, based on information available.

### Chemical Stability

Stable under normal conditions.

### Possibility of Hazardous Reactions

Hazardous Polymerization	No information available.
Hazardous Reactions	None under normal processing.

### Conditions to Avoid

Keep away from open flames, hot surfaces and sources of ignition.

### Incompatible Materials

None known.

### Hazardous Decomposition Products

Carbon oxides. Hydrogen chloride.

## SECTION 11: TOXICOLOGICAL INFORMATION

### Information on Toxicological Effects

#### Product Information

##### (a) acute toxicity;

Oral	Based on available data, the classification criteria are not met
Dermal	Based on available data, the classification criteria are not met
Inhalation	Category 3

### Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl alcohol	LD50 = 7060 mg/kg ( Rat )	-	20000 ppm/10H ( Rat )
Hydrogen chloride	LD50 238 - 277 mg/kg ( Rat )	LD50 > 5010 mg/kg ( Rabbit )	LC50 = 1.68 mg/L ( Rat ) 1 h

(b) skin corrosion/irritation; Category 1 A

# SAFETY DATA SHEET

Hydrogen chloride, ethanol solution

Revision Date 01-Apr-2025

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory No data available

Skin No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; No data available

(h) STOT-single exposure; No data available

(i) STOT-repeated exposure; No data available

Target Organs None known.

(j) aspiration hazard; No data available

**Symptoms / effects, both acute and delayed** Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

**Endocrine Disrupting Properties** Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## SECTION 12: ECOLOGICAL INFORMATION

### Ecotoxicity effects

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Ethyl alcohol	Fathead minnow (Pimephales promelas) LC50 = 14200 mg/l/96h	EC50 = 9268 mg/L/48h EC50 = 10800 mg/L/24h	EC50 (72h) = 275 mg/l (Chlorella vulgaris)	Photobacterium phosphoreum: EC50 = 34634 mg/L/30 min Photobacterium phosphoreum: EC50 = 35470 mg/L/5 min

**Persistence and degradability** No information available

**Bioaccumulative potential** No information available

Component	log Pow	Bioconcentration factor (BCF)
Ethyl alcohol	-0.32	No data available

**Mobility in soil** No information available.

# SAFETY DATA SHEET

Hydrogen chloride, ethanol solution

Revision Date 01-Apr-2025

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors

**Other adverse effects** No information available

## SECTION 13: DISPOSAL CONSIDERATIONS

### Waste treatment methods

**Waste from Residues/Unused Products** Waste is classified as hazardous Dispose of in accordance with the European Directives on waste and hazardous waste Dispose of in accordance with local regulations

**Contaminated Packaging** Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous Keep product and empty container away from heat and sources of ignition

**Other Information** Waste codes should be assigned by the user based on the application for which the product was used Do not flush to sewer Can be landfilled or incinerated, when in compliance with local regulations Do not empty into drains Large amounts will affect pH and harm aquatic organisms

## SECTION 14: TRANSPORT INFORMATION

### IMDG/IMO

**UN-No** UN2924  
**Hazard Class** 3  
**Subsidiary Hazard Class** 8  
**Packing Group** II  
**Proper Shipping Name** FLAMMABLE LIQUID, CORROSIVE, N.O.S. Ethanol/Hydrogen chloride

### Road and Rail Transport

**UN-No** UN2924  
**Hazard Class** 3  
**Subsidiary Hazard Class** 8  
**Packing Group** II  
**Proper Shipping Name** FLAMMABLE LIQUID, CORROSIVE, N.O.S. Ethanol/Hydrogen chloride

### IATA

**UN-No** UN2924  
**Hazard Class** 3  
**Subsidiary Hazard Class** 8  
**Packing Group** II  
**Proper Shipping Name** FLAMMABLE LIQUID, CORROSIVE, N.O.S. Ethanol/Hydrogen chloride

**Special Precautions for User** No special precautions required

## SECTION 15: REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

**International Inventories** China X = listed Australia U.S.A. (TSCA) Canada (DSL/NDL) Europe (EINECS/ELINCS/NLP) Australia (AICS) Korea (KECL) China (IECSC) Japan (ENCS) Philippines (PICCS) Taiwan (TCSI) Japan (ISHL) New Zealand (NZIoC) Japan (ISHL)



# SAFETY DATA SHEET

Hydrogen chloride, ethanol solution

Revision Date 01-Apr-2025

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Ethyl alcohol	200-578-6	X	X	X	X	X	X	X	KE-13217
Hydrogen chloride	231-595-7	X	X	X	X	X	X	X	KE-20189

Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Ethyl alcohol				Annex I - Y42
Hydrogen chloride	25 tonne	250 tonne		Annex I - Y34

## National Regulations

**Persistent Organic Pollutant**  
**Ozone Depletion Potential**

This product does not contain any known or suspected substance  
This product does not contain any known or suspected substance

## SECTION 16: OTHER INFORMATION

### Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**POW** - Partition coefficient Octanol:Water

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - (Volatile Organic Compound)

### Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadviser - LOLI, Merck index, RTECS

**Prepared By**

**Revision Date**

**Revision Summary**

Health, Safety and Environmental Department

01-Apr-2025

Initial Release.

**In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013**

### Disclaimer

# SAFETY DATA SHEET

Hydrogen chloride, ethanol solution

Revision Date 01-Apr-2025

---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**