

according to Regulation (EC) No. 1907/2006

Creation Date 28-Apr-2009 Revision Date 18-Mar-2024 Revision Number 3

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Acetone, ACS, 99.5+%, benzene NMT 2ppm

 Cat No.:
 \$55593

 Synonyms
 2-Propanone

 Index No
 606-001-00-8

 CAS No
 67-64-1

 EC No
 200-662-2

 Molecular Formula
 C3 H6 O

REACH registration number -

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.

Sector of use SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

Product category PC21 - Laboratory chemicals

Process categories PROC15 - Use as a laboratory reagent

Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

Thermo Fisher (Kandel) GmbH

Erlenbachweg 2, 76870 Kandel, Germany

Tel: +49 (0) 721 84007 280 Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG Neuhofstrasse 11, CH 4153 Reinach

Tel: +41 (0) 56 618 41 11

https://www.fishersci.ch/ch/en/customer-help-

support/forms/email-us.html

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:

Tox Info Suisse Emergency Number: 145 (24hr)

Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)

Chemtrec (24h) Toll-Free: 0800 564 402 Chemtrec Local: +41-43 508 20 11 (Zurich)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids Category 2 (H225)

Health hazards

Serious Eye Damage/Eye Irritation Category 2 (H319)
Specific target organ toxicity - (single exposure) Category 3 (H336)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280 - Wear eye protection/ face protection

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P312 - Call a POISON CENTER or doctor if you feel unwell

P337 + P313 - If eye irritation persists: Get medical advice/attention

2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB) This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Acetone	67-64-1	200-662-2	>95	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319) STOT SE 3 (H336) EUH066

REACH registration number

Full text of Hazard Statements: see section 16

Acetone, ACS, 99.5+%, benzene NMT 2ppm

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice If symptoms persist, call a physician.

Eve Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, **Skin Contact**

call a physician.

Clean mouth with water and drink afterwards plenty of water. Ingestion

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

Self-Protection of the First Aider Remove all sources of ignition. Use personal protective equipment as required.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness,

nausea and vomiting: May cause pulmonary edema

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Symptoms may be delayed. Notes to Physician

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use water jetstream.

5.2. Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

ALFAAS55593

Acetone, ACS, 99.5+%, benzene NMT 2ppm

Revision Date 18-Mar-2024

Carbon monoxide (CO), Carbon dioxide (CO₂), Formaldehyde, Methanol.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Should not be released into the environment.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Do not get in eyes, on skin, or on clothing. Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Flammables area. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame.

Technical Rules for Hazardous Substances (TRGS) 510 Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3

https://www.kvu.ch/de/themen/stoffe-und-produkte https://www.kvu.ch/fr/themes/substances-et-produits https://www.kvu.ch/it/temi/sostanze-e-prodotti

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Revision Date 18-Mar-2024

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Acetone	TWA: 500 ppm (8h) TWA: 1210 mg/m³ (8h)	TWA: 500 ppm TWA: 1210 mg/m³ STEL: 1500 ppm STEL: 3620 mg/m³	TWA / VME: 500 ppm (8 heures). restrictive limit TWA / VME: 1210 mg/m³ (8 heures). restrictive limit STEL / VLCT: 1000 ppm. restrictive limit STEL / VLCT: 2420 mg/m³. restrictive limit	• • • • • • • • • • • • • • • • • • • •	TWA / VLA-ED: 500 ppm (8 horas) TWA / VLA-ED: 121 mg/m³ (8 horas)
	1				
Component	Italy	Germany	Portugal	The Netherlands	Finland
Acetone	TWA: 500 ppm 8 ore. Time Weighted Average TWA: 1210 mg/m³ 8 ore. Time Weighted Average	TWA: 500 ppm TWA: 1200 mg/m³	STEL: 750 ppm 15 minutos TWA: 500 ppm 8 horas TWA: 1210 mg/m³ 8 horas	STEL: 2420 mg/m³ 15 minuten TWA: 1210 mg/m³ 8 uren	TWA: 500 ppm 8 tunteina TWA: 1200 mg/m³ tunteina STEL: 630 ppm 15 minuutteina STEL: 1500 mg/m³ minuutteina

Component	Austria	Denmark	Switzerland	Poland	Norway
Acetone	MAK-KZGW: 2000 ppm	TWA: 250 ppm 8 timer	STEL: 1000 ppm 15	STEL: 1800 mg/m ³ 15	TWA: 125 ppm 8 timer
	15 Minuten	TWA: 600 mg/m ³ 8 timer	Minuten	minutach	TWA: 295 mg/m ³ 8 timer
	MAK-KZGW: 4800	STEL: 500 ppm 15	STEL: 2400 mg/m ³ 15	TWA: 600 mg/m ³ 8	STEL: 156.25 ppm 15
	mg/m ³ 15 Minuten	minutter	Minuten	godzinach	minutter. value
	MAK-TMW: 500 ppm 8	STEL: 1200 mg/m ³ 15	TWA: 500 ppm 8	-	calculated
	Stunden	minutter	Stunden		STEL: 368.75 mg/m ³ 15
	MAK-TMW: 1200 mg/m ³		TWA: 1200 mg/m ³ 8		minutter. value
	8 Stunden		Stunden		calculated

	Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
	Acetone	TWA: 600 mg/m ³	TWA-GVI: 500 ppm 8	TWA: 500 ppm 8 hr.	Skin-potential for	TWA: 800 mg/m ³ 8
		STEL: 1400 mg/m ³	satima.	TWA: 1210 mg/m ³ 8 hr.	cutaneous absorption	hodinách.
		_	TWA-GVI: 1210 mg/m ³	STEL: 1500 ppm 15 min	TWA: 500 ppm	Ceiling: 1500 mg/m ³
			8 satima.	STEL: 3630 mg/m ³ 15	TWA: 1210 mg/m ³	
L				min	_	

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Acetone	TWA: 500 ppm 8 tundides. TWA: 1210 mg/m³ 8 tundides.	TWA: 500 ppm 8 hr TWA: 1210 mg/m ³ 8 hr	STEL: 3560 mg/m ³ TWA: 1780 mg/m ³	TWA: 1210 mg/m³ 8 órában. AK	TWA: 250 ppm 8 klukkustundum. TWA: 600 mg/m³ 8 klukkustundum. Ceiling: 500 ppm Ceiling: 1200 mg/m³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Acetone	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm IPRD TWA: 1210 mg/m ³ IPRD STEL: 1000 ppm	TWA: 500 ppm 8 Stunden TWA: 1210 mg/m³ 8 Stunden	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm 8 ore TWA: 1210 mg/m ³ 8 ore
		STEL: 2420 mg/m ³			

Component Russia Slovak Republic Slovenia Sweden	Turkey
--------------------------------------------------	--------

TWA: 500 ppm

TWA: 1210 mg/m³

Acetone, ACS, 99.5+%, benzene NMT 2ppm

TWA: 200 ma/m³ 1763

MAC: 800 mg/m³

TWA: 500 ppm 8 urah
TWA: 1210 mg/m³ 8
urah
STEL: 2420 mg/m³ 15
minutah
STEL: 1000 ppm 15

STEL: 1000 ppm 15

Indicative STEL: 500
ppm 15 minuter
Indicative STEL: 1200
mg/m³ 15 minuter
TLV: 250 ppm 8 timmar.
NGV

TLV: 600 mg/m³ 8 timmar. NGV

Revision Date 18-Mar-2024

Biological limit values

Acetone

List source(s):

	Component	European Union	United Kingdom	France	Spain	Germany
Γ	Acetone			Acetone: 100 mg/L urine	Acetone: 50 mg/L urine	Acetone: 80 mg/L urine
1				end of shift	end of shift	(end of shift)

minutah

Component	Italy	Finland	Denmark	Bulgaria	Romania
Acetone				Acetone: 80 mg/L urine	Acetone: 50 mg/L urine
				at the end of exposure	end of shift
				or end of work shift	

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Acetone			Acetone: 80 mg/L urine		
			end of exposure or work		
			shift		

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Acetone 67-64-1 (>95)				DNEL = 186mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Acetone 67-64-1 (>95)	DNEL = 2420mg/m ³			DNEL = 1210mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water	Water Intermittent	Soil (Agriculture)	
		sediment	sewage treatment		
Acetone	PNEC = 10.6mg/L	PNEC = 30.4 mg/kg	PNEC = 21mg/L	PNEC = 100mg/L	PNEC = 29.5 mg/kg
67-64-1 (>95)		sediment dw			soil dw

Component	Marine water	Marine water	Marine water	Food chain	Air
		sediment	Intermittent		

Acetone, ACS, 99.5+%, benzene NMT 2ppm

PNEC = 1.06mg/LPNEC = 3.04 mg/kgAcetone 67-64-1 (>95) sediment dw

8.2. Exposure controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eve Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

ſ	Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
1	Butyl rubber	> 480 minutes	0.5 mm	EN 374 Level 6	As tested under EN374-3 Determination of
1					Resistance to Permeation by Chemicals
L	Neoprene gloves	< 30 minutes	0.45 mm		·

Skin and body protection Long sleeved clothing.

Inspect gloves before use, observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits Large scale/emergency use

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to

FN371

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure Small scale/Laboratory use

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

141

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls Do not allow material to contaminate ground water system.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State Liquid

Colorless **Appearance** Odor sweet **Odor Threshold** 19.8 ppm

Melting Point/Range -95 °C / -139 °F **Softening Point** No data available **Boiling Point/Range** 56 °C / 132.8 °F Flammability (liquid) Highly flammable

On basis of test data Liquid

Flammability (solid,gas) Not applicable

ALFAAS55593

Acetone, ACS, 99.5+%, benzene NMT 2ppm

Explosion Limits Lower 2.1 vol%

Upper 13 vol%

Flash Point -20 °C / -4 °F Method - CC (closed cup)

Autoignition Temperature 465 °C / 869 °F Decomposition Temperature > 4°C

pH 7

Viscosity 0.32 mPa.s @ 20 °C

Water Solubility Soluble

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Component log Pow Acetone -0.24

Vapor Pressure 247 mbar @ 20 °C

Density / Specific Gravity 0.790

Bulk DensityNot applicableLiquidVapor Density2.0(Air = 1.0)

Particle characteristics Not applicable (liquid)

9.2. Other information

Molecular Formula C3 H6 O
Molecular Weight 58.08
VOC Content(%) 100

Explosive Properties Not explosive Vapors may form explosive mixtures with air

Oxidizing Properties Not oxidising

Evaporation Rate 5.6 (Butyl Acetate = 1.0)

Refractive index 1.358 - 1.359

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Heat, flames and sparks. Incompatible products. Keep away from open flames, hot

surfaces and sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents. Strong reducing agents. Strong bases. Peroxides. Halogenated

compounds. Alkali metals. Amines.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Formaldehyde. Methanol.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

ALFAAS55593

Acetone, ACS, 99.5+%, benzene NMT 2ppm

Product Information

(a) acute toxicity;

OralBased on available data, the classification criteria are not metDermalBased on available data, the classification criteria are not metInhalationBased on available data, the classification criteria are not met

Component LD50 Oral		LD50 Dermal	LC50 Inhalation		
Acetone	5800 mg/kg (Rat)	> 15800 mg/kg (rabbit)	76 mg/l, 4 h, (rat)		
		> 7400 mg/kg (rat)			

(b) skin corrosion/irritation; Based on available data, the classification criteria are not met

(c) serious eye damage/irritation; Category 2
Test method OECD 405
Test species rabbit

Observation end point Irritating to eyes

(d) respiratory or skin sensitization;

RespiratorySkin
Based on available data, the classification criteria are not met
Based on available data, the classification criteria are not met

Component		Test method	Test species	Study result		
Acetone Guinea Pig		Guinea Pig Maximisation Test	guinea pig	non-sensitising		
	67-64-1 (>95)	(GPMT)		_		

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

Component	Test method	Test species	Study result
Acetone	Acetone OECD Test Guideline 471		negative
67-64-1 (>95) AMES test			
	OECD Test Guideline 476	in vitro	negative
	Mammalian		
	Gene cell mutation		

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Based on available data, the classification criteria are not met

(h) STOT-single exposure; Category 3

Results / Target organs Central nervous system (CNS).

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Test method OECD Test No. 408

Test species / Duration Rat / 90 days **Study result** NOAEL = 900 mg/kg

Route of exposure Oral

Target Organs None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Acetone, ACS, 99.5+%, benzene NMT 2ppm

Revision Date 18-Mar-2024

delayed May cause pulmonary edema.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any

known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity
Ecotoxicity effects

Component	Freshwater Fish	Water Flea	Freshwater Algae
Acetone	Oncorhynchus mykiss: LC50 =	EC50 = 8800 mg/L/48h	NOEC = 430 mg/l (algae; 96 h)
	5540 mg/l 96h	EC50 = 12700 mg/L/48h	
	Alburnus alburnus: LC50 =	EC50 = 12600 mg/L/48h	
	11000 mg/l 96h		
	Leuciscus idus: LC50 = 11300		
	mg/L/48h		
	Salmo gairdneri: LC50 = 6100		
	mg/L/24h		

Component	Microtox	M-Factor
Acetone EC50 = 14500 mg/L/15 min		

12.2. Persistence and degradability Readily biodegradable

Persistence Persistence is unlikely, based on information available.

Component	Degradability		
Acetone	91 % (28 d) (OECD 301 B)		
67-64-1 (>95)			

12.3. Bioaccumulative potential Bioaccumulation is unlikely

Component log Pow		Bioconcentration factor (BCF)			
Acetone	-0.24	0.69 dimensionless			

12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all

surfaces Will likely be mobile in the environment due to its volatility. Disperses rapidly in

air

12.5. Results of PBT and vPvB

<u>assessment</u>

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent

and very bioaccumulative (vPvB).

12.6. Endocrine disrupting

properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

Acetone, ACS, 99.5+%, benzene NMT 2ppm

Revision Date 18-Mar-2024

13.1. Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives

on waste and hazardous waste. Dispose of in accordance with local regulations.

Dispose of this container to hazardous or special waste collection point. Empty containers **Contaminated Packaging**

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but

application specific.

Other Information Waste codes should be assigned by the user based on the application for which the product

was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with

local regulations.

Switzerland - Waste Ordinance Disposal should be in accordance with applicable regional, national and local laws and

regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance,

ADWO) SR 814.600

https://www.fedlex.admin.ch/eli/cc/2015/891/en

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN1090 **ACETONE** 14.2. UN proper shipping name

14.3. Transport hazard class(es) II 14.4. Packing group

ADR

14.1. UN number UN1090 ACETONE 14.2. UN proper shipping name

14.3. Transport hazard class(es) 3 II 14.4. Packing group

IATA

14.1. UN number UN1090 14.2. UN proper shipping name **ACETONE**

14.3. Transport hazard class(es) 3 П 14.4. Packing group

No hazards identified 14.5. Environmental hazards

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia

Acetone, ACS, 99.5+%, benzene NMT 2ppm

Revision Date 18-Mar-2024

(AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

L	Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
	Acetone	67-64-1	200-662-2	ı	-	X	X	KE-29367	Х	X
										•
Γ	Component	CAS No	TSCA	TCCA In	ventory	DSL	NDSL	AICS	NZIoC	PICCS

	Component	CAS No	TSCA TSCA Inventory notification - Active-Inactive		DSL	NDSL	AICS	NZIoC	PICCS
[Acetone	67-64-1	Х	ACTIVE	Х	-	Х	Х	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization		REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Acetone	67-64-1	-	Use restricted. See item 75. (see link for restriction details)	-

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Seveso III Directive (2012/	
		Qualifying Quantities for Major Accident	Qualifying Quantities for Safety Report
		Notification	Requirements
Acetone	67-64-1	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Acetone	WGK1	

Component	France - INRS (Tables of occupational diseases)
Acetone	Tableaux des maladies professionnelles (TMP) - RG 84

Swiss Regulations

Revision Date 18-Mar-2024

Acetone, ACS, 99.5+%, benzene NMT 2ppm

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Acetone 67-64-1 (>95)		Group I	

15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has been conducted by the manufacturer/importer

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

EUH066 - Repeated exposure may cause skin dryness or cracking

Legend

Inventory

Substances List

TSCA - United States Toxic Substances Control Act Section 8(b)

ICAO/IATA - International Civil Aviation Organization/International Air

MARPOL - International Convention for the Prevention of Pollution from

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

IARC - International Agency for Research on Cancer

NZIoC - New Zealand Inventory of Chemicals

Predicted No Effect Concentration (PNEC)

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

EC50 - Effective Concentration 50%

TWA - Time Weighted Average

LD50 - Lethal Dose 50%

Transport Association

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Ships

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Prepared By Health, Safety and Environmental Department

Creation Date 28-Apr-2009

ALFAAS55593 Page 13/14

Acetone, ACS, 99.5+%, benzene NMT 2ppm

Revision Date 18-Mar-2024

Revision Date 18-Mar-2024

Revision Summary New emergency telephone response service provider.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No. 1907/2006

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet