

Creation Date 05-Apr-2011 Revision Date 10-Dec-2021 Revision Number 6

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Gram Crystal Violet
Cat No.: R40052, R40053, R40073

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company Oxoid Ltd

Wade Road

Basingstoke, Hants, UK

RG24 8PW

Tel: +44 (0) 1256 841144

EU entity/business name Oxoid Deutschland GmbH

Postfach 10 07 53

D-46483 Wesel GERMANY

Tel: + 49 (0) 281 1520 Fax: 49 (0) 281 1521

E-mail address mbd-sds@thermofisher.com

1.4. Emergency telephone number

Chemtrec EU: 001-703-527-3887 Chemtrec US: (800) 424-9300

For customers in Switzerland:

Tox Info Suisse Emergency Number: 145 (24hr)

Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)

Chemtrec (24h) Toll-Free: 0800 564 402 Chemtrec Local: +41-43 508 20 11 (Zurich)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Gram Crystal Violet Revision Date 10-Dec-2021

Flammable liquids Category 3

Health hazards

Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2
Germ Cell Mutagenicity Category 2

Carcinogenicity Category 1B (H350)

Specific target organ toxicity - (single exposure)

Category 2

Environmental hazards

Chronic aguatic toxicity Category 3 (H412)

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

- H226 Flammable liquid and vapor
- H350 May cause cancer
- H412 Harmful to aquatic life with long lasting effects
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H341 Suspected of causing genetic defects
- H371 May cause damage to organs

Precautionary Statements

- P280 Wear protective gloves/protective clothing/eye protection/face protection
- P308 + P313 IF exposed or concerned: Get medical advice/attention
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
- P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction
- P332 + P313 If skin irritation occurs: Get medical advice/attention
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P308 + P313 IF exposed or concerned: Get medical advice/attention

Additional EU labelling

Restricted to professional users

2.3. Other hazards

No information available

Gram Crystal Violet Revision Date 10-Dec-2021

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Ethyl alcohol	64-17-5	200-578-6	14	Flam. Liq. 2 (H225)
Methanol	67-56-1	200-659-6	<1.0	Flam. Liq. 2 (H225)
				Acute Tox. 3 (H301)
				Acute Tox. 3 (H311)
				Acute Tox. 3 (H331)
				STOT SE 1 (H370)
Phenol	108-95-2	EEC No. 203-632-7	<1.0	Acute Tox. 3 (H301)
				Acute Tox. 3 (H311)
				Acute Tox. 3 (H331)
				Skin Corr. 1B (H314)
				Eye Dam. 1 (H318)
				Muta. 2 (H341)
				STOT RE 2 (H373)
Isopropyl alcohol	67-63-0	200-661-7	<1.0	Flam. Liq. 2 (H225)
				Eye Irrit. 2 (H319)
				STOT SE 3 (H336)
C.I. Basic Violet 3	548-62-9	EEC No. 208-953-6	<1.0	Acute Tox. 4 (H302)
				Eye Dam. 1 (H318)
				Carc. 1B (H350)
				Aquatic Acute 1 (H400)
				Aquatic Chronic 1 (H410)

Component	Specific concentration limits	M-Factor	Component notes
	(SCL's)		
Methanol	STOT SE 1 (H370) :: C>=10%	-	-
	STOT SE 2 (H371) ::		
	3%<=C<10%		
Phenol	Eye Irrit. 2 (H319) :: 1%<=C<3%	-	-
	Skin Corr. 1B (H314) :: C>=3%		
	Skin Irrit. 2 (H315) :: 1%<=C<3%		
C.I. Basic Violet 3	-	1	-

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Inhalation Remove to fresh air. Get medical attention if symptoms occur. If not breathing, give artificial

respiration.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

Gram Crystal Violet Revision Date 10-Dec-2021

4.2. Most important symptoms and effects, both acute and delayed

None reasonably foreseeable. . Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

None under normal use conditions.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Gram Crystal Violet Revision Date 10-Dec-2021

Ensure adequate ventilation. Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, sparks and flame.

Technical Rules for Hazardous Substances (TRGS) 510 Class 3 Storage Class (LGK) (Germany)

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Third edition. Published 2018. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am arbeitplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Ethyl alcohol		TWA: 1000 ppm TWA;	TWA / VME: 1000 ppm	TWA: 1000 ppm 8 uren	STEL / VLA-EC: 1000
		1920 mg/m³ TWA	(8 heures).	TWA: 1907 mg/m ³ 8	ppm (15 minutos).
		WEL - STEL: 3000 ppm		uren	STEL / VLA-EC: 1910
		STEL; 5760 mg/m ³	mg/m³ (8 heures).		mg/m³ (15 minutos).
		STEL	STEL / VLCT: 5000		
			ppm.		
			STEL / VLCT: 9500		
			mg/m³.		
Methanol	TWA: 200 ppm 8 hr	WEL - TWA: 200 ppm	TWA / VME: 200 ppm (8		TWA / VLA-ED: 200
	TWA: 260 mg/m ³ 8 hr	TWA; 266 mg/m ³ TWA	heures). restrictive limit	TWA: 266 mg/m ³ 8 uren	
	Skin	WEL - STEL: 250 ppm	TWA / VME: 260 mg/m ³	STEL: 250 ppm 15	TWA / VLA-ED: 266
		STEL; 333 mg/m ³ STEL	(8 heures). restrictive	minuten	mg/m³ (8 horas)
			limit	STEL: 333 mg/m ³ 15	Piel
			STEL / VLCT: 1000	minuten	
			ppm.	Huid	
			STEL / VLCT: 1300		
			mg/m³.		
Phenol	TMA: 2 ppm (0h)	CTCL: 4 nnm 45 min	Peau	TM/A: 2 nnm 0	CTEL /\// A EC: 4 nnm
Prienoi	TWA: 2 ppm (8h)	STEL: 4 ppm 15 min STEL: 16 mg/m ³ 15 min	TWA / VME: 2 ppm (8 heures). restrictive limit	TWA: 2 ppm 8 uren	STEL / VLA-EC: 4 ppm (15 minutos).
	TWA: 8 mg/m³ (8h) STEL: 4 ppm (15min)	TWA: 2 ppm 8 hr	TWA / VME: 7.8 mg/m ³	TWA: 8 mg/m ³ 8 uren STEL: 4 ppm 15	STEL / VLA-EC: 16
	STEL: 4 ppin (1311111) STEL: 16 mg/m ³	TWA: 7.8 mg/m ³ 8 hr	(8 heures). restrictive	minuten	mg/m ³ (15 minutos).
	(15min)	Skin	limit	STEL: 16 mg/m ³ 15	TWA / VLA-ED: 2 ppm
	Skin	OKIII	STEL / VLCT: 4 ppm.	minuten	(8 horas)
	OKIT		restrictive limit		TWA / VLA-ED: 8 mg/m ³
			STEL / VLCT: 15.6	i idid	(8 horas)
			mg/m ³ . restrictive limit		Piel
			Peau		1 101
Isopropyl alcohol			STEL / VLCT: 400 ppm.	TWA: 200 ppm 8 uren	STEL / VLA-EC: 400
		STEL: 1250 mg/m ³ 15	STEL / VLCT: 980	TWA: 500 mg/m ³ 8 uren	ppm (15 minutos).

min	mg/m³.	STEL: 400 ppm 15	STEL / VLA-EC: 1000
TWA: 400 ppm 8 hr	_	minuten	mg/m³ (15 minutos).
TWA: 999 mg/m ³ 8 hr		STEL: 1000 mg/m ³ 15	TWA / VLA-ED: 200
_		minuten	ppm (8 horas)
			TWA / VLA-ED: 500
			mg/m³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Ethyl alcohol		200 ppm TWA MAK;	TWA: 1000 ppm 8 horas	huid	TWA: 1000 ppm 8
		380 mg/m ³ TWA MAK		STEL: 1900 mg/m ³ 15	tunteina
				minuten	TWA: 1900 mg/m ³ 8
				TWA: 260 mg/m ³ 8 uren	
					STEL: 1300 ppm 15
					minuutteina
					STEL: 2500 mg/m ³ 15
			0771 070		minuutteina
Methanol	TWA: 200 ppm 8 ore.	100 ppm TWA MAK;	STEL: 250 ppm 15	huid	TWA: 200 ppm 8
	Media Ponderata nel	130 mg/m³ TWA	minutos	TWA: 133 mg/m ³ 8 uren	
	Tempo	MAKSkin absorber	TWA: 200 ppm 8 horas		TWA: 270 mg/m ³ 8 tunteina
	TWA: 260 mg/m ³ 8 ore. Media Ponderata nel		TWA: 260 mg/m³ 8 horas		STEL: 250 ppm 15
	Tempo		Pele		minuutteina
	Pelle		rele		STEL: 330 mg/m ³ 15
	I elle				minuutteina
					lho
Phenol	TWA: 2 ppm 8 ore.	TWA: 2 ppm (8	STEL: 4 ppm 15	huid	TWA: 2 ppm 8 tunteina
	Media Ponderata nel	Stunden). AGW -	minutos	TWA: 8 mg/m ³ 8 uren	TWA: 8 mg/m ³ 8
	Tempo	exposure factor 2	STEL: 16 mg/m ³ 15	3	tunteina
	TWA: 8.0 mg/m ³ 8 ore.	TWA: 8 mg/m³ (8	minutos		STEL: 4 ppm 15
	Media Ponderata nel	Stunden). AGW -	TWA: 2 ppm 8 horas		minuutteina
	Tempo	exposure factor 2	TWA: 8 mg/m ³ 8 horas		STEL: 16 mg/m ³ 15
	STEL: 4 ppm 15 minuti.	Haut	Pele		minuutteina
	Breve termine				lho
	STEL: 16 mg/m ³ 15				
	minuti. Breve termine				
	Pelle				
Isopropyl alcohol		TWA: 200 ppm (8	STEL: 400 ppm 15		TWA: 200 ppm 8
		Stunden). AGW -	minutos		tunteina
		exposure factor 2	TWA: 200 ppm 8 horas		TWA: 500 mg/m³ 8
		TWA: 500 mg/m³ (8			tunteina
		Stunden). AGW - exposure factor 2			STEL: 250 ppm 15 minuutteina
		TWA: 200 ppm (8			STEL: 620 mg/m ³ 15
		Stunden). MAK			minuutteina
		TWA: 500 mg/m ³ (8			minuuttoma
		Stunden). MAK			
		Höhepunkt: 400 ppm			
		Höhepunkt: 1000 mg/m ³			

Component	Austria	Denmark	Switzerland	Poland	Norway
Ethyl alcohol	MAK-KZGW: 2000 ppm	TWA: 1000 ppm 8 timer	STEL: 1000 ppm 15	TWA: 1900 mg/m ³ 8	TWA: 500 ppm 8 timer
	15 Minuten	TWA: 1900 mg/m ³ 8	Minuten	godzinach	TWA: 950 mg/m ³ 8 timer
	MAK-KZGW: 3800	timer	STEL: 1920 mg/m ³ 15		STEL: 625 ppm 15
	mg/m ³ 15 Minuten		Minuten		minutter. value
	MAK-TMW: 1000 ppm 8		TWA: 500 ppm 8		calculated
	Stunden		Stunden		STEL: 1187.5 mg/m ³ 15
	MAK-TMW: 1900 mg/m ³		TWA: 960 mg/m ³ 8		minutter. value
	8 Stunden		Stunden		calculated
Methanol	Haut	TWA: 200 ppm 8 timer	Haut/Peau	STEL: 300 mg/m ³ 15	TWA: 100 ppm 8 timer
	MAK-KZGW: 800 ppm	TWA: 260 mg/m ³ 8 timer	STEL: 400 ppm 15	minutach	TWA: 130 mg/m ³ 8 timer
	15 Minuten	Hud	Minuten	TWA: 100 mg/m ³ 8	STEL: 150 ppm 15
	MAK-KZGW: 1040		STEL: 520 mg/m ³ 15	godzinach	minutter. value
	mg/m ³ 15 Minuten		Minuten		calculated
	MAK-TMW: 200 ppm 8		TWA: 200 ppm 8		STEL: 162.5 mg/m ³ 15
	Stunden		Stunden		minutter. value
	MAK-TMW: 260 mg/m ³		TWA: 260 mg/m ³ 8		calculated
	8 Stunden		Stunden		Hud
Phenol	Haut	TWA: 1 ppm 8 timer	Haut/Peau	STEL: 16 mg/m ³ 15	TWA: 1 ppm 8 timer
	MAK-KZGW: 4 ppm 15	TWA: 4 mg/m ³ 8 timer	STEL: 5 ppm 15	minutach	TWA: 4 mg/m ³ 8 timer

Gram Crystal Violet

	T			= 1.11 = 2 / 22	0
	Minuten	Hud	Minuten	TWA: 7.8 mg/m ³ 8	STEL: 3 ppm 15
	MAK-KZGW: 16 mg/m ³		STEL: 19 mg/m ³ 15	godzinach	minutter. value from the
	15 Minuten		Minuten		regulation
	MAK-TMW: 2 ppm 8		TWA: 5 ppm 8 Stunden		STEL: 12 mg/m ³ 15
	Stunden		TWA: 19 mg/m ³ 8		minutter. value from the
	MAK-TMW: 8 mg/m ³ 8		Stunden		regulation
	Stunden				Hud
Isopropyl alcohol	MAK-KZGW: 800 ppm	TWA: 200 ppm 8 timer	STEL: 400 ppm 15	STEL: 1200 mg/m ³ 15	TWA: 100 ppm 8 timer
	15 Minuten	TWA: 490 mg/m ³ 8 timer	Minuten	minutach	TWA: 245 mg/m ³ 8 timer
	MAK-KZGW: 2000		STEL: 1000 mg/m ³ 15	TWA: 900 mg/m ³ 8	STEL: 150 ppm 15
	mg/m ³ 15 Minuten		Minuten	godzinach	minutter. value
	MAK-TMW: 200 ppm 8		TWA: 200 ppm 8		calculated
	Stunden		Stunden		STEL: 306.25 mg/m ³ 15
	MAK-TMW: 500 mg/m ³		TWA: 500 mg/m ³ 8		minutter. value
	8 Stunden		Stunden		calculated

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Ethyl alcohol	TWA: 1000 mg/m ³	TWA-GVI: 1000 ppm 8	STEL: 1000 ppm 15 min		TWA: 1000 mg/m ³ 8
		satima.			hodinách.
		TWA-GVI: 1900 mg/m ³			Ceiling: 3000 mg/m ³
		8 satima.			
Methanol	TWA: 200 ppm	kože	TWA: 200 ppm 8 hr.	Skin-potential for	TWA: 250 mg/m ³ 8
	TWA: 260.0 mg/m ³	TWA-GVI: 200 ppm 8	TWA: 260 mg/m ³ 8 hr.	cutaneous absorption	hodinách.
	Skin notation	satima.	STEL: 600 ppm 15 min	TWA: 200 ppm	Potential for cutaneous
		TWA-GVI: 260 mg/m ³ 8	STEL: 780 mg/m ³ 15	TWA: 260 mg/m ³	absorption
		satima.	min		Ceiling: 1000 mg/m ³
			Skin		
Phenol	TWA: 2 ppm	kože	TWA: 2 ppm 8 hr.	Skin-potential for	TWA: 7.5 mg/m ³ 8
	TWA: 8 mg/m ³	TWA-GVI: 2 ppm 8	TWA: 8 mg/m ³ 8 hr.	cutaneous absorption	hodinách.
	STEL: 4 ppm	satima.	STEL: 4 ppm 15 min	STEL: 16 mg/m ³	Potential for cutaneous
	STEL: 16 mg/m ³	TWA-GVI: 8 mg/m ³ 8	STEL: 16 mg/m ³ 15 min	STEL: 4 ppm	absorption
	Skin notation	satima.	Skin	TWA: 8 mg/m ³	Ceiling: 15 mg/m ³
		STEL-KGVI: 4 ppm 15		TWA: 2 ppm	
		minutama.			
		STEL-KGVI: 16 mg/m ³			
		15 minutama.			
Isopropyl alcohol	TWA: 980.0 mg/m ³	TWA-GVI: 400 ppm 8	TWA: 200 ppm 8 hr.		TWA: 500 mg/m ³ 8
	STEL: 1225.0 mg/m ³	satima.	STEL: 400 ppm 15 min		hodinách.
		TWA-GVI: 999 mg/m ³ 8	Skin		Potential for cutaneous
		satima.			absorption
		STEL-KGVI: 500 ppm			Ceiling: 1000 mg/m ³
		15 minutama.			
		STEL-KGVI: 1250			
	l	mg/m ³ 15 minutama.	1		l

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Ethyl alcohol	TWA: 500 ppm 8 tundides. TWA: 1000 mg/m³ 8 tundides. STEL: 1000 ppm 15 minutites. STEL: 1900 mg/m³ 15 minutites.		TWA: 1000 ppm TWA: 1900 mg/m³	STEL: 3800 mg/m³ 15 percekben. CK TWA: 1900 mg/m³ 8 órában. AK	TWA: 1000 ppm 8 klukkustundum. TWA: 1900 mg/m³ 8 klukkustundum. Ceiling: 2000 ppm Ceiling: 3800 mg/m³
Methanol	Nahk TWA: 200 ppm 8 tundides. TWA: 250 mg/m³ 8 tundides. STEL: 250 ppm 15 minutites. STEL: 350 mg/m³ 15 minutites.	Skin notation TWA: 200 ppm 8 hr TWA: 260 mg/m ³ 8 hr	skin - potential for cutaneous absorption STEL: 250 ppm STEL: 325 mg/m ³ TWA: 200 ppm TWA: 260 mg/m ³	TWA: 260 mg/m³ 8 órában. AK lehetséges borön keresztüli felszívódás	TWA: 200 ppm 8 klukkustundum. TWA: 260 mg/m³ 8 klukkustundum. Skin notation Ceiling: 400 ppm Ceiling: 520 mg/m³
Phenol	Nahk TWA: 2 ppm 8 tundides. TWA: 8 mg/m³ 8 tundides. STEL: 16 mg/m³ 15 minutites.	Skin notation TWA: 2 ppm 8 hr TWA: 8 mg/m³ 8 hr STEL: 16 mg/m³ 15 min STEL: 4 ppm 15 min	skin - potential for cutaneous absorption STEL: 4 ppm STEL: 16 mg/m³ TWA: 2 ppm TWA: 8 mg/m³	STEL: 16 mg/m³ 15 percekben. CK TWA: 8 mg/m³ 8 órában. AK lehetséges borön keresztüli felszívódás	TWA: 1 ppm 8 klukkustundum. TWA: 4 mg/m³ 8 klukkustundum. Skin notation Ceiling: 2 ppm

OXDGCV

Gram Crystal Violet

Isopropyl alcohol

STEL: 4 ppm 15 minutites.

TWA: 150 ppm 8 tundides. TWA: 350 mg/m³ 8 tundides.

STEL: 250 ppm 15

minutites. STEL: 600 mg/m³ 15

minutites.

		Ceiling: 8 mg/m ³
STEL: 500 ppm	STEL: 1000 mg/m ³ 15	TWA: 200 ppm 8
STEL: 1225 mg/m ³	percekben. CK	klukkustundum.
TWA: 400 ppm	TWA: 500 mg/m ³ 8	TWA: 490 mg/m ³ 8
TWA: 980 mg/m ³	órában. AK	klukkustundum.
_		

lehetséges borön

keresztüli felszívódás

Revision Date 10-Dec-2021

Skin notation

Ceiling: 400 ppm Ceiling: 980 mg/m³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Ethyl alcohol	TWA: 1000 mg/m ³	TWA: 500 ppm IPRD TWA: 1000 mg/m³ IPRD STEL: 1000 ppm STEL: 1900 mg/m³			TWA: 1000 ppm 8 ore TWA: 1900 mg/m³ 8 ore STEL: 5000 ppm 15 minute STEL: 9500 mg/m³ 15 minute
Methanol	skin - potential for cutaneous exposure TWA: 200 ppm TWA: 260 mg/m ³	TWA: 200 ppm IPRD TWA: 260 mg/m³ IPRD Oda	Possibility of significant uptake through the skin TWA: 200 ppm 8 Stunden TWA: 260 mg/m³ 8 Stunden	possibility of significant uptake through the skin TWA: 200 ppm TWA: 260 mg/m ³	Skin notation TWA: 200 ppm 8 ore TWA: 260 mg/m ³ 8 ore
Phenol	skin - potential for cutaneous exposure STEL: 4 ppm STEL: 16 mg/m³ TWA: 2 ppm TWA: 8 mg/m³	TWA: 2 ppm IPRD TWA: 8 mg/m³ IPRD Oda STEL: 4 ppm STEL: 16 mg/m³	Possibility of significant uptake through the skin TWA: 2 ppm 8 Stunden TWA: 8 mg/m³ 8 Stunden STEL: 16 mg/m³ 15 Minuten STEL: 4 ppm 15 Minuten	possibility of significant uptake through the skin TWA: 2 ppm TWA: 8 mg/m³ STEL: 16 mg/m³ 15 minuti STEL: 4 ppm 15 minuti	Skin notation TWA: 2 ppm 8 ore TWA: 8 mg/m³ 8 ore STEL: 4 ppm 15 minute STEL: 16 mg/m³ 15 minute
Isopropyl alcohol	STEL: 600 mg/m ³ TWA: 350 mg/m ³	TWA: 150 ppm IPRD TWA: 350 mg/m³ IPRD STEL: 250 ppm STEL: 600 mg/m³			TWA: 81 ppm 8 ore TWA: 200 mg/m ³ 8 ore STEL: 203 ppm 15 minute STEL: 500 mg/m ³ 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Ethyl alcohol	TWA: 1000 mg/m ³ 2391 MAC: 2000 mg/m ³	Ceiling: 1920 mg/m³ TWA: 500 ppm TWA: 960 mg/m³	TWA: 960 mg/m³ 8 urah TWA: 500 ppm 8 urah STEL: 1000 ppm 15 minutah STEL: 1920 mg/m³ 15 minutah	Indicative STEL: 1000 ppm 15 minuter Indicative STEL: 1900 mg/m³ 15 minuter TLV: 500 ppm 8 timmar. NGV TLV: 1000 mg/m³ 8 timmar. NGV	
Methanol	TWA: 5 mg/m³ 1250 Skin notation MAC: 15 mg/m³	Potential for cutaneous absorption TWA: 200 ppm TWA: 260 mg/m ³	TWA: 200 ppm 8 urah TWA: 260 mg/m³ 8 urah Koža STEL: 800 ppm 15 minutah STEL: 1040 mg/m³ 15 minutah	Indicative STEL: 250 ppm 15 minuter Indicative STEL: 350 mg/m³ 15 minuter TLV: 200 ppm 8 timmar. NGV TLV: 250 mg/m³ 8 timmar. NGV Hud	Deri TWA: 200 ppm 8 saat TWA: 260 mg/m³ 8 saat
Phenol	TWA: 0.3 mg/m³ 0539 Skin notation MAC: 1 mg/m³	Ceiling: 16 mg/m³ Potential for cutaneous absorption TWA: 2 ppm TWA: 8 mg/m³	TWA: 2 ppm 8 urah TWA: 8 mg/m³ 8 urah Koža STEL: 4 ppm 15 minutah STEL: 16 mg/m³ 15 minutah	Binding STEL: 4 ppm 15 minuter Binding STEL: 16 mg/m³ 15 minuter TLV: 1 ppm 8 timmar. NGV TLV: 4 mg/m³ 8 timmar. NGV Hud	Deri TWA: 2 ppm 8 saat TWA: 8 mg/m³ 8 saat STEL: 4 ppm 15 dakika STEL: 16 mg/m³ 15 dakika
Isopropyl alcohol	TWA: 10 mg/m ³ 1761 MAC: 50 mg/m ³	Ceiling: 1000 mg/m ³ TWA: 200 ppm	TWA: 200 ppm 8 urah TWA: 500 mg/m³ 8 urah	Indicative STEL: 250 ppm 15 minuter	

Gram Crystal Violet

	TWA: 500 mg/m ³	STEL: 400 ppm 15	Indicative STEL: 600	
	_	minutah	mg/m³ 15 minuter	
		STEL: 1000 mg/m ³ 15	TLV: 150 ppm 8 timmar.	
		minutah	NGV	
			TLV: 350 mg/m ³ 8	
i			timmar, NGV	

Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Methanol			Methanol: 15 mg/L urine	Methanol: 15 mg/L urine	Methanol: 15 mg/L urine
			end of shift	end of shift	(end of shift)
					Methanol: 15 mg/L urine
					(for long-term
					exposures: at the end of
					the shift after several
					shifts)
Phenol			Total Phenol: 250 mg/g	: 120 mg/g Creatinine	Phenol (after
			creatinine urine end of	urine end of shift	hydrolysis): 120 mg/g
			shift		Creatinine urine (end of
					shift)
Isopropyl alcohol				Acetone: 40 mg/L urine	Acetone: 25 mg/L whole
				end of workweek	blood (end of shift)
					Acetone: 25 mg/L urine
					(end of shift)

Component	Italy	Finland	Denmark	Bulgaria	Romania
Methanol					Methanol: 6 mg/L urine
					end of shift
Phenol		Total phenol: 1.3		Phenol: 200 µg/L urine	total Phenol: 120 mg/g
		mmol/L urine after the		at the end of exposure	Creatinine urine end of
		shift.		or end of work shift	shift
Isopropyl alcohol					Acetone: 50 mg/L urine
					end of shift

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Methanol			Methanol: 30 mg/L urine		
			end of exposure or work		
			shift		
			Methanol: 30 mg/L urine		
			after all work shifts for		
			long-term exposure		
Phenol			Phenol: 200 mg/L urine		
			end of exposure or work		
			shift		

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Ethyl alcohol				DNEL = 343mg/kg

OXDGCV

Gram Crystal Violet

64-17-5 (14)		bw/day
Methanol	DNEL = 20mg/kg	DNEL = 20mg/kg
67-56-1 (<1.0)	bw/day	bw/day
Phenol		DNEL = 1.23mg/kg
108-95-2 (<1.0)		bw/day
Isopropyl alcohol		DNEL = 888mg/kg
67-63-0 (<1.0)		bw/day
C.I. Basic Violet 3		DNEL = 0.42mg/kg
548-62-9 (<1.0)		bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Ethyl alcohol 64-17-5 (14)	DNEL = 1900mg/m ³			DNEL = 950mg/m ³
Methanol 67-56-1 (<1.0)	DNEL = 130mg/m ³	DNEL = 130mg/m ³	DNEL = 130mg/m ³	DNEL = 130mg/m ³
Phenol 108-95-2 (<1.0)	DNEL = 16mg/m ³			DNEL = 8mg/m ³
Isopropyl alcohol 67-63-0 (<1.0)				DNEL = 500mg/m ³
C.I. Basic Violet 3 548-62-9 (<1.0)				DNEL = 1.48mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water	Water Intermittent	Microorganisms in	Soil (Agriculture)
		sediment		sewage treatment	
Ethyl alcohol	PNEC = 0.96mg/L	PNEC = 3.6mg/kg	PNEC = 2.75mg/L	PNEC = 580mg/L	PNEC = 0.63 mg/kg
64-17-5 (14)		sediment dw	-		soil dw
Methanol	PNEC = 20.8mg/L	PNEC = 77mg/kg	PNEC = 1540mg/L	PNEC = 100mg/L	PNEC = 100mg/kg
67-56-1 (<1.0)		sediment dw	_	-	soil dw
Phenol	PNEC =	PNEC =	PNEC = 0.031mg/L	PNEC = 2.1mg/L	PNEC =
108-95-2 (<1.0)	0.0077mg/L	0.0915mg/kg			0.136mg/kg soil dw
		sediment dw			
Isopropyl alcohol	PNEC = 140.9mg/L	PNEC = 552mg/kg	PNEC = 140.9mg/L	PNEC = 2251mg/L	PNEC = 28mg/kg
67-63-0 (<1.0)		sediment dw	-	-	soil dw
C.I. Basic Violet 3	PNEC =				
548-62-9 (<1.0)	0.0024mg/L				

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Ethyl alcohol 64-17-5 (14)	PNEC = 0.79mg/L	PNEC = 2.9mg/kg sediment dw		PNEC = 0.38g/kg food PNEC = 0.72g/kg food	
Methanol 67-56-1 (<1.0)	PNEC = 2.08mg/L	PNEC = 7.7mg/kg sediment dw			
Phenol 108-95-2 (<1.0)	PNEC = 0.00077mg/L	PNEC = 0.00915mg/kg sediment dw			
Isopropyl alcohol 67-63-0 (<1.0)	PNEC = 140.9mg/L	PNEC = 552mg/kg sediment dw		PNEC = 160mg/kg food	

8.2. Exposure controls

Engineering MeasuresEnsure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that

Gram Crystal Violet Revision Date 10-Dec-2021

evewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Disposable gloves	See manufacturers	-	EN 374	(minimum requirement)
	recommendations			

Skin and body protection Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use In case of insufficient ventilation, wear suitable respiratory equipment

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water

system. Local authorities should be advised if significant spillages cannot be contained.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State Liquid

Appearance Dark purple

Odor
Odor No information available
Odor Threshold No data available
Melting Point/Range No data available
Softening Point No data available
Boiling Point/Range Not applicable

Flammability (liquid) Flammable On basis of test data

Flammability (solid,gas) Not applicable Liquid

Explosion Limits No data available

Flash Point 36.11 °C / 97 °F Method - CC (closed cup)

Autoignition Temperature No data available Decomposition Temperature No data available

pH 3.0 - 5.5

Viscosity No data available
Water Solubility No information available

Solubility in other solvents

No information available

Partition Coefficient (n-octanol/water)

Componentlog PowEthyl alcohol-0.32Methanol-0.74

Gram Crystal Violet Revision Date 10-Dec-2021

Phenol 1.5 Isopropyl alcohol 0.05

Vapor PressureNo data availableDensity / Specific GravityNo data available

Bulk DensityNot applicableLiquidVapor DensityNo data available(Air = 1.0)

Particle characteristics Not applicable (liquid)

9.2. Other information

Explosive Properties explosive air/vapour mixtures possible

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

None under normal use conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information Product does not present an acute toxicity hazard based on known or supplied information

(a) acute toxicity;

Dermal

Inhalation

Oral Based on ATE data, the classification criteria are not met

Based on available data, the classification criteria are not met Based on ATE data, the classification criteria are not met

Based on available data, the classification criteria are not met

Based on ATE data, the classification criteria are not met

Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl alcohol	LD50 = 7060 mg/kg (Rat)	-	20000 ppm/10H (Rat)
Methanol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h
Phenol	LD50 = 340 mg/kg (Rat)	LD50 = 630 mg/kg (Rabbit)	•
Isopropyl alcohol	5045 mg/kg (Rat)	12800 mg/kg (Rat)	72.6 mg/L (Rat) 4 h

Gram Crystal Violet Revision Date 10-Dec-2021

	3600 mg/kg (Mouse)		
C.I. Basic Violet 3	LD50 = 420 mg/kg (Rat)	-	-

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

Respiratory No data available Skin No data available

Component	Test method	Test species	Study result
Methanol	OECD Test Guideline 406	guinea pig	non-sensitising
67-56-1 (<1.0)	Guinea Pig Maximisation Test (GPMT)		

(e) germ cell mutagenicity; Category 2

(f) carcinogenicity; Category 1B

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
C.I. Basic Violet 3	Carc Cat. 1B			Group 2B

(g) reproductive toxicity; No data available

Component	Test method	Test species / Duration	Study result
Methanol	OECD Test Guideline 416	Rat / Inhalation	NOAEC =
67-56-1 (<1.0)		2 Generation	1.3 mg/l (air)

(h) STOT-single exposure; Category 2

Results / Target organs Optic nerve, Central nervous system (CNS).

(i) STOT-repeated exposure; No data available

None known. **Target Organs**

No data available (j) aspiration hazard;

Symptoms / effects, both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. delayed

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any

known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects The product contains following substances which are hazardous for the environment.

Contains a substance which is:. Very toxic to aquatic organisms.

Page 13/19

Gram Crystal Violet

Component	Freshwater Fish	Water Flea	Freshwater Algae
Ethyl alcohol	Fathead minnow (Pimephales promelas) LC50 = 14200 mg/l/96h	EC50 = 9268 mg/L/48h EC50 = 10800 mg/L/24h	EC50 (72h) = 275 mg/l (Chlorella vulgaris)
Methanol	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 > 10000 mg/L 24h	
Phenol	4-7 mg/L LC50 96 h 32 mg/L LC50 96 h	EC50: 10.2 - 15.5 mg/L, 48h (Daphnia magna) EC50: 4.24 - 10.7 mg/L, 48h Static (Daphnia magna)	EC50: 0.0188 - 0.1044 mg/L, 96h static (Pseudokirchneriella subcapitata) EC50: 187 - 279 mg/L, 72h static (Desmodesmus subspicatus) EC50: = 46.42 mg/L, 96h (Pseudokirchneriella subcapitata)
Isopropyl alcohol	LC50: = 9640 mg/L, 96h flow-through (Pimephales promelas) LC50: > 1400000 μg/L, 96h (Lepomis macrochirus) LC50: = 11130 mg/L, 96h static (Pimephales promelas) LC50: = 10000000 μg/L, 96h (Daphnia)	13299 mg/L EC50 = 48 h 9714 mg/L EC50 = 24 h	EC50: > 1000 mg/L, 96h (Desmodesmus subspicatus) EC50: > 1000 mg/L, 72h (Desmodesmus subspicatus)

Component	Microtox	M-Factor
Ethyl alcohol	Photobacterium phosphoreum:EC50 = 34634	
	mg/L/30 min	
	Photobacterium phosphoreum:EC50 = 35470	
	mg/L/5 min	
Methanol	EC50 = 39000 mg/L 25 min	
	EC50 = 40000 mg/L 15 min	
	EC50 = 43000 mg/L 5 min	
Phenol	EC50 21 - 36 mg/L 30 min	
	EC50 = 23.28 mg/L 5 min	
	EC50 = 25.61 mg/L 15 min	
	EC50 = 28.8 mg/L 5 min	
	EC50 = 31.6 mg/L 15 min	
Isopropyl alcohol	= 35390 mg/L EC50 Photobacterium phosphoreum	
	5 min	
C.I. Basic Violet 3		1

12.2. Persistence and degradability No information available

Component	Degradability
Methanol	DT50 ~ 17.2d
67-56-1 (<1.0)	>94% after 20d

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential No information available

Component	log Pow	Bioconcentration factor (BCF)
Ethyl alcohol	-0.32	No data available
Methanol	-0.74	<10
Phenol	1.5	No data available
Isopropyl alcohol	0.05	No data available

12.4. Mobility in soil No information available .

12.5. Results of PBT and vPvB No data available for assessment.

Revision Date 10-Dec-2021 **Gram Crystal Violet**

assessment

12.6. Endocrine disrupting

properties

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects **Persistent Organic Pollutant Ozone Depletion Potential**

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused

Products

Dispose of in accordance with local regulations. Waste is classified as hazardous. Dispose

of in accordance with the European Directives on waste and hazardous waste.

Dispose of this container to hazardous or special waste collection point. Empty containers **Contaminated Packaging**

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

According to the European Waste Catalog, Waste Codes are not product specific, but **European Waste Catalogue (EWC)**

application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the

> application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not

empty into drains.

Switzerland - Waste Ordinance Disposal should be in accordance with applicable regional, national and local laws and

regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance,

ADWO) SR 814.600

https://www.fedlex.admin.ch/eli/cc/2015/891/en

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN1170

Ethanol solution 14.2. UN proper shipping name

14.3. Transport hazard class(es) 14.4. Packing group Ш

ADR

14.1. UN number UN1170

Ethanol solution 14.2. UN proper shipping name

14.3. Transport hazard class(es) 3 14.4. Packing group Ш

IATA

14.1. UN number UN1170

14.2. UN proper shipping name Ethanol solution

14.3. Transport hazard class(es) 3 Ш

14.4. Packing group

Gram Crystal Violet Revision Date 10-Dec-2021

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Ethyl alcohol	64-17-5	200-578-6	-	-	Х	X	KE-13217	Χ	Х
Methanol	67-56-1	200-659-6	-	-	Х	X	KE-23193	X	X
Phenol	108-95-2	203-632-7	-	-	Х	Χ	KE-28209	Х	Х
Isopropyl alcohol	67-63-0	200-661-7	-	-	Х	X	KE-29363	X	Х
C.I. Basic Violet 3	548-62-9	208-953-6	-	-	Х	X	KE-07006	Х	Х

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Ethyl alcohol	64-17-5	Х	ACTIVE	Х	-	X	Х	Х
Methanol	67-56-1	X	ACTIVE	Х	-	X	Х	Х
Phenol	108-95-2	Х	ACTIVE	Х	-	X	Х	Х
Isopropyl alcohol	67-63-0	X	ACTIVE	X	-	X	X	Х
C.I. Basic Violet 3	548-62-9	X	ACTIVE	Х	-	Χ	Χ	Х

Legend: X - Listed '-' - Not Listed **KECL** - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methanol	-	Use restricted. See item 69. (see link for restriction details)	-
Phenol	-	Use restricted. See item 75. (see link for restriction details)	-
Isopropyl alcohol	-	Use restricted. See item 75. (see link for restriction details)	-
C.I. Basic Violet 3	-	Use restricted. See item 28. (see link for restriction details) Use restricted. See item 72. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	SVHC Candidate list - 208-953-6 - Carcinogenic, Article 57a

After the sunset date the use of this substance requires either an authorization or can only be used for exempted uses, e.g. use in scientific research and development which includes routine analytics or use as intermediate.

https://echa.europa.eu/authorisation-list

https://echa.europa.eu/substances-restricted-under-reach

https://echa.europa.eu/candidate-list-table

Component	CAS No	Seveso III Directive (2012/18/EC) -	Seveso III Directive (2012/18/EC) -
		Qualifying Quantities for Major	Qualifying Quantities for Safety

Gram Crystal Violet

		Accident Notification	Report Requirements
Ethyl alcohol	64-17-5	Not applicable	Not applicable
Methanol	67-56-1	500 tonne	5000 tonne
Phenol	108-95-2	Not applicable	Not applicable
Isopropyl alcohol	67-63-0	Not applicable	Not applicable
C.I. Basic Violet 3	548-62-9	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Dir 76/769/EEC relating to restrictions on the marketing and use of certain dangerous substances and preparations

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 3 (self classification)

Component	Germany - Water Classification (VwVwS)	Germany - TA-Luft Class
Ethyl alcohol	WGK1	
Methanol	WGK 2	
Phenol	WGK2	Class I: 20 mg/m³ (Massenkonzentration)
Isopropyl alcohol	WGK1	
C.I. Basic Violet 3	WGK3	

Component	France - INRS (Tables of occupational diseases)		
Ethyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84		
Methanol	Tableaux des maladies professionnelles (TMP) - RG 84		
Phenol	Tableaux des maladies professionnelles (TMP) - RG 14		
Isopropyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84		

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Ethyl alcohol 64-17-5 (14)		Group I	
Methanol 67-56-1 (<1.0)	Prohibited and Restricted Substances	Group I	
Phenol 108-95-2 (<1.0)	Prohibited and Restricted Substances		
Isopropyl alcohol 67-63-0 (<1.0)		Group I	
C.I. Basic Violet 3 548-62-9 (<1.0)	Prohibited and Restricted Substances		

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION	

OXDGCV

Gram Crystal Violet Revision Date 10-Dec-2021

Full text of H-Statements referred to under sections 2 and 3

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H371 - May cause damage to organs

H341 - Suspected of causing genetic defects

H350 - May cause cancer

H412 - Harmful to aquatic life with long lasting effects

H225 - Highly flammable liquid and vapor

H301 - Toxic if swallowed

H302 - Harmful if swallowed

H311 - Toxic in contact with skin

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H331 - Toxic if inhaled

H336 - May cause drowsiness or dizziness

H370 - Causes damage to organs H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

Legend

Inventory

Substances List

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic

Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TWA - Time Weighted Average

ACGIH - American Conference of Governmental Industrial Hygienists IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC) **DNEL** - Derived No Effect Level

RPE - Respiratory Protective Equipment LD50 - Lethal Dose 50%

LC50 - Lethal Concentration 50% EC50 - Effective Concentration 50% NOEC - No Observed Effect Concentration POW - Partition coefficient Octanol:Water

PBT - Persistent, Bioaccumulative, Toxic vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of

Dangerous Goods by Road

WEL - Workplace Exposure Limit

IMO/IMDG - International Maritime Organization/International Maritime

Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

ICAO/IATA - International Civil Aviation Organization/International Air **Transport Association**

TSCA - United States Toxic Substances Control Act Section 8(b)

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

MARPOL - International Convention for the Prevention of Pollution from

Ships

ATE - Acute Toxicity Estimate VOC - (volatile organic compound)

BCF - Bioconcentration factor

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data Calculation method **Health Hazards Environmental hazards** Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

05-Apr-2011 **Creation Date** 10-Dec-2021 **Revision Date**

Revision Summary Update to CLP Format.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

Gram Crystal Violet Revision Date 10-Dec-2021

COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet