

SAFETY DATA SHEET

Revision Date 01-April-2024 Revision Number 4

1. Identification

Product Name Barium tungsten isopropoxide, 10% inisopropanol

Cat No.: 41046

Synonyms No information available

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Importer/Distributor

Fisher Scientific 112 Colonnade Road, Ottawa, ON K2E 7L6,

Canada

Tel: 1-800-234-7437

Emergency Telephone Number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

WHMIS 2015 Classification Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

Flammable liquids

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Specific target organ toxicity (single exposure)

Category 2

Category 2

Category 2

Category 2

Category 3

Target Organs - Central nervous system (CNS), Respiratory system.

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor Causes skin irritation Causes serious eye damage

May cause respiratory irritation
May cause drowsiness and dizziness



Precautionary Statements

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection/face protection

Use non-sparking tools

Take action to prevent static discharges

Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

IF INHALED: Remove person to fresh air and keep comfortable for breathing

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER/doctor

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Take off contaminated clothing and wash it before reuse

Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Isopropyl alcohol	67-63-0	90.00
Barium tungsten isopropoxide	333971-25-8	10.00

4. First-aid measures

General Advice If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Most important symptoms/effects

Difficulty in breathing. Causes eye burns. Causes severe eye damage. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea

and vomiting

Treat symptomatically Notes to Physician

Fire-fighting measures

Suitable Extinguishing Media Water mist may be used to cool closed containers.

Unsuitable Extinguishing Media No information available

12 °C / 53.6 °F **Flash Point**

Method -No information available

Autoignition Temperature

Explosion Limits

No information available

No data available Upper Lower No data available Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

None known.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health	Flammability	Instability	Physical hazards
2	3	0	-

Accidental release measures

Ensure adequate ventilation. Use personal protective equipment as required. Remove all **Personal Precautions**

sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions Should not be released into the environment. See Section 12 for additional Ecological

Information.

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment

Oρ	Nemove all sources of ignition. Ose spank proof tools and explosion proof equipment.
	7. Handling and storage
Handling	Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not

get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Take precautionary measures against static discharges.

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, Storage. sparks and flame.

8. Exposure controls / personal protection

Exposure Guidelines

Component	Alberta	British	Ontario TWAEV	Quebec	ACGIH TLV	OSHA PEL	NIOSH
		Columbia					
Isopropyl alcohol	TWA: 200 ppm	(Vacated) TWA:	IDLH: 2000 ppm				
	TWA: 492	STEL: 400 ppm	STEL: 400 ppm	STEL: 400 ppm	STEL: 400 ppm	400 ppm	TWA: 400 ppm
	mg/m³					(Vacated) TWA:	TWA: 980
	STEL: 400 ppm					980 mg/m ³	mg/m³
	STEL: 984					(Vacated) STEL:	STEL: 500 ppm
	mg/m³					500 ppm	STEL: 1225
						(Vacated) STEL:	mg/m³
						1225 mg/m ³	
						TWA: 400 ppm	
						TWA: 980	
						mg/m³	

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location.

Ensure adequate ventilation, especially in confined areas. Use explosion-proof

electrical/ventilating/lighting/equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control

hazardous materials at source

Personal protective equipment

Eye Protection Goggles

Hand Protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Glove material	Breakthrough time	Glove thickness	Glove comments
Nitrile rubber	See manufacturers	-	Splash protection only
Viton (R)	recommendations		

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly **Recommended Filter type:** low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

No information available.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

9. Physical and chemical properties

Physical StateLiquidAppearanceYellowOdorAlcohol

Odor Threshold
pHNo information available
No information availableMelting Point/RangeNo data availableBoiling Point/RangeNo information availableFlash Point12 °C / 53.6 °F

Evaporation Rate
No information available
Flammability (solid,gas)
Not applicable

Flammability or explosive limits

Upper
Lower
No data available
No data available
No information available
Vapor Pressure
Vapor Density
No information available
Specific Gravity
No information available
No information available
No information available
No data available
No data available

Autoignition TemperatureNo information availableDecomposition TemperatureNo information availableViscosityNo information available

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Stable under normal conditions.

Conditions to Avoid Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials Strong oxidizing agents

Hazardous Decomposition Products None under normal use conditions

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous ReactionsNone under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Oral LD50

Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

Dermal LD50

Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

Vapor LC50

Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.

Component Information

Component	Component LD50 Oral		LC50 Inhalation		
Isopropyl alcohol	5045 mg/kg (Rat)	12800 mg/kg (Rat)	72.6 mg/L (Rat) 4 h		
	3600 mg/kg (Mouse)				

Toxicologically Synergistic No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

IrritationNo information availableSensitizationNo information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

С	omponent	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico

Barium tungsten isopropoxide, 10% inisopropanol

Not listed Not listed	Not listed
Not listed Not listed	Not listed

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure Central nervous system (CNS) Respiratory system

STOT - repeated exposure None known

Aspiration hazard No information available

delayed

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Isopropyl alcohol	EC50: > 1000 mg/L, 72h	LC50: = 9640 mg/L, 96h	= 35390 mg/L EC50	13299 mg/L EC50 = 48 h
	(Desmodesmus	flow-through (Pimephales	Photobacterium	9714 mg/L EC50 = 24 h
	subspicatus)	promelas)	phosphoreum 5 min	
	EC50: > 1000 mg/L, 96h	LC50: > 1400000 µg/L, 96h		
	(Desmodesmus	(Lepomis macrochirus)		
	subspicatus)	LC50: = 11130 mg/L, 96h		
		static (Pimephales		
		promelas)		
		LC50: = 10000000 µg/L, 96h		
		(Daphnia)		
		` , ,		

Persistence and Degradability Persistence is unlikely

Bioaccumulation/ Accumulation No information available.

Is not likely mobile in the environment due its low water solubility. **Mobility**

Component	log Pow
Isopropyl alcohol	0.05

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN1219 **ISOPROPANOL Proper Shipping Name**

Hazard Class 3 **Packing Group** Ш

TDG

UN-No UN1219

Proper Shipping Name ISOPROPANOL

Hazard Class Packing Group Ш

IATA

UN1219 **UN-No**

Proper Shipping Name ISOPROPANOL Hazard Class 3

Packing Group Ш

IMDG/IMO

UN-No UN1219

ISOPROPANOL Proper Shipping Name

Hazard Class Packing Group Ш

15. Regulatory information

International Inventories

Component	CAS-No	DSL	NDSL	TSCA	TSCA Inventory notification - Active-Inactive	EINECS	ELINCS	NLP
Isopropyl alcohol	67-63-0	X	-	X	ACTIVE	200-661-7	-	-
Barium tungsten isopropoxide	333971-25-8	-	-	-	-	-	-	-

Component	CAS-No	IECSC	KECL	ENCS	ISHL	TCSI	AICS	NZIoC	PICCS
Isopropyl alcohol	67-63-0	Х	KE-29363	Х	Х	X	Х	Х	Х
Barium tungsten isopropoxide	333971-25-8	-	-	-	-	-	-	-	-

Legend:

X - Listed '-' - Not Listed

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

Canada

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

Component	Canada - National Pollutant Release Inventory (NPRI)	Canadian Environmental Protection Agency (CEPA) - List of Toxic Substances	Canada's Chemicals Management Plan (CEPA)
Isopropyl alcohol	Part 1, Group A Substance Part 5, Individual Substances Part 4 Substance		

Legend NPRI - National Pollutant Release Inventory

Other International Regulations

Authorisation/Restrictions according to EU REACH

Component		REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	
Isopropyl alcohol	-	Use restricted. See item 75.	-

	(see link for restriction details)	

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS-No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Isopropyl alcohol	67-63-0	Listed	Not applicable	Not applicable	Not applicable
Barium tungsten isopropoxide	333971-25-8	Not applicable	Not applicable	Not applicable	Not applicable

Component	CAS-No	Seveso III Directive (2012/18/EC) - Qualifying Quantities	(2012/18/EC) -	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
		for Major Accident Notification	for Safety Report Requirements		
Isopropyl alcohol	67-63-0	Not applicable	Not applicable	Not applicable	Annex I - Y42
Barium tungsten isopropoxide	333971-25-8	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By Product Safety Department

Email: chem.techinfo@thermofisher.com

www.thermofisher.com

Revision Date 01-April-2024 Print Date 01-April-2024

Revision Summary New emergency telephone response service provider.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS