

# **SAFETY DATA SHEET**

Creation Date 23-Sep-2009 Revision Date 24-May-2018 Revision Number 3

1. Identification

Product Name Zinc PVA Fixative

Cat No.: R21278, R21279, R21765, R21927

Synonyms No information available

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet

Company

Remel 12076 Santa Fe Drive Lenexa, KS 66215 United States Telephone: 1-800-255-6730 Fax:1-800-621-8251

**Emergency Telephone Number** 

INFOTRAC - 24 Hour Number: 1-800-535-5053

Outside of the United States, call 24 Hour Number: 001-352-323-3500 (Call Collect)

# 2. Hazard(s) identification

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids

Skin Corrosion/irritation

Serious Eye Damage/Eye Irritation

Specific target organ toxicity (single exposure)

Category 1

Category 1

Category 1

Category 1

Category 1

Label Elements

### Signal Word

Danger

# **Hazard Statements**

Flammable liquid and vapor Causes skin irritation Causes serious eye damage May cause respiratory irritation May cause drowsiness or dizziness Causes damage to organs

Zinc PVA Fixative Revisio



## **Precautionary Statements**

#### Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

### Response

IF exposed: Call a POISON CENTER or doctor/physician

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

### Skin

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

#### Eves

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician

#### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

### Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

### **Disposal**

Dispose of contents/container to an approved waste disposal plant

# Hazards not otherwise classified (HNOC)

Toxic to aquatic life with long lasting effects

WARNING. Reproductive Harm - https://www.p65warnings.ca.gov/.

# 3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Glycerin	56-81-5	1.5
Ethyl alcohol	64-17-5	28 - 29
Methyl alcohol	67-56-1	1.5
Acetic acid	64-19-7	4.5
Zinc sulfate heptahydrate	7446-20-0	2.5

# 4. First-aid measures

Zinc PVA Fixative

**General Advice** Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

**Eye Contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

SPEEDY ACTION IS CRITICAL, GET MEDICAL AID IMMEDIATELY. **Skin Contact** 

Inhalation Move to fresh air.

Rinse mouth. Get medical attention. Ingestion

Most important symptoms and

effects

**Notes to Physician** 

Breathing difficulties. Causes eye burns. . Symptoms of overexposure may be headache,

dizziness, tiredness, nausea and vomiting

Treat symptomatically

# Fire-fighting measures

Cool closed containers exposed to fire with water spray. Suitable Extinguishing Media

No information available Unsuitable Extinguishing Media

**Flash Point** 29.4 °C / 84.9 °F

Method -No information available

**Autoignition Temperature** 

**Explosion Limits** 

No information available

Upper No data available Lower No data available Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

### **Specific Hazards Arising from the Chemical**

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

### **Hazardous Combustion Products**

None known

# **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health	Flammability	Instability	Physical hazards
3	3	0	N/A

# Accidental release measures

Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate **Personal Precautions** 

ventilation. Take precautionary measures against static discharges.

**Environmental Precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. See Section 12 for additional ecological information. Avoid release to the environment.

Collect spillage. Do not flush into surface water or sanitary sewer system.

Up

Methods for Containment and Clean Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Ground and bond containers when transferring material. Take precautionary measures against static discharges. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

# Handling and storage

Handling Ensure adequate ventilation. Do not breathe vapors or spray mist. Keep container tightly

Zinc PVA Fixative

closed. Ensure adequate ventilation. Take precautionary measures against static discharges. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools.

Storage

Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

# 8. Exposure controls / personal protection

## **Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Glycerin		(Vacated) TWA: 10 mg/m³ (Vacated) TWA: 5 mg/m³ TWA: 15 mg/m³ TWA: 5 mg/m³		TWA: 10 mg/m <sup>3</sup>
Ethyl alcohol	STEL: 1000 ppm	(Vacated) TWA: 1000 ppm (Vacated) TWA: 1900 mg/m³ TWA: 1000 ppm TWA: 1900 mg/m³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m³	TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>
Methyl alcohol	TWA: 200 ppm STEL: 250 ppm Skin	(Vacated) TWA: 200 ppm (Vacated) TWA: 260 mg/m³ (Vacated) STEL: 250 ppm (Vacated) STEL: 325 mg/m³ Skin TWA: 200 ppm TWA: 260 mg/m³	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m³ STEL: 250 ppm STEL: 325 mg/m³	TWA: 200 ppm TWA: 260 mg/m³ STEL: 250 ppm STEL: 310 mg/m³
Acetic acid	TWA: 10 ppm STEL: 15 ppm	(Vacated) TWA: 10 ppm (Vacated) TWA: 25 mg/m³ TWA: 10 ppm TWA: 25 mg/m³	IDLH: 50 ppm TWA: 10 ppm TWA: 25 mg/m³ STEL: 15 ppm STEL: 37 mg/m³	TWA: 10 ppm TWA: 25 mg/m³ STEL: 15 ppm STEL: 37 mg/m³

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

**Engineering Measures** Ensure that eyewash stations and safety showers are close to the workstation location.

Ensure adequate ventilation, especially in confined areas. Use explosion-proof

electrical/ventilating/lighting/equipment.

Personal Protective Equipment

**Eye/face Protection** Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Antistatic boots. Wear fire/flame resistant/retardant clothing. Impervious gloves. Skin and body protection

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard **Respiratory Protection** 

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

**Hygiene Measures** When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area

and clothing.

# Physical and chemical properties

**Physical State** Liquid Clear **Appearance** 

Zinc PVA Fixative

Odor
Odor Threshold
No information available
No information available
No information available
No information available
No data available
No data available
No information available
Soiling Point/Range
No information available
Flash Point
29.4 °C / 84.9 °F
Evaporation Rate
No information available

Flammability (solid,gas) Not applicable

Flammability or explosive limits

Upper
Lower
No data available
No data available
No data available
No information available
Vapor Density
No information available
Specific Gravity
No information available
No information available
No information available
No data available
No data available

Autoignition TemperatureNo information availableDecomposition TemperatureNo information available

Viscosity No information available

VOC Content(%) 36.5

# 10. Stability and reactivity

Reactive Hazard None known, based on information available

**Stability** Stable under normal conditions.

Conditions to Avoid Heating in air. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials Strong oxidizing agents

Hazardous Decomposition Products None under normal use conditions

Hazardous Polymerization Hazardous polymerization does not occur.

**Hazardous Reactions**None under normal processing.

# 11. Toxicological information

**Acute Toxicity** 

**Product Information** 

Oral LD50Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.Dermal LD50Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.Vapor LC50Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.

**Component Information** 

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Glycerin	12600 mg/kg ( Rat )	> 10 g/kg(Rabbit)	> 2.75 mg/L/4h ( Rat )(mist)
Ethyl alcohol	LD50 = 7060 mg/kg (Rat)	Not listed	20000 ppm/10H ( Rat )
Methyl alcohol	Calc. ATE 60 mg/kg LD50 > 1187 – 2769 mg/kg ( Rat )	<b>Calc. ATE 60 mg/kg</b> LD50 = 17100 mg/kg(Rabbit)	Calc. ATE 0.6 mg/L (vapours) or 0.5 mg/L (mists) LC50 = 128.2 mg/L ( Rat ) 4 h
Acetic acid	3310 mg/kg (Rat)	-	> 40 mg/L (Rat) 4 h
Zinc sulfate heptahydrate	1260 mg/kg (Rat)	Not listed	Not listed

Toxicologically Synergistic

No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation No information available

Zinc PVA Fixative

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

This product contains one or more substances which are classified by IARC as

carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly

carcinogenic to humans (Group 2B). Ethanol has been shown to be carcinogenic in long-term studies only when consumed and abused as an alcoholic beverage.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Glycerin	56-81-5	Not listed				
Ethyl alcohol	64-17-5	Group 1	Known	A3	Х	Not listed
Methyl alcohol	67-56-1	Not listed				
Acetic acid	64-19-7	Not listed				
Zinc sulfate	7446-20-0	Not listed				
heptahydrate						

IARC: (International Agency for Research on Cancer)

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

No information available **Mutagenic Effects** 

No information available. **Reproductive Effects** 

**Developmental Effects** No information available.

No information available. **Teratogenicity** 

STOT - single exposure Respiratory system Central nervous system (CNS) Optic nerve

STOT - repeated exposure None known

No information available **Aspiration hazard** 

delayed

Symptoms / effects, both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

**Endocrine Disruptor Information** No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

## 12. Ecological information

#### **Ecotoxicity**

Contains a substance which is:. Toxic to aquatic organisms. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Glycerin	Not listed	LC50: 51 - 57 mL/L, 96h static (Oncorhynchus mykiss)	Not listed	EC50: > 500 mg/L, 24h (Daphnia magna)
Ethyl alcohol	EC50 (72h) = 275 mg/l (Chlorella vulgaris)	LC50 = 14200 mg/l/96h	Photobacterium phosphoreum:EC50 = 34634 mg/L/30 min Photobacterium phosphoreum:EC50 = 35470 mg/L/5 min	S
Methyl alcohol	Not listed	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	EC50 > 10000 mg/L 24h

#### Zinc PVA Fixative

Acetic acid	-	Pimephales promelas: LC50	Photobacterium	EC50 = 95 mg/L/24h
		= 88 mg/L/96h	phosphoreum: EC50 = 8.8	•
		Lepomis macrochirus: LC50	mg/L/15 min	
		= 75 mg/L/96h	Photobacterium	
		_	phosphoreum: EC50 = 8.8	
			mg/L/25 min	
			Photobacterium	
			phosphoreum: EC50 = 8.8	
			mg/L/5 min	
Zinc sulfate heptahydrate	Not listed	1.9 mg/L LC50 96 h	Not listed	Not listed

**Persistence and Degradability** 

No information available

**Bioaccumulation/ Accumulation** 

No information available.

**Mobility** 

Component	log Pow
Glycerin	-1.76
Ethyl alcohol	-0.32
Methyl alcohol	-0.74
Acetic acid	-0.2

# 13. Disposal considerations

**Waste Disposal Methods** 

Should not be released into the environment. Dispose of in accordance with local regulations.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl alcohol - 67-56-1	U154	=

# 14. Transport information

DOT

**UN-No** UN1170

Proper Shipping Name ETHANOL SOLUTION

Hazard Class 3 Packing Group III

<u>TDG</u>

**UN-No** UN1170

Proper Shipping Name ETHANOL SOLUTION

Hazard Class 3
Packing Group III

IATA

**UN-No** UN1170

Proper Shipping Name ETHANOL SOLUTION

Hazard Class 3 Packing Group III

IMDG/IMO

**UN-No** UN1170

Proper Shipping Name ETHANOL SOLUTION

Hazard Class 3
Packing Group III

# 15. Regulatory information

All of the components in the product are on the following Inventory lists: X = listed

#### International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Glycerin	Х	Х	-	200-289-5	-		Х	Х	Χ	Χ	Χ
Ethyl alcohol	Х	Х	-	200-578-6	-		Χ	Χ	Χ	Χ	Χ

#### Zinc PVA Fixative

Methyl alcohol	Х	Χ	-	200-659-6	-	Х	Х	Х	Х	Х
Acetic acid	Х	Χ	-	200-580-7	-	Х	Χ	Χ	Х	Х
Zinc sulfate heptahydrate	-	Χ	-	-	-	Χ	-	Χ	Х	-

#### Legend:

- X Listed
- E Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.
- F Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.
- N Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
- P Indicates a commenced PMN substance
- R Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S Indicates a substance that is identified in a proposed or final Significant New Use Rule
- T Indicates a substance that is the subject of a Section 4 test rule under TSCA.
- XU Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).
- Y1 Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.
- Y2 Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

#### U.S. Federal Regulations

**TSCA 12(b)** 

Not applicable

### **SARA 313**

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Methyl alcohol	67-56-1	1.5	1.0
Zinc sulfate heptahydrate	7446-20-0	2.5	1.0

### SARA 311/312 Hazard Categories

See section 2 for more information

#### **CWA (Clean Water Act)**

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Acetic acid	X	5000 lb	-	-
Zinc sulfate heptahydrate	-	-	X	-

#### Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl alcohol	X		-

### **OSHA** Occupational Safety and Health Administration

Not applicable

### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Methyl alcohol	5000 lb	-
Acetic acid	5000 lb	-

# **California Proposition 65**

This product contains the following proposition 65 chemicals

Component	CAS-No	California Prop. 65	Prop 65 NSRL	Category
Ethyl alcohol	64-17-5	Development (alcoholic	-	Developmental
_		beverages only)		Carcinogen
Methyl alcohol	67-56-1	Developmental	-	Developmental

## U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Glycerin	X	Х	X	-	Х

#### Zinc PVA Fixative

Ethyl alcohol	Χ	X	X	X	X
Methyl alcohol	Χ	X	X	X	X
Acetic acid	Χ	X	X	-	X
Zinc sulfate heptahydrate	=	Х	X	=	=

#### **U.S. Department of Transportation**

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

### **U.S. Department of Homeland Security**

This product does not contain any DHS chemicals.

### Other International Regulations

Mexico - Grade Serious risk, Grade 3

16. Other information
-----------------------

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 23-Sep-2009

 Revision Date
 24-May-2018

 Print Date
 24-May-2018

**Revision Summary** This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS).

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**