

SAFETY DATA SHEET

Creation Date 06-October-2009

Revision Date 26-December-2021

Revision Number 5

1. Identification

Product Name Methylmagnesium iodide, 3M solution in diethyl ether

AC427400000, AC427401000, AC427408000 Cat No.:

Synonyms No information available

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Manufacturer Importer/Distributor

Acros Organics Fisher Scientific Company Fisher Scientific One Reagent Lane 112 Colonnade Road, One Reagent Lane Fair Lawn, NJ 07410 Fair Lawn, NJ 07410 Ottawa, ON K2E 7L6. Tel: (201) 796-7100 Canada

Tel: 1-800-234-7437

Emergency Telephone Number For information **US** call: 001-800-ACROS-01 / Europe call: +32 14 57 52 11

> Emergency Number US:001-201-796-7100 / Europe: +32 14 57 52 99 CHEMTREC Tel. No. US: 001-800-424-9300 / Europe: 001-703-527-3887

2. Hazard(s) identification

Classification

WHMIS 2015 Classification Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

Flammable liquids Category 1 Acute oral toxicity Category 4 Category 4 Acute dermal toxicity Acute Inhalation Toxicity Category 4 Category 1 B Skin Corrosion/Irritation Serious Eye Damage/Eye Irritation Category 1 Specific target organ toxicity (single exposure) Category 3 Target Organs - Respiratory system, Central nervous system (CNS).

Physical Hazards Not Otherwise Classified Category 1

Reacts violently with water May form explosive peroxides

Health Hazards Not Otherwise Classified Category 1

Prolonged or repeated contact may dry skin and cause irritation or cracking

Label Elements

Signal Word

Danger

Hazard Statements

Extremely flammable liquid and vapor
Harmful if swallowed, in contact with skin or if inhaled
Causes severe skin burns and eye damage
Causes serious eye damage
Harmful if inhaled
Reacts violently with water
May form explosive peroxides

Prolonged or repeated contact may dry skin and cause irritation or cracking



Precautionary Statements

Prevention

Do not allow contact with water Keep container tightly closed

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Ground/bond container and receiving equipment

Use only non-sparking tools

Take precautionary measures against static discharges

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection/face protection

Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

IF INHALED: Remove person to fresh air and keep comfortable for breathing

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER/doctor

Rinse mouth

Do NOT induce vomiting

Wash contaminated clothing before reuse

Explosion risk in case of fire

Fight fire with normal precautions from a reasonable distance

Evacuate area

Storage

Store locked up

Store in a closed container

Store in a well-ventilated place. Keep cool

Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Light sensitive

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Ethyl ether	60-29-7	60
Magnesium, iodomethyl-	917-64-6	40

4. First-aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Inhalation Remove to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the

substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required. If

not breathing, give artificial respiration.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

Most important symptoms/effects Difficulty in breathing. Causes burns by all exposure routes. Inhalation of high vapor

concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting: Product is a corrosive material. Use of gastric lavage or emesis is

contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of

perforation

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool

closed containers.

Unsuitable Extinguishing Media No information available

Flash Point -40 °C / -40 °F

Method - No information available

Autoignition Temperature

Explosion Limits

No information available

Upper No data available
Lower No data available

Sensitivity to Mechanical Impact No information available **Sensitivity to Static Discharge** No information available

Specific Hazards Arising from the Chemical

Extremely flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Contact with water liberates extremely flammable gases.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO2). Hydrogen iodide.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health Flammability Instability Physical hazards

6. Accidental release measures

Personal Precautions

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing.

Environmental Precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

Up

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Do not expose spill to water.

7. Handling and storage

Handling

Use only under a chemical fume hood. Wear personal protective equipment/face protection. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing. Do not breathe (dust, vapor, mist, gas). Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. If peroxide formation is suspected, do not open or move container. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Storage.

Corrosives area. Flammables area. Keep away from heat, sparks and flame. Store under an inert atmosphere. Keep away from water or moist air. Protect from light. Store indoors. May form explosive peroxides on prolonged storage. Keep containers tightly closed in a dry. cool and well-ventilated place. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Incompatible Materials. Strong oxidizing agents. Strong acids.

8. Exposure controls / personal protection

Exposure Guidelines

Component	Alberta	British Columbia	Ontario TWAEV	Quebec	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethyl ether	TWA: 400 ppm TWA: 1210 mg/m³ STEL: 500 ppm STEL: 1520 mg/m³		TWA: 400 ppm STEL: 500 ppm	TWA: 400 ppm TWA: 1210 mg/m³ STEL: 500 ppm STEL: 1520 mg/m³	TWA: 400 ppm STEL: 500 ppm	(Vacated) TWA: 400 ppm (Vacated) TWA: 1200 mg/m³ (Vacated) STEL: 500 ppm (Vacated) STEL: 1500 mg/m³ TWA: 400 ppm TWA: 1200 mg/m³	''

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles

Hand Protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Glove material	Breakthrough time	Glove thickness	Glove comments
Nitrile rubber	See manufacturers	-	Splash protection only
Viton (R)	recommendations		

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly **Recommended Filter type:** low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

No information available.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

9. Physical and chemical properties

Physical State Liquid

AppearanceNo information availableOdorNo information availableOdor ThresholdNo information availablePHNo information available

Melting Point/RangeNo data availableBoiling Point/RangeNo information availableFlash Point-40 °C / -40 °FEvaporation RateNo information available

Flammability (solid,gas) Not applicable

Flammability or explosive limits

Upper No data available
Lower No data available
Vapor Pressure No information available

Vapor Density

No information available

Specific Gravity 1.26

Solubility
No information available
Partition coefficient; n-octanol/water
No data available

Autoignition TemperatureNo information availableDecomposition TemperatureNo information availableViscosityNo information available

Molecular FormulaC H3 I MgMolecular Weight166.24

10. Stability and reactivity

Reactive Hazard Yes

Stability Light sensitive. heat sensitive. Moisture sensitive. Air sensitive.

Conditions to Avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition. Exposure to light. Exposure to moist air or water. Exposure to air.

Strong oxidizing agents, Strong acids **Incompatible Materials**

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), Hydrogen iodide

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions Reacts violently with water.

11. Toxicological information

Acute Toxicity

Product Information

Category 4. Oral LD50

Category 4. ATE = 1000 - 2000 mg/kg. **Dermal LD50** Vapor LC50 Category 4. ATE = 10 - 20 mg/l.

Component Information

Component LD50 Oral		LD50 Dermal	LC50 Inhalation	
Ethyl ether	1215 mg/kg (Rat)	20 mL/kg (Rabbit)	32000 ppm (Rat) 4 h	

Toxicologically Synergistic

Products

No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Causes burns by all exposure routes Irritation

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Ethyl ether	60-29-7	Not listed				
Magnesium,	917-64-6	Not listed				
iodomethyl-						

Mutagenic Effects No information available

Reproductive Effects No information available.

No information available. **Developmental Effects**

Teratogenicity No information available.

STOT - single exposure Respiratory system Central nervous system (CNS)

STOT - repeated exposure None known

No information available **Aspiration hazard**

delayed

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and

danger of perforation

No information available **Endocrine Disruptor Information**

Other Adverse Effects

The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Do not empty into drains. .

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ethyl ether	Not listed	LC50: > 10000 mg/L, 96h	EC50 = 5600 mg/L 15 min	EC50 = 165 mg/L/24h
		static (Lepomis macrochirus)	_	_
		LC50: = 2560 mg/L, 96h		
		flow-through (Pimephales		
		promelas)		

Persistence and Degradability

No information available

Bioaccumulation/ Accumulation No information available.

Mobility .

Component	log Pow
Ethyl ether	0.82

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

	Component	RCRA - U Series Wastes	RCRA - P Series Wastes	
-	Ethyl ether - 60-29-7	U117	-	

14. Transport information

DOT

UN-No UN3399

Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE

Technical Name Methylmagnesium iodide, 3M in Diethyl ether

Hazard Class 4.3 Subsidiary Hazard Class 3 Packing Group 1

TDG

UN-No UN3399

Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE

Hazard Class 4.3 Subsidiary Hazard Class 3 Packing Group 1

<u>IATA</u>

UN-No UN3399

Proper Shipping Name Organometalic substance, liquid, water-reactive, flammable (Mixture)

Hazard Class 4.3 Subsidiary Hazard Class 3 Packing Group 1

IMDG/IMO

UN-No UN3399

Proper Shipping Name Organometallic substance, liquid, water-reactive, flammable (Mixture)

Hazard Class 4.3 Subsidiary Hazard Class 3 Packing Group 1

15. Regulatory information

International Inventories

Component	CAS-No	DSL	NDSL	TSCA	TSCA Inventory notification - Active-Inactive	EINECS	ELINCS	NLP
Ethyl ether	60-29-7	Х	-	Х	ACTIVE	200-467-2	•	-
Magnesium, iodomethyl-	917-64-6	-	Х	Х	ACTIVE	213-031-1	-	-

Component	CAS-No	IECSC	KECL	ENCS	ISHL	TCSI	AICS	NZIoC	PICCS
Ethyl ether	60-29-7	X	KE-27690	X	Х	X	X	X	X
Magnesium, iodomethyl-	917-64-6	-	-	-	Х	X	-	-	-

Legend:

X - Listed '-' - Not Listed

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

Canada

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

Component	Canada - National Pollutant Release Inventory (NPRI)	Canadian Environmental Protection Agency (CEPA) - List of Toxic Substances	Canada's Chemicals Management Plan (CEPA)
Ethyl ether	Part 4 Substance		

Other International Regulations

Authorisation/Restrictions according to EU REACH

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS-No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Ethyl ether	60-29-7	Listed	Not applicable	Not applicable	Not applicable
Magnesium, iodomethy	l- 917-64-6	Not applicable	Not applicable	Not applicable	Not applicable

Component	CAS-No	Seveso III Directive (2012/18/EC) -	Seveso III Directive (2012/18/EC) -	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
		Qualifying Quantities Qualifying Quantities			
		for Major Accident	for Safety Report		
		Notification	Requirements		
Ethyl ether	60-29-7	Not applicable	Not applicable	Not applicable	Annex I - Y40 Annex I
					- Y42
Magnesium, iodomethyl-	917-64-6	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

Creation Date06-October-2009Revision Date26-December-2021Print Date26-December-2021

Revision Summary This document has been updated to comply with the requirements of WHMIS 2015 to align

with the Globally Harmonised System (GHS) for the Classification and Labelling of

Chemicals.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS