

Page 1 / 10 Creation Date 17-Sep-2014 Revision Date 22-Mar-2025

Version 5

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THECOMPANY/UNDERTAKING

Product Identifier

Perihalan Produk:

Product Description:

Cat No.:

Diethylaluminium iodide, 0.9M solution in toluene
Diethylaluminium iodide, 0.9M solution in toluene
381160000: 381161000: 381168000

 Cat No.:
 381160000;

 Synonyms
 DEAI

 Molecular Formula
 C4 H10 Al I

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

Company Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd

Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square, No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,

Selangor Darul Ehsan, Malaysia. Main line: +60 3-5525 7888

E-mail address Enquiry.my@thermofisher.com

Emergency Telephone Number Tel: +03-5525 7888

CHEMTREC Malaysia 1-800-815-308 (Malay)

CHEMTREC Malaysia (Kuala Lumpur) +(60)-327884561 (Malay)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

Flammable liquids	Category 2 (H225)
Substances/mixtures which, in contact with water, emit flammable gases	Category 1 (H260)
Aspiration Toxicity	Category 1 (H304)
Skin Corrosion/Irritation	Category 1 (H314) A
Serious Eye Damage/Eye Irritation	Category 1 (H318)
Reproductive Toxicity	Category 2 (H361d)
Specific target organ toxicity - (single exposure)	Category 3 (H336)
Specific target organ toxicity - (repeated exposure)	Category 2 (H373)
Chronic aquatic toxicity	Category 3 (H412)

Label Elements



Signal Word

Danger

Hazard Statements

- H225 Highly flammable liquid and vapor
- H260 In contact with water releases flammable gases which may ignite spontaneously
- H304 May be fatal if swallowed and enters airways
- H314 Causes severe skin burns and eye damage
- H336 May cause drowsiness or dizziness
- H361d Suspected of damaging the unborn child
- H373 May cause damage to organs through prolonged or repeated exposure
- H412 Harmful to aquatic life with long lasting effects

Precautionary Statements

Prevention

- P201 Obtain special instructions before use
- P202 Do not handle until all safety precautions have been read and understood
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P231 + P232 Handle and store contents under inert gas. Protect from moisture
- P240 Ground and bond container and receiving equipment
- P242 Use non-sparking tools
- P243 Take action to prevent static discharges
- P264 Wash face, hands and any exposed skin thoroughly after handling
- P271 Use only outdoors or in a well-ventilated area
- P280 Wear protective gloves/protective clothing/eye protection/face protection
- P273 Avoid release to the environment

Response

- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P310 Immediately call a POISON CENTER or doctor
- P330 Rinse mouth
- P331 Do NOT induce vomiting
- P302 + P335 + P334 IF ON SKIN: Brush off loose particles from skin. Immerse in cool water
- P363 Wash contaminated clothing before reuse
- P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Storage

P402 + P404 - Store in a dry place. Store in a closed container

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other Hazards

EUH014 - Reacts violently with water

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Toluene	108-88-3	80
Aluminum, diethyliodo-	2040-00-8	19.5-20.5

SECTION 4: FIRST AID MEASURES

Revision Date 22-Mar-2025

Description of first aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

Wash off immediately with plenty of water for at least 15 minutes. Remove and wash Skin Contact

contaminated clothing and gloves, including the inside, before re-use. Call a physician

immediately.

Ingestion Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an

unconscious person. Call a physician immediately. Call a physician or poison control center

immediately. If vomiting occurs naturally, have victim lean forward.

Inhalation If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use

> mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately. Risk of serious damage to the lungs (by

aspiration).

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible

perforation of stomach or esophagus should be investigated.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Dry chemical. Water mist may be used to cool closed containers. CO₂, dry chemical, dry sand, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

Water.

Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Hydrogen, Burning produces obnoxious and toxic fumes, Ethane.

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges. DO NOT GET WATER on spilled substance or inside containers.

Environmental precautions

Should not be released into the environment. Do not flush into surface water or sanitary sewer system.

Methods and Material for Containment and Cleaning Up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Do not get in eyes, on skin, or on clothing. Wear personal protective equipment/face protection. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. Handle under an inert atmosphere. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Conditions for Safe Storage, Including any Incompatibilities

Keep from any possible contact with water. Flammables area. Keep under nitrogen. Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area. Keep away from heat, sparks and flame. Keep away from water or moist air. Store under an inert atmosphere. Protect from moisture.

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	Malaysia	ACGIH TLV	OSHA PEL
Toluene		TWA: 20 ppm	(Vacated) TWA: 100 ppm (Vacated) TWA: 375 mg/m³ Ceiling: 300 ppm (Vacated) STEL: 150 ppm (Vacated) STEL: 560 mg/m³ TWA: 200 ppm
Aluminum, diethyliodo-		TWA: 0.01 mg/m³ Skin	

Component	European Union	The United Kingdom	Germany
Toluene	TWA: 50 ppm (8hr)	STEL: 100 ppm 15 min	TWA: 50 ppm (8 Stunden). AGW -
	TWA: 192 mg/m³ (8hr)	STEL: 384 mg/m ³ 15 min	exposure factor 2
	STEL: 100 ppm (15min)	TWA: 50 ppm 8 hr	TWA: 190 mg/m ³ (8 Stunden). AGW
	STEL: 384 mg/m ³ (15min)	TWA: 191 mg/m ³ 8 hr	- exposure factor 2

Diethylaluminium iodide, 0.9M solution in toluene

Skin	Skin	TWA: 50 ppm (8 Stunden). MAK
		TWA: 190 mg/m³ (8 Stunden). MAK
		Höhepunkt: 100 ppm
		Höhepunkt: 380 mg/m ³
		Haut

Exposure Controls

Engineering Measures

Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles

Hand Protection Protective gloves

Skin and body protectionWear appropriate protective gloves and clothing to prevent skin exposure

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and

vapours filter Type A Brown conforming to EN14387

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

When RPE is used a face piece Fit Test should be conducted

<u>Hygiene Measures</u> Handle in accordance with good industrial hygiene and safety practice

system

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance Clear Physical State Liquid

Odor No information available
Odor Threshold No data available
pH No information available

Melting Point/RangeNo data availableSoftening PointNo data availableBoiling Point/RangeNo information available

Flash Point No information available Method - No information available

Revision Date 22-Mar-2025

Diethylaluminium iodide, 0.9M solution in toluene

Liquid

(Air = 1.0)

Liquid

Evaporation Rate No data available Flammability (solid,gas) Not applicable

Explosion Limits No data available

Vapor PressureNo data availableVapor DensityNo data available

Specific Gravity / Density

No data available

No data available

Bulk Density Not applicable

Water Solubility Reacts violently with water Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Componentlog PowToluene2.73

Autoignition Temperature Decomposition Temperature

Viscosity

Explosive Properties Oxidizing Properties

No data available No data available No data available

No information available

Molecular Formula C4 H10 Al I Molecular Weight 212.01 Vapors may form explosive mixtures with air

Revision Date 22-Mar-2025

SECTION 10: STABILITY AND REACTIVITY

Reactivity

Yes.

Chemical Stability

Moisture sensitive. Air sensitive.

Possibility of Hazardous Reactions

Hazardous Polymerization
Hazardous Reactions

No information available.

None under normal processing. Reacts violently with water.

Conditions to Avoid

Keep away from open flames, hot surfaces and sources of ignition. Exposure to air. Incompatible products. Exposure to moist air or water. Exposure to moisture.

Incompatible Materials

Acids. Water. Alcohols.

Hazardous Decomposition Products

Carbon monoxide (CO). Carbon dioxide (CO2). Hydrogen. Burning produces obnoxious and

toxic fumes. Ethane.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Product Information No acute toxicity information is available for this product

(a) acute toxicity;

OralBased on available data, the classification criteria are not metDermalBased on available data, the classification criteria are not metInhalationBased on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Toluene	> 5000 mg/kg (Rat)	12000 mg/kg (Rabbit)	26700 ppm (Rat) 1 h

(b) skin corrosion/irritation; Category 1 A

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory No data available Skin No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Category 2

Teratogenicity Teratogenic effects have occurred in experimental animals.

(h) STOT-single exposure; Category 3

Results / Target organs Central nervous system (CNS).

(i) STOT-repeated exposure; Category 2

Target Organs Neuropsychological effects, Eyes, Ears.

(j) aspiration hazard; Category 1

Other Adverse Effects The toxicological properties have not been fully investigated.

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

delayed

tiredness, nausea and vomiting. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should

be investigated.

Revision Date 22-Mar-2025

Diethylaluminium iodide, 0.9M solution in toluene

Revision Date 22-Mar-2025

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity effectsThe product contains following substances which are hazardous for the environment.

Contains a substance which is:. Harmful to aquatic organisms. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Reacts with

water so no ecotoxicity data for the substance is available.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Toluene	50-70 mg/L LC50 96 h	EC50: = 11.5 mg/L, 48h	EC50: = 12.5 mg/L, 72h	EC50 = 19.7 mg/L 30
	5-7 mg/L LC50 96 h	(Daphnia magna)	static	min
	15-19 mg/L LC50 96 h	EC50: 5.46 - 9.83 mg/L,	(Pseudokirchneriella	
	28 mg/L LC50 96 h	48h Static (Daphnia	subcapitata)	
	12 mg/L LC50 96 h	magna)	EC50: > 433 mg/L, 96h	
			(Pseudokirchneriella	
			subcapitata)	

Persistence and degradability

Persistence Soluble in water, Persistence is unlikely, based on information available.

Degradability Reacts with water.

Component	Degradability	
Toluene	86% (20d)	
108-88-3 (80)	· '	

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants. Reacts violently with water.

Bioaccumulative potential Product does not bioaccumulate due to reaction with water

Component	log Pow	Bioconcentration factor (BCF)			
Toluene	2.73	90			

Mobility in soil Reacts violently with water. Is not likely mobile in the environment. Highly mobile in soils.

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

Other adverse effects No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous Dispose of in accordance with the European Directives on waste and hazardous waste Dispose of in accordance with local regulations

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empt

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous Keep product and

retail product residue, (liquid allurol vapor), allu call be daligerous Reep product allu

empty container away from heat and sources of ignition

application for which the product was used Can be landfilled or incinerated, when in

compliance with local regulations Do not empty into drains Large amounts will affect pH and

harm aquatic organisms Do not let this chemical enter the environment

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

UN-No UN3399
Hazard Class 4.3
Subsidiary Hazard Class 3
Packing Group |

Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE

(DIETHYLALUMINUM IODIDE, TOLUENE)

Road and Rail Transport

UN-No UN3399
Hazard Class 4.3
Subsidiary Hazard Class 3
Packing Group |

Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE

(DIETHYLALUMINUM IODIDE, TOLUENE)

<u>IATA</u>

UN-No UN3399
Hazard Class 4.3
Subsidiary Hazard Class 3
Packing Group |

Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE

(DIETHYLALUMINUM IODIDE, TOLUENE)

Special Precautions for User No special precautions required

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories X = listed

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Toluene	203-625-9	X	X	Х	X	X	Х	Χ	KE-33936
Aluminum, diethyliodo-	218-032-0	Х	-	Х	-	X	-	Χ	-

Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Toluene				Annex I - Y42

National Regulations

Persistent Organic Pollutant
Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

SECTION 16: OTHER INFORMATION

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

Substances List

PICCS - Philippines Inventory of Chemicals and Chemical Substances IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

ENCS - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50%

POW - Partition coefficient Octanol:Water

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Revision Date 22-Mar-2025

Revision Summary SDS sections updated.

In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet