

SAFETY DATA SHEET

Australian statement of hazardous nature: Classified as hazardous according to criteria of Safe Work Australia

Section 1 - Identification

Product Name Para-Release Spray

Product Code ALP9990420

Address ThermoFisher Scientific Australia Pty Ltd

5 Caribbean Drive, Scoresby VICTORIA 3179, Australia

Emergency Tel. CHEMTREC®

03 9757 4559 or +613 9757 4559

Telephone / Fax NumbersTel: 1300 735 292
Fax: 1800 067 639

ANZinfo@thermofisher.com

Recommended Use Laboratory chemicals.

Uses advised against

This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list.

This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction. This product does not contain any substance(s) listed on the voluntary National

Code of Practice for Chemicals of Security Concern.

Section 2 - Hazard(s) Identification

Classification under Safe Work Australia

Classified as hazardous according to criteria of Safe Work Australia

Physical hazards

E-mail address

Flammable liquids Category 2 Category 3

Health hazards

Serious Eye Damage/Eye Irritation Category 2

Specific target organ toxicity - (single exposure)

Category 3 Category 1

Environmental hazards

No hazards identified

Label Elements



Flame





AUS-000414 Version 2 14-Jul-2023 Page 1/12

Signal Word Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H226 - Flammable liquid and vapor

H370 - Causes damage to organs

Precautionary Statements

P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P233 - Keep container tightly closed

P240 - Ground and bond container and receiving equipment

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P264 - Wash face, hands and any exposed skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear eye protection/ face protection

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P312 - Call a POISON CENTER or doctor if you feel unwell

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P308 + P311 - IF exposed or concerned: Call a POISON CENTER or doctor

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P501 - Dispose of contents/ container to an approved waste disposal plant

Other information

Contains a known or suspected endocrine disruptor

Included in the list established in accordance with Article 59(1) for having endocrine disrupting properties

Section 3 - Composition and Information on Ingredients

Component	CAS No	Weight %
Isopropyl alcohol	67-63-0	90-95
Polyethylene glycol octylphenyl ether	9036-19-5	2-3
Ethyl alcohol	64-17-5	2-3
Polyethylene glycol	25322-68-3	<1
Methyl alcohol	67-56-1	<1

Section 4 - First Aid Measures

Inhalation Remove to fresh air.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Skin Contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes.

Eye ContactRinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

AUS-000414 Version 2 14-Jul-2023 Page 2/12

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

First Aid Facilities Eyewash, safety shower and washroom.

Most important symptoms and

Self-Protection of the First Aider

effects

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting

Notes to Physician Treat symptomatically. Symptoms may be delayed.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media

Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Special protective equipment and precautions for fire fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6 - Accidental Release Measures

Emergency procedures

Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

See Section 12 for additional Ecological Information. Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Up

Clean-up methods - small spillage

Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Clean-up methods - large spillage

Typically only supplied is small quantiites as packaged goods.

If extremely toxic or used in larger quantities ensure a spillage action plan is in place. Evacuate area. Control the source and/or contain the spill if safe and able to do so. Use temporary diking, sand bags, dry sand, earth or proprietary booms/absorbent pads if available. Obtain advice on containment, neutralisation and clean-up from local emergency responders.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

Section 7 - Handling and Storage

Precautions for Safe Handling

Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Conditions for Safe Storage, Including any Incompatibilities

AUS-000414 Version 2 14-Jul-2023 Page 3 / 12

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, sparks and flame.

AS/NZS 2243.10:2004, Safety in laboratories - Storage of chemicals AS 1940-2004 - The storage and handling of flammable and combustible liquids

Section 8 - Exposure Controls and Personal Protection

Exposure limits

AUS - Exposure Standards for Atmospheric Contaminants in the Occupational Environment - Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:3008(1995)] Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)] updated in August, 2005. Safe Work Australia

ACGIH - Threshold Limit Values - Ceiling (TLV-C) guidelines by the American Conference of Governmental Industrial Hygienists (ACGIH) for controlling worker exposure to airborne chemical concentrations in the workplace.

UK - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020.

DE - MAK and BAT values of Hazardous Chemical Compounds in the Work Area. Published by German Research Foundation on July 1, 2011

NZ - Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor

Component	Australia	New Zealand WEL	ACGIH TLV	The United Kingdom	Germany
Isopropyl alcohol	STEL: 500 ppm STEL: 1230 mg/m³ TWA: 400 ppm TWA: 983 mg/m³	TWA: 400 ppm TWA: 983 mg/m³ STEL: 500 ppm STEL: 1230 mg/m³	TWA: 200 ppm STEL: 400 ppm	STEL: 500 ppm 15 min STEL: 1250 mg/m³ 15 min TWA: 400 ppm 8 hr TWA: 999 mg/m³ 8 hr	TWA: 200 ppm (8 Stunden). AGW - exposure factor 2 TWA: 500 mg/m³ (8 Stunden). AGW - exposure factor 2 TWA: 200 ppm (8 Stunden). MAK TWA: 500 mg/m³ (8 Stunden). MAK Höhepunkt: 400 ppm Höhepunkt: 1000 mg/m³
Ethyl alcohol	TWA: 1000 ppm TWA: 1880 mg/m ³	TWA: 1000 ppm TWA: 1880 mg/m ³	STEL: 1000 ppm	TWA: 1000 ppm TWA; 1920 mg/m³ TWA WEL - STEL: 3000 ppm STEL; 5760 mg/m³ STEL	200 ppm TWA MAK; 380 mg/m³ TWA MAK
Polyethylene glycol					TWA: 200 mg/m³ (8 Stunden). AGW - exposure factor 2 TWA: 250 mg/m³ (8 Stunden). MAK average molecular weight 200-600;because formation of a mist is possible, exposure should be minimized for reasons of occupational safety and hygiene Höhepunkt: 500 mg/m³
Methyl alcohol	STEL: 250 ppm STEL: 328 mg/m ³ TWA: 200 ppm TWA: 262 mg/m ³	TWA: 200 ppm TWA: 262 mg/m³ STEL: 250 ppm STEL: 328 mg/m³ Skin	TWA: 200 ppm STEL: 250 ppm Skin	WEL - TWA: 200 ppm TWA; 266 mg/m³ TWA WEL - STEL: 250 ppm STEL; 333 mg/m³ STEL	100 ppm TWA MAK; 130 mg/m³ TWA MAKSkin absorber

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Component	Australia	New Zealand	European Union	United Kingdom	Germany
Isopropyl alcohol					Acetone: 25 mg/L whole
					blood (end of shift)
					Acetone: 25 mg/L urine
					(end of shift)
Methyl alcohol		15 mg/L (urine) end of			Methanol: 15 mg/L urine
		shift (Methyl alcohol)			(end of shift)

AUS-000414 Version 2 14-Jul-2023 Page 4/12

SAFETY DATA SHEET

	Methanol: 15 mg/L urine
	(for long-term
	exposures: at the end of
	the shift after several
	shifts)

Exposure Controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (Australian/New Zealand Standard AS/NZS 1337 - Eye protectors for Industrial

applications)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	AUS/NZ Standard	Glove comments
Viton (R)	See manufacturers	-	AS/NZS 2161	(minimum requirement)
	recommendations			

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection Long sleeved clothing

Repiratory Protection Use an AS/NZS 1716 approved respirator if exposure limits are exceeded or if irritation or

other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained in line with AS/NZS 1715 on the use

and maintenance of repiratory protective devices

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387 (or AUS/NZ

equivalent)

Recommended half mask:- Valve filtering: EN405 or Half mask: EN140 plus filter, EN 141 (or AUS/NZ equivalent)

When RPE is used a face piece Fit Test should be conducted

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water

system.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance Clear, colorless solution

Physical State Liquid

Odor No information available

Odor Threshold No data available pH Not applicable

Melting Point/Range
-89 °C / -128.2 °F
Softening Point
No data available
Boiling Point/Range
82.6 °C / 180.7 °F

Flash Point 11.7 °C / 53.1 °F Method - No information available

AUS-000414 Version 2 14-Jul-2023 Page 5 / 12

SAFETY DATA SHEET

Evaporation Rate No data available

Flammability (solid,gas) Not applicable Liquid

Explosion Limits No data available

Vapor Pressure No data available

Vapor Density No data available (Air = 1.0)

Specific Gravity / Density

Bulk Density

No data available

Not applicable

Liquid

Water Solubility Miscible

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Componentlog PowIsopropyl alcohol0.05Ethyl alcohol-0.32Methyl alcohol-0.74

Autoignition Temperature

Decomposition Temperature

Viscosity

No data available
No data available
No data available

Explosive Properties explosive air/vapour mixtures possible Vapors may

form explosive mixtures with air

Oxidizing Properties No information available

Other information

Section 10 - Stability and Reactivity

Reactivity None known, based on information available

Stability Stable under normal conditions.

Conditions to Avoid Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials None known.

Hazardous Decomposition Products None under normal use conditions.

Hazardous Polymerization No information available.

Section 11 - Toxicological Information

Information on Toxicological Effects

Product Information

(a) acute toxicity;

OralBased on available data, the classification criteria are not metDermalBased on available data, the classification criteria are not metInhalationBased on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Isopropyl alcohol	5045 mg/kg (Rat)	12800 mg/kg (Rat)	72.6 mg/L (Rat) 4 h
	3600 mg/kg (Mouse)		
Polyethylene glycol octylphenyl ether	LD50 = 1700 mg/kg (Rat)		
Ethyl alcohol	LD50 = 7060 mg/kg (Rat)		20000 ppm/10H (Rat)
Polyethylene glycol	LD50 = 22 g/kg (Rat)	LD50 > 20 g/kg (Rabbit)	

AUS-000414 Version 2 14-Jul-2023 Page 6/12

			ı
Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h

(b) skin corrosion/irritation; Based on available data, the classification criteria are not met

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

RespiratoryBased on available data, the classification criteria are not met
Skin
Based on available data, the classification criteria are not met

Component	Test method	Test species	Study result
Polyethylene glycol	in vivo: Test method Human	Man	non-sensitising
25322-68-3 (<1)	Repeat Insult Patch Test		
Methyl alcohol	OECD Test Guideline 406	guinea pig	non-sensitising
67-56-1 (<1)	Guinea Pig Maximisation Test		
	(GPMT)		

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

Component	Test method	Test species	Study result
Polyethylene glycol	OECD Test Guideline 471	in vivo	negative
25322-68-3 (<1)			

(f) carcinogenicity; Based on available data, the classification criteria are not met

The table below indicates whether each agency has listed any ingredient as a carcinogen

(g) reproductive toxicity; Based on available data, the classification criteria are not met

Component	Test method	Test species / Duration	Study result
Methyl alcohol	OECD Test Guideline 416	Rat / Inhalation 2 Generation	NOAEC = 1.3 mg/l (air)
67-56-1 (<1)			

(h) STOT-single exposure; Category 3

Results / Target organs Central nervous system (CNS)

Optic nerve

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Target Organs None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, delayed tiredness, nausea and vomiting

Section 12 - Ecological Information

Ecotoxicity effectsContains a substance which is:. Toxic to aquatic organisms. The product contains following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Isopropyl alcohol	LC50: = 9640 mg/L, 96h	13299 mg/L EC50 = 48	EC50: > 1000 mg/L, 72h	= 35390 mg/L EC50
	flow-through	h	(Desmodesmus	Photobacterium
	(Pimephales promelas)	9714 mg/L EC50 = 24 h	subspicatus)	phosphoreum 5 min
	LC50: > 1400000 μg/L,		EC50: > 1000 mg/L, 96h	
	96h (Lepomis		(Desmodesmus	
	macrochirus)		subspicatus)	
	LC50: = 11130 mg/L,			
	96h static (Pimephales			
	promelas)			
	$LC50$: = 10000000 μ g/L,			
	96h (Daphnia)			

AUS-000414 Version 2 14-Jul-2023 Page 7 / 12

	 <u> </u>			
Ethyl alcohol	Fathead minnow (Pimephales promelas) LC50 = 14200 mg/l/96h	EC50 = 9268 mg/L/48h EC50 = 10800 mg/L/24h	EC50 (72h) = 275 mg/l (Chlorella vulgaris)	phosphoreum:EC50 = 34634 mg/L/30 min Photobacterium phosphoreum:EC50 =
Polyethylene glycol	LC50 > 100 mg/L 96h, (Poecilia reticulata) OECD Guideline 203	EC50 > 100 mg/L 48h, (Daphnia magna) OECD Guideline 202	EC50 > 100 mg/L 96h, (Scenedesmus subspicatus) OECD Guideline 201	35470 mg/L/5 min
Methyl alcohol	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 > 10000 mg/L 24h		EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min

Persistence and Degradability

Persistence Persistence is unlikely, based on information available.

Component	Degradability
Methyl alcohol	DT50 ~ 17.2d
67-56-1 (<1)	>94% after 20d

Degradation in sewage treatment plant Bioaccumulative Potential

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)		
Isopropyl alcohol	0.05	No data available		
Ethyl alcohol	-0.32	No data available		
Methyl alcohol	-0.74	<10 dimensionless		

Mobility

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air

Endocrine Disruptor Information

Component	EU - Endocrine Disrupters	EU - Endocrine Disruptors -	Japan - Endocrine Disruptor	
	Candidate List	Evaluated Substances	Information	
Polyethylene glycol octylphenyl ether	Group III Chemical			

Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected substance This product does not contain any known or suspected substance

Section 13 - Disposal Considerations

Waste from Residues/Unused Products

Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure conformity with all applicable regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

Other Information

Chemical wastes should be disposed through a licensed commercial waste collection service. Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations.

Section 14 - Transport Information

IMDG/IMO

UN-No UN1219
Proper Shipping Name ISOPROPANOL

AUS-000414 Version 2 14-Jul-2023 Page 8/12

Technical Shipping Name Para-Release Spray

Hazard Class 3
Packing Group ||

<u>ADG</u>

UN-No UN1219
Proper Shipping Name ISOPROPANOL

Technical Shipping Name Para-Release Spray

Hazard Class 3
Packing Group ||

Component	Hazchem Code
Isopropyl alcohol	1Z
67-63-0 (90-95)	
Ethyl alcohol	2YE
64-17-5 (2-3)	2Y
Methyl alcohol	2WE
67-56-1 (<1)	

IATA

UN-No
Proper Shipping Name
Technical Shipping Name
UN1219
ISOPROPANOL
Para-Release Spray

Hazard Class 3
Packing Group II

Environmental hazards No hazards identified

Special Precautions No special precautions required

Additional information None known

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations Australia

See section 8 for national exposure control parameters.

Standard for the Uniform Scheduling of Medicines and Poisons

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons.

Component	Standard for the Uniform Scheduling of Medicines and Poisons				
Polyethylene glycol - 25322-68-3	Schedule 2 listed				
	Schedule 3 listed				
Methyl alcohol - 67-56-1	Schedule 5 listed - except its derivatives;in preparations except a) when included in Schedule 10, or b)				
	in preparations containing <=2% of Methanol, or c) when Methanol is present only as a denaturant of Ethanol				
	Schedule 6 listed - except its derivatives; except a) when included in Schedule 5, or b) when included in				
	Schedule 10, or c) in preparations containing <=2% of Methanol				
	Schedule 10 listed				

Australian Industrial Chemicals Introduction Scheme (AICIS)

Component	Australian Industrial	Additional information
•	Chemicals Introduction	
	Chemicals introduction	
	Scheme (AICIS)	

AUS-000414 Version 2 14-Jul-2023 Page 9/12

Isopropyl alcohol - 67-63-0	Present	-
Polyethylene glycol octylphenyl ether -	Present	-
9036-19-5		
Ethyl alcohol - 64-17-5	Present	-
Polyethylene glycol - 25322-68-3	Present	-
Methyl alcohol - 67-56-1	Present	-

Australian - Illicit Drug Precursors/Reagents Substance List

This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list.

Chemicals of Security Concern

This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern

National pollutant inventory Subject to reporting requirements

Component	National pollutant inventory
Ethyl alcohol - 64-17-5	10 tonne/yr. Threshold category 1
Methyl alcohol - 67-56-1	10 tonne/yr. Threshold category 1

Prohibition or notification/licensing requirements

Shown below are details of specific prohibition/notifications or licencing requirements when they apply.

This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction.

International Inventories

Component	AICS	NZIoC	EINECS	ELINCS	TSCA	DSL	NDSL	PICCS	ENCS	ISHL	IECSC	KECL
Isopropyl alcohol	X	X	200-661-7	-	X	X	-	Х	Х	Х	Х	KE-29363
Polyethylene glycol octylphenyl ether	Х	Х	=	1	Х	Х	-	Х	Х	Х	Х	KE-33567
Ethyl alcohol	Х	X	200-578-6	-	X	X	-	Х	Х	Х	Х	KE-13217
Polyethylene glycol	X	Х	-	-	X	Х	-	Х	Х	Х	Х	KE-20228
Methyl alcohol	X	Χ	200-659-6	-	X	Х	-	Х	Х	Х	Х	KE-23193

Legend: X - Listed. '-' - Not Listed. XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B). **KECL** - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

International Regulations

Ozone Depletion Potential This product does not contain any known or suspected substance

Persistent Organic Pollutant This product does not contain any known or suspected substance

Rotterdam Convention (PIC) Not applicable

Basel convention on the control of transboundary movements of hazardous wastes and their dispoal

Take note that wastes may be subject to export, import, or transit controls pursuant to the Basel convention and/or local regulations implementing the Basel convention.

Component	Basel Convention (Hazardous Waste)	Australian Hazardous Waste Act - Categories of Wastes to Be Controlled
Isopropyl alcohol - 67-63-0	Annex I - Y42	Y42 except Halogenated solvents

AUS-000414 Version 2 14-Jul-2023 Page 10 / 12

Ethyl alcohol - 64-17-5	Annex I - Y42	Y42 except Halogenated solvents

Component	CAS No	OECD HPV	Restriction of Hazardous Substances (RoHS)	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Isopropyl alcohol	67-63-0	Listed	Not applicable	Not applicable	Not applicable
Polyethylene glycol octylphenyl ether	9036-19-5	Not applicable	Not applicable	Not applicable	Not applicable
Ethyl alcohol	64-17-5	Listed	Not applicable	Not applicable	Not applicable
Polyethylene glycol	25322-68-3	Listed	Not applicable	Not applicable	Not applicable
Methyl alcohol	67-56-1	Listed	Not applicable	500 tonne	5000 tonne

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Isopropyl alcohol	-	Use restricted. See item 75. (see link for restriction details)	-
Polyethylene glycol octylphenyl ether	-	-	SVHC Candidate list - Endocrine disrupting properties, Article 57f - environment
Methyl alcohol	-	Use restricted. See item 69. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-

After the sunset date the use of this substance requires either an authorization or can only be used for exempted uses, e.g. use in scientific research and development which includes routine analytics or use as intermediate.

https://echa.europa.eu/authorisation-list

https://echa.europa.eu/candidate-list-table

https://echa.europa.eu/substances-restricted-under-reach

Section 16 - Other Information

Legend

AICS - Australian Inventory of Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

IECSC - Chinese Inventory of Existing Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Shins

NZS 5433:2020 - Transport of Dangerous Goods on Land

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50% **WEL** - Workplace Exposure Limit

DNEL - Derived No Effect Level

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

VOC - (Volatile Organic Compound)

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

NZIoC - New Zealand Inventory of Chemicals

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japanese Existing and New Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

CAS - Chemical Abstracts Service

ACGIH - American Conference of Governmental Industrial Hygienists

Predicted No Effect Concentration (PNEC)

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

ADG - Australian Code for the Transport of Dangerous Goods by Road and Rail

OECD - Organisation for Economic Co-operation and Development

LC50 - Lethal Concentration 50%

ATE - Acute Toxicity Estimate

RPE - Respiratory Protective Equipment **NOEC** - No Observed Effect Concentration

BCF - Bioconcentration factor

PBT - Persistent, Bioaccumulative, Toxic

AUS-000414 Version 2 14-Jul-2023 Page 11 / 12

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards

Health Hazards

Environmental hazards

On basis of test data
Calculation method
Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Revision Date 14-Jul-2023

Revision Summary Update to GHS format.

This Safety Data Sheet (SDS) is prepared in accordance to and complies with the requirements of Safe Work Australia - Work Health and Safety Regulations (WHS Regulations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

AUS-000414 Version 2 14-Jul-2023 Page 12 / 12