

Page 1/9 Creation Date 23-Apr-2014 Revision Date 04-Apr-2024 Version 3

FSUTS0214

Di-iso-propyl ether

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

产品说明: Di-iso-propyl ether Product Description: Di-iso-propyl ether

Cat No. : TS/0214/99SS

Synonyms 2-Isopropoxypropane; DIPE; Diisopropyl ether

CAS No 108-20-3 Molecular Formula C6 H14 O

Supplier UK entity/business name

Fisher Scientific UK

Bishop Meadow Road, Loughborough, Leicestershire LE11 5RG, United Kingdom

EU entity/business name Thermo Fisher Scientific Janssen Pharmaceuticalaan 3a

2440 Geel, Belgium

Emergency Telephone Number Tel: 01509 231166

Chemtrec US: (800) 424-9300 Chemtrec EU: 001-703-527-3887

E-mail address begel.sdsdesk@thermofisher.com

Recommended Use Laboratory chemicals. Uses advised against No Information available

SECTION 2. HAZARD IDENTIFICATION

Physical StateAppearanceOdorLiquidColorlessStrong Ether

Emergency Overview

Highly flammable liquid and vapor. May cause drowsiness and dizziness. Harmful to aquatic life with long lasting effects. May be harmful if swallowed. May form explosive peroxides. Repeated exposure may cause skin dryness or cracking. Sensitivity to light.

Air sensitive.

Classification of the substance or mixture

Flammable liquids.	Category 2
Acute Oral Toxicity	Category 5
Specific target organ toxicity - (single exposure)	Category 3
Chronic aquatic toxicity	Category 3

Label Elements

Di-iso-propyl ether



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H303 - May be harmful if swallowed

H336 - May cause drowsiness or dizziness

H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P240 - Ground and bond container and receiving equipment

P241 - Use explosion-proof electrical/ ventilating/ lighting equipment

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P270 - Do not eat, drink or smoke when using this product

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

Response

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P312 - Call a POISON CENTER or doctor if you feel unwell

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Physical and Chemical Hazards

Vapors may cause flash fire or explosion. Highly flammable. May form explosive peroxides.

Health Hazards

May cause drowsiness or dizziness. May be harmful if swallowed.

Environmental hazards

Harmful to aquatic life with long lasting effects. Will likely be mobile in the environment due to its volatility. The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

This product does not contain any known or suspected endocrine disruptors. Toxic to terrestrial vertebrates.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Isopropyl ether	108-20-3	<=100

SECTION 4. FIRST AID MEASURES

General Advice

If symptoms persist, call a physician.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Page 3/9 Revision Date 04-Apr-2024

Di-iso-propyl ether

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.

Ingestion

Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Self-Protection of the First Aider

No special precautions required.

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. May form explosive peroxides. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

Methods for Containment and Clean Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Refer to protective measures listed in Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. If peroxide formation is suspected, do not open or move container. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal

Page 4/9 Revision Date 04-Apr-2024

Di-iso-propyl ether

parts of the equipment must be grounded. Take precautionary measures against static discharges.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from direct sunlight. Keep away from heat, sparks and flame. Keep under nitrogen. Flammables area. May form explosive peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Containers should be dated when opened and tested periodically for the presence of peroxides.

Specific Use(s)

Use in laboratories

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	China	Taiwan	Thailand	Hong Kong
Isopropyl ether	=	TWA: 250 ppm		TWA: 250 ppm
		TWA: 1040 mg/m ³		TWA: 1040 mg/m ³
		_		STEL: 310 ppm
				STEL: 1300 mg/m ³

Component	ACGIH TLV	OSHA PEL	NIOSH	The United Kingdom	European Union
Isopropyl ether	TWA: 250 ppm	(Vacated) TWA: 500	IDLH: 1400 ppm	STEL: 310 ppm 15 min	
	STEL: 310 ppm	ppm	TWA: 500 ppm	STEL: 1310 mg/m ³ 15	
		(Vacated) TWA: 2100	TWA: 2100 mg/m ³	min	
		mg/m³		TWA: 250 ppm 8 hr	
		TWA: 500 ppm		TWA: 1060 mg/m ³ 8 hr	
		TWA: 2100 mg/m ³		_	

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. MDHS70 General methods for sampling airborne gases and vapours MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Exposure Controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source.

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Γ	Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
	Viton (R)	> 480 minutes	0.4 mm	EN 374 Level 6	As tested under EN374-3 Determination of
	Nitrile rubber	> 480 minutes	0.35 mm		Resistance to Permeation by Chemicals
	PVC	> 120 minutes	0.5 mm		

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Page 5/9 Revision Date 04-Apr-2024

Di-iso-propyl ether

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: low boiling organic solvent Type A conforming to EN 141

@ 760 mmHg

Liquid

Method - No information available

Vapors may form explosive mixtures with air

Small scale/Laboratory use Maintain adequate ventilation No personal respiratory protective equipment normally

required

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls Prevent product from entering drains.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Colorless
Physical State Liquid

Odor Strong Ether
Odor Threshold No data available
PH No information available
Melting Point/Range -85.5 °C / -121.9 °F
Softening Point No data available
Boiling Point/Range 68 °C / 154.4 °F
Flash Point -29 °C / -20.2 °F

Evaporation Rate No data available

Flammability (solid,gas) Not applicable Explosion Limits Lower 1.1

Upper 21

Vapor Pressure 180 mbar @ 20 °C

Vapor Density 1.42 @ 20 °C

Specific Gravity / Density 0.720

Bulk Density Not applicable Liquid

Water Solubility 9 g/L (20°C)

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Component log Pow lsopropyl ether 2.4

Autoignition Temperature 405 °C / 761 °F

Percomposition Temperature No data available

Decomposition Temperature
Viscosity

No data available
0.38 mPa s at 25 °C

Explosive Properties Not explosive

Oxidizing Properties No information available

Molecular Formula C6 H14 O Molecular Weight 102.18

Refractive index 1.367 - 1.369 @ 20 °C

Page 6/9 Revision Date 04-Apr-2024

Di-iso-propyl ether

SECTION 10. STABILITY AND REACTIVITY

Stability May form explosive peroxides. Air sensitive. Light sensitive. heat sensitive.

Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to Avoid Incompatible products. Keep away from open flames, hot surfaces and sources of ignition.

Excess heat. Exposure to air. Exposure to light.

Materials to avoid Acids. Strong oxidizing agents. Amines. Aldehydes.

Hazardous Decomposition Products Carbon monoxide (CO). Carbon dioxide (CO₂), peroxides.

SECTION 11. TOXICOLOGICAL INFORMATION

Product Information

(a) acute toxicity:

(a) acute temony;			
Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Isopropyl ether	LD50 = 4700 mg/kg (Rat)	LD50 > 2000 mg/kg (Rabbit)	

Based on available data, the classification criteria are not met (b) skin corrosion/irritation;

Based on available data, the classification criteria are not met (c) serious eye damage/irritation;

(d) respiratory or skin sensitization;

Respiratory

Skin

Based on available data, the classification criteria are not met Based on available data, the classification criteria are not met

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

Based on available data, the classification criteria are not met (g) reproductive toxicity;

(h) STOT-single exposure: Category 3

Central nervous system (CNS) Results / Target organs

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Target Organs None known.

Based on available data, the classification criteria are not met (j) aspiration hazard;

delayed

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting

SECTION 12. ECOLOGICAL INFORMATION

Page 7/9 Revision Date 04-Apr-2024

Di-iso-propyl ether

Ecotoxicity effects

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Isopropyl ether	LC50: = 91.7 mg/L, 96h flow-through (Pimephales promelas) LC50: = 7000 mg/L, 96h static (Lepomis macrochirus)			EC50 = 500 mg/L 5 min

Persistence and Degradability

Persistence Persistence is unlikely, based on information available.

Component	Degradability	
Isopropyl ether	11 % (5 days)	
108-20-3 (<=100)		

Bioaccumulative Potential

Bioaccumulation is unlikely

	Component	log Pow	Bioconcentration factor (BCF)
I	Isopropyl ether	2.4	4.67 - 6

Mobility in soil The product contains volatile organic compounds (VOC) which will evaporate easily from all

surfaces Will likely be mobile in the environment due to its volatility Disperses rapidly in air

Endocrine Disruptor Information Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected endocrine disruptors

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13. DISPOSAL CONSIDERATIONS

Waste from Residues/Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Todasis of Maste and Nazar season Master. Proposed of Mr. accordance Marinesar regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the

application for which the product was used. Can be landfilled or incinerated, when in

compliance with local regulations.

SECTION 14. TRANSPORT INFORMATION

Road and Rail Transport

UN-No UN1159

Proper Shipping Name DIISOPROPYL ETHER

Hazard Class 3
Packing Group ||

IMDG/IMO

UN-No UN1159

Proper Shipping Name DIISOPROPYL ETHER

Hazard Class 3
Packing Group ||

Page 8/9 Revision Date 04-Apr-2024

Di-iso-propyl ether

IATA

UN1159 **UN-No**

DIISOPROPYL ETHER **Proper Shipping Name**

Hazard Class 3 Ш **Packing Group**

Special Precautions for User No special precautions required

SECTION 15. REGULATORY INFORMATION

International Inventories

X = listed, China (IECSC), Europe (EINECS/ELINCS/NLP), U.S.A. (TSCA), Canada (DSL/NDSL), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), Korea (KECL).

Component	The Inventory of Hazardous Chemicals (2015 Edition)	goods GB	TCSI	IECSC	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	AICS	KECL
Isopropyl ether	X	X	X	X	203-560-6	Х	Х	X	Х	Х	Χ	KE-27717

Component	Seveso III Directive (2012/18/EC) - Qualifying	Seveso III Directive (2012/18/EC) - Qualifying Quantities
	Quantities for Major Accident Notification	for Safety Report Requirements
Isopropyl ether	50, 000 tonnes	5, 000 tonnes

National Regulations

SECTION 16. OTHER INFORMATION

23-Apr-2014 **Creation Date Revision Date** 04-Apr-2024

Revision Summary SDS sections updated.

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical incident response training.

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b)

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances

Substances List **ENCS** - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances

WEL - Workplace Exposure Limit

TWA - Time Weighted Average **ACGIH** - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

IARC - International Agency for Research on Cancer

PNEC - Predicted No Effect Concentration

NZIoC - New Zealand Inventory of Chemicals

FSUTS0214

SAFETY DATA SHEET

Page 9/9 Revision Date 04-Apr-2024

Di-iso-propyl ether

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50% NOEC - No Observed Effect Concentration PBT - Persistent, Bioaccumulative, Toxic

LD50 - Lethal Dose 50% EC50 - Effective Concentration 50% POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative

ICAO/IATA - International Civil Aviation Organization/International Air **Transport Association**

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

MARPOL - International Convention for the Prevention of Pollution from

ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet