

SAFETY DATA SHEET

Classified as hazardous in accordance with the criteria of EPA New Zealand

Section 1 - Identification

Product Identifier

Product Name Acetone

CAS No 67-64-1

Synonyms 2-Propanone

Molecular FormulaC3 H6 OMolecular Weight58.08

Recommended Use Laboratory chemicals.
Uses advised against No Information available

Product Code A/0606/15, A/0606/15X, A/0606/17, A/0606/17X, A/0606/27Z, A/0606/34SS,

A/0606/10RSS, A/0606/21RSS, A/0606/25RSS, A/0606/30RSS, A/0606/27RSS

Address Thermo Fisher Scientific New Zealand Ltd

244 Bush Road, Albany, Auckland, New Zealand

Emergency Tel. CHEMTREC®

09 980 6780 or +64 9 980 6780

Telephone / Fax Numbers Tel: 09 980 6700

Fax: 09 980 6788

E-mail address ANZinfo@thermofisher.com

Section 2 - Hazard(s) Identification

Classification under Work Safe New Zealand

Classified as hazardous in accordance with the criteria of EPA New Zealand

HSNO Approval Number HSR001070

GHS Classification

Physical hazards

Flammable liquids Category 2

Health hazards

Serious Eye Damage/Eye Irritation Category 2
Specific target organ toxicity - (single exposure) Category 3

Environmental hazards
Based on available data, the classification criteria are not met

Label Elements

FSUA0606 Version 2 13-Mar-2023 Page 1/11



Signal Word Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

Precautionary Statements

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P233 - Keep container tightly closed

P240 - Ground and bond container and receiving equipment

P241 - Use explosion-proof electrical/ ventilating/ lighting equipment

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P264 - Wash face, hands and any exposed skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

Response

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P312 - Call a POISON CENTER or doctor if you feel unwell

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other hazards which do not result in classification

Repeated exposure may cause skin dryness or cracking

Section 3 - Composition and Information on Ingredients

Component	CAS No	Weight %
Acetone	67-64-1	>95

Section 4 - First Aid Measures

Description of first aid measures

General Advice If symptoms persist, call a physician.

New Zealand Emergency Tel. CHEMTREC®

09 980 6780 or +64 9 980 6780

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

FSUA0606 Version 2 13-Mar-2023 Page 2/11

Eye Contact

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Self-Protection of the First Aider Remove all sources of ignition. Use personal protective equipment as required.

First Aid Facilities Eyewash, safety shower and washroom.

Most important symptoms and

effects

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness,

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

nausea and vomiting: May cause pulmonary edema

Notes to Physician Treat symptomatically. Symptoms may be delayed.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use water jetstream.

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO2), Formaldehyde, Methanol.

Decomposition Temperature

> 4°C

Special protective equipment and precautions for fire fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6 - Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures

Emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Should not be released into the environment.

Methods for Containment and Clean Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Precautions to prevent secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

FSUA0606 Version 2 13-Mar-2023 Page 3 / 11

Section 7 - Handling and Storage

Precautions for Safe Handling

Advice on safe handling

Do not get in eyes, on skin, or on clothing. Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions

Flammables area. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame.

Incompatible Materials

Strong oxidizing agents. Strong reducing agents. Strong bases. Peroxides. Halogenated compounds. Alkali metals. Amines.

AS/NZS 2243.10:2004, Safety in laboratories - Storage of chemicals AS 1940-2004 - The storage and handling of flammable and combustible liquids

Section 8 - Exposure Controls and Personal Protection

Control parameters

Exposure limits

NZ - Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor AUS - Exposure Standards for Atmospheric Contaminants in the Occupational Environment - Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:3008(1995)] Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)] updated in August, 2005. Safe Work Australia

ACGIH - Threshold Limit Values - Ceiling (TLV-C) guidelines by the American Conference of Governmental Industrial Hygienists (ACGIH) for controlling worker exposure to airborne chemical concentrations in the workplace.

UK - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020.

Component	New Zealand WEL	Australia	ACGIH TLV	The United Kingdom
Acetone	TWA: 500 ppm	STEL: 1000 ppm	TWA: 250 ppm	TWA: 500 ppm
	TWA: 1185 mg/m ³	STEL: 2375 mg/m ³	STEL: 500 ppm	TWA: 1210 mg/m ³
	STEL: 1000 ppm	TWA: 500 ppm		STEL: 1500 ppm
	STEL: 2375 mg/m ³	TWA: 1185 mg/m ³		STEL: 3620 mg/m ³

Biological limit values

NZ - Substances assigned Biological Exposure Indices in the New Zealand Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor

ACGIH - American Conference of Governmental Industrial Hygienists (ACGIH) TLVs® and BEIs®- Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices. 2022 Edition

Component	New Zealand	Australia	ACGIH - Biological Exposure Indices	United Kingdom
Acetone	50 mg/L (urine) end of shift (Acetone)		25 mg/L Medium: urine Time: end of shift Determinant: Acetone	

Appropriate engineering controls

Engineering Measures

FSUA0606 Version 2 13-Mar-2023 Page 4 / 11

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Individual protection measures, such as personal protective equipment

Goggles (Australian/New Zealand Standard AS/NZS 1337 - Eye protectors for Industrial **Eye Protection**

applications)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	AUS/NZ Standard	Glove comments
Butyl rubber.	> 480 minutes	0.5 mm	AS/NZS 2161	As tested under EN374-3 Determination of
				Resistance to Permeation by Chemicals
Neoprene gloves	< 30 minutes	0.45 mm		·

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Long sleeved clothing Skin and body protection

Repiratory Protection Use an AS/NZS 1716 approved respirator if exposure limits are exceeded or if irritation or

other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained in line with AS/NZS 1715 on the use

On basis of test data

and maintenance of repiratory protective devices

low boiling organic solvent Type AX Brown conforming to EN371 (or AUS/NZ equivalent) **Recommended Filter type:**

Recommended half mask:-Valve filtering: EN405 or Half mask: EN140 plus filter, EN 141 (or AUS/NZ equivalent)

When RPE is used a face piece Fit Test should be conducted

Handle in accordance with good industrial hygiene and safety practice. **Hygiene Measures**

Environmental exposure controls Do not allow material to contaminate ground water system.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State Liquid

Appearance Colorless Odor sweet **Odor Threshold** 19.8 ppm

Hq

-95 °C / -139 °F **Melting Point/Range Softening Point** No data available **Boiling Point/Range** 56 °C / 132.8 °F Flammability (liquid) Highly flammable

Flammability (solid, gas) Not applicable Liquid

Explosion Limits Lower 2.1 vol%

Upper 13 vol%

Flash Point -20 °C / -4 °F Method - CC (closed cup) 465 °C / 869 °F

Autoignition Temperature Decomposition Temperature > 4°C

0.32 mPa.s @ 20 °C

Viscosity Water Solubility Soluble

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

FSUA0606 Version 2 13-Mar-2023 Page 5/11 Component log Pow Acetone -0.24

Vapor Pressure 247 mbar @ 20 °C

Density / Specific Gravity 0.790

Bulk DensityNot applicableLiquidVapor Density2.0(Air = 1.0)

Particle characteristics Not applicable (liquid)

Other information

Molecular Formula C3 H6 O Molecular Weight 58.08

Explosive PropertiesNot explosive Vapors may form explosive mixtures with air

Oxidizing Properties Not oxidising

Evaporation Rate 5.6 (Butyl Acetate = 1.0)

Refractive index 1.358 - 1.359

Section 10 - Stability and Reactivity

Reactivity None known, based on information available

Stability Stable under normal conditions.

Sensitivity to Mechanical Impact No information available

Sensitivity to Static Discharge No information available

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous ReactionsNone under normal processing.

Conditions to Avoid Heat, flames and sparks, Incompatible products, Keep away from open flames, hot

surfaces and sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong reducing agents, Strong bases, Peroxides, Halogenated

compounds, Alkali metals, Amines.

Hazardous Decomposition Products Carbon monoxide (CO). Carbon dioxide (CO2). Formaldehyde. Methanol.

Section 11 - Toxicological Information

Acute Effects

Information on likely routes of exposure

Product Information

Inhalation May be harmful if inhaled. INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM

EFFECTS. May cause drowsiness and dizziness. May cause irritation of respiratory tract.

Eyes Irritating to eyes.

Skin Irritating to skin. May be harmful in contact with skin. Repeated exposure may cause skin

dryness or cracking.

Ingestion May be harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

Numerical measures of toxicity

(a) acute toxicity;

OralBased on available data, the classification criteria are not metDermalBased on available data, the classification criteria are not metInhalationBased on available data, the classification criteria are not met

FSUA0606 Version 2 13-Mar-2023 Page 6 / 11

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Acetone	5800 mg/kg (Rat)	> 15800 mg/kg (rabbit)	76 mg/l, 4 h, (rat)
		> 7400 mg/kg (rat)	

(b) skin corrosion/irritation; Based on available data, the classification criteria are not met

(c) serious eye damage/irritation; Category 2
Test method OECD 405
Test species rabbit

Observation end point Irritating to eyes

(d) respiratory or skin sensitization;

RespiratorySkin
Based on available data, the classification criteria are not met
Based on available data, the classification criteria are not met

Component	Test method	Test species	Study result
Acetone	Guinea Pig Maximisation Test	guinea pig	non-sensitising
67-64-1 (>95)	(GPMT)		

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

Component	Test method	Test species	Study result
Acetone 67-64-1 (>95)	OECD Test Guideline 471 AMES test	in vivo	negative
	OECD Test Guideline 476 Mammalian Gene cell mutation	in vitro	negative

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Based on available data, the classification criteria are not met

(h) STOT-single exposure; Category 3

Results / Target organs Central nervous system (CNS)

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Test method OECD Test No. 408
Test species / Duration Rat / 90 days
Study result NOAEL = 900 mg/kg

Route of exposure Oral

Target Organs None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Symptoms / effects,both acute and delayed

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. May cause pulmonary edema.

Section 12 - Ecological Information

Ecotoxicity

Aquatic ecotoxicity .

FSUA0606 Version 2 13-Mar-2023 Page 7/11

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Acetone	Oncorhynchus mykiss:	EC50 = 8800 mg/L/48h	NOEC = 430 mg/l	EC50 = 14500 mg/L/15
	LC50 = 5540 mg/l 96h	EC50 = 12700 mg/L/48h	(algae; 96 h)	min
	Alburnus alburnus:	EC50 = 12600 mg/L/48h	, ,	
	LC50 = 11000 mg/l 96h			
	Leuciscus idus: LC50 =			
	11300 mg/L/48h			
	Salmo gairdneri: LC50 =			
	6100 mg/L/24h			

Terrestrial ecotoxicity

Component	Earthworm	Avian	Honeybees
Acetone	Acute toxicity: LC50 200 - 1000	Dietary toxicity: LC50 > 40000	
	μg/cm2 (Eisenia foetida, 48 h,	ppm (Coturnix coturnix japonica,	
	filter paper)	5 Days)	
		Dietary toxicity: LC50 > 40000	
		ppm (Phasianus colchicus, 5	
		Days)	

Persistence and Degradability

Readily biodegradable

Persistence

Persistence is unlikely, based on information available.

Component	Degradability
Acetone	91 % (28 d) (OECD 301 B)
67-64-1 (>95)	

Bioaccumulative Potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Acetone	-0.24	0.69 dimensionless

Mobility

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air

Other adverse effects

Endocrine Disruptor Information Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected endocrine disruptors

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

Section 13 - Disposal Considerations

Waste treatment methods

Waste from Residues/Unused Products

Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure

conformity with all applicable regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

Other Information Disposal agencies or waste contractors must comply with the New Zealand Hazardous

Substances (Disposal) Regulations. Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled

FSUA0606 Version 2 13-Mar-2023 Page 8 / 11

or incinerated, when in compliance with local regulations.

Section 14 - Transport Information

Component	Hazchem Code
Acetone	2YE
67-64-1 (>95)	

NZS 5433:2020

UN-No UN1090 Proper Shipping Name ACETONE

Hazard Class 3
Packing Group ||

<u>IATA</u>

UN-No UN1090 Proper Shipping Name ACETONE

Hazard Class 3
Packing Group ||

IMDG/IMO

UN-No UN1090 Proper Shipping Name ACETONE

Hazard Class 3
Packing Group ||

Environmental hazards No hazards identified

Transport in bulk according to Annex II of MARPOL 73/78 and the

IBC Code

Not applicable, packaged goods

Special Precautions No special precautions required. Please refer to the applicable dangerous goods

regulations for additional information.

Additional information None known

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

HSNO Approval Number HSR001070

National Regulations

There are no applicable tolerable exposure limits or environmental exposure limits according to the EPA Controls for Hazardous Substances

Certified handlers, tracking and controlled substance license requirements

Certified handlers are required for some substances. This includes substances requiring a controlled substance license, and most explosives, vertebrates toxic agents, and certain fumigants. Acutely toxic substances which are a Category 1 or 2, such as pesticides also require Certified handlers. Please check the Health and Safety at Work Act 2015 for further information. Tracking is required for some highly hazardous substances. These substances need to be under the control of an appropriately trained person or appropriately secured. Please check the Health and Safety at Work Act 2015 for further information.

Prohibition or notification/licensing requirements

Shown below are details of specific prohibition/notifications or licencing requirements when they apply.

International Regulations

FSUA0606 Version 2 13-Mar-2023 Page 9/11

Ozone Depletion Potential This product does not contain any known or suspected substance

Persistent Organic Pollutant This product does not contain any known or suspected substance

Rotterdam Convention (PIC) Not applicable

Authorisation/Restrictions according to EU REACH

Component		REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous			
	Authorization	Substances	List of Substances of Very High Concern (SVHC)		
Acetone	-	Use restricted. See item 75. (see link for restriction details)	-		

https://echa.europa.eu/substances-restricted-under-reach

International Inventories

Component

New Zealand (NZIoC), Australia (AICS), Europe (EINECS/ELINCS/NLP), Korea (KECL), China (IECSC), Taiwan (TCSI), Japan (ISHL), Canada (DSL/NDSL), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Acetone	67-64-1	X	X	-	-	ı	KE-29367	Х	Х
Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive		DSL	NDSL	PICCS	ISHL	ENCS
Acetone	67-64-1	X	AC.	ΓIVF	X	-	X	X	X

Legend: X - Listed '-' - Not Listed KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Section 16 - Other Information

CAS No

This safety data sheet complies with the requirements of the EPA Hazardous Substances (Hazard Classification) Notice 2020 and WorkSafe New Zealand Regulations

Legend

NZIoC - New Zealand Inventory of Chemicals

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

IECSC - Chinese Inventory of Existing Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
NZS 5433:2020 - Transport of Dangerous Goods on Land

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50% **WEL** - Workplace Exposure Limit

DNEL - Derived No Effect Level

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

VOC - (Volatile Organic Compound)

AICS - Australian Inventory of Chemical Substances

NZIOC AICS EINECS ELINCS NLP KECL IECSC TCSI

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japanese Existing and New Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

CAS - Chemical Abstracts Service

ACGIH - American Conference of Governmental Industrial Hygienists

PNEC - Predicted No Effect Concentration

OECD - Organisation for Economic Co-operation and Development **IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

ADG - Australian Code for the Transport of Dangerous Goods by Road and Rail

LC50 - Lethal Concentration 50% ATE - Acute Toxicity Estimate

RPE - Respiratory Protective Equipment

NOEC - No Observed Effect Concentration

BCF - Bioconcentration factor

PBT - Persistent, Bioaccumulative, Toxic

FSUA0606 Version 2 13-Mar-2023 Page 10 / 11

Key literature references and sources for data

HSNO classifications provided in the New Zealand Chemical Classification Information Database (CCID).

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

EPA Guide to classifying hazardous substances in New Zealand

EPA - Assigning a product to an existing HSNO approval guide

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Revision Date 13-Mar-2023 Revision Summary Not applicable

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

FSUA0606 Version 2 13-Mar-2023 Page 11 / 11