

Page 1 / 10 Creation Date 09-Feb-2010 Revision Date 24-Mar-2025 Version 2

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THECOMPANY/UNDERTAKING

Product Identifier

Perihalan Produk: Methyl iso-Butyl Ketone
Product Description: Methyl iso-Butyl Ketone

**Cat No. :** M213-1; M213-4; M213-20; M213-200

Synonyms Hexone; Isobutyl methyl ketone; Isopropylacetone; 4-Methyl-2-pentanone (Certified ACS)

CAS No 108-10-1 Molecular Formula C6H12O

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

Company Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd

Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square, No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,

Selangor Darul Ehsan, Malaysia. Main line: +60 3-5525 7888

**E-mail address** Enquiry.my@thermofisher.com

Emergency Telephone Number Tel: +03-5525 7888

CHEMTREC Malaysia 1-800-815-308 (Malay)

CHEMTREC Malaysia (Kuala Lumpur) +(60)-327884561 (Malay)

# **SECTION 2: HAZARDS IDENTIFICATION**

#### Classification of the substance or mixture

Flammable liquids	Category 2 (H225)
Acute Inhalation Toxicity - Vapors	Category 4 (H332)
Serious Eye Damage/Eye Irritation	Category 2 (H319)
Specific target organ toxicity - (single exposure)	Category 3 (H335)

## Label Elements



Signal Word Danger

**Hazard Statements** 

FSH14550

## Methyl iso-Butyl Ketone Revision Date 24-Mar-2025

H225 - Highly flammable liquid and vapor

H332 - Harmful if inhaled

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

## **Precautionary Statements**

#### Prevention

P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P240 - Ground and bond container and receiving equipment

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P264 - Wash face, hands and any exposed skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear eye protection/ face protection

P280 - Wear protective gloves

#### Response

P301 + P312 - IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

#### Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

#### **Disposal**

P501 - Dispose of contents/ container to an approved waste disposal plant

#### Other Hazards

EUH066 - Repeated exposure may cause skin dryness or cracking

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS No	Weight %
Methylisobutyl ketone	108-10-1	> 98.5

## **SECTION 4: FIRST AID MEASURES**

Description of first aid measures

General Advice If symptoms persist, call a physician.

**Eye Contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

**Ingestion** Clean mouth with water and drink afterwards plenty of water.

Methyl iso-Butyl Ketone Revision Date 24-Mar-2025

**Inhalation** Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

**Self-Protection of the First Aider** Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

**Notes to Physician** Treat symptomatically. Symptoms may be delayed.

## **SECTION 5: FIREFIGHTING MEASURES**

#### Extinguishing media

## **Suitable Extinguishing Media**

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

#### Extinguishing media which must not be used for safety reasons

No information available.

#### Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition. Vapors may form explosive mixtures with air.

#### **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO2), peroxides.

## Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### Personal Precautions, Protective Equipment and Emergency Procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

# Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

## Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

#### Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

#### Revision Date 24-Mar-2025

## **SECTION 7: HANDLING AND STORAGE**

## Precautions for Safe Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

## Conditions for Safe Storage, Including any Incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

#### Specific End Uses

Use in laboratories.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### **Control Parameters**

Component	Malaysia	ACGIH TLV	OSHA PEL
Methylisobutyl ketone		TWA: 20 ppm	(Vacated) TWA: 50 ppm
		STEL: 75 ppm	(Vacated) TWA: 205 mg/m <sup>3</sup>
			(Vacated) STEL: 75 ppm
			(Vacated) STEL: 300 mg/m <sup>3</sup>
			TWA: 100 ppm
			TWA: 410 mg/m <sup>3</sup>

Component	European Union	The United Kingdom	Germany
Methylisobutyl ketone	TWA: 20 ppm (8h)	STEL: 100 ppm 15 min	TWA: 20 ppm (8 Stunden). AGW -
	TWA: 83 mg/m³ (8h)	STEL: 416 mg/m <sup>3</sup> 15 min	exposure factor 2
	STEL: 50 ppm (15min)	TWA: 50 ppm 8 hr	TWA: 83 mg/m³ (8 Stunden). AGW -
	STEL: 208 mg/m³ (15min)	TWA: 208 mg/m <sup>3</sup> 8 hr	exposure factor 2
		Skin	TWA: 20 ppm (8 Stunden). MAK
			TWA: 83 mg/m³ (8 Stunden). MAK
			Höhepunkt: 40 ppm
			Höhepunkt: 166 mg/m <sup>3</sup>
			Haut

#### **Exposure Controls**

#### **Engineering Measures**

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

## Personal protective equipment

 Eye Protection
 Goggles

 Hand Protection
 Protective gloves

 Skin and body protection
 Long sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

\_\_\_\_\_

Methyl iso-Butyl Ketone Revision Date 24-Mar-2025

**Respiratory Protection** When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators

**Recommended Filter type:** Organic gases and vapours filter Type A Brown conforming to EN14387

To protect the wearer, respiratory protective equipment must be the correct fit and be used

@ 760 mmHg

and maintained properly

When RPE is used a face piece Fit Test should be conducted

<u>Hygiene Measures</u> Handle in accordance with good industrial hygiene and safety practice

Environmental exposure controls No information available

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Information on basic physical and chemical properties

Appearance Clear Physical State Liquid Odor sweet

Odor Threshold No data available PH Not applicable

Melting Point/Range-84 °C / -119.2 °FSoftening PointNo data availableBoiling Point/Range117 °C / 242.6 °F

Flash Point 14 °C / 57.2 °F Method - No information available

**Evaporation Rate** 1.6 (Butyl Acetate = 1.0)

Flammability (solid,gas) Not applicable Liquid

Explosion Limits No data available Lower 1.2% @

93°C

**Upper** 8.0% @ 93°C

Vapor Pressure 19.9 mmHg @ 25 °C

**Vapor Density** 3.45 (Air = 1.0) (Air = 1.0)

Specific Gravity / Density 0.80

Bulk Density Not applicable Liquid

Water Solubility 17 g/l

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Component log Pow
Methylisobutyl ketone 1.9

Autoignition Temperature 448 - °C / 838.4 - °F

Decomposition Temperature No data available Viscosity No data available

Explosive Properties

Oxidizing Properties No information available

Molecular FormulaC6H12OMolecular Weight100.16

FSH14550

Vapors may form explosive mixtures with air

Methyl iso-Butyl Ketone Revision Date 24-Mar-2025

# **SECTION 10: STABILITY AND REACTIVITY**

Reactivity

None known, based on information available.

**Chemical Stability** 

Stable under normal conditions.

Possibility of Hazardous Reactions

Hazardous Polymerization Hazardous Reactions

Hazardous polymerization does not occur.

None under normal processing.

Conditions to Avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

Incompatible Materials

Strong oxidizing agents. Strong reducing agents. Strong bases.

<u>Hazardous Decomposition Products</u>

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). peroxides.

# **SECTION 11: TOXICOLOGICAL INFORMATION**

#### Information on Toxicological Effects

## **Product Information**

(a) acute toxicity;

Oral Based on available data, the classification criteria are not met

Dermal Based on available data, the classification criteria are not met

Inhalation Category 4

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methylisobutyl ketone	LD50 = 2080 mg/kg (Rat)	LD50 = 3000 mg/kg (Rabbit)	LC50 2000 - 4000 ppm (Rat) 4
			h

Component	ECHA (RAC) ATE (Oral)	ECHA (RAC) ATE (Dermal)	ECHA (RAC) ATE (Inhalation)
Methylisobutyl ketone	-	-	ATE = 11 mg/L (vapour)

(b) skin corrosion/irritation; Based on available data, the classification criteria are not met

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

**Respiratory** Based on available data, the classification criteria are not met

Methyl iso-Butyl Ketone Revision Date 24-Mar-2025

Skin Based on available data, the classification criteria are not met

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met (f) carcinogenicity;

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Methylisobutyl ketone				Group 2B

Based on available data, the classification criteria are not met (g) reproductive toxicity;

Component	Test method	Test species / Duration	Study result
Methylisobutyl ketone	OECD Test Guideline 414	Rat	NOAEL =
108-10-1 ( > 98.5 )			4.1 mg/l
, ,			_
		Inhalation	

(h) STOT-single exposure; Category 3

Results / Target organs Respiratory system.

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

**Target Organs** None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

**Other Adverse Effects** Tumorigenic effects have been reported in experimental animals.

delayed

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

**Endocrine Disrupting Properties** Assess endocrine disrupting properties for human health. This product does not contain any

known or suspected endocrine disruptors.

## **SECTION 12: ECOLOGICAL INFORMATION**

**Ecotoxicity effects** This product contains the following substance(s) which are hazardous for the environment. .

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Methylisobutyl ketone	LC50: 496 - 514 mg/L, 96h flow-through	EC50: 4280.0 mg/L/24h EC50: 170 mg/L/48h	EC50: 400 mg/L/96h	EC50 = 79.6 mg/L 5 min
	(Pimephales promelas)	EC50: 4280.0 mg/L/24h		

#### Persistence and degradability

**Persistence** Persistence is unlikely.

Component	Degradability
Methylisobutyl ketone	83 % (28 d) (OECD 301F)
108-10-1 ( > 98.5 )	

Bioaccumulative potential	Bioaccumulation is unlikely
---------------------------	-----------------------------

Component	log Pow	Bioconcentration factor (BCF)
Methylisobutyl ketone	1.9	No data available

FSH14550

Methyl iso-Butyl Ketone Revision Date 24-Mar-2025

<u>Mobility in soil</u>

The product is water soluble, and may spread in water systems. . Will likely be mobile in the environment due to its water solubility. Highly mobile in soils.

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors

Other adverse effects No information available

## **SECTION 13: DISPOSAL CONSIDERATIONS**

Waste treatment methods

Waste from Residues/Unused

**Products** 

Waste is classified as hazardous Dispose of in accordance with the European Directives on

waste and hazardous waste Dispose of in accordance with local regulations

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous Keep product and

empty container away from heat and sources of ignition

Other Information Waste codes should be assigned by the user based on the application for which the product

was used Do not flush to sewer Can be landfilled or incinerated, when in compliance with

local regulations

## **SECTION 14: TRANSPORT INFORMATION**

IMDG/IMO

UN-No UN1245 Hazard Class 3 Packing Group II

Proper Shipping Name METHYL ISOBUTYL KETONE

Road and Rail Transport

UN-No UN1245 Hazard Class 3 Packing Group II

Proper Shipping Name METHYL ISOBUTYL KETONE

IATA

UN-No UN1245
Hazard Class 3
Packing Group II

Proper Shipping Name METHYL ISOBUTYL KETONE

Special Precautions for User No special precautions required

#### **SECTION 15: REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories X = listed

#### Methyl iso-Butyl Ketone

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Methylisobutyl ketone	203-550-1	Х	Х	Х	X	Х	X	X	KE-24725

Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Methylisobutyl ketone				Annex I - Y42

**National Regulations** 

**Persistent Organic Pollutant Ozone Depletion Potential** 

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

## **SECTION 16: OTHER INFORMATION**

#### Legend

**CAS** - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

Revision Date 24-Mar-2025

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances IECSC - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

Substances List **ENCS** - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50%

POW - Partition coefficient Octanol:Water

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime

Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)

#### Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

**Revision Date** 24-Mar-2025 **Revision Summary** Not applicable.

# In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

Revision Date 24-Mar-2025

materials or in any process, unless specified in the text

**End of Safety Data Sheet** 

FSH14550