

Creation Date 18-Oct-2010

Revision Date 16-May-2024

Revision Number 4

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product Description: n-Butyllithium, 1.6M in hexane  
Cat No. : 96605  
REACH registration number -

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.  
Uses advised against No Information available

### 1.3. Details of the supplier of the safety data sheet

#### Company

Thermo Fisher (Kandel) GmbH  
Erlenbachweg 2, 76870 Kandel, Germany  
Tel: +49 (0) 721 84007 280  
Fax: +49 (0) 721 84007 300

**Swiss distributor** - Fisher Scientific AG  
Neuhofstrasse 11, CH 4153 Reinach  
Tel: +41 (0) 56 618 41 11  
<https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html>

E-mail address begel.sdsdesk@thermofisher.com

### 1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11  
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99  
**CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:  
Tox Info Suisse Emergency Number: **145 (24hr)**  
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)  
Chemtrec (24h) Toll-Free: 0800 564 402  
Chemtrec Local: +41-43 508 20 11 (Zurich)

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

Flammable liquids	Category 2 (H225)
Substances/mixtures which, in contact with water, emit flammable gases	Category 1 (H260)
Pyrophoric liquids	Category 1 (H250)
<b><u>Health hazards</u></b>	
Aspiration Toxicity	Category 1 (H304)
Skin Corrosion/Irritation	Category 1 B (H314)
Serious Eye Damage/Eye Irritation	Category 1 (H318)
Reproductive Toxicity	Category 2 (H361f)
Specific target organ toxicity - (single exposure)	Category 3 (H336)
Specific target organ toxicity - (repeated exposure)	Category 2 (H373)
<b><u>Environmental hazards</u></b>	
Chronic aquatic toxicity	Category 2 (H411)

Full text of Hazard Statements: see section 16

## 2.2. Label elements



Signal Word

**Danger**

### Hazard Statements

H225 - Highly flammable liquid and vapor  
H250 - Catches fire spontaneously if exposed to air  
H260 - In contact with water releases flammable gases which may ignite spontaneously  
H304 - May be fatal if swallowed and enters airways  
H314 - Causes severe skin burns and eye damage  
H336 - May cause drowsiness or dizziness  
H361f - Suspected of damaging fertility  
H373 - May cause damage to organs through prolonged or repeated exposure  
H411 - Toxic to aquatic life with long lasting effects  
EUH014 - Reacts violently with water

### Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P280 - Wear protective gloves/protective clothing/eye protection/face protection  
P302 + P335 + P334 - IF ON SKIN: Brush off loose particles from skin. Immerse in cool water  
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P310 - Immediately call a POISON CENTER or doctor/physician

## 2.3. Other hazards

This product does not contain any known or suspected endocrine disruptors

# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Hexane	110-54-3	EEC No. 203-777-6	85	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Repr. 2 (H361f) STOT RE 2 (H373) Aquatic Chronic 2 (H411)
Butyl lithium	109-72-8	203-698-7	15	Pyr. Liq. 1 (H250) Water react. 1 (H260) Skin Corr. 1B (H314) Eye Dam. 1 (H318) (EUH014)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Hexane	STOT RE 2 (H373) :: C>=5%	-	-

REACH registration number		-
Components	Reach Registration Number	
Butyl lithium	01-2119494906-21	

Full text of Hazard Statements: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

<b>General Advice</b>	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
<b>Ingestion</b>	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
<b>Inhalation</b>	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately. Risk of serious damage to the lungs (by aspiration).
<b>Self-Protection of the First Aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

### 4.2. Most important symptoms and effects, both acute and delayed

# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

Difficulty in breathing. Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting; Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

## **4.3. Indication of any immediate medical attention and special treatment needed**

### **Notes to Physician**

Treat symptomatically. Symptoms may be delayed.

## **SECTION 5: FIREFIGHTING MEASURES**

### **5.1. Extinguishing media**

#### **Suitable Extinguishing Media**

Dry chemical. Limestone powder. Dry sand. approved class D extinguishers. Water mist may be used to cool closed containers.

#### **Extinguishing media which must not be used for safety reasons**

Water. Carbon dioxide (CO<sub>2</sub>). Foam.

### **5.2. Special hazards arising from the substance or mixture**

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

#### **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Thermal decomposition can lead to release of irritating gases and vapors, Butane.

### **5.3. Advice for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

### **6.2. Environmental precautions**

Do not flush into surface water or sanitary sewer system.

### **6.3. Methods and material for containment and cleaning up**

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

### **6.4. Reference to other sections**

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

## 7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

## Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

## 7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and flame. Keep under nitrogen. Keep refrigerated. Flammables area. Corrosives area. Keep away from water or moist air. Keep container tightly closed in a dry and well-ventilated place.

**Technical Rules for Hazardous Substances (TRGS) 510**  
**Storage Class (LGK) (Germany)**

Storage Class/LGK 4.2

**Switzerland - Storage of hazardous substances**

Storage class - SC 4.2  
<https://www.kvu.ch/de/themen/stoffe-und-produkte>  
<https://www.kvu.ch/fr/themes/substances-et-produits>  
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

## 7.3. Specific end use(s)

Use in laboratories

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Hexane	TWA: 20 ppm (8hr) TWA: 72 mg/m <sup>3</sup> (8hr)	TWA: 72 mg/m <sup>3</sup> TWA: 20 ppm STEL: 60 ppm STEL: 216 mg/m <sup>3</sup>	TWA / VME: 20 ppm (8 heures). restrictive limit TWA / VME: 72 mg/m <sup>3</sup> (8 heures). restrictive limit TWA / VME: 1000 mg/m <sup>3</sup> (8 heures). STEL / VLCT: 1500 mg/m <sup>3</sup> .	TWA: 20 ppm 8 uren TWA: 72 mg/m <sup>3</sup> 8 uren	TWA / VLA-ED: 20 ppm (8 horas) TWA / VLA-ED: 72 mg/m <sup>3</sup> (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Hexane	TWA: 20 ppm 8 ore. Time Weighted Average TWA: 72 mg/m <sup>3</sup> 8 ore. Time Weighted Average	TWA: 180 mg/m <sup>3</sup> TWA: 50 ppm	TWA: 20 ppm 8 horas TWA: 72 mg/m <sup>3</sup> 8 horas Pele	STEL: 144 mg/m <sup>3</sup> 15 minuten TWA: 72 mg/m <sup>3</sup> 8 uren	TWA: 20 ppm 8 tunteina TWA: 72 mg/m <sup>3</sup> 8 tunteina Iho
Butyl lithium		TWA: 0.2 mg/m <sup>3</sup> (8 Stunden). MAK inorganic compounds,			

# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

		except Lithium and strong irritant Lithium compounds such as Lithium amide, Lithium hydride, Lithium hydroxide, Lithium nitride, Lithium oxide, Lithium tetrahydroaluminate, Lithium tetrahydroborate			
--	--	---	--	--	--

Component	Austria	Denmark	Switzerland	Poland	Norway
Hexane	MAK-KZGW: 80 ppm 15 Minuten MAK-KZGW: 288 mg/m <sup>3</sup> 15 Minuten MAK-TMW: 20 ppm 8 Stunden MAK-TMW: 72 mg/m <sup>3</sup> 8 Stunden	TWA: 20 ppm 8 timer TWA: 72 mg/m <sup>3</sup> 8 timer STEL: 40 ppm 15 minutter STEL: 144 mg/m <sup>3</sup> 15 minutter	Haut/Peau STEL: 400 ppm 15 Minuten STEL: 1440 mg/m <sup>3</sup> 15 Minuten TWA: 50 ppm 8 Stunden TWA: 180 mg/m <sup>3</sup> 8 Stunden	TWA: 72 mg/m <sup>3</sup> 8 godzinach	TWA: 20 ppm 8 timer TWA: 72 mg/m <sup>3</sup> 8 timer TWA: 40 ppm 8 timer TWA: 275 mg/m <sup>3</sup> 8 timer STEL: 30 ppm 15 minutter. value calculated STEL: 108 mg/m <sup>3</sup> 15 minutter. value calculated

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Hexane	TWA: 20 ppm TWA: 72.0 mg/m <sup>3</sup>	kože TWA-GVI: 20 ppm 8 satima. TWA-GVI: 72 mg/m <sup>3</sup> 8 satima.	TWA: 20 ppm 8 hr. TWA: 72 mg/m <sup>3</sup> 8 hr. STEL: 60 ppm 15 min STEL: 216 mg/m <sup>3</sup> 15 min Skin	TWA: 20 ppm TWA: 72 mg/m <sup>3</sup>	TWA: 70 mg/m <sup>3</sup> 8 hodinách. Potential for cutaneous absorption Ceiling: 200 mg/m <sup>3</sup>

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Hexane	TWA: 20 ppm 8 tundides. TWA: 72 mg/m <sup>3</sup> 8 tundides.	TWA: 20 ppm 8 hr TWA: 72 mg/m <sup>3</sup> 8 hr	TWA: 20 ppm TWA: 72 mg/m <sup>3</sup>	TWA: 72 mg/m <sup>3</sup> 8 órában. AK lehetséges borön keresztül felszívódás	TWA: 20 ppm 8 klukkustundum. TWA: 72 mg/m <sup>3</sup> 8 klukkustundum. Ceiling: 40 ppm Ceiling: 144 mg/m <sup>3</sup>

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Hexane	TWA: 20 ppm TWA: 72 mg/m <sup>3</sup>	TWA: 20 ppm IPRD TWA: 72 mg/m <sup>3</sup> IPRD	TWA: 20 ppm 8 Stunden TWA: 72 mg/m <sup>3</sup> 8 Stunden	TWA: 20 ppm TWA: 72 mg/m <sup>3</sup>	TWA: 20 ppm 8 ore TWA: 72 mg/m <sup>3</sup> 8 ore

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Hexane	TWA: 300 mg/m <sup>3</sup> 0780 MAC: 900 mg/m <sup>3</sup>	Ceiling: 140 mg/m <sup>3</sup> TWA: 20 mg/m <sup>3</sup> TWA: 72 mg/m <sup>3</sup>	TWA: 20 ppm 8 urah TWA: 72 mg/m <sup>3</sup> 8 urah STEL: 576 mg/m <sup>3</sup> 15 minutah STEL: 160 ppm 15 minutah	Binding STEL: 50 ppm 15 minuter Binding STEL: 180 mg/m <sup>3</sup> 15 minuter TLV: 20 ppm 8 timmar. NGV TLV: 72 mg/m <sup>3</sup> 8 timmar. NGV	TWA: 20 ppm 8 saat TWA: 72 mg/m <sup>3</sup> 8 saat

## Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Hexane			2,5-Hexanedione: 5 mg/g creatinine urine end of shift	2,5-Hexanedione: 0.2 mg/L urine end of workweek	2,5-Hexandione plus 4,5-Dihydroxy-2-hexanone (after hydrolysis): 5 mg/L urine (end of shift)

Component	Italy	Finland	Denmark	Bulgaria	Romania
Hexane					2,5-Hexandion: 5 mg/g Creatinine urine end of

# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

					shift
Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Hexane			2,5-Hexanedione: 5 mg/L urine end of exposure or work shift 4,5-Dihydroxy-2-hexanone: 5 mg/L urine end of exposure or work shift		

## Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

## Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Hexane 110-54-3 ( 85 )				DNEL = 11mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Hexane 110-54-3 ( 85 )				DNEL = 75mg/m <sup>3</sup>

## Predicted No Effect Concentration (PNEC)

No information available.

## 8.2. Exposure controls

### Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

### Personal protective equipment

#### Eye Protection

Goggles (European standard - EN 166)

#### Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	See manufacturers	-	EN 374	(minimum requirement)
Viton (R)	recommendations			

#### Skin and body protection

Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the

# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

<b>Respiratory Protection</b>	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly
<b>Large scale/emergency use</b>	Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced <b>Recommended Filter type:</b> low boiling organic solvent Type AX Brown conforming to EN371
<b>Small scale/Laboratory use</b>	Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. <b>Recommended half mask:-</b> Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141 When RPE is used a face piece Fit Test should be conducted
<b>Environmental exposure controls</b>	Prevent product from entering drains. Do not allow material to contaminate ground water system.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

<b>Physical State</b>	Liquid	
<b>Appearance</b>	Yellow	
<b>Odor</b>	Petroleum distillates	
<b>Odor Threshold</b>	No data available	
<b>Melting Point/Range</b>	-95 °C / -139 °F	
<b>Softening Point</b>	No data available	
<b>Boiling Point/Range</b>	60 - 80 °C / 140 - 176 °F	@ 760 mmHg
<b>Flammability (liquid)</b>	Highly flammable	On basis of test data
<b>Flammability (solid,gas)</b>	Not applicable	Liquid
<b>Explosion Limits</b>	<b>Lower</b> 1.2 Vol% <b>Upper</b> 7.8 Vol%	
<b>Flash Point</b>	-21 °C / -5.8 °F	<b>Method -</b> (based on components)
<b>Autoignition Temperature</b>	240 °C / 464 °F	
<b>Decomposition Temperature</b>	No data available	
<b>pH</b>	No information available	
<b>Viscosity</b>	No data available	
<b>Water Solubility</b>	Reacts with water	
<b>Solubility in other solvents</b>	No information available	
<b>Partition Coefficient (n-octanol/water)</b>		
<b>Component</b>	<b>log Pow</b>	
Hexane	4.11	
<b>Vapor Pressure</b>	160 mbar @ 20 °C	
<b>Density / Specific Gravity</b>	0.680	
<b>Bulk Density</b>	Not applicable	Liquid
<b>Vapor Density</b>	No data available	(Air = 1.0)
<b>Particle characteristics</b>	Not applicable (liquid)	

### 9.2. Other information

<b>Explosive Properties</b>	Vapors may form explosive mixtures with air
<b>Substances/mixtures which, in contact with water, emit flammable</b>	Emitted gas ignites spontaneously Gas(es) = Butane



# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

gases

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

Yes

### 10.2. Chemical stability

Water reactive. Reacts violently with water. Air sensitive.

### 10.3. Possibility of hazardous reactions

#### Hazardous Polymerization Hazardous Reactions

Hazardous polymerization does not occur.  
Reacts violently with water.

### 10.4. Conditions to avoid

Incompatible products. Heat, flames and sparks. Exposure to moist air or water. Exposure to air. Exposure to moisture. Keep away from open flames, hot surfaces and sources of ignition.

### 10.5. Incompatible materials

Strong oxidizing agents. Halogens.

### 10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Thermal decomposition can lead to release of irritating gases and vapors. Butane.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Product Information

#### (a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

#### Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Hexane	LD50 = 25 g/kg ( Rat )	LD50 = 3000 mg/kg ( Rabbit )	LC50 = 48000 ppm ( Rat ) 4 h

#### (b) skin corrosion/irritation;

Category 1 B

#### (c) serious eye damage/irritation;

Category 1

#### (d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

#### (e) germ cell mutagenicity;

No data available

# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

(f) carcinogenicity;	No data available There are no known carcinogenic chemicals in this product
(g) reproductive toxicity; Reproductive Effects	Category 2 Possible risk of impaired fertility.
(h) STOT-single exposure; Results / Target organs	Category 3 Central nervous system (CNS).
(i) STOT-repeated exposure; Target Organs	Category 2 Eyes, Respiratory system, Skin, Gastrointestinal tract (GI), Central nervous system (CNS), Liver, Peripheral Nervous System (PNS).
(j) aspiration hazard; Other Adverse Effects	Category 1 Tumorigenic effects have been reported in experimental animals.
Symptoms / effects, both acute and delayed	Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

## 11.2. Information on other hazards

Endocrine Disrupting Properties	Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.
---------------------------------	---

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

Ecotoxicity effects	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.
---------------------	--

Component	Freshwater Fish	Water Flea	Freshwater Algae
Hexane	LC50: 2.1 - 2.98 mg/L, 96h flow-through (Pimephales promelas)	EC50: 3.87 mg/L/48h	

### 12.2. Persistence and degradability

Persistence	Persistence is unlikely, based on information available.
Degradation in sewage treatment plant	Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

### 12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Hexane	4.11	No data available

# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

## 12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air.

## 12.5. Results of PBT and vPvB assessment

No data available for assessment.

## 12.6. Endocrine disrupting properties

### Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors.

## 12.7. Other adverse effects

### Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance.

This product does not contain any known or suspected substance.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

#### Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

#### Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

#### European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

#### Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms. Do not let this chemical enter the environment.

#### Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600  
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

## SECTION 14: TRANSPORT INFORMATION

### IMDG/IMO

#### 14.1. UN number

UN3394

#### 14.2. UN proper shipping name

ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE

#### Technical Shipping Name

Hexane, Butyl lithium

#### 14.3. Transport hazard class(es)

4.2

#### Subsidiary Hazard Class

4.3

#### 14.4. Packing group

I

### ADR

#### 14.1. UN number

UN3394

#### 14.2. UN proper shipping name

ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE

#### Technical Shipping Name

Hexane, Butyl lithium

ALFAA96605

# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

**14.3. Transport hazard class(es)** 4.2  
**Subsidiary Hazard Class** 4.3  
**14.4. Packing group** I

**IATA** FORBIDDEN FOR IATA TRANSPORT

**14.1. UN number** UN3394  
**14.2. UN proper shipping name** ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE  
**Technical Shipping Name** FORBIDDEN FOR IATA TRANSPORT  
Hexane, Butyl lithium  
**14.3. Transport hazard class(es)** 4.2  
**Subsidiary Hazard Class** 4.3  
**14.4. Packing group** I

**14.5. Environmental hazards** Dangerous for the environment  
Product is a marine pollutant according to the criteria set by IMDG/IMO

**14.6. Special precautions for user** No special precautions required.

**14.7. Maritime transport in bulk according to IMO instruments** Not applicable, packaged goods

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Hexane	110-54-3	203-777-6	438-390-3	-	X	X	KE-18626	X	X
Butyl lithium	109-72-8	203-698-7	-	-	X	X	KE-04320	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Hexane	110-54-3	X	ACTIVE	X	-	X	X	X
Butyl lithium	109-72-8	X	ACTIVE	X	-	X	X	X

**Legend:** X - Listed '-' - Not Listed

**KECL** - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

### Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Hexane	110-54-3	-	Use restricted. See item 75. (see link for restriction details)	-
Butyl lithium	109-72-8	-	-	-

#### REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

### Seveso III Directive (2012/18/EC)

ALFAA96605

# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Hexane	110-54-3	Not applicable	Not applicable
Butyl lithium	109-72-8	Not applicable	Not applicable

**Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals**

Not applicable

**Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?**

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Directive 94/33/EC on the protection of young people at work

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

## National Regulations

**UK** - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

## WGK Classification

Water endangering class = 2 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Hexane	WGK2	
Butyl lithium	WGK1	

Component	France - INRS (Tables of occupational diseases)
Hexane	Tableaux des maladies professionnelles (TMP) - RG 59,RG 84

## Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Hexane 110-54-3 ( 85 )	Prohibited and Restricted Substances	Group I	

## 15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

## SECTION 16: OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor

H250 - Catches fire spontaneously if exposed to air

H260 - In contact with water releases flammable gases which may ignite spontaneously

H304 - May be fatal if swallowed and enters airways

H314 - Causes severe skin burns and eye damage

# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

H315 - Causes skin irritation  
H318 - Causes serious eye damage  
H336 - May cause drowsiness or dizziness  
H361f - Suspected of damaging fertility  
H411 - Toxic to aquatic life with long lasting effects  
EUH014 - Reacts violently with water

## Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**NOEC** - No Observed Effect Concentration

**PBT** - Persistent, Bioaccumulative, Toxic

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**POW** - Partition coefficient Octanol:Water

**vPvB** - very Persistent, very Bioaccumulative

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

### **Key literature references and sources for data**

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadviser - LOLI, Merck index, RTECS

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - (volatile organic compound)

### **Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:**

**Physical hazards** On basis of test data

**Health Hazards** Calculation method

**Environmental hazards** Calculation method

### **Training Advice**

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

**Prepared By** Health, Safety and Environmental Department

**Creation Date** 18-Oct-2010

**Revision Date** 16-May-2024

**Revision Summary** New emergency telephone response service provider.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.  
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No  
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,  
Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and  
Preparations).**

# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

---

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**