

according to Regulation (EC) No. 1907/2006

Creation Date 28-May-2009 Revision Date 20-Oct-2023 **Revision Number** 8

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE **COMPANY/UNDERTAKING**

1.1. Product identifier

Product Description: Methyl-tert-butyl ether

M/4496/25SS, M/4496/27SS, M/4496/27Z, M/4496/17, M/4496/17X, M/4496/21RSS, Cat No.:

M/4496/10RSS, M/4496/25RSS, M/4496/30RSS, M/4496/27RSS

Synonyms 2-Methyl-2-methoxy propane; MTBE; Methyl tert-butyl ether

Index No 603-181-00-X **CAS No** 1634-04-4 EC No 216-653-1 Molecular Formula C5 H12 O

01-2119452786-27 **REACH** registration number

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.

SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites Sector of use

Product category PC21 - Laboratory chemicals

Process categories PROC15 - Use as a laboratory reagent

Environmental release category ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)

Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

EU entity/business name

Thermo Fisher Scientific Janssen Pharmaceuticalaan 3a

2440 Geel, Belgium

UK entity/business name

Fisher Scientific UK

Bishop Meadow Road, Loughborough, Leicestershire LE11 5RG, United Kingdom

Swiss distributor - Fisher Scientific AG Neuhofstrasse 11, CH 4153 Reinach

Tel: +41 (0) 56 618 41 11

e-mail - infoch@thermofisher.com

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

Chemtrec US: (800) 424-9300 Chemtrec EU: 001-703-527-3887

For customers in Switzerland:

Tox Info Suisse Emergency Number: 145 (24hr)

Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)

Chemtrec (24h) Toll-Free: 0800 564 402 Chemtrec Local: +41-43 508 20 11 (Zurich)

Tel: 01509 231166

Revision Date 20-Oct-2023

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids Category 2 (H225)

Health hazards

Skin Corrosion/Irritation Category 2 (H315)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H315 - Causes skin irritation

Precautionary Statements

P240 - Ground and bond container and receiving equipment

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

Contains a known or suspected endocrine disruptor

Contains a substance on the National Authorities Endocrine Disruptor Lists

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Methyl-tert-butyl ether Revision Date 20-Oct-2023

3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No
Methyl tert-butyl ether	1634-04-4	EEC No. 216-653-1	>95	Flam. Liq. 2 (H225) Skin Irrit. 2 (H315)

REACH registration number	01-2119452786-27

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Get medical attention.

Ingestion Do NOT induce vomiting. Get medical attention.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur. If not breathing,

give artificial respiration.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO2).

Methyl-tert-butyl ether Revision Date 20-Oct-2023

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Ensure adequate ventilation.

6.2. Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Use only under a chemical fume hood. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Flammables area. Keep away from heat, sparks and flame. Keep container tightly closed in a dry and well-ventilated place. May form explosive peroxides on prolonged storage.

Technical Rules for Hazardous Substances (TRGS) 510

Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3

https://www.kvu.ch/de/themen/stoffe-und-produkte https://www.kvu.ch/fr/themes/substances-et-produits https://www.kvu.ch/it/temi/sostanze-e-prodotti

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Methyl-tert-butyl ether Revision Date 20-Oct-2023

8.1. Control parameters

Exposure limits

List source(s): EU - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC UK - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. IRE - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. CH - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Methyl tert-butyl	TWA: 50 ppm (8h)		TWA / VME: 50 ppm (8	TWA: 40 ppm 8 uren	STEL / VLA-EC: 100
ether	TWA: 183.5 mg/m ³ (8h)	STEL: 367 mg/m ³ 15	heures). restrictive limit	TWA: 146 mg/m ³ 8 uren	ppm (15 minutos).
	STEL: 100 ppm (15min)	min	TWA / VME: 183.5	STEL: 100 ppm 15	STEL / VLA-EC: 367
	STEL: 367 mg/m ³	TWA: 50 ppm 8 hr	mg/m³ (8 heures).	minuten	mg/m³ (15 minutos).
	(15min)	TWA: 183.5 mg/m ³ 8 hr	restrictive limit	STEL: 367 mg/m ³ 15	TWA / VLA-ED: 50 ppm
			STEL / VLCT: 367	minuten	(8 horas)
			mg/m ³ . restrictive limit		TWA / VLA-ED: 183.5
			STEL / VLCT: 100 ppm.		mg/m³ (8 horas)
			restrictive limit		į į

Component	Italy	Germany	Portugal	The Netherlands	Finland
Methyl tert-butyl	TWA: 50 ppm 8 ore.	TWA: 50 ppm (8	STEL: 100 ppm 15	STEL: 360 mg/m ³ 15	TWA: 50 ppm 8 tunteina
ether	Time Weighted Average	Stunden). AGW -	minutos	minuten	TWA: 180 mg/m ³ 8
	TWA: 183.5 mg/m ³ 8	exposure factor 1.5	STEL: 367 mg/m ³ 15	TWA: 180 mg/m ³ 8 uren	tunteina
	ore. Time Weighted	TWA: 180 mg/m ³ (8	minutos		STEL: 100 ppm 15
	Average	Stunden). AGW -	TWA: 50 ppm 8 horas		minuutteina
	STEL: 100 ppm 15	exposure factor 1.5	TWA: 183.5 mg/m ³ 8		STEL: 360 mg/m ³ 15
	minuti. Short-term	TWA: 50 ppm (8	horas		minuutteina
	STEL: 367 mg/m ³ 15	Stunden). MAK			
	minuti. Short-term	TWA: 180 mg/m ³ (8			
		Stunden). MAK			
		Höhepunkt: 75 ppm			
		Höhepunkt: 270 mg/m ³			

Component	Austria	Denmark	Switzerland	Poland	Norway
Methyl tert-butyl	MAK-KZGW: 100 ppm	TWA: 40 ppm 8 timer	STEL: 75 ppm 15	STEL: 270 mg/m ³ 15	TWA: 50 ppm 8 timer
ether	15 Minuten	TWA: 144 mg/m ³ 8 timer	Minuten	minutach	TWA: 183.5 mg/m ³ 8
	MAK-KZGW: 360 mg/m ³	STEL: 376 mg/m ³ 15	STEL: 270 mg/m ³ 15	TWA: 180 mg/m ³ 8	timer
	15 Minuten	minutter	Minuten	godzinach	STEL: 100 ppm 15
	MAK-TMW: 50 ppm 8	STEL: 100 ppm 15	TWA: 50 ppm 8	_	minutter. value from the
	Stunden	minutter	Stunden		regulation
	MAK-TMW: 180 mg/m ³		TWA: 180 mg/m ³ 8		STEL: 367 mg/m ³ 15
	8 Stunden		Stunden		minutter. value from the
					regulation

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Methyl tert-butyl ether	TWA: 50 ppm TWA: 183.5 mg/m³ STEL : 100 ppm STEL : 367 mg/m³	kože TWA-GVI: 50 ppm 8 satima. TWA-GVI: 183.5 mg/m³	TWA: 50 ppm 8 hr. TWA: 183.5 mg/m³ 8 hr. STEL: 100 ppm 15 min STEL: 367 mg/m³ 15	STEL: 367 mg/m³ STEL: 100 ppm TWA: 183.5 mg/m³ TWA: 50 ppm	TWA: 100 mg/m³ 8 hodinách. Ceiling: 200 mg/m³
		8 satima. STEL-KGVI: 100 ppm 15 minutama. STEL-KGVI: 367 mg/m³ 15 minutama.	min		

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Methyl tert-butyl ether	TWA: 50 ppm 8 tundides. TWA: 183.5 mg/m ³ 8 tundides.	TWA: 183.5 mg/m ³ 8 hr TWA: 50 ppm 8 hr STEL: 367 mg/m ³ 15 min	STEL: 367 mg/m ³ TWA: 50 ppm TWA: 183.5 mg/m ³	STEL: 367 mg/m³ 15 percekben. CK TWA: 183.5 mg/m³ 8 órában. AK	STEL: 100 ppm branched in three STEL: 367 mg/m³ branched in three
	STEL: 100 ppm 15 minutites. STEL: 367 mg/m ³ 15	STEL: 100 ppm 15 min			TWA: 50 ppm 8 klukkustundum. branched in three

Methyl-tert-butyl ether

Revision Date 20-Oct-2023

minutites.	TWA: 183.5 mg/m ³ 8
	klukkustundum.
	branched in three

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Methyl tert-butyl	STEL: 100 ppm	TWA: 50 ppm IPRD	TWA: 183.5 mg/m ³ 8	TWA: 183.5 mg/m ³	TWA: 50 ppm 8 ore
ether	STEL: 367 mg/m ³	TWA: 183.5 mg/m ³	Stunden	TWA: 50 ppm	TWA: 183.5 mg/m ³ 8
	TWA: 50 ppm	IPRD	TWA: 50 ppm 8	STEL: 367 mg/m ³ 15	ore
	TWA: 183.5 mg/m ³	STEL: 100 ppm	Stunden	minuti	STEL: 100 ppm 15
		STEL: 367 mg/m ³	STEL: 367 mg/m ³ 15	STEL: 100 ppm 15	minute
			Minuten	minuti	STEL: 367 mg/m ³ 15
			STEL: 100 ppm 15		minute
			Minuten		

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Methyl tert-butyl	TWA: 100 mg/m ³ 1333	Ceiling: 367 mg/m ³	TWA: 50 ppm 8 urah	Binding STEL: 100 ppm	TWA: 50 ppm 8 saat
ether	MAC: 300 mg/m ³	TWA: 50 ppm	TWA: 183.5 mg/m ³ 8	15 minuter	TWA: 183.5 mg/m ³ 8
		TWA: 183.5 mg/m ³	urah	Binding STEL: 367	saat
			STEL: 100 ppm 15	mg/m ³ 15 minuter	STEL: 100 ppm 15
			minutah	TLV: 30 ppm 8 timmar.	dakika
			STEL: 367 mg/m ³ 15	NGV	STEL: 367 mg/m ³ 15
			minutah	TLV: 110 mg/m ³ 8	dakika
				timmar. NGV	

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Methyl tert-butyl ether 1634-04-4 (>95)				DNEL = 5100mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Methyl tert-butyl ether 1634-04-4 (>95)	DNEL = 357mg/m ³			DNEL = 178.5mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water	Water Intermittent	Microorganisms in	Soil (Agriculture)
		sediment		sewage treatment	
Methyl tert-butyl ether	PNEC = 5.1mg/L	PNEC = 23mg/kg	PNEC = 47.2mg/L	PNEC = 71mg/L	PNEC = 1.56mg/kg

Methyl-tert-butyl ether

Revision Date 20-Oct-2023

Page 7/13

1634-04-4 (> 95) sediment dw soil dw
--

	Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Meth	yl tert-butyl ether	PNEC = 0.26mg/L	PNEC = 1.17mg/kg			
16	34-04-4 (>95)		sediment dw			

8.2. Exposure controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Wear safety glasses with side shields (or goggles) (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	< 211 minutes	0.38 mm	Level 4	Permeation rate 1 µg/cm2/min
Viton (R)	< 152 minutes	0.7 mm	Level 4	Permeation rate 17 µg/cm2/min
Neoprene			EN 374	As tested under EN374-3 Determination of
Natural rubber				Resistance to Permeation by Chemicals
PVC				•

Skin and body protectionWear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory ProtectionNo protective equipment is needed under normal use conditions.

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Small scale/Laboratory use Maintain adequate ventilation

Environmental exposure controls No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State Liquid

Appearance Colorless

Odor Petroleum distillates
Odor Threshold No data available
Melting Point/Range -110 °C / -166 °F
Softening Point No data available

Boiling Point/Range 54 - 56 °C / 129.2 - 132.8 °F

Flammability (liquid) Highly flammable On basis of test data

Flammability (solid,gas) Not applicable Liquid

Methyl-tert-butyl ether Revision Date 20-Oct-2023

Explosion Limits Lower 1.6 vol%

Upper 8.4 vol%

Flash Point -28 °C / -18.4 °F Method - No information available

Autoignition Temperature

Decomposition Temperature

pH

Viscosity

224 °C / 435.2 °F

No data available

No information available

No information available

0.36 mPa.s at 20 °C

Water Solubility 51 g/L (20°C)

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Componentlog PowMethyl tert-butyl ether1.06

Vapor Pressure 268 mbar @ 20 °C

Density / Specific Gravity 0.740

Bulk DensityNot applicableLiquidVapor Density0.2(Air = 1.0)

Particle characteristics Not applicable (liquid)

9.2. Other information

Molecular FormulaC5 H12 OMolecular Weight88.15

Explosive Properties Vapors may form explosive mixtures with air

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral Based on available data, the classification criteria are not met
Dermal Based on available data, the classification criteria are not met

Revision Date 20-Oct-2023 Methyl-tert-butyl ether

Inhalation Based on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl tert-butyl ether	LD50 = 2963 mg/kg (Rat)	LD50 = 10000 mg/kg (Rabbit)	LC50 = 85 mg/L (Rat) 4 h

Category 2 (b) skin corrosion/irritation;

Based on available data, the classification criteria are not met (c) serious eye damage/irritation;

(d) respiratory or skin sensitization;

Respiratory Based on available data, the classification criteria are not met Based on available data, the classification criteria are not met Skin

Based on available data, the classification criteria are not met (e) germ cell mutagenicity;

Mutagenic effects have occurred in experimental animals

(f) carcinogenicity; Based on available data, the classification criteria are not met

The table below indicates whether each agency has listed any ingredient as a carcinogen

Limited evidence of a carcinogenic effect

(g) reproductive toxicity; Based on available data, the classification criteria are not met

(h) STOT-single exposure; Based on available data, the classification criteria are not met

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Target Organs None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Other Adverse Effects Tumorigenic effects have been reported in experimental animals.

delayed

Symptoms / effects, both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health

Contains a substance on the National Authorities Endocrine Disruptor Lists

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Do not empty into drains. . **Ecotoxicity effects**

Component	Freshwater Fish	Water Flea	Freshwater Algae
Methyl tert-butyl ether	887 mg/L LC50 96 h	EC50: = 542 mg/L, 48h	800 mg/L EC50 > 72 h
	100 mg/L LC50 96 h	(Daphnia magna)	184 mg/L EC50 = 96 h
	929 mg/L LC50 96 h	1	

Methyl-tert-butyl ether

Revision Date 20-Oct-2023

672 mg/L LC50 96 h	

Component	Microtox	M-Factor
Methyl tert-butyl ether	EC50 = 11.4 mg/L 30 min	
	EC50 = 8.23 mg/L 5 min	
	EC50 = 9.67 mg/L 15 min	

12.2. Persistence and degradability

Persistence Persistence is unlikely, based on information available.

12.3. Bioaccumulative potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Methyl tert-butyl ether	1.06	No data available

12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all

surfaces Will likely be mobile in the environment due to its volatility. Disperses rapidly in

air

12.5. Results of PBT and vPvB

assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent

and very bioaccumulative (vPvB).

12.6. Endocrine disrupting

properties

Endocrine Disruptor Information
Assess endocrine disrupting

properties for the environment

Contains a substance on the National Authorities Endocrine Disruptor Lists.

ſ	Component	EU - Endocrine Disrupters Candidate List	EU - Endocrine Disruptors - Evaluated					
	•	-	Substances					
Ī	Methyl tert-butyl ether	Group III Chemical						

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but

application specific.

Other Information

Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with

local regulations.

Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance,

ADWO) SR 814.600

Methyl-tert-butyl ether

https://www.fedlex.admin.ch/eli/cc/2015/891/en

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN2398

14.2. UN proper shipping name METHYL tert-BUTYL ETHER

14.3. Transport hazard class(es) 3 14.4. Packing group II

ADR

14.1. UN number UN2398

14.2. UN proper shipping name METHYL tert-BUTYL ETHER

14.3. Transport hazard class(es) 3 14.4. Packing group II

<u>IATA</u>

14.1. UN number UN2398

14.2. UN proper shipping name METHYL tert-BUTYL ETHER

14.3. Transport hazard class(es) 3 14.4. Packing group II

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk Not applicable, packaged goods

according to IMO instruments

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Methyl tert-butyl ether	1634-04-4	216-653-1	-	-	Х	X	KE-23648	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Methyl tert-butyl ether	1634-04-4	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed **KECL** - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) -	REACH (1907/2006) -	REACH Regulation (EC
·		Annex XIV - Substances	Annex XVII - Restrictions	1907/2006) article 59 -
		Subject to Authorization	on Certain Dangerous	Candidate List of
		-	Substances	Substances of Very High
				Concern (SVHC)

Revision Date 20-Oct-2023

Methyl-tert-butyl ether

Revision Date 20-Oct-2023

Methyl tert-butyl ether	1634-04-4	-	Use restricted. See item	-
			75.	
			(see link for restriction	
			details)	

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident	
		Notification	Requirements
Methyl tert-butyl ether	1634-04-4	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Methyl tert-butyl ether	WGK1	

Component	France - INRS (Tables of occupational diseases)
Methyl tert-butyl ether	Tableaux des maladies professionnelles (TMP) - RG 84

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor

H315 - Causes skin irritation

Legend

Methyl-tert-butyl ether Revision Date 20-Oct-2023

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

ENCS - Japanese Existing and New Chemical Substances

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic

Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances

Substances List

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration PBT - Persistent. Bioaccumulative. Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50% POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate VOC - (volatile organic compound)

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical incident response training.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Creation Date 28-May-2009 **Revision Date** 20-Oct-2023 **Revision Summary** Not applicable.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet