

Creation Date 13-Apr-2009

Revision Date 22-Mar-2024

Revision Number 3

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product Description:	<b>2-Butanone</b>
Cat No. :	<b>R18400</b>
Synonyms	Methyl ethyl ketone; MEK; Ethyl methyl ketone
Index No	606-002-00-3
CAS No	78-93-3
EC No	201-159-0
Molecular Formula	C <sub>4</sub> H <sub>8</sub> O
REACH registration number	-

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use	Laboratory chemicals.
Sector of use	SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites
Product category	PC21 - Laboratory chemicals
Process categories	PROC15 - Use as a laboratory reagent
Environmental release category	ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)
Uses advised against	No Information available

### 1.3. Details of the supplier of the safety data sheet

#### Company

Thermo Fisher (Kandel) GmbH  
Erlenbachweg 2, 76870 Kandel, Germany  
Tel: +49 (0) 721 84007 280  
Fax: +49 (0) 721 84007 300

**Swiss distributor** - Fisher Scientific AG  
Neuhofstrasse 11, CH 4153 Reinach  
Tel: +41 (0) 56 618 41 11  
<https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html>

#### E-mail address

[begel.sdsdesk@thermofisher.com](mailto:begel.sdsdesk@thermofisher.com)

### 1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11  
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99  
**CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:  
Tox Info Suisse Emergency Number: **145 (24hr)**  
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)  
Chemtrec (24h) Toll-Free: 0800 564 402  
Chemtrec Local: +41-43 508 20 11 (Zurich)

## SECTION 2: HAZARDS IDENTIFICATION

# SAFETY DATA SHEET

2-Butanone

Revision Date 22-Mar-2024

## 2.1. Classification of the substance or mixture

### CLP Classification - Regulation (EC) No 1272/2008

#### Physical hazards

Flammable liquids

Category 2 (H225)

#### Health hazards

Serious Eye Damage/Eye Irritation  
Specific target organ toxicity - (single exposure)

Category 2 (H319)  
Category 3 (H336)

#### Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

## 2.2. Label elements



Signal Word

Danger

### Hazard Statements

H225 - Highly flammable liquid and vapor  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
EUH066 - Repeated exposure may cause skin dryness or cracking

### Precautionary Statements

P280 - Wear protective gloves/protective clothing/eye protection/face protection  
P240 - Ground and bond container and receiving equipment  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

## 2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

Contains a substance on the National Authorities Endocrine Disruptor Lists  
Contains a known or suspected endocrine disruptor

# SAFETY DATA SHEET

2-Butanone

Revision Date 22-Mar-2024

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Methyl ethyl ketone	78-93-3	EEC No. 201-159-0	<=100	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319) STOT SE 3 (H336) (EUH066)

REACH registration number

-

Full text of Hazard Statements: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if symptoms occur.
<b>Ingestion</b>	Do NOT induce vomiting. Get medical attention.
<b>Inhalation</b>	Remove to fresh air. Get medical attention if symptoms occur. If not breathing, give artificial respiration.
<b>Self-Protection of the First Aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

### 4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes to Physician** Treat symptomatically. Symptoms may be delayed.

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### Suitable Extinguishing Media

CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

#### Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

### 5.2. Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

# SAFETY DATA SHEET

2-Butanone

Revision Date 22-Mar-2024

Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

## Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>).

### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation.

### 6.2. Environmental precautions

Avoid release to the environment. See Section 12 for additional Ecological Information.

### 6.3. Methods and material for containment and cleaning up

Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Use spark-proof tools and explosion-proof equipment. Avoid contact with skin, eyes or clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

### Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

**Technical Rules for Hazardous Substances (TRGS) 510**  
**Storage Class (LGK) (Germany)**

Class 3

**Switzerland - Storage of hazardous substances**

Storage class - SC 3  
<https://www.kvu.ch/de/themen/stoffe-und-produkte>  
<https://www.kvu.ch/fr/themes/substances-et-produits>  
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

# SAFETY DATA SHEET

2-Butanone

Revision Date 22-Mar-2024

## 7.3. Specific end use(s)

Use in laboratories

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Methyl ethyl ketone	TWA: 200 ppm (8h) TWA: 600 mg/m <sup>3</sup> (8h) STEL: 300 ppm (15min) STEL: 900 mg/m <sup>3</sup> (15min)	STEL: 300 ppm 15 min STEL: 899 mg/m <sup>3</sup> 15 min TWA: 200 ppm 8 hr TWA: 600 mg/m <sup>3</sup> 8 hr Skin	TWA / VME: 200 ppm (8 heures). restrictive limit TWA / VME: 600 mg/m <sup>3</sup> (8 heures). restrictive limit STEL / VLCT: 300 ppm. restrictive limit STEL / VLCT: 900 mg/m <sup>3</sup> . restrictive limit Peau	TWA: 200 ppm 8 uren TWA: 600 mg/m <sup>3</sup> 8 uren STEL: 300 ppm 15 minuten STEL: 900 mg/m <sup>3</sup> 15 minuten	STEL / VLA-EC: 300 ppm (15 minutos). STEL / VLA-EC: 900 mg/m <sup>3</sup> (15 minutos). TWA / VLA-ED: 200 ppm (8 horas) TWA / VLA-ED: 600 mg/m <sup>3</sup> (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Methyl ethyl ketone	TWA: 200 ppm 8 ore. Time Weighted Average TWA: 600 mg/m <sup>3</sup> 8 ore. Time Weighted Average STEL: 300 ppm 15 minuti. Short-term STEL: 900 mg/m <sup>3</sup> 15 minuti. Short-term	TWA: 200 ppm (8 Stunden). AGW - exposure factor 1 TWA: 600 mg/m <sup>3</sup> (8 Stunden). AGW - exposure factor 1 TWA: 200 ppm (8 Stunden). MAK TWA: 600 mg/m <sup>3</sup> (8 Stunden). MAK Höhepunkt: 200 ppm Höhepunkt: 600 mg/m <sup>3</sup> Haut	STEL: 300 ppm 15 minutos STEL: 900 mg/m <sup>3</sup> 15 minutos TWA: 200 ppm 8 horas TWA: 600 mg/m <sup>3</sup> 8 horas	huid STEL: 900 mg/m <sup>3</sup> 15 minuten TWA: 590 mg/m <sup>3</sup> 8 uren	TWA: 20 ppm 8 tunteina TWA: 60 mg/m <sup>3</sup> 8 tunteina STEL: 100 ppm 15 minuutteina STEL: 300 mg/m <sup>3</sup> 15 minuutteina Iho

Component	Austria	Denmark	Switzerland	Poland	Norway
Methyl ethyl ketone	Haut MAK-KZGW: 200 ppm 15 Minuten MAK-KZGW: 590 mg/m <sup>3</sup> 15 Minuten MAK-TMW: 100 ppm 8 Stunden MAK-TMW: 295 mg/m <sup>3</sup> 8 Stunden	TWA: 50 ppm 8 timer TWA: 145 mg/m <sup>3</sup> 8 timer STEL: 900 mg/m <sup>3</sup> 15 minutter STEL: 300 ppm 15 minutter Hud	Haut/Peau STEL: 200 ppm 15 Minuten STEL: 590 mg/m <sup>3</sup> 15 Minuten TWA: 200 ppm 8 Stunden TWA: 590 mg/m <sup>3</sup> 8 Stunden	STEL: 900 mg/m <sup>3</sup> 15 minutach TWA: 450 mg/m <sup>3</sup> 8 godzinach	TWA: 75 ppm 8 timer TWA: 220 mg/m <sup>3</sup> 8 timer STEL: 112.5 ppm 15 minutter. value calculated STEL: 275 mg/m <sup>3</sup> 15 minutter. value calculated

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Methyl ethyl ketone	TWA: 590 mg/m <sup>3</sup> STEL : 885 mg/m <sup>3</sup>	TWA-GVI: 200 ppm 8 satima. TWA-GVI: 600 mg/m <sup>3</sup> 8 satima. STEL-KGVI: 300 ppm 15 minutama. STEL-KGVI: 900 mg/m <sup>3</sup> 15 minutama.	TWA: 200 ppm 8 hr. TWA: 600 mg/m <sup>3</sup> 8 hr. STEL: 300 ppm 15 min STEL: 900 mg/m <sup>3</sup> 15 min Skin	STEL: 300 ppm STEL: 900 mg/m <sup>3</sup> TWA: 200 ppm TWA: 600 mg/m <sup>3</sup>	TWA: 600 mg/m <sup>3</sup> 8 hodinách. Ceiling: 900 mg/m <sup>3</sup>

# SAFETY DATA SHEET

2-Butanone

Revision Date 22-Mar-2024

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Methyl ethyl ketone	TWA: 200 ppm 8 tundides. TWA: 600 mg/m <sup>3</sup> 8 tundides. STEL: 300 ppm 15 minutites. STEL: 900 mg/m <sup>3</sup> 15 minutites.	TWA: 200 ppm 8 hr TWA: 600 mg/m <sup>3</sup> 8 hr STEL: 300 ppm 15 min STEL: 900 mg/m <sup>3</sup> 15 min	STEL: 300 ppm STEL: 900 mg/m <sup>3</sup> TWA: 200 ppm TWA: 600 mg/m <sup>3</sup>	STEL: 900 mg/m <sup>3</sup> 15 percekben. CK TWA: 600 mg/m <sup>3</sup> 8 órában. AK lehetőség borön keresztüli felszívódás	STEL: 300 ppm STEL: 900 mg/m <sup>3</sup> TWA: 50 ppm 8 klukkustundum. TWA: 145 mg/m <sup>3</sup> 8 klukkustundum. Skin notation

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Methyl ethyl ketone	STEL: 300 ppm STEL: 900 mg/m <sup>3</sup> TWA: 67 ppm TWA: 200 mg/m <sup>3</sup>		TWA: 200 ppm 8 Stunden TWA: 600 mg/m <sup>3</sup> 8 Stunden STEL: 300 ppm 15 Minuten STEL: 900 mg/m <sup>3</sup> 15 Minuten	TWA: 200 ppm TWA: 600 mg/m <sup>3</sup> STEL: 300 ppm 15 minuti STEL: 900 mg/m <sup>3</sup> 15 minuti	TWA: 200 ppm 8 ore TWA: 600 mg/m <sup>3</sup> 8 ore STEL: 300 ppm 15 minute STEL: 900 mg/m <sup>3</sup> 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Methyl ethyl ketone	TWA: 200 mg/m <sup>3</sup> 0421 MAC: 400 mg/m <sup>3</sup>	Ceiling: 900 mg/m <sup>3</sup> TWA: 200 ppm TWA: 600 mg/m <sup>3</sup>	TWA: 200 ppm 8 urah TWA: 600 mg/m <sup>3</sup> 8 urah Koža STEL: 300 ppm 15 minutah STEL: 900 mg/m <sup>3</sup> 15 minutah	Binding STEL: 300 ppm 15 minuter Binding STEL: 900 mg/m <sup>3</sup> 15 minuter TLV: 50 ppm 8 timmar. NGV TLV: 150 mg/m <sup>3</sup> 8 timmar. NGV	TWA: 200 ppm 8 saat TWA: 600 mg/m <sup>3</sup> 8 saat STEL: 300 ppm 15 dakika STEL: 900 mg/m <sup>3</sup> 15 dakika

## Biological limit values

List source(s): **UK** - Biological Monitoring Guidance Values provided by the UK's Health and Safety Executive (HSE) Control of Substances Hazardous to Health Regulations (COSHH) 2002 (as amended) and EH40/2005.

Component	European Union	United Kingdom	France	Spain	Germany
Methyl ethyl ketone		Butan-2-one: 70 µmol/L urine post shift	Methylethylketone: 2 mg/L urine end of shift	Methyl ethyl ketone: 2 mg/L urine end of shift	2-Butanone: 2 mg/L urine (end of shift)

Component	Italy	Finland	Denmark	Bulgaria	Romania
Methyl ethyl ketone					Methylethylketone: 2 mg/L urine end of shift

## Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

## Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

Workers; See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Methyl ethyl ketone 78-93-3 ( <=100 )				DNEL = 1161mg/kg bw/day

Component	Acute effects local	Acute effects	Chronic effects local	Chronic effects
-----------	---------------------	---------------	-----------------------	-----------------

# SAFETY DATA SHEET

2-Butanone

Revision Date 22-Mar-2024

	(Inhalation)	systemic (Inhalation)	(Inhalation)	systemic (Inhalation)
Methyl ethyl ketone 78-93-3 ( ≤100 )				DNEL = 600mg/m <sup>3</sup>

## Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Methyl ethyl ketone 78-93-3 ( ≤100 )	PNEC = 55.8mg/L	PNEC = 284.74mg/kg sediment dw	PNEC = 55.8mg/L	PNEC = 709mg/L	PNEC = 22.5mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Methyl ethyl ketone 78-93-3 ( ≤100 )	PNEC = 55.8mg/L	PNEC = 284.7mg/kg sediment dw		PNEC = 1000mg/kg food	

## 8.2. Exposure controls

### Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

### Personal protective equipment

#### Eye Protection

Goggles (European standard - EN 166)

#### Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Butyl rubber	< 60 minutes	0.5 mm	Level 4 EN 374	Permeation rate 36 µg/cm <sup>2</sup> /min As tested under EN374-3 Determination of Resistance to Permeation by Chemicals

#### Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

#### Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

### Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

**Recommended Filter type:** Type A Organic gases and vapours filter Brown conforming to EN14387

### Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

**Recommended half mask:-** Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141

# SAFETY DATA SHEET

2-Butanone

Revision Date 22-Mar-2024

Environmental exposure controls No information available.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Colorless	
Odor	Characteristic - sweet	
Odor Threshold	No data available	
Melting Point/Range	-87 °C / -124.6 °F	
Softening Point	No data available	
Boiling Point/Range	80 °C / 176 °F	
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	<b>Lower</b> 1.8 Vol% <b>Upper</b> 11.5 Vol%	
Flash Point	-7 °C / 19.4 °F	<b>Method -</b> CC (closed cup)
Autoignition Temperature	404 °C / 759.2 °F	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	0.42 mPa.s @ 15°C	
Water Solubility	290 g/L (20°C)	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	<b>log Pow</b>	
Methyl ethyl ketone	0.29	
Vapor Pressure	105 mbar @ 20 °C	
Density / Specific Gravity	0.806	
Bulk Density	Not applicable	Liquid
Vapor Density	2.41	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

### 9.2. Other information

Molecular Formula	C4 H8 O
Molecular Weight	72.11
Explosive Properties	Not explosive Vapors may form explosive mixtures with air
Oxidizing Properties	Not oxidising
Evaporation Rate	3.7 - (Butyl Acetate = 1.0)

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

None known, based on information available

### 10.2. Chemical stability

Hygroscopic.

### 10.3. Possibility of hazardous reactions

Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

### 10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition. Exposure to moist air or water.



# SAFETY DATA SHEET

2-Butanone

Revision Date 22-Mar-2024

## 10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases. Strong reducing agents. Ammonia. copper. Amines.

## 10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Product Information

##### (a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl ethyl ketone	LD50 = 2483 mg/kg ( Rat )	LD50 = 5000 mg/kg ( Rabbit )	LC50 = 11700 ppm ( Rat ) 4 h

##### (b) skin corrosion/irritation;

Based on available data, the classification criteria are not met

##### (c) serious eye damage/irritation;

Category 2

##### (d) respiratory or skin sensitization;

Respiratory

Based on available data, the classification criteria are not met

Skin

Based on available data, the classification criteria are not met

##### (e) germ cell mutagenicity;

Based on available data, the classification criteria are not met

Not mutagenic in AMES Test

##### (f) carcinogenicity;

Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

##### (g) reproductive toxicity;

Based on available data, the classification criteria are not met

##### (h) STOT-single exposure;

Category 3

Results / Target organs

Central nervous system (CNS).

##### (i) STOT-repeated exposure;

Based on available data, the classification criteria are not met

Target Organs

None known.

##### (j) aspiration hazard;

Based on available data, the classification criteria are not met

**Symptoms / effects, both acute and delayed**

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

# SAFETY DATA SHEET

2-Butanone

Revision Date 22-Mar-2024

## 11.2. Information on other hazards

### Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health

Contains a substance on the National Authorities Endocrine Disruptor Lists

Component	EU National Authorities Endocrine Disruptor Lists - Health
Methyl ethyl ketone 78-93-3 ( <=100 )	List II

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

Ecotoxicity effects

Component	Freshwater Fish	Water Flea	Freshwater Algae
Methyl ethyl ketone	Lepomis macrochirus: LC50=3,22 g/L 96 h	EC50: = 5091 mg/L, 48h (Daphnia magna) EC50: 4025 - 6440 mg/L, 48h Static (Daphnia magna) EC50: > 520 mg/L, 48h (Daphnia magna)	

Component	Microtox	M-Factor
Methyl ethyl ketone	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	

### 12.2. Persistence and degradability

Persistence

Readily biodegradable  
Persistence is unlikely, based on information available.

Component	Degradability
Methyl ethyl ketone 78-93-3 ( <=100 )	98% (28d)

### 12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Methyl ethyl ketone	0.29	No data available

### 12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces Will likely be mobile in the environment due to its volatility. Disperses rapidly in air

### 12.5. Results of PBT and vPvB assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

### 12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

### 12.7. Other adverse effects Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance  
This product does not contain any known or suspected substance

# SAFETY DATA SHEET

2-Butanone

Revision Date 22-Mar-2024

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

<b>Waste from Residues/Unused Products</b>	Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.
<b>Contaminated Packaging</b>	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.
<b>European Waste Catalogue (EWC)</b>	According to the European Waste Catalog, Waste Codes are not product specific, but application specific.
<b>Other Information</b>	Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations.
<b>Switzerland - Waste Ordinance</b>	Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600 <a href="https://www.fedlex.admin.ch/eli/cc/2015/891/en">https://www.fedlex.admin.ch/eli/cc/2015/891/en</a>

## SECTION 14: TRANSPORT INFORMATION

### IMDG/IMO

<b>14.1. UN number</b>	UN1193
<b>14.2. UN proper shipping name</b>	Ethyl methyl ketone (Methyl ethyl ketone)
<b>14.3. Transport hazard class(es)</b>	3
<b>14.4. Packing group</b>	II

### ADR

<b>14.1. UN number</b>	UN1193
<b>14.2. UN proper shipping name</b>	Ethyl methyl ketone (Methyl ethyl ketone)
<b>14.3. Transport hazard class(es)</b>	3
<b>14.4. Packing group</b>	II

### IATA

<b>14.1. UN number</b>	UN1193
<b>14.2. UN proper shipping name</b>	Methyl ethyl ketone
<b>14.3. Transport hazard class(es)</b>	3
<b>14.4. Packing group</b>	II

<b>14.5. Environmental hazards</b>	No hazards identified
<b>14.6. Special precautions for user</b>	No special precautions required.
<b>14.7. Maritime transport in bulk according to IMO instruments</b>	Not applicable, packaged goods

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# SAFETY DATA SHEET

2-Butanone

Revision Date 22-Mar-2024

## International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Methyl ethyl ketone	78-93-3	201-159-0	-	-	X	X	KE-24094	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Methyl ethyl ketone	78-93-3	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

## Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methyl ethyl ketone	78-93-3	-	Use restricted. See item 75. (see link for restriction details)	-

## REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

## Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Methyl ethyl ketone	78-93-3	Not applicable	Not applicable

## Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

## Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

## National Regulations

**UK** - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

## WGK Classification

See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Methyl ethyl ketone	WGK1	

# SAFETY DATA SHEET

2-Butanone

Revision Date 22-Mar-2024

Component	France - INRS (Tables of occupational diseases)
Methyl ethyl ketone	Tableaux des maladies professionnelles (TMP) - RG 84

## Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Methyl ethyl ketone 78-93-3 ( <=100 )		Group I	

## 15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has been conducted by the manufacturer/importer

## SECTION 16: OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

EUH066 - Repeated exposure may cause skin dryness or cracking

### Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**NOEC** - No Observed Effect Concentration

**PBT** - Persistent, Bioaccumulative, Toxic

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer Predicted No Effect Concentration (PNEC)

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**POW** - Partition coefficient Octanol:Water

**vPvB** - very Persistent, very Bioaccumulative

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

### Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadviser - LOLI, Merck index, RTECS

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - (volatile organic compound)

## Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

# SAFETY DATA SHEET

2-Butanone

Revision Date 22-Mar-2024

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Prepared By	Health, Safety and Environmental Department
Creation Date	13-Apr-2009
Revision Date	22-Mar-2024
Revision Summary	New emergency telephone response service provider.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.  
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No  
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,  
Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and  
Preparations).**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**