

SAFETY DATA SHEET

Creation Date 08-February-2010 Revision Date 25-March-2024 Revision Number 3

1. Identification

Product Name Lithium Acetylide, Ethylene Diamine Complex

Cat No.: H36882

CAS-No 6867-30-7

Synonyms 1,2-Ethanediamine, compound with lithium acetylide (Li(C2H)) (1:1); Lithium acetylide

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Importer/Distributor

Fisher Scientific 112 Colonnade Road, Ottawa, ON K2E 7L6,

Canada

Tel: 1-800-234-7437

Emergency Telephone Number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

WHMIS 2015 Classification Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

Substances/mixtures which, in contact with water, emit Category 1 Gas(es) = Acetylene

flammable gases

Acute oral toxicity

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Specific target organ toxicity (single exposure)

Category 1

Category 1

Category 3

Target Organs - Respiratory system.

Physical Hazards Not Otherwise Classified Category 1

Reacts violently with water

Label Elements

Signal Word

Danger

Hazard Statements

In contact with water releases flammable gases which may ignite spontaneously Harmful if swallowed Causes severe skin burns and eye damage May cause respiratory irritation Reacts violently with water



Precautionary Statements

Prevention

Do not allow contact with water Keep container tightly closed

Do not breathe dust/fumes/gas/mist/vapours/spray

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection/face protection

Handle and store contents under inert gas. Protect from moisture

Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

IF INHALED: Remove person to fresh air and keep comfortable for breathing

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER/doctor

Rinse mouth

Do NOT induce vomiting

Wash contaminated clothing before reuse

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

IF ON SKIN: Brush off loose particles from skin. Immerse in cool water

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Store in a dry place. Store in a closed container

Disposal

Dispose of contents/container to an approved waste disposal plant

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
1,2-Ethanediamine, compound with lithium	6867-30-7	>80
acetylide (Li(C2H)) (1:1)		

4. First-aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required. Keep eye wide open while rinsing.

Skin Contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. Call a physician immediately.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Call a physician or poison

control center immediately. Do not use mouth-to-mouth method if victim ingested or inhaled

the substance; give artificial respiration with the aid of a pocket mask equipped with a

one-way valve or other proper respiratory medical device.

Ingestion Immediate medical attention is required. Do NOT induce vomiting. Drink plenty of water.

Never give anything by mouth to an unconscious person.

Most important symptoms/effects Causes burns by all exposure routes. Product is a corrosive material. Use of gastric

> lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue

and danger of perforation

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Limestone powder. Dry chemical.

DO NOT USE WATER, FOAM OR CO2 **Unsuitable Extinguishing Media**

Flash Point No information available No information available Method -

Autoignition Temperature

Explosion Limits

Upper

No data available No data available

No information available

Lower Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

The product causes burns of eyes, skin and mucous membranes. Reacts violently with water.

Hazardous Combustion Products

Acetylene. Lithium oxide. Nitrogen oxides (NOx). Carbon monoxide (CO). Carbon dioxide (CO2).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health **Flammability** Instability Physical hazards 3 3 2 W

Accidental release measures

Personal Precautions Use personal protective equipment as required. Evacuate personnel to safe areas. Avoid

contact with skin, eyes or clothing.

Should not be released into the environment. Do not allow material to contaminate ground **Environmental Precautions**

water system.

Methods for Containment and Clean Sweep up and shovel into suitable containers for disposal. Avoid dust formation. Do not expose spill to water. Up

7. Handling and storage Handling Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe dust. Do not ingest. If

swallowed then seek immediate medical assistance. Do not allow contact with water.

Storage.

Corrosives area. Flammables area. Keep away from heat, sparks and flame. Keep refrigerated. Store under an inert atmosphere. Keep away from water or moist air. Keep container tightly closed in a dry and well-ventilated place. Incompatible Materials. Acids. Alcohols. Carbon dioxide (CO2). Water. copper. Copper alloys. Oxidizing agent.

8. Exposure controls / personal protection

Exposure Guidelines

This product does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof

electrical/ventilating/lighting/equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles

Hand Protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Glove material	Breakthrough time	Glove thickness	Glove comments
Nitrile rubber	See manufacturers	-	Splash protection only
Neoprene	recommendations		
Natural rubber			
PVC			

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly **Recommended Filter type:** Particulates filter conforming to EN 143

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

No information available.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

9. Physical and chemical properties

Physical StateSolidAppearanceBeige

Odor Amine compounds
Odor Threshold No information available

pHNo information availableMelting Point/Range76 °C / 168.8 °FBoiling Point/Range110.6 °C / 231.1 °FFlash PointNo information availableEvaporation RateNot applicable

Flammability (solid,gas)

No information available

Flammability or explosive limits

UpperNo data availableLowerNo data availableVapor PressureNo information available

Vapor DensityNot applicableSpecific GravityNo information available

Solubility Reacts with water
Partition coefficient; n-octanol/water No data available

Autoignition Temperature No information available

Decomposition Temperature 40 °C

ViscosityNot applicableMolecular FormulaC4 H9 N2 LiMolecular Weight92.07

10. Stability and reactivity

Reactive Hazard Yes

Stability Reacts violently with water. heat sensitive. Moisture sensitive. Air sensitive.

Conditions to Avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition. Avoid dust formation. Exposure to moist air or water. Temperatures

above 40°C. Exposure to moisture.

Incompatible Materials Acids, Alcohols, Carbon dioxide (CO2), Water, copper, Copper alloys, Oxidizing agent

Hazardous Decomposition Products Acetylene, Lithium oxide, Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide

(CO₂)

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions Reacts violently with water.

11. Toxicological information

Acute Toxicity

Product Information

LD50 Oral VALUE 637-1850 mg/kg (rat)

Oral LD50 Category 4. ATE = 300 - 2000 mg/kg.

Dermal LD50 Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

Mist LC50 Based on ATE data, the classification criteria are not met. ATE > 5 mg/l.

Component Information

Toxicologically Synergistic No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Causes severe burns by all exposure routes

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
1.2-Ethanediamine.	6867-30-7	Not listed				

compound with lithium acetylide (Li(C2H)) (1:1)

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

Respiratory system STOT - single exposure STOT - repeated exposure None known

Aspiration hazard No information available

delayed

Symptoms / effects,both acute and Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes

severe swelling, severe damage to the delicate tissue and danger of perforation

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Do not empty into drains. .

Persistence and Degradability No information available

Bioaccumulation/ Accumulation No information available.

No information available. Mobility

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN3131 **UN-No**

Proper Shipping Name Water-reactive solid, corrosive, n.o.s.

Technical Name 1,2-Ethanediamine, compound with lithium acetylide (Li(C2H)) (1:1)

Hazard Class 4.3 **Subsidiary Hazard Class** 8 **Packing Group**

TDG

UN-No UN3131

Proper Shipping Name Water-reactive solid, corrosive, n.o.s.

Hazard Class 4.3 **Subsidiary Hazard Class** 8 **Packing Group**

IATA

UN-No

Proper Shipping Name Water-reactive solid, corrosive, n.o.s.

Hazard Class 4.3 **Subsidiary Hazard Class** 8 **Packing Group**

IMDG/IMO

UN-No UN3131

Proper Shipping Name Water-reactive solid, corrosive, n.o.s. Hazard Class 4.3

Subsidiary Hazard Class 8
Packing Group

15. Regulatory information

International Inventories

Component	CAS-No	DSL	NDSL	TSCA	TSCA Inventory notification - Active-Inactive	EINECS	ELINCS	NLP
1,2-Ethanediamine, compound with lithium acetylide (Li(C2H)) (1:1)	6867-30-7	1	X	Х	ACTIVE	229-967-9	1	-

Component	CAS-No	IECSC	KECL	ENCS	ISHL	TCSI	AICS	NZIoC	PICCS
1,2-Ethanediamine, compound	6867-30-7	-	-	-	Х	X	-	Х	Х
with lithium acetylide (Li(C2H))									
(1:1)									

Legend:

X - Listed '-' - Not Listed

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

Canada

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

Other International Regulations

Authorisation/Restrictions according to EU REACH

Not applicable

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS-No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
1,2-Ethanediamine, compound with lithium acetylide (Li(C2H)) (1:1)	6867-30-7	Not applicable	Not applicable	Not applicable	Not applicable

Component	CAS-No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	(2012/18/EC) -	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
1,2-Ethanediamine, compound with lithium acetylide (Li(C2H)) (1:1)	6867-30-7	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By Product Safety Department

Email: chem.techinfo@thermofisher.com

www.thermofisher.com

Creation Date08-February-2010Revision Date25-March-2024Print Date25-March-2024

Revision Summary New emergency telephone response service provider.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS