

# SAFETY DATA SHEET

Page 1/9 Creation Date 15-Apr-2009 Revision Date 24-Mar-2025

Version 2

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THECOMPANY/UNDERTAKING

Product Identifier

Perihalan Produk: Ethyl ether **Product Description:** Ethyl ether

E138-1; E138-20; E138-4; E138-4LC; E138-500; E138RS-19; E138RS-28; E138RS-50 Cat No.:

**Synonyms** Ethyl ether: Ether

**CAS No** 60-29-7 **Molecular Formula** C4 H10 O

Relevant identified uses of the substance or mixture and uses advised against

Laboratory chemicals. **Recommended Use** No Information available Uses advised against

Company Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd

> Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square, No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,

Selangor Darul Ehsan, Malaysia. Main line: +60 3-5525 7888

E-mail address Enquiry.my@thermofisher.com

Tel: +03-5525 7888 **Emergency Telephone Number** 

CHEMTREC Malaysia 1-800-815-308 (Malay)

CHEMTREC Malaysia (Kuala Lumpur) +(60)-327884561 (Malay)

# **SECTION 2: HAZARDS IDENTIFICATION**

### Classification of the substance or mixture

Flammable liquids	Category 1 (H224)
Acute oral toxicity	Category 4 (H302)
Specific target organ toxicity - (single exposure)	Category 3 (H336)

### Label Elements



Signal Word **Danger** 

**Hazard Statements** 

H224 - Extremely flammable liquid and vapor

### SAFETY DATA SHEET

Ethyl ether Revision Date 24-Mar-2025

H302 - Harmful if swallowed

H336 - May cause drowsiness or dizziness

#### **Precautionary Statements**

#### Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P240 - Ground and bond container and receiving equipment

P241 - Use explosion-proof electrical/ ventilating/ lighting equipment

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P264 - Wash face, hands and any exposed skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

#### Response

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P312 - Call a POISON CENTER or doctor if you feel unwell

P330 - Rinse mouth

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

#### Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

#### Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

#### Other Hazards

EUH019 - May form explosive peroxides

EUH066 - Repeated exposure may cause skin dryness or cracking

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS No	Weight %
Ethyl ether	60-29-7	<=100

# **SECTION 4: FIRST AID MEASURES**

Description of first aid measures

**General Advice** If symptoms persist, call a physician.

**Eye Contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

Clean mouth with water and drink afterwards plenty of water. Ingestion

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

Ethyl ether Revision Date 24-Mar-2025

protect themselves and prevent spread of contamination.

### Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

#### Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

### **SECTION 5: FIREFIGHTING MEASURES**

#### Extinguishing media

#### **Suitable Extinguishing Media**

CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

#### Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

#### Special hazards arising from the substance or mixture

Extremely flammable. Risk of ignition. Vapors may travel to source of ignition and flash back. Vapors may form explosive mixtures with air. Containers may explode when heated. May form explosive peroxides. Vapors may form explosive mixtures with air.

#### **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO2), peroxides.

### Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### Personal Precautions, Protective Equipment and Emergency Procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

### **Environmental precautions**

Should not be released into the environment. See Section 12 for additional Ecological Information.

### Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

#### Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

### **SECTION 7: HANDLING AND STORAGE**

#### Precautions for Safe Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid

Ethyl ether Revision Date 24-Mar-2025

ingestion and inhalation. If peroxide formation is suspected, do not open or move container. Keep away from open flames, hot surfaces and sources of ignition. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

#### Conditions for Safe Storage, Including any Incompatibilities

Flammables area. Store under an inert atmosphere. Keep away from open flames, hot surfaces and sources of ignition. May form explosive peroxides. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Keep away from heat, sparks and flame. Keep container tightly closed in a dry and well-ventilated place. Protect from moisture.

### Specific End Uses

Use in laboratories.

### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### **Control Parameters**

Component	Malaysia	ACGIH TLV	OSHA PEL
Ethyl ether		TWA: 400 ppm	(Vacated) TWA: 400 ppm
		STEL: 500 ppm	(Vacated) TWA: 1200 mg/m <sup>3</sup>
			(Vacated) STEL: 500 ppm
			(Vacated) STEL: 1500 mg/m <sup>3</sup>
			TWA: 400 ppm
			TWA: 1200 mg/m <sup>3</sup>

Component	European Union	The United Kingdom	Germany
Ethyl ether	TWA: 100 ppm (8h)	STEL: 200 ppm 15 min	TWA: 400 ppm (8 Stunden). AGW -
	TWA: 308 mg/m <sup>3</sup> (8h)	STEL: 620 mg/m <sup>3</sup> 15 min	exposure factor 1
	STEL: 200 ppm (15min)	TWA: 100 ppm 8 hr	TWA: 1200 mg/m³ (8 Stunden).
	STEL: 616 mg/m <sup>3</sup> (15min)	TWA: 310 mg/m <sup>3</sup> 8 hr	AGW - exposure factor 1
		_	TWA: 400 ppm (8 Stunden). MAK
			TWA: 1200 mg/m³ (8 Stunden).
			MAK
			Höhepunkt: 400 ppm
			Höhepunkt: 1200 mg/m <sup>3</sup>

#### **Exposure Controls**

### **Engineering Measures**

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

#### Personal protective equipment

**Eye Protection** Wear safety glasses with side shields (or goggles)

Hand Protection Protective gloves

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure

### Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

\_\_\_\_\_

Ethyl ether Revision Date 24-Mar-2025

**Respiratory Protection** When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

When RPE is used a face piece Fit Test should be conducted

<u>Hygiene Measures</u> Handle in accordance with good industrial hygiene and safety practice

Environmental exposure controls No information available

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Information on basic physical and chemical properties

Appearance Colorless
Physical State Liquid
Odor aromatic

Odor Threshold No data available No information available

Melting Point/Range-116 °C / -176.8 °FSoftening PointNo data availableBoiling Point/Range34.6 °C / 94.3 °FFlash Point-45 °C / -49 °F

Flash Point -45 °C / -49 °F Method - No information available

Evaporation Rate 37.5 (Butyl Acetate = 1.0)

Flammability (solid,gas)

Not applicable

Liquid

Explosion Limits Lower 1.7 vol % Upper 48 vol %

Vapor Pressure 587 mbar @ 20 °C

Vapor Density 2.55 (Air = 1.0)

Specific Gravity / Density 0.714

Bulk Density Not applicable Liquid

Water Solubility 69 g/L (20°C)

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Componentlog PowEthyl ether0.82

Autoignition Temperature 160 °C / 320 °F Decomposition Temperature No data available

Viscosity 0.2448 cP at 20 °C Explosive Properties

**Explosive Properties**Vapors may form explosive mixtures with air

Oxidizing Properties
No information available

Molecular FormulaC4 H10 OMolecular Weight74.12

Ethyl ether Revision Date 24-Mar-2025

### **SECTION 10: STABILITY AND REACTIVITY**

Reactivity

Yes.

Chemical Stability

May form explosive peroxides. Air sensitive. Light sensitive. Hygroscopic.

Possibility of Hazardous Reactions

Hazardous Polymerization Hazardous Reactions

Hazardous polymerization does not occur.

None under normal processing.

**Conditions to Avoid** 

Incompatible products. Heat, flames and sparks. Exposure to air. Exposure to light. Exposure to moisture. Keep away from open flames, hot surfaces and sources of ignition.

Exposure to moist air or water.

Incompatible Materials

Strong oxidizing agents. Strong acids.

**Hazardous Decomposition Products** 

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). peroxides.

### **SECTION 11: TOXICOLOGICAL INFORMATION**

### Information on Toxicological Effects

### **Product Information**

(a) acute toxicity;

Oral Category 4

DermalBased on available data, the classification criteria are not metInhalationBased on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	
Ethyl ether	Ethyl ether 1215 mg/kg (Rat)		32000 ppm (Rat) 4 h	

(b) skin corrosion/irritation; Based on available data, the classification criteria are not met

(c) serious eye damage/irritation; Based on available data, the classification criteria are not met

(d) respiratory or skin sensitization;

**Respiratory**Skin
Based on available data, the classification criteria are not met
Based on available data, the classification criteria are not met

### SAFETY DATA SHEET

Ethyl ether Revision Date 24-Mar-2025

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

Mutagenic effects have occurred in experimental animals

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Based on available data, the classification criteria are not met

(h) STOT-single exposure; Category 3

Results / Target organs Central nervous system (CNS).

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

None known. **Target Organs** 

(j) aspiration hazard; Based on available data, the classification criteria are not met

delayed

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

Assess endocrine disrupting properties for human health. This product does not contain any **Endocrine Disrupting Properties** 

known or suspected endocrine disruptors.

### **SECTION 12: ECOLOGICAL INFORMATION**

**Ecotoxicity effects** Do not empty into drains. .

L	Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
	Ethyl ether	LC50: > 10000 mg/L,	EC50 = 165 mg/L/24h		EC50 = 5600 mg/L 15
		96h static (Lepomis macrochirus)			min
		LC50: = 2560 mg/L, 96h			
		flow-through			
1		(Pimephales promelas)			
L					

Persistence and degradability

**Persistence** 

Persistence is unlikely, based on information available.

Bioaccumulative potential Bioaccumulation is unlikely

İ	Component	log Pow	Bioconcentration factor (BCF)
	Ethyl ether	0.82	No data available

The product contains volatile organic compounds (VOC) which will evaporate easily from all Mobility in soil

surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors

Other adverse effects No information available Ethyl ether Revision Date 24-Mar-2025

# **SECTION 13: DISPOSAL CONSIDERATIONS**

Waste treatment methods Waste from Residues/Unused

**Products** 

Waste is classified as hazardous Dispose of in accordance with the European Directives on

waste and hazardous waste Dispose of in accordance with local regulations

Dispose of this container to hazardous or special waste collection point. Empty containers **Contaminated Packaging** 

retain product residue, (liquid and/or vapor), and can be dangerous Keep product and

empty container away from heat and sources of ignition

Other Information Waste codes should be assigned by the user based on the application for which the product

was used Do not flush to sewer Can be landfilled or incinerated, when in compliance with

local regulations

# **SECTION 14: TRANSPORT INFORMATION**

IMDG/IMO

**UN-No** UN1155 **Hazard Class** 3 **Packing Group** 

**Proper Shipping Name** Diethyl ether

Road and Rail Transport

UN-No UN1155 **Hazard Class** 3 **Packing Group** 

**Proper Shipping Name** Diethyl ether

IATA

UN-No UN1155 **Hazard Class** 3 **Packing Group** 

**Proper Shipping Name** Diethyl ether

**Special Precautions for User** No special precautions required

### **SECTION 15: REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories X = listed

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Ethyl ether	200-467-2	X	X	Х	X	X	Χ	Χ	KE-27690

Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Ethyl ether				Annex I - Y40 Annex I - Y42

Ethyl ether Revision Date 24-Mar-2025

**National Regulations** 

**Persistent Organic Pollutant Ozone Depletion Potential** 

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

Substances List

### **SECTION 16: OTHER INFORMATION**

#### Legend

**CAS** - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances **ENCS** - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50% POW - Partition coefficient Octanol:Water TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from

Shins

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

#### Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

**Revision Date** 24-Mar-2025

SDS sections updated. **Revision Summary** 

In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

# **End of Safety Data Sheet**