

Australian statement of hazardous nature : Classified as hazardous according to criteria of Safe Work Australia

Section 1 - Identification

Product Name

Reconditioning kit for all NanoDrop models

Product Code

NDTPR1-KIT

Address

ThermoFisher Scientific Australia Pty Ltd
 5 Caribbean Drive, Scoresby
 VICTORIA 3179, Australia

Emergency Tel.

CHEMTREC®
03 9757 4559 or +613 9757 4559

Telephone / Fax Numbers

Tel: 1300 735 292
 Fax: 1800 067 639

E-mail address

ANZinfo@thermofisher.com

Recommended Use

Laboratory chemicals.

Uses advised against

This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list. This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction. This product contains one or more substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern.

Section 2 - Hazard(s) Identification

Classification under Safe Work Australia

Classified as hazardous according to criteria of Safe Work Australia

Physical hazards

No hazards identified

Health hazards

Aspiration Toxicity
 Skin Corrosion/Irritation
 Serious Eye Damage/Eye Irritation
 Specific target organ toxicity - (repeated exposure)

Category 1
 Category 2
 Category 2
 Category 1

Environmental hazards

No hazards identified

Label Elements



Health Hazard



Exclamation Mark

Signal Word

Danger

Hazard Statements

H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary Statements

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P260 - Do not breathe dust/fume/gas/mist/vapors/spray
P264 - Wash face, hands and any exposed skin thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P280 - Wear eye protection/ face protection
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308 + P313 - IF exposed or concerned: Get medical advice/attention
P331 - Do NOT induce vomiting
P332 + P313 - If skin irritation occurs: Get medical advice/attention
P362 + P364 - Take off contaminated clothing and wash it before reuse
P403 - Store in a well-ventilated place
P501 - Dispose of contents/ container to an approved waste disposal plant

Other information

This product does not contain any known or suspected endocrine disruptors

Section 3 - Composition and Information on Ingredients

Component	CAS No	Weight %
Petroleum distillates, hydrotreated light	64742-47-8	25-50
Aluminum oxide	1344-28-1	25-50
Triethanolamine	102-71-6	<10
Tall oil fatty acids	61790-12-3	<10
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	<10
Hexylene glycol	107-41-5	<10

Section 4 - First Aid Measures

Inhalation	Risk of serious damage to the lungs (by aspiration).
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

First Aid Facilities Eyewash, safety shower and washroom.

Most important symptoms and effects No information available.

Notes to Physician Treat symptomatically.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media

Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

Specific Hazards Arising from the Chemical

Combustible material. Containers may explode when heated.

Special protective equipment and precautions for fire fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6 - Accidental Release Measures

Emergency procedures

Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

See Section 12 for additional Ecological Information. Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Up

Clean-up methods - small spillage

Remove all sources of ignition.

Clean-up methods - large spillage

Typically only supplied in small quantities as packaged goods.

If extremely toxic or used in larger quantities ensure a spillage action plan is in place. Evacuate area. Control the source and/or contain the spill if safe and able to do so. Use temporary diking, sand bags, dry sand, earth or proprietary booms/absorbent pads if available. Obtain advice on containment, neutralisation and clean-up from local emergency responders.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

Section 7 - Handling and Storage

Precautions for Safe Handling

Keep away from open flames, hot surfaces and sources of ignition.

Conditions for Safe Storage, Including any Incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame.

AS/NZS 2243.10:2004, Safety in laboratories - Storage of chemicals

AS 1940-2004 - The storage and handling of flammable and combustible liquids

Section 8 - Exposure Controls and Personal Protection

Exposure limits

AUS - Exposure Standards for Atmospheric Contaminants in the Occupational Environment - Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:3008(1995)]

Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)] updated in August, 2005. Safe Work Australia

ACGIH - Threshold Limit Values - Ceiling (TLV-C) guidelines by the American Conference of Governmental Industrial Hygienists (ACGIH) for controlling worker exposure to airborne chemical concentrations in the workplace.

UK - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020.

DE - MAK and BAT values of Hazardous Chemical Compounds in the Work Area. Published by German Research Foundation on July 1, 2011

NZ - Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor

Component	Australia	New Zealand WEL	ACGIH TLV	The United Kingdom	Germany
Petroleum distillates, hydrotreated light					TWA: (8 Stunden). AGW - TWA: 5 mg/m ³ (8 Stunden). MAK aerosols TWA: 50 ppm (8 Stunden). MAK vapor TWA: 350 mg/m ³ (8 Stunden). MAK vapor Höhepunkt: 20 mg/m ³ Höhepunkt: 100 ppm Höhepunkt: 700 mg/m ³
Aluminum oxide	TWA: 10 mg/m ³	TWA: 10 mg/m ³	TWA: 1 mg/m ³	STEL: 30 mg/m ³ 15 min STEL: 12 mg/m ³ 15 min TWA: 10 mg/m ³ 8 hr TWA: 4 mg/m ³ 8 hr	TWA: 1.25 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 10 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 4 mg/m ³ (8 Stunden). MAK TWA: 1.5 mg/m ³ (8 Stunden). MAK
Triethanolamine	TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³		TWA: 1 mg/m ³ (8 Stunden). AGW - exposure factor 1 TWA: 1 mg/m ³ (8 Stunden). MAK can occur as vapor and aerosol at the same time Höhepunkt: 1 mg/m ³
Hexylene glycol		Ceiling: 25 ppm Ceiling: 121 mg/m ³	TWA: 25 ppm STEL: 50 ppm STEL: 10 mg/m ³	STEL: 25 ppm 15 min STEL: 123 mg/m ³ 15 min TWA: 25 ppm 8 hr TWA: 123 mg/m ³ 8 hr	TWA: 10 ppm (8 Stunden). MAK can occur as vapor and aerosol at the same time TWA: 49 mg/m ³ (8 Stunden). MAK can occur as vapor and aerosol at the same time Höhepunkt: 20 ppm Höhepunkt: 98 mg/m ³

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Exposure Controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment**Eye Protection**

Goggles (Australian/New Zealand Standard AS/NZS 1337 - Eye protectors for Industrial applications)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	AUS/NZ Standard	Glove comments
Disposable gloves	See manufacturers recommendations	-	AS/NZS 2161	(minimum requirement)

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection

Long sleeved clothing

Respiratory Protection

Use an AS/NZS 1716 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained in line with AS/NZS 1715 on the use and maintenance of respiratory protective devices (or AUS/NZ equivalent)
When RPE is used a face piece Fit Test should be conducted

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	White	
Physical State	Solid	
Odor	No information available	
Odor Threshold	No data available	
pH	No information available	
Melting Point/Range	55 °C / 131 °F	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flash Point	90 °C / 194 °F	Method - No information available
Evaporation Rate	Not applicable	Solid
Flammability (solid,gas)	No information available	
Explosion Limits	No data available	
Vapor Pressure	No data available	
Vapor Density	Not applicable	Solid
Specific Gravity / Density	No data available	
Bulk Density	No data available	
Water Solubility	No information available	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Triethanolamine	-2.53	

Tall oil fatty acids	5.98	
Hexylene glycol	0.14	
Autoignition Temperature	Not applicable	
Decomposition Temperature	No data available	
Viscosity	Not applicable	Solid
Explosive Properties		explosive air/vapour mixtures possible
Oxidizing Properties	No information available	

Other information**Section 10 - Stability and Reactivity**

Reactivity	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	None known.
Hazardous Decomposition Products	None under normal use conditions.
Hazardous Polymerization	No information available.

Section 11 - Toxicological Information

Information on Toxicological Effects

Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Petroleum distillates, hydrotreated light	LD50 > 5000 mg/kg (Rat)	LD50 > 2000 mg/kg (Rabbit)	LC50 > 5.2 mg/L (Rat) 4 h
Aluminum oxide	> 5000 mg/kg (Rat) (OECD Guideline 401)		> 2.3 mg/l 4 h (OECD Guideline 403)
Triethanolamine	LD50 = 4190 mg/kg (Rat)	>16 mL/kg (Rat) >2000 mg/kg (Rabbit)	
Tall oil fatty acids	LD50 > 10000 mg/kg (Rat)		
Solvent naphtha (petroleum), medium aliphatic	LD50 > 25 mL/kg (Rat)	LD50 > 4000 mg/kg (Rabbit)	LC50 > 5.28 mg/L (Rat) 4 h
Hexylene glycol	LD50 = 3700 mg/kg (Rat)	LD50 = 12300 mg/kg (Rabbit)	LC50 > 310 mg/m ³ (Rat) 1 h

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	Australia	New Zealand	New South Wales	Western Australia	IARC	EU	UK	Germany
Aluminum oxide								Cat. 2 (Fibre dust)

(g) reproductive toxicity; No data available

(h) STOT-single exposure; No data available

(i) STOT-repeated exposure; Category 1

Target Organs No information available.

(j) aspiration hazard; Category 1

Symptoms / effects, both acute and delayed No information available

Section 12 - Ecological Information

Ecotoxicity effects

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Petroleum distillates, hydrotreated light	LC50: = 2.4 mg/L, 96h static (Oncorhynchus mykiss) LC50: = 2.2 mg/L, 96h static (Lepomis macrochirus) LC50: = 45 mg/L, 96h flow-through (Pimephales promelas)			
Triethanolamine	LC50: 10600 - 13000 mg/L, 96h flow-through (Pimephales promelas) LC50: > 1000 mg/L, 96h static (Pimephales promelas) LC50: 450 - 1000 mg/L, 96h static (Lepomis macrochirus)		EC50: = 169 mg/L, 96h (Desmodesmus subspicatus) EC50: = 216 mg/L, 72h (Desmodesmus subspicatus)	EC50 > 10000 mg/L 30 min
Tall oil fatty acids			EC50: >= 1000 mg/L, 72h (Pseudokirchneriella subcapitata)	
Solvent naphtha (petroleum), medium aliphatic	LC50: = 800 mg/L, 96h static (Pimephales promelas)	EC50: > 100 mg/L, 48h (Daphnia magna)	EC50: = 450 mg/L, 96h (Pseudokirchneriella subcapitata)	
Hexylene glycol	LC50: 10500 - 11000 mg/L, 96h flow-through (Pimephales promelas) LC50: = 10000 mg/L,	EC50: 2700 - 3700 mg/L, 48h (Daphnia magna)		EC50 = 3038 mg/L 5 min

	96h static (Lepomis macrochirus) LC50: = 8690 mg/L, 96h flow-through (Pimephales promelas) LC50: = 10700 mg/L, 96h static (Pimephales promelas)			
--	---	--	--	--

Persistence and Degradability**Degradation in sewage****treatment plant****Bioaccumulative Potential**

No information available

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

No information available

Component	log Pow	Bioconcentration factor (BCF)
Petroleum distillates, hydrotreated light		61 - 159 dimensionless
Triethanolamine	-2.53	<3.9 dimensionless
Tall oil fatty acids	5.98	No data available
Hexylene glycol	0.14	No data available

Mobility

No information available.

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

Persistent Organic Pollutant

This product does not contain any known or suspected substance

Ozone Depletion Potential

This product does not contain any known or suspected substance

Section 13 - Disposal Considerations

Waste from Residues/Unused Products

Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure conformity with all applicable regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point.

Other Information

Chemical wastes should be disposed through a licensed commercial waste collection service. Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Do not empty into drains.

Section 14 - Transport Information

IMDG/IMO

Not regulated

ADG

Not regulated

IATA

Not regulated

Environmental hazards

No hazards identified

Special Precautions

No special precautions required

Additional information

None known

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations**Australia**

See section 8 for national exposure control parameters.

Standard for the Uniform Scheduling of Medicines and Poisons

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons.

Component	Standard for the Uniform Scheduling of Medicines and Poisons
Petroleum distillates, hydrotreated light - 64742-47-8	Schedule 5 listed - including Kerosene, Diesel [distillate], Mineral turpentine, White petroleum spirit, Toluene, Xylene and light mineral and paraffin oils but except their derivative; except a) Toluene and Xylene when included in Schedule 6, b) Benzene and liquid aromatic hydrocarbons when included in Schedule 7, c) food grade and pharmaceutical grade White mineral oil, d) in solid or semi-solid preparations, e) in preparations containing $\leq 25\%$ of designated solvents, f) in preparations packed in pressurized spray packs, g) in adhesives packed in containers each containing ≤ 50 grams of adhesive, h) in writing correction fluids and thinners for writing correction fluids packed in containers having a capacity of ≤ 20 mL, or i) in other preparations when packed in containers with a capacity of ≤ 2 mL
Triethanolamine - 102-71-6	Schedule 4 listed - when in preparations for tattoo removal Schedule 5 listed - except its salts and derivatives; except when in Schedule 4 or in preparations containing $\leq 5\%$ of Trolamine Schedule 5 listed - for use as curing agents for Epoxy resins except when separately specified in these Schedules

Australian Industrial Chemicals Introduction Scheme (AICIS)

Component	Australian Industrial Chemicals Introduction Scheme (AICIS)	Additional information
Petroleum distillates, hydrotreated light - 64742-47-8	Present	-
Aluminum oxide - 1344-28-1	Present	-
Triethanolamine - 102-71-6	Present	-
Tall oil fatty acids - 61790-12-3	Present	-
Solvent naphtha (petroleum), medium aliphatic - 64742-88-7	Present	-
Hexylene glycol - 107-41-5	Present	-

Australian - Illicit Drug Precursors/Reagents Substance List

This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list.

Chemicals of Security Concern

This product contains one or more substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern

Component	Australian - Illicit Drug Precursors/Reagents Substance List	Chemicals of Security Concern
Triethanolamine - 102-71-6		Listed in Appendix A

Legend

Chemicals of Security Concern - for further information see <http://www.chemicalsecurity.gov.au/securityconcerns>

National pollutant inventory Not applicable

Prohibition or notification/licensing requirements

Shown below are details of specific prohibition/notifications or licensing requirements when they apply.

This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction.

International Inventories

Component	AICS	NZIoC	EINECS	ELINCS	TSCA	DSL	NDL	PICCS	ENCS	ISHL	IECSC	KECL
Petroleum distillates, hydrotreated light	X	X	265-149-8	-	X	X	-	X	-		X	KE-12550
Aluminum oxide	X	X	215-691-6	-	X	X	-	X	X	X	X	KE-01012
Triethanolamine	X	X	203-049-8	-	X	X	-	X	X	X	X	KE-25940
Tall oil fatty acids	X	X	263-107-3	-	X	X	-	X	X	X	X	KE-32785
Solvent naphtha (petroleum), medium aliphatic	X	X	265-191-7	-	X	X	-	X	-		X	KE-31664
Hexylene glycol	X	X	203-489-0	-	X	X	-	X	X	X	X	KE-24702

Legend: X - Listed. '-' - Not Listed. **KECL** - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

International Regulations

Ozone Depletion Potential This product does not contain any known or suspected substance

Persistent Organic Pollutant This product does not contain any known or suspected substance

Rotterdam Convention (PIC) Not applicable

Basel convention on the control of transboundary movements of hazardous wastes and their disposal
Not applicable.

Component	CAS No	OECD HPV	Restriction of Hazardous Substances (RoHS)	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Petroleum distillates, hydrotreated light	64742-47-8	Listed	Not applicable	Not applicable	Not applicable
Aluminum oxide	1344-28-1	Listed	Not applicable	Not applicable	Not applicable
Triethanolamine	102-71-6	Listed	Not applicable	Not applicable	Not applicable
Tall oil fatty acids	61790-12-3	Listed	Not applicable	Not applicable	Not applicable
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	Listed	Not applicable	Not applicable	Not applicable
Hexylene glycol	107-41-5	Listed	Not applicable	Not applicable	Not applicable

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Hexylene glycol	-	Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

Section 16 - Other Information

Legend

AICS - Australian Inventory of Chemical Substances TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List IECSC - Chinese Inventory of Existing Chemical Substances PICCS - Philippines Inventory of Chemicals and Chemical Substances TWA - Time Weighted Average IARC - International Agency for Research on Cancer ICAO/IATA - International Civil Aviation Organization/International Air Transport Association MARPOL - International Convention for the Prevention of Pollution from Ships NZS 5433:2020 - Transport of Dangerous Goods on Land LD50 - Lethal Dose 50% EC50 - Effective Concentration 50% WEL - Workplace Exposure Limit DNEL - Derived No Effect Level POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative VOC - (Volatile Organic Compound)	NZIoC - New Zealand Inventory of Chemicals EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances ENCS - Japanese Existing and New Chemical Substances KECL - Korean Existing and Evaluated Chemical Substances CAS - Chemical Abstracts Service ACGIH - American Conference of Governmental Industrial Hygienists Predicted No Effect Concentration (PNEC) IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code ADG - Australian Code for the Transport of Dangerous Goods by Road and Rail OECD - Organisation for Economic Co-operation and Development LC50 - Lethal Concentration 50% ATE - Acute Toxicity Estimate RPE - Respiratory Protective Equipment NOEC - No Observed Effect Concentration BCF - Bioconcentration factor PBT - Persistent, Bioaccumulative, Toxic
--	---

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>
Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health Hazards	Calculation method
Environmental hazards	Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Revision Date	14-Jul-2023
Revision Summary	Update to GHS format.

This Safety Data Sheet (SDS) is prepared in accordance to and complies with the requirements of Safe Work Australia - Work Health and Safety Regulations (WHS Regulations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet