Thermo Fisher SCIENTIFIC

SAFETY DATA SHEET

Page 1 / 9 Creation Date 28-Apr-2011 Revision Date 15-Apr-2025 Version 5

FSUH0408

IsoHexane (contains <5% n-Hexane)

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

产品说明: 石油醚, 己烷支链异构体<5%

Product Description: IsoHexane (contains <5% n-Hexane)

Cat No.: H/0408/15, H/0408/17

 CAS No
 73513-42-5

 Molecular Formula
 C6 H14

Supplier UK entity/business name

Fisher Scientific UK

Bishop Meadow Road, Loughborough, Leicestershire LE11 5RG, United Kingdom

EU entity/business name Thermo Fisher Scientific Janssen Pharmaceuticalaan 3a

2440 Geel, Belgium

Emergency Telephone Number Tel: 01509 231166

Chemtrec US: (800) 424-9300 Chemtrec EU: 001-703-527-3887

E-mail address begel.sdsdesk@thermofisher.com

Recommended Use Laboratory chemicals.
Uses advised against No Information available

SECTION 2. HAZARD IDENTIFICATION

Physical StateAppearanceOdorLiquidColorlessSlight

Emergency Overview

Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. May be harmful in contact with skin. Causes skin irritation. May cause drowsiness and dizziness. Toxic to aquatic life with long lasting effects.

Classification of the substance or mixture

Flammable liquids.	Category 2
Aspiration Toxicity	Category 1
Acute Dermal Toxicity	Category 5
Skin Corrosion/Irritation	Category 2
Specific target organ toxicity - (single exposure)	Category 3
Chronic aquatic toxicity	Category 2

Label Elements

Page 2/9 Revision Date 15-Apr-2025

IsoHexane (contains <5% n-Hexane)



Signal Word

Danger

Hazard Statements

- H225 Highly flammable liquid and vapor
- H304 May be fatal if swallowed and enters airways
- H313 May be harmful in contact with skin
- H315 Causes skin irritation
- H336 May cause drowsiness or dizziness
- H411 Toxic to aquatic life with long lasting effects

Precautionary Statements

Prevention

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P240 Ground and bond container and receiving equipment
- P241 Use explosion-proof electrical/ ventilating/ lighting equipment
- P242 Use non-sparking tools
- P243 Take action to prevent static discharges
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P264 Wash face, hands and any exposed skin thoroughly after handling
- P271 Use only outdoors or in a well-ventilated area
- P280 Wear protective gloves/protective clothing/eye protection/face protection

Response

- P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor
- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P312 Call a POISON CENTER or doctor if you feel unwell
- P331 Do NOT induce vomiting
- P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
- P362 + P364 Take off contaminated clothing and wash it before reuse

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Physical and Chemical Hazards

Highly flammable. Vapors may cause flash fire or explosion.

Health Hazards

Aspiration hazard if swallowed - can enter lungs and cause damage. May be harmful in contact with skin. Causes skin irritation. May cause drowsiness or dizziness.

Environmental hazards

Toxic to aquatic life with long lasting effects. Will likely be mobile in the environment due to its volatility. The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

Other Hazards

This product does not contain any known or suspected endocrine disruptors.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Hydrocarbons, C6, isoalkanes < 5% n-hexane (Iso-Hexane)	64742-49-0	> 95
Hexane, mixed isomers	73513-42-5	-

IsoHexane (contains <5% n-Hexane)

Page 3/9 Revision Date 15-Apr-2025

Note

REACH UVCB Hydrocarbons C6, isoalkanes, < 5% n-Hexane Contains CAS 73513-42-5 (Iso-Hexane)

SECTION 4. FIRST AID MEASURES

General Advice

If symptoms persist, call a physician.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

Inhalation

Remove to fresh air. If breathing is difficult, give oxygen. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).

Ingestion

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.

Most important symptoms and effects

Difficulty in breathing. . Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Self-Protection of the First Aider

Use personal protective equipment as required.

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Water may be ineffective. Do not use a solid water stream as it may scatter and spread fire.

Specific Hazards Arising from the Chemical

Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition. Extremely flammable.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information. Avoid release to the

Page 4/9 Revision Date 15-Apr-2025

IsoHexane (contains <5% n-Hexane)

environment. Collect spillage.

Methods for Containment and Clean Up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges.

Refer to protective measures listed in Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment.

Storage

Keep in a dry, cool and well-ventilated place. Keep container tightly closed. Keep away from heat, sparks and flame. Flammables area. Keep containers tightly closed in a cool, well-ventilated place. Keep in properly labeled containers. Keep container tightly closed in a dry and well-ventilated place.

Specific Use(s)

Use in laboratories

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	China	Taiwan	Thailand	Hong Kong
Hexane, mixed isomers	=	=		TWA: 500 ppm
				TWA: 1760 mg/m ³
				STEL: 1000 ppm
				STEL: 3500 mg/m ³

Component	ACGIH TLV	OSHA PEL	NIOSH	The United Kingdom	European Union
Hydrocarbons, C6,				RCP Isohexanes,	
isoalkanes < 5% n-hexane				TWA (8 h) 250 ppm,	
(Iso-Hexane)				1000 mg/m ³	
Hexane, mixed isomers	TWA: 500 ppm		REL = 100 ppm (TWA)	-	
	STEL: 1000 ppm		REL = 350 mg/m ³		
			(TWA)		
			Ceiling: 510 ppm		
			Ceiling: 1800 mg/m ³		

Legend

ACGIH - American Conference of Governmental Industrial Hygienists NIOSH: NIOSH - National Institute for Occupational Safety and Health

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. MDHS70 General methods for sampling airborne gases and vapours MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Exposure Controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas. Use spark-proof tools and explosion-proof equipment. Wherever possible, engineering control measures such as the isolation or enclosure of the process,

Page 5/9 Revision Date 15-Apr-2025

IsoHexane (contains <5% n-Hexane)

the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation

Personal protective equipment

Eye Protection Wear safety glasses with side shields (or goggles) (European standard - EN 166)

Hand Protection Protective gloves

systems, should be adopted to control hazardous materials at source.

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	> 480 minutes	0.38 mm	Level 6	As tested under EN374-3 Determination of
Viton (R)	> 480 minutes	0.35 mm	EN 374	Resistance to Permeation by Chemicals
Neoprene gloves	< 45 minutes	0.45 mm		-

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion

Remove gloves with care avoiding skin contamination.

Skin and body protection Long sleeved clothing

Respiratory ProtectionNo protective equipment is needed under normal use conditions.

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to

EN371

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

141

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water

system.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Colorless Physical State Liquid

Odor Slight

Odor Threshold
PH
No data available
No information available
No information available
No information available
-154 °C / -245.2 °F

Softening Point No data available
Boiling Point/Range 48 - 70 °C / 118.4 - 158 °F

Flash Point -33 °C / -27.4 °F Method - No information available

Evaporation Rate 13 (Butyl acetate = 1.0)

Flammability (solid,gas) Not applicable Liquid

 Explosion Limits
 Lower 1.0 vol%

 Upper 7.4 vol%

 Vapor Pressure
 23 hPa @ 20 °C

Vapor Density > 1 (Air = 1.0)

Specific Gravity / Density 0.660

Page 6/9 Revision Date 15-Apr-2025

IsoHexane (contains <5% n-Hexane)

Bulk Density Not applicable Liquid

Water Solubility Insoluble

No information available Solubility in other solvents

Partition Coefficient (n-octanol/water)

265 - °C / 509 - °F **Autoignition Temperature Decomposition Temperature** No data available No data available **Viscosity**

Explosive Properties Oxidizing Properties

No information available

Vapors may form explosive mixtures with air

C6 H14 Molecular Formula 86.18 **Molecular Weight**

SECTION 10. STABILITY AND REACTIVITY

Stability Stable under normal conditions.

Hazardous Reactions None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Keep away from open flames, hot surfaces and sources of ignition. Incompatible products. **Conditions to Avoid**

Materials to avoid Strong oxidizing agents.

Hazardous Decomposition Products Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11. TOXICOLOGICAL INFORMATION

Product Information

(a) acute toxicity;

Component		LD50 Oral	LD50 Dermal	LC50 Inhalation		
	Hydrocarbons, C6, isoalkanes < 5%	LD50 > 5000 mg/kg (Rat)	LD50 > 3160 mg/kg (Rabbit)	LC50 = 73680 ppm (Rat) 4 h		
	n-hexane (Iso-Hexane)					

Category 2 (b) skin corrosion/irritation;

(c) serious eye damage/irritation; Based on available data, the classification criteria are not met

(d) respiratory or skin sensitization;

Based on available data, the classification criteria are not met Respiratory Skin Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met (e) germ cell mutagenicity;

(f) carcinogenicity; Based on available data, the classification criteria are not met

> The table below indicates whether each agency has listed any ingredient as a carcinogen The classification as a carcinogen need not apply if the full refining history is known and it can be shown that the substance from which it is produced is not a carcinogen. This note

applies only to certain complex oil derived substances in Annex I

Component	EU	UK	Germany	IARC
Hydrocarbons, C6, isoalkanes < 5% n-hexane (Iso-Hexane)	Carc Cat. 1B			

FSUH0408

SAFETY DATA SHEET

Page 7/9 Revision Date 15-Apr-2025

IsoHexane (contains <5% n-Hexane)

(g) reproductive toxicity; Based on available data, the classification criteria are not met

(h) STOT-single exposure; Category 3

Central nervous system (CNS) Results / Target organs

Based on available data, the classification criteria are not met (i) STOT-repeated exposure;

Target Organs None known.

(j) aspiration hazard; Category 1

Other Adverse Effects See actual entry in RTECS for complete information

delaved

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity effects Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment. The product contains following substances which are hazardous for the

environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Hydrocarbons, C6, isoalkanes < 5% n-hexane (Iso-Hexane)	LC50: = 8.41 mg/L, 96h semi-static, closed (Oncorhynchus mykiss)			

Persistence and Degradability

Persistence

Degradation in sewage treatment plant

Persistence is unlikely, based on information available.

Contains substances known to be hazardous to the environment or not degradable in waste

water treatment plants.

Bioaccumulative Potential Bioaccumulation is unlikely

Mobility in soil The product contains volatile organic compounds (VOC) which will evaporate easily from all

surfaces Will likely be mobile in the environment due to its volatility Disperses rapidly in air

Endocrine Disruptor Information Persistent Organic Pollutant

Ozone Depletion Potential

This product does not contain any known or suspected endocrine disruptors

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13. DISPOSAL CONSIDERATIONS

Waste from Residues/Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the

application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not

Page 8 / 9 Revision Date 15-Apr-2025

IsoHexane (contains <5% n-Hexane)

empty into drains.

SECTION 14. TRANSPORT INFORMATION

Road and Rail Transport

UN-No UN1208
Proper Shipping Name HEXANES

Hazard Class 3 Packing Group II

IMDG/IMO

UN-No UN1208
Proper Shipping Name HEXANES

Hazard Class 3 Packing Group II

<u>IATA</u>

UN-No UN1208 Proper Shipping Name HEXANES

Hazard Class 3
Packing Group ||

Special Precautions for User No special precautions required

SECTION 15. REGULATORY INFORMATION

International Inventories

X = listed, China (IECSC), Europe (EINECS/ELINCS/NLP), U.S.A. (TSCA), Canada (DSL/NDSL), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), Korea (KECL).

Component	The Inventory of Hazardous Chemicals (2015 Edition)	goods GB	TCSI	IECSC	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	AICS	KECL
Hydrocarbons, C6, isoalkanes < 5% n-hexane (Iso-Hexane)	-	Х	Х	Х	265-151-9	Х	Х	Х	-		Х	KE-25623
Hexane, mixed isomers	-	-	Х	Х	-	-	-	-	Х	Х	-	-

Note REACH UVCB Hydrocarbons C6, isoalkanes, < 5% n-Hexane

Contains CAS 73513-42-5 (Iso-Hexane)

National Regulations

SECTION 16. OTHER INFORMATION

Creation Date28-Apr-2011Revision Date15-Apr-2025Revision SummaryNot applicable.

Page 9/9 Revision Date 15-Apr-2025

IsoHexane (contains <5% n-Hexane)

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and

First aid for chemical exposure, including the use of eye wash and safety showers.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical incident response training.

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b)

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances Substances List **ENCS** - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

PNEC - Predicted No Effect Concentration

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50% POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative

ICAO/IATA - International Civil Aviation Organization/International Air **Transport Association**

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

MARPOL - International Convention for the Prevention of Pollution from

ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet