Thermo Fisher SCIENTIFIC

SAFETY DATA SHEET

Page 1/9 Revision Date 12-May-2024 Version 4

ALFAA41913

Copper Beryllium foil, alloy C17200

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

产品说明: 铜铍合金箔

Product Description: Copper Beryllium foil, alloy C17200

Cat No. : 41913

Molecular Formula Cu:Be; 98.1:1.9 wt%

Supplier Avocado Research Chemicals Ltd.

(Part of Thermo Fisher Scientific)

Shore Road, Heysham Lancashire, LA3 2XY, United Kingdom

Office Tel: +44 (0) 1524 850506 Office Fax: +44 (0) 1524 850608

Emergency Telephone Number For information US call: 001-800-227-6701 / Europe call: +32 14 57 52 11

Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

E-mail address begel.sdsdesk@thermofisher.com

Recommended Use Laboratory chemicals.
Uses advised against No Information available

SECTION 2. HAZARD IDENTIFICATION

Physical StateAppearanceOdorSolidBronzeOdorless

Emergency Overview

Causes mild skin irritation. May cause an allergic skin reaction. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. Harmful if inhaled. May cause cancer by inhalation.

Classification of the substance or mixture

Acute Inhalation Toxicity - Dusts and Mists	Category 4
Skin Corrosion/Irritation	Category 3
Skin Sensitization	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity - (single exposure)	Category 3
Specific target organ toxicity - (repeated exposure)	Category 2

Label Elements



Copper Beryllium foil, alloy C17200

Page 2/9 Revision Date 12-May-2024

Signal Word

Danger

Hazard Statements

- H316 Causes mild skin irritation
- H317 May cause an allergic skin reaction
- H335 May cause respiratory irritation
- H373 May cause damage to organs through prolonged or repeated exposure
- H332 Harmful if inhaled
- H350i May cause cancer by inhalation

Precautionary Statements

Prevention

- P201 Obtain special instructions before use
- P202 Do not handle until all safety precautions have been read and understood
- P260 Do not breathe dust/fume/gas/mist/vapors/spray
- P271 Use only outdoors or in a well-ventilated area
- P272 Contaminated work clothing should not be allowed out of the workplace
- P280 Wear protective gloves

Response

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P362 + P364 - Take off contaminated clothing and wash it before reuse

Storage

P403 - Store in a well-ventilated place

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Physical and Chemical Hazards

None identified.

Health Hazards

Causes mild skin irritation. May cause an allergic skin reaction. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. Harmful if inhaled. May cause cancer by inhalation.

Environmental hazards

Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants. Is not likely mobile in the environment due its low water solubility. Spillage unlikely to penetrate soil.

Toxicity to Soil Dwelling Organisms. Toxic to terrestrial vertebrates. This product does not contain any known or suspected endocrine disruptors.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Copper	7440-50-8	98.1
Beryllium	7440-41-7	1.9

SECTION 4. FIRST AID MEASURES

General Advice

If symptoms persist, call a physician.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.

Page 3/9 Revision Date 12-May-2024

Copper Beryllium foil, alloy C17200

Ingestion

Clean mouth with water and drink afterwards plenty of water. Get medical attention if symptoms occur.

Most important symptoms and effects

May cause allergic skin reaction. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Notes to Physician

Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Not combustible. approved class D extinguishers.

Extinguishing media which must not be used for safety reasons

Water may be ineffective.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Ensure adequate ventilation. Use personal protective equipment as required. Avoid dust formation. No special precautions required.

Environmental Precautions

Do not flush into surface water or sanitary sewer system. Should not be released into the environment. Do not allow material to contaminate ground water system.

Methods for Containment and Clean Up

Sweep up and shovel into suitable containers for disposal. Keep in suitable, closed containers for disposal. Pick up and transfer to properly labelled containers.

Refer to protective measures listed in Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Avoid dust formation.

Storage

Keep in a dry place. Keep away from acids.

Specific Use(s)

Use in laboratories

Copper Beryllium foil, alloy C17200

Page 4/9 Revision Date 12-May-2024

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	China	Taiwan	Thailand	Hong Kong
Copper	TWA: 1 mg/m ³	TWA: 0.2 mg/m ³		TWA: 0.2 mg/m ³
	TWA: 0.2 mg/m ³	TWA: 1 mg/m ³		TWA: 1 mg/m ³
Beryllium	TWA: 0.0005 mg/m ³	TWA: 0.002 mg/m ³	Ceiling: 0.005 mg/m ³	TWA: 0.002 mg/m ³
	STEL: 0.001 mg/m ³	_	STEL: 0.025 mg/m ³	STEL: 0.01 mg/m ³
	Skin		TWA: 0.002 mg/m ³	-

Component	ACGIH TLV	OSHA PEL	NIOSH	The United Kingdom	European Union
Copper	TWA: 0.2 mg/m ³	(Vacated) TWA: 0.1	IDLH: 100 mg/m ³	STEL: 0.6 mg/m ³ 15	
		mg/m³	TWA: 1 mg/m ³	min	
		TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³	STEL: 2 mg/m ³ 15 min	
		TWA: 1 mg/m ³		TWA: 1 mg/m ³ 8 hr	
				TWA: 0.2 mg/m ³ 8 hr	
Beryllium	TWA: 0.00005 mg/m ³	(Vacated) TWA: 2	IDLH: 4 mg/m ³	STEL: 0.006 mg/m ³ 15	TWA: 0.0002 mg/m ³
		μg/m³	Ceiling: 0.0005 mg/m ³	min	(8h)
		Ceiling: 2 µg/m³		TWA: 0.002 mg/m ³ 8	Skin
		(Vacated) STEL: 25		hr	
		μg/m³		Carc.	
		(Vacated) Ceiling: 5			
		μg/m³			
		TWA: 0.2 μg/m ³			
		STEL: 2 µg/m ³			

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust MDHS 91 Metals and metalloids in workplace air by X-ray fluorescence spectrometry MDHS 99 Metals in air by ICP-AES

Exposure Controls

Engineering Measures

None under normal use conditions. Ensure that eyewash stations and safety showers are close to the workstation location. .

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection No special protective equipment required

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Natural rubber	See manufacturers	-	EN 374	(minimum requirement)
Nitrile rubber	recommendations			
Neoprene				
PVC				

Skin and body protection Long sleeved clothing

Respiratory Protection No special protective equipment required.

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced **Recommended Filter type:** Particulates filter conforming to EN 143

Page 5/9 Revision Date 12-May-2024

Copper Beryllium foil, alloy C17200

Small scale/Laboratory use No personal respiratory protective equipment normally required Use a NIOSH/MSHA or

European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if

irritation or other symptoms are experienced.

Recommended half mask:- Particle filtering: EN149:2001 When RPE is used a face piece Fit Test should be conducted

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

system. Local authorities should be advised if significant spillages cannot be contained.

Solid

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Bronze
Physical State Solid

Odor Odorless

Odor Threshold No data available

pH No information available

Melting Point/RangeNo data availableSoftening PointNo data available

Softening Point No data available
Boiling Point/Range No information available

Flash Point No information available Method - No information available

Evaporation Rate Not applicable Solid

Flammability (solid,gas) No information available

Explosion Limits No data available

Vapor Pressure 23 hPa @ 20 °C

Vapor DensityNot applicableSolidSpecific Gravity / Density8.36 g/cm3@ 20 °C

Bulk Density
Water Solubility
Solubility in other solvents
No data available
Insoluble in water
No information available

Partition Coefficient (n-octanol/water)

Autoignition Temperature

Decomposition Temperature

Viscosity

No data available
No data available
Not applicable

Explosive Properties No information available Oxidizing Properties No information available

Molecular Formula Cu:Be; 98.1:1.9 wt%

SECTION 10. STABILITY AND REACTIVITY

Stability Stable under normal conditions.

Hazardous ReactionsNone under normal processing.Hazardous PolymerizationNo information available.

Conditions to Avoid None known.

Materials to avoid No information available.

Hazardous Decomposition Products Heavy metal oxides. Metal oxides.

SECTION 11. TOXICOLOGICAL INFORMATION

Page 6/9 Revision Date 12-May-2024

Copper Beryllium foil, alloy C17200

Product Information

(a) acute toxicity;

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Copper			LC50 > 5.11 mg/L (Rat) 4 h

No data available (b) skin corrosion/irritation;

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;

Respiratory No data available Skin Category 1

No information available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Beryllium	Carc Cat. 1B		Cat. 1	Group 1

(g) reproductive toxicity; No data available

(h) STOT-single exposure; No data available

(i) STOT-repeated exposure; Category 2

Inhalation Route of exposure **Target Organs** Lungs.

(j) aspiration hazard; Not applicable

Solid

delayed

Symptoms / effects, both acute and Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity effects Contains a substance which is:. Very toxic to aquatic organisms. The product contains

following substances which are hazardous for the environment. May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water

system.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Copper	LC50: = 1.25 mg/L, 96h	EC50: = 0.03 mg/L, 48h	EC50: 0.031 - 0.054	
	static (Lepomis	Static (Daphnia magna)	mg/L, 96h static	
	macrochirus)		(Pseudokirchneriella	
	LC50: = 0.3 mg/L, 96h		subcapitata)	
	semi-static (Cyprinus		EC50: 0.0426 - 0.0535	

Page 7/9 Revision Date 12-May-2024

Copper Beryllium foil, alloy C17200

carpio)	mg/L, 72h static	
LC50: = 0.8 mg/L, 96h	(Pseudokirchneriella	
static (Cyprinus carpio)	subcapitata)	
LC50: = 0.112 mg/L,		
96h flow-through		
(Poecilia reticulata)		
LC50: = 0.052 mg/L,		
96h flow-through		
(Oncorhynchus mykiss)		
LC50: 0.0068 - 0.0156		
mg/L, 96h (Pimephales		
promelas)		
LC50: < 0.3 mg/L, 96h		
static (Pimephales		
promelas)		
LC50: = 0.2 mg/L, 96h		
flow-through		
(Pimephales promelas)		
,		
mg/L, 96h (Pimephales promelas) LC50: < 0.3 mg/L, 96h static (Pimephales promelas) LC50: = 0.2 mg/L, 96h flow-through		

Persistence and Degradability

Product contains heavy metals. Discharge into the environment must be avoided. Special

pre-treatment is necessary

Persistence Degradability Insoluble in water, May persist.

Degradation in sewage treatment plant

Not relevant for inorganic substances.

Contains substances known to be hazardous to the environment or not degradable in waste

water treatment plants.

Bioaccumulative Potential

May have some potential to bioaccumulate; Product has a high potential to bioconcentrate

Mobility in soil

Spillage unlikely to penetrate soil Is not likely mobile in the environment due its low water

solubility

Endocrine Disruptor Information Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected endocrine disruptors

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13. DISPOSAL CONSIDERATIONS

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the

application for which the product was used. Do not empty into drains.

SECTION 14. TRANSPORT INFORMATION

Road and Rail Transport Not Regulated

IMDG/IMO Not regulated

IATA Not regulated

Page 8/9 Revision Date 12-May-2024

Copper Beryllium foil, alloy C17200

No special precautions required **Special Precautions for User**

SECTION 15. REGULATORY INFORMATION

International Inventories

X = listed, China (IECSC), Europe (EINECS/ELINCS/NLP), U.S.A. (TSCA), Canada (DSL/NDSL), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), Korea (KECL).

Component	The Inventory of Hazardous Chemicals (2015 Edition)	goods GB	TCSI	IECSC	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	AICS	KECL
Copper	-	X	X	Х	231-159-6	Х	Х	Х	X		Χ	KE-08896
Beryllium	X	Х	X	X	231-150-7	Х	X	Х	Х		Χ	KE-02829

National Regulations

Component	Toxic Chemical Substances Control Act
Beryllium	Class II (95 wt%)
7440-41-7 (1.9)	TRQ = 50 kg

SECTION 16. OTHER INFORMATION

Prepared By Health, Safety and Environmental Department

12-May-2024 **Revision Date**

Revision Summary New emergency telephone response service provider.

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances Substances List

ENCS - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

PNEC - Predicted No Effect Concentration

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50% POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative

ALFAA41913

SAFETY DATA SHEET

Page 9/9 Revision Date 12-May-2024

Copper Beryllium foil, alloy C17200

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate
VOC - (Volatile Organic Compound)

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Physical hazards
Health Hazards
Calculation method
Environmental hazards
Cn basis of test data
Calculation method

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet
