

according to Regulation (EC) No. 1907/2006

Creation Date 14-May-2009 Revision Date 19-Oct-2023 Revision Number 11

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product Description: <u>1,2-Diaminoethane anhydrous</u>

Cat No.: D/0370/25, D/0370/PB08, D/0370/PB17

 Synonyms
 1,2-Diaminoethane

 Index No
 612-006-00-6

 CAS No
 107-15-3

 EC No
 203-468-6

 Molecular Formula
 C2 H8 N2

REACH registration number -

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended Use**Laboratory chemicals.

Sector of use SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

**Product category** PC21 - Laboratory chemicals

**Process categories** PROC15 - Use as a laboratory reagent

**Environmental release category** ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)

Uses advised against No Information available

## 1.3. Details of the supplier of the safety data sheet

Company

**EU entity/business name** Thermo Fisher Scientific

Janssen Pharmaceuticalaan 3a

2440 Geel, Belgium

UK entity/business name

Fisher Scientific UK

Bishop Meadow Road, Loughborough, Leicestershire LE11 5RG, United Kingdom

Swiss distributor - Fisher Scientific AG Neuhofstrasse 11, CH 4153 Reinach

Tel: +41 (0) 56 618 41 11

e-mail - infoch@thermofisher.com

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

Tel: 01509 231166

Chemtrec US: (800) 424-9300 Chemtrec EU: 001-703-527-3887

For customers in Switzerland:

Tox Info Suisse Emergency Number: 145 (24hr)

Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)

Chemtrec (24h) Toll-Free: 0800 564 402 Chemtrec Local: +41-43 508 20 11 (Zurich)

Revision Date 19-Oct-2023

## **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

#### CLP Classification - Regulation (EC) No 1272/2008

#### **Physical hazards**

Flammable liquids Category 3 (H226)

#### **Health hazards**

Acute oral toxicity	Category 4 (H302)
Acute dermal toxicity	Category 3 (H311)
Acute Inhalation Toxicity - Vapors	Category 4 (H332)
Skin Corrosion/Irritation	Category 1 B (H314)
Serious Eye Damage/Eye Irritation	Category 1 (H318)
Respiratory Sensitization	Category 1 (H334)
Skin Sensitization	Category 1 (H317)

## **Environmental hazards**

Chronic aquatic toxicity Category 3 (H412)

Full text of Hazard Statements: see section 16

## 2.2. Label elements



**Signal Word** 

**Danger** 

## **Hazard Statements**

H226 - Flammable liquid and vapor

H311 - Toxic in contact with skin

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

H412 - Harmful to aquatic life with long lasting effects

H302 + H332 - Harmful if swallowed or if inhaled

## **Precautionary Statements**

P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

#### 1,2-Diaminoethane anhydrous

Revision Date 19-Oct-2023

easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

#### 2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

#### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Ethylenediamine	107-15-3	EEC No. 203-468-6	>95	Flam. Liq. 3 (H226)
				Acute Tox. 4 (H302)
				Acute Tox. 3 (H311)
				Acute Tox. 4 (H332)
				Skin Corr. 1B (H314)
				Eye Dam. 1 (H318)
				Skin Sens. 1 (H317)
				Resp. Sens. 1 (H334)
				Aquatic Chronic 3 (H412)

REACH registration number -
-----------------------------

Full text of Hazard Statements: see section 16

## **SECTION 4: FIRST AID MEASURES**

#### 4.1. Description of first aid measures

**General Advice** Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In

the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

**Ingestion** Do NOT induce vomiting. Call a physician or poison control center immediately.

**Inhalation** If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim

ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh

air. Immediate medical attention is required.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

#### 1,2-Diaminoethane anhydrous

Revision Date 19-Oct-2023

#### 4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause allergic skin reaction. Difficulty in breathing. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

## 4.3. Indication of any immediate medical attention and special treatment needed

**Notes to Physician** 

Treat symptomatically.

## **SECTION 5: FIREFIGHTING MEASURES**

#### 5.1. Extinguishing media

#### Suitable Extinguishing Media

Water mist may be used to cool closed containers, CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam.

#### Extinguishing media which must not be used for safety reasons

No information available.

#### 5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

#### **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Nitrogen oxides (NOx), Thermal decomposition can lead to release of irritating gases and vapors.

#### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

#### 6.2. Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information. Avoid release to the environment. Collect spillage. Do not flush into surface water or sanitary sewer system.

#### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

#### 1,2-Diaminoethane anhydrous

Revision Date 19-Oct-2023

#### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

#### 7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

#### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice.

#### 7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area. Keep away from heat, sparks and flame. Flammables area.

Technical Rules for Hazardous Substances (TRGS) 510

Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances Storage class - SC 3

https://www.kvu.ch/de/themen/stoffe-und-produkte https://www.kvu.ch/fr/themes/substances-et-produits https://www.kvu.ch/it/temi/sostanze-e-prodotti

#### 7.3. Specific end use(s)

Use in laboratories

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

## 8.1. Control parameters

#### **Exposure limits**

List source(s): **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

	Component	European Union	The United Kingdom	France	Belgium	Spain
I	Ethylenediamine			TWA / VME: 10 ppm (8	TWA: 10 ppm 8 uren	TWA / VLA-ED: 10 ppm
-				heures).	TWA: 25 mg/m <sup>3</sup> 8 uren	(8 horas)
-				TWA / VME: 25 mg/m <sup>3</sup>	Huid	TWA / VLA-ED: 25
-				(8 heures).		mg/m³ (8 horas)
-				STEL / VLCT: 15 ppm.		Piel
				STEL / VLCT: 35		
				mg/m³.		

Component	Italy	Germany	Portugal	The Netherlands	Finland
Ethylenediamine			TWA: 10 ppm 8 horas		TWA: 10 ppm 8 tunteina
			Pele		TWA: 25 mg/m <sup>3</sup> 8
					tunteina
					STEL: 20 ppm 15
					minuutteina
					STEL: 50 mg/m <sup>3</sup> 15
					minuutteina

#### 1,2-Diaminoethane anhydrous

Revision Date 19-Oct-2023

absorption

Ceiling: 50 mg/m<sup>3</sup>

					lho
Component	Austria	Denmark	Switzerland	Poland	Norway
Ethylenediamine	Haut MAK-KZW: 40 ppm 15 Minuten MAK-KZW: 100 mg/m³ 15 Minuten MAK-TMW: 10 ppm 8 Stunden MAK-TMW: 25 mg/m³ 8 Stunden	TWA: 10 ppm 8 timer TWA: 25 mg/m <sup>3</sup> 8 timer	STEL: 20 ppm 15 Minuten STEL: 50 mg/m³ 15 Minuten TWA: 10 ppm 8 Stunden TWA: 25 mg/m³ 8 Stunden	STEL: 50 mg/m³ 15 minutach TWA: 20 mg/m³ 8 godzinach	TWA: 10 ppm 8 timer TWA: 25 mg/m³ 8 timer STEL: 20 ppm 15 minutter. STEL: 37.5 mg/m³ 15 minutter.
Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Ethylenediamine	TWA: 25 mg/m <sup>3</sup>	kože TWA-GVI: 10 ppm 8 satima.	TWA: 10 ppm 8 hr. TWA: 25 mg/m <sup>3</sup> 8 hr. STEL: 30 ppm 15 min		TWA: 25 mg/m³ 8 hodinách. Potential for cutaneous

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Ethylenediamine	TWA: 10 ppm 8 tundides. TWA: 25 mg/m³ 8 tundides. STEL: 15 ppm 15 minutites. STEL: 35 mg/m³ 15 minutites.		TWA: 10 ppm TWA: 25 mg/m <sup>3</sup>		TWA: 10 ppm 8 klukkustundum. TWA: 25 mg/m³ 8 klukkustundum. Ceiling: 20 ppm Ceiling: 50 mg/m³

STEL: 75 mg/m<sup>3</sup> 15 min

TWA-GVI: 25 mg/m<sup>3</sup> 8

satima.

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Ethylenediamine	TWA: 0.5 mg/m <sup>3</sup> TWA: 2 mg/m <sup>3</sup>	TWA: 10 ppm IPRD TWA: 25 mg/m³ IPRD STEL: 15 ppm STEL: 35 mg/m³			TWA: 8 ppm 8 ore TWA: 20 mg/m³ 8 ore STEL: 12 ppm 15 minute STEL: 30 mg/m³ 15
					minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Ethylenediamine	MAC: 2 mg/m <sup>3</sup>	Ceiling: 50 mg/m³ TWA: 10 ppm TWA: 25 mg/m³	TWA: 10 ppm 8 urah TWA: 25 mg/m³ 8 urah Koža STEL: 40 ppm 15 minutah STEL: 100 mg/m³ 15	STV: 15 ppm 15 minuter STV: 35 mg/m³ 15 minuter LLV: 10 ppm 8 timmar. LLV: 25 mg/m³ 8 timmar.	
			minutah		

## **Biological limit values**

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

#### **Monitoring methods**

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

\_\_\_\_\_

#### 1,2-Diaminoethane anhydrous

Revision Date 19-Oct-2023

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

Workers: See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Ethylenediamine 107-15-3 ( >95 )				DNEL = 3.6mg/kg bw/dav
				DNEL = 33.3mg/kg bw/dav

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Ethylenediamine 107-15-3 ( >95 )				$DNEL = 25mg/m^3 DNEL$ $= 11.75mg/m^3$

#### **Predicted No Effect Concentration (PNEC)**

See values below.

Component	Fresh water	Fresh water	Water Intermittent	Microorganisms in	Soil (Agriculture)
		sediment		sewage treatment	
Ethylenediamine	PNEC = 0.016mg/L	PNEC = 7.68mg/kg	PNEC = 0.167mg/L	PNEC = 0.5mg/L	PNEC = 4.36mg/kg
107-15-3 (>95)	PNEC = 1mg/L	sediment dw	PNEC = 1mg/L	PNEC = 10mg/L	soil dw
		PNEC = 1384mg/kg			PNEC =
		sediment dw			275.2mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Ethylenediamine	PNEC = 0.002mg/L	PNEC =	PNEC = 1mg/L	PNEC = 4.9mg/kg	
107-15-3 ( >95 )	PNEC = 1mg/L	0.768mg/kg		food	
		sediment dw			
		PNEC = 1384mg/kg			
		sediment dw			

## 8.2. Exposure controls

#### **Engineering Measures**

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

## Personal protective equipment

**Eye Protection** Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	> 480 minutes	0.38 mm	Level 6	As tested under EN374-3 Determination of
Neoprene	> 480 minutes	0.45 mm	EN 374	Resistance to Permeation by Chemicals
Natural rubber				·
PVC				
Butyl rubber	> 480 minutes	0.35 mm		
Viton (R)	> 480 minutes	0.3 mm		

Skin and body protection Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability,

#### 1,2-Diaminoethane anhydrous

Revision Date 19-Oct-2023

Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: conforming to EN14387 Organic gases and vapours filter

Type A Brown

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

141

When RPE is used a face piece Fit Test should be conducted

**Environmental exposure controls** Prevent product from entering drains.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

#### 9.1. Information on basic physical and chemical properties

Physical State Liquid

Appearance Colorless
Odor Ammonia-like
Odor Threshold No data available
Melting Point/Range 11 °C / 51.8 °F
Softening Point No data available

Boiling Point/Range 117 - 118 °C / 242.6 - 244.4 °F @ 760 mmHg
Flammability (liquid) Flammable On basis of test data

Flammability (solid,gas) Not applicable Liquid

Explosion Limits Lower 2.7 vol%

**Upper** 16.6 vol%

Flash Point 38 °C / 100.4 °F Method - No information available

**Autoignition Temperature** 385 °C / 725 °F **Decomposition Temperature** > 120 °C

**pH** 12.2 11% aq.sol

Viscosity

1.6 mPa.s @ 20 °C

Water Solubility

Solubility in other solvents

1.6 mPa.s @ 20 °C

Completely soluble

No information available

Partition Coefficient (n-octanol/water)

**Component** log Pow Ethylenediamine -1.221

Vapor Pressure 13.3 mbar @ 20 °C

Density / Specific Gravity 0.898
Bulk Density Not applicable

Bulk DensityNot applicableLiquidVapor Density2.1(Air = 1.0)

Particle characteristics (liquid) Not applicable

#### 9.2. Other information

Molecular Formula C2 H8 N2 Molecular Weight 60.1

**Explosive Properties** explosive air/vapour mixtures possible

**Evaporation Rate** 0.91 - (Butyl Acetate = 1.0)

\_\_\_\_\_

Revision Date 19-Oct-2023

## **SECTION 10: STABILITY AND REACTIVITY**

10.1. Reactivity None known, based on information available

10.2. Chemical stability

Stable under normal conditions. Air sensitive.

10.3. Possibility of hazardous reactions

**Hazardous Polymerization** Hazardous polymerization does not occur.

None under normal processing. **Hazardous Reactions** 

10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition. Exposure to air.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO2). Nitrogen oxides (NOx). Thermal

decomposition can lead to release of irritating gases and vapors.

## **SECTION 11: TOXICOLOGICAL INFORMATION**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Product Information**

(a) acute toxicity:

Category 4 Oral Category 3 **Dermal** Inhalation Category 4

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethylenediamine	637 mg/kg (Rat)	560 mg/kg (Rabbit)	14.7 mg/L/4h ( Rat )
	866 mg/kg ( Rat )		

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory Category 1 Skin Category 1

May cause sensitization by skin contact

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

Mutagenic effects have occured in microorganisms

(f) carcinogenicity; Based on available data, the classification criteria are not met

#### 1,2-Diaminoethane anhydrous

Revision Date 19-Oct-2023

There are no known carcinogenic chemicals in this product

Based on available data, the classification criteria are not met (g) reproductive toxicity;

Based on available data, the classification criteria are not met (h) STOT-single exposure;

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

**Target Organs** None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Symptoms / effects, both acute and Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling

delayed

of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Symptoms

of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

#### 11.2. Information on other hazards

**Endocrine Disrupting Properties** 

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## **SECTION 12: ECOLOGICAL INFORMATION**

## 12.1. Toxicity

**Ecotoxicity effects** 

Contains no substances known to be hazardous to the environment or that are not degradable in waste water treatment plants. Contains a substance which is:. Harmful to aquatic organisms. The product contains following substances which are hazardous for the environment. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Ethylenediamine	180 - 560 mg/L LC50 96 h 115.7	17 mg/L EC50 = 48 h	151 mg/L EC50 = 96 h 645 mg/L
	mg/L LC50 96 h 191 - 254 mg/L		EC50 = 72 h
	LC50 96 h 98.6 - 131.6 mg/L		
	LC50 96 h		

Component	Microtox	M-Factor
Ethylenediamine	EC50 = 20 mg/L 15 min	
· ·	EC50 = 29 mg/L 17 h	

## 12.2. Persistence and degradability Readily biodegradable

**Persistence** 

Persistence is unlikely.

Degradation in sewage

treatment plant

Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants. Contains substances known to be hazardous to the

environment or not degradable in waste water treatment plants.

#### 12.3. Bioaccumulative potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Ethylenediamine	-1.221	No data available

1,2-Diaminoethane anhydrous

•

12.4. Mobility in soil

The product is water soluble, and may spread in water systems . Will likely be mobile in the

environment due to its water solubility. Highly mobile in soils

12.5. Results of PBT and vPvB

assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent

Revision Date 19-Oct-2023

and very bioaccumulative (vPvB).

12.6. Endocrine disrupting

properties

**Endocrine Disruptor Information** 

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected substance This product does not contain any known or suspected substance

## **SECTION 13: DISPOSAL CONSIDERATIONS**

13.1. Waste treatment methods

Waste from Residues/Unused

**Products** 

Waste is classified as hazardous. Dispose of in accordance with the European Directives

on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but

application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the

application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms. Solutions with high pH-value must be neutralized before

discharge. Do not let this chemical enter the environment.

**Switzerland - Waste Ordinance** Disposal should be in accordance with applicable regional, national and local laws and

regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance,

ADWO) SR 814.600

https://www.fedlex.admin.ch/eli/cc/2015/891/en

## **SECTION 14: TRANSPORT INFORMATION**

IMDG/IMO

**14.1. UN number** UN1604

14.2. UN proper shipping name Ethylenediamine

14.3. Transport hazard class(es)8Subsidiary Hazard Class314.4. Packing groupII

<u>ADR</u>

**14.1. UN number** UN1604

14.2. UN proper shipping name Ethylenediamine

14.3. Transport hazard class(es) 8
Subsidiary Hazard Class 3

#### 1,2-Diaminoethane anhydrous

Revision Date 19-Oct-2023

14.4. Packing group

IATA

**14.1. UN number** UN1604

14.2. UN proper shipping name Ethylenediamine

14.3. Transport hazard class(es)8Subsidiary Hazard Class314.4. Packing groupII

14.5. Environmental hazards No hazards identified

**14.6. Special precautions for user** No special precautions required.

Π

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

## **SECTION 15: REGULATORY INFORMATION**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **International Inventories**

Component

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

EINECS ELINCS

L	Ethylenediamine	107-15-3	203-468-6	430-750-8 -	X	X	X	X	X
_		Y		r	T	1			
	Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Γ	Ethylenediamine	107-15-3	X	ACTIVE	Х	-	Х	Х	X

NLP

**IECSC** 

**TCSI** 

**KECL** 

**ENCS** 

ISHL

Legend: X - Listed '-' - Not Listed KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

CAS No

#### Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization		REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Ethylenediamine	107-15-3	•	Use restricted. See item 75. (see link for restriction details)	SVHC Candidate list - 203-468-6 - Respiratory sensitising properties (Article 57(f) - human health)

After the sunset date the use of this substance requires either an authorization or can only be used for exempted uses, e.g. use in scientific research and development which includes routine analytics or use as intermediate.

## **REACH links**

https://echa.europa.eu/authorisation-list https://echa.europa.eu/substances-restricted-under-reach

https://echa.europa.eu/candidate-list-table

## Seveso III Directive (2012/18/EC)

	Component	CAS No	Seveso III Directive (2012/18/EC) -	Seveso III Directive (2012/18/EC) -
_				

#### 1,2-Diaminoethane anhydrous

Revision Date 19-Oct-2023

		Qualifying Quantities for Major Accident Notification	Qualifying Quantities for Safety Report Requirements
Ethylenediamine	107-15-3	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

## **National Regulations**

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Ethylenediamine	WGK 2	Class I: 20 mg/m³ (Massenkonzentration)

Component	France - INRS (Tables of occupational diseases)
Ethylenediamine	Tableaux des maladies professionnelles (TMP) - RG 49,RG 49bis

#### **Swiss Regulations**

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

## 15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

## **SECTION 16: OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3

H332 - Harmful if inhaled

H302 - Harmful if swallowed

H311 - Toxic in contact with skin

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

H318 - Causes serious eye damage

H412 - Harmful to aquatic life with long lasting effects

H226 - Flammable liquid and vapor

#### Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b)
Inventory

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical **DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

Substances List

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

AICS - Australian Inventory of Chemical Substances

#### 1,2-Diaminoethane anhydrous

Revision Date 19-Oct-2023

**KECL** - Korean Existing and Evaluated Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

Predicted No Effect Concentration (PNEC)

POW - Partition coefficient Octanol:Water

IARC - International Agency for Research on Cancer

ICAO/IATA - International Civil Aviation Organization/International Air

MARPOL - International Convention for the Prevention of Pollution from

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment **LC50** - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

vPvB - very Persistent, very Bioaccumulative

EC50 - Effective Concentration 50%

TWA - Time Weighted Average

LD50 - Lethal Dose 50%

ADR - European Agreement Concerning the International Carriage of

Dangerous Goods by Road

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

Ships **ATE** - Acute Toxicity Estimate

Transport Association

VOC - (volatile organic compound)

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

**Training Advice** 

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Creation Date14-May-2009Revision Date19-Oct-2023Revision SummaryNot applicable.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No. 1907/2006

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

## **End of Safety Data Sheet**