

Page 1/10 Creation Date 11-Nov-2010 Revision Date 21-Mar-2025

Version 4

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THECOMPANY/UNDERTAKING

Product Identifier

Perihalan Produk: N,N-Diethylethanolamine **Product Description:** N,N-Diethylethanolamine

114330000; 114330010; 114330025; ACR114330100 Cat No.:

Synonyms 2-Diethylaminoethanol

CAS No 100-37-8 **Molecular Formula** C6 H15 N O

Relevant identified uses of the substance or mixture and uses advised against

Laboratory chemicals. **Recommended Use** No Information available Uses advised against

Company Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd

> Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square, No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,

Selangor Darul Ehsan, Malaysia. Main line: +60 3-5525 7888

E-mail address Enquiry.my@thermofisher.com

Emergency Telephone Number Tel: +03-5525 7888

CHEMTREC Malaysia 1-800-815-308 (Malay)

CHEMTREC Malaysia (Kuala Lumpur) +(60)-327884561 (Malay)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

Flammable liquids	Category 3 (H226)
Acute oral toxicity	Category 4 (H302)
Acute dermal toxicity	Category 3 (H311)
Acute Inhalation Toxicity - Vapors	Category 3 (H331)
Skin Corrosion/Irritation	Category 1 B (H314)
Serious Eye Damage/Eye Irritation	Category 1 (H318)
Specific target organ toxicity - (single exposure)	Category 3 (H335)

Label Elements



N,N-Diethylethanolamine

Revision Date 21-Mar-2025

Signal Word

Danger

Hazard Statements

H226 - Flammable liquid and vapor

H302 - Harmful if swallowed

H314 - Causes severe skin burns and eye damage

H335 - May cause respiratory irritation

H311 + H331 - Toxic in contact with skin or if inhaled

Precautionary Statements

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P240 - Ground and bond container and receiving equipment

P241 - Use explosion-proof electrical/ventilating/lighting equipment

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P264 - Wash face, hands and any exposed skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

Response

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor

P330 - Rinse mouth

P331 - Do NOT induce vomiting

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P362 + P364 - Take off contaminated clothing and wash it before reuse

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other Hazards

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %	
Diethylaminoethanol	100-37-8	>95	

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General Advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

N,N-Diethylethanolamine Revision Date 21-Mar-2025

Skin ContactWash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

Inhalation If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim

ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh

air. Immediate medical attention is required.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO₂).

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental precautions

Should not be released into the environment. Do not flush into surface water or sanitary sewer system.

N,N-Diethylethanolamine Revision Date 21-Mar-2025

Methods and Material for Containment and Cleaning Up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

Conditions for Safe Storage, Including any Incompatibilities

Keep in a dry, cool and well-ventilated place. Keep container tightly closed. Keep away from heat, sparks and flame. Flammables area. Corrosives area. Keep containers tightly closed in a dry, cool and well-ventilated place.

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Outroi i didilictors			
Component	Malaysia	ACGIH TLV	OSHA PEL
Diethylaminoethanol		TWA: 2 ppm	(Vacated) TWA: 10 ppm
		Skin	(Vacated) TWA: 50 mg/m ³
			Skin
			TWA: 10 ppm
			TWA: 50 mg/m ³

Component	European Union	The United Kingdom	Germany
Diethylaminoethanol			TWA: 2 ppm (8 Stunden). AGW -
			ceiling factor 2.5; exposure factor 1
			TWA: 9.7 mg/m³ (8 Stunden). AGW
			- ceiling factor 2.5; exposure factor
			1
			TWA: 2 ppm (8 Stunden). MAK
			even if the MAK value is adhered to,
			"odor-associated" symptoms cannot
			be ruled out in individual cases
			TWA: 9.7 mg/m³ (8 Stunden). MAK
			even if the MAK value is adhered to,
			"odor-associated" symptoms cannot
			be ruled out in individual cases
			Höhepunkt: 2 ppm
			Höhepunkt: 9.7 mg/m ³
			Haut

Exposure Controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or

N,N-Diethylethanolamine Revision Date 21-Mar-2025

equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles

Hand Protection Protective gloves Skin and body protection Long sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

When workers are facing concentrations above the exposure limit they must use **Respiratory Protection**

appropriate certified respirators

Particulates filter conforming to EN 143 Ammonia and organic ammonia derivatives filter Recommended Filter type:

Type K Green conforming to EN14387

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

When RPE is used a face piece Fit Test should be conducted

Handle in accordance with good industrial hygiene and safety practice **Hygiene Measures**

Environmental exposure controls Prevent product from entering drains

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance Colorless **Physical State** Liquid Odor Ammonia-like **Odor Threshold** No data available

(10%)11 - 12 (@ 20) рH

-70 °C / -94 °F **Melting Point/Range Softening Point** No data available

Boiling Point/Range 161 °C / 321.8 °F @ 760 mmHa

51.5 °C / 124.7 °F **Flash Point** Method - No information available

Evaporation Rate No data available

Flammability (solid,gas) Not applicable Liquid **Explosion Limits** Lower 0.7 vol%

Upper 10.1 vol%

1.9 mbar @ 20 °C **Vapor Pressure** Vapor Density No data available

(Air = 1.0)

Specific Gravity / Density 0.880

Bulk Density Not applicable Liquid

Water Solubility Soluble

No information available Solubility in other solvents

N,N-Diethylethanolamine Revision Date 21-Mar-2025

Partition Coefficient (n-octanol/water)

Component log Pow Diethylaminoethanol 0.21

Autoignition Temperature Decomposition Temperature

260 °C / 500 °F No data available No data available

Viscosity

Explosive Properties Oxidizing Properties

No information available

explosive air/vapour mixtures possible

Molecular Formula C6 H15 N O 117.19 **Molecular Weight**

SECTION 10: STABILITY AND REACTIVITY

Reactivity

None known, based on information available.

Chemical Stability

Hygroscopic.

Possibility of Hazardous Reactions

Hazardous Polymerization Hazardous Reactions

No information available. None under normal processing.

Conditions to Avoid

Keep away from open flames, hot surfaces and sources of ignition. Excess heat. Exposure

to light. Incompatible products. Exposure to moist air or water.

Incompatible Materials

Acids. Strong oxidizing agents. Acid anhydrides. Metals. copper.

Hazardous Decomposition Products

Nitrogen oxides (NOx). Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Product Information

(a) acute toxicity;

Oral Category 4 **Dermal** Category 3

N,N-Diethylethanolamine

Inhalation	Category 3						
Component	LD50 Oral	LD50 Dermal	LC50 Inhalation				
Diethylaminoethanol	LD50 = 1320 mg/kg (Rat)	LD50 = 1 mL/kg (Rabbit)	LC50: 4.6 mg/L/4h (Rat)				

Category 1 B (b) skin corrosion/irritation;

Category 1 (c) serious eye damage/irritation;

(d) respiratory or skin sensitization;

Respiratory Skin

Based on available data, the classification criteria are not met Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met (e) germ cell mutagenicity;

Not mutagenic in AMES Test

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Based on available data, the classification criteria are not met

(h) STOT-single exposure; Category 3

Results / Target organs Respiratory system.

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Target Organs None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

delayed

Symptoms / effects, both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any

known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

Contains a substance which is:. Harmful to aquatic organisms. The product contains **Ecotoxicity effects**

following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Diethylaminoethanol	LC50: 1660 - 1920	EC50: = 83.6 mg/L, 48h	EC50: = 30 mg/L, 72h	
	mg/L, 96h flow-through	(Daphnia magna Straus)	(Desmodesmus	
	(Pimephales promelas)		subspicatus)	
	1			

Persistence and degradability Expected to be biodegradable

ACR11433

Revision Date 21-Mar-2025

N,N-Diethylethanolamine

Persistence
Degradation in sewage
treatment plant

Soluble in water, Persistence is unlikely, based on information available.

Contains substances known to be hazardous to the environment or not degradable in waste

Revision Date 21-Mar-2025

water treatment plants.

Bioaccumulative potential Bioaccumulation is unlikely

 Component
 log Pow
 Bioconcentration factor (BCF)

 Diethylaminoethanol
 0.21
 <6.1 L/kg</td>

the environment due to its water solubility. Highly mobile in soils.

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

Other adverse effects No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous Dispose of in accordance with the European Directives on

waste and hazardous waste Dispose of in accordance with local regulations

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous Keep product and

empty container away from heat and sources of ignition

Other Information Do not flush to sewer Waste codes should be assigned by the user based on the

application for which the product was used Can be landfilled or incinerated, when in

compliance with local regulations Do not empty into drains Large amounts will affect pH and

harm aquatic organisms

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

UN-No UN2686

Hazard Class 8
Subsidiary Hazard Class 3
Packing Group || |

Proper Shipping Name 2-DIETHYLAMINOETHANOL

Road and Rail Transport

UN-No UN2686

Hazard Class 8
Subsidiary Hazard Class 3
Packing Group ||

Proper Shipping Name 2-DIETHYLAMINOETHANOL

IATA

UN-No UN2686 Hazard Class 8

Subsidiary Hazard Class
Packing Group

Proper Shipping Name 2-DIETHYLAMINOETHANOL

N,N-Diethylethanolamine Revision Date 21-Mar-2025

Special Precautions for User No special precautions required

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories X = listed

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Diethylaminoethanol	202-845-2	Х	X	Х	Х	X	Х	Х	KE-20903

National Regulations

Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 16: OTHER INFORMATION

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical **DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List of Notified Chemical Substances

Substances/EU List of Notified Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECS - Philippines Inventory of Chemicals and Chemical Substantial IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

AICS - Australian Inventory of Chemical Substances
NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment **LC50** - Lethal Concentration 50%

POW - Partition coefficient Octanol:Water

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Revision Date 21-Mar-2025 Revision Summary 21-Mar-2025 Not applicable.

In accordance with local and national regulations: Occupational Safety and Health

Revision Date 21-Mar-2025

(Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet