

# **SAFETY DATA SHEET**

Creation Date 23-September-2009 Revision Date 24-May-2018 Revision Number 3

1. Identification

Product Name Zinc PVA Fixative

Cat No.: R21278, R21279, R21765, R21927

Synonyms No information available

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet

<u>Company</u> Remel 12076 Santa Fe Drive

Lenexa, KS 66215 United States Telephone: 1-800-255-6730 Fax:1-800-621-8251 Manufacturer Fisher Scientific One Reagent Lane Fair Lawn, NJ 07410

Tel: (201) 796-7100

**Emergency Telephone Number** 

INFOTRAC - 24 Hour Number: 1-800-535-5053

Outside of the United States, call 24 Hour Number: 001-352-323-3500 (Call Collect)

# 2. Hazard(s) identification

Classification

WHMIS 2015 Classification Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

Flammable liquids

Skin Corrosion/irritation

Serious Eye Damage/Eye Irritation

Specific target organ toxicity (single exposure)

Target Organs - Respiratory system, Central nervous system (CNS), Optic nerve.

### **Label Elements**

## Signal Word

Danger

#### **Hazard Statements**

Flammable liquid and vapor Causes skin irritation Causes serious eye damage May cause respiratory irritation May cause drowsiness and dizziness Causes damage to organs

Zinc PVA Fixative



## **Precautionary Statements**

#### Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use only non-sparking tools

Take precautionary measures against static discharges

Do not breathe dust/fumes/gas/mist/vapours/spray

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection/face protection

#### Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

IF INHALED: Remove person to fresh air and keep comfortable for breathing

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If exposed or concerned: Call a POISON CENTER/ doctor

Immediately call a POISON CENTER/doctor

Wash contaminated clothing before reuse

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

### Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

### **Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Other Hazards

Toxic to aquatic life with long lasting effects

# 3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Glycerin	56-81-5	1.5
Ethyl alcohol	64-17-5	28 - 29
Methyl alcohol	67-56-1	1.5
Acetic acid	64-19-7	4.5
Zinc sulfate heptahydrate	7446-20-0	2.5

## 4. First-aid measures

**General Advice** Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. **Eye Contact** 

**Skin Contact** SPEEDY ACTION IS CRITICAL, GET MEDICAL AID IMMEDIATELY.

Inhalation Move to fresh air.

Ingestion Rinse mouth. Get medical attention.

Breathing difficulties. Causes eye burns. . Symptoms of overexposure may be headache, Most important symptoms/effects

dizziness, tiredness, nausea and vomiting

Treat symptomatically Notes to Physician

## Fire-fighting measures

Suitable Extinguishing Media Cool closed containers exposed to fire with water spray.

**Unsuitable Extinguishing Media** No information available

29.4 °C / 84.9 °F **Flash Point** 

Method -No information available

**Autoignition Temperature** 

**Explosion Limits** 

No information available

Upper No data available Lower No data available Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

### Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

#### **Hazardous Combustion Products**

None known

### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health	Flammability	Instability	Physical hazards
3	3	0	N/A

## Accidental release measures

**Personal Precautions** 

Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation. Take precautionary measures against static discharges.

**Environmental Precautions** 

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. See Section 12 for additional ecological information. Avoid release to the environment. Collect spillage. Do not flush into surface water or sanitary sewer system.

Up

Methods for Containment and Clean Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Ground and bond containers when transferring material. Take precautionary measures against static discharges. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

## 7. Handling and storage

Handling

Ensure adequate ventilation. Do not breathe vapors or spray mist. Keep container tightly closed. Ensure adequate ventilation. Take precautionary measures against static discharges. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools.

Storage

Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and

sources of ignition.

Zinc PVA Fixative

## 8. Exposure controls / personal protection

### **Exposure Guidelines**

Component	Alberta	British Columbia	Ontario TWAEV	Quebec	ACGIH TLV	OSHA PEL	NIOSH IDLH
Glycerin	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>		TWA: 10 mg/m <sup>3</sup>		(Vacated) TWA:	
Glyceilli	TWA. TO HIg/III	TWA: 10 mg/m <sup>3</sup>		TWA. 10 mg/m²		10 mg/m <sup>3</sup>	
		TWA. 5 mg/m				(Vacated) TWA:	
						5 mg/m <sup>3</sup>	
						TWA: 15 mg/m <sup>3</sup>	
						TWA: 5 mg/m <sup>3</sup>	
Ethyl alcohol	TWA: 1000 ppm	STFL: 1000 ppm	STEL: 1000 ppm	TWA: 1000 ppm	STEL: 1000 ppm		IDLH: 3300 ppm
	TWA: 1880	0122. 1000 pp	0122. 1000 pp	TWA: 1880	0122. 1000 pp	1000 ppm	TWA: 1000 ppm
	mg/m³			mg/m³		(Vacated) TWA:	TWA: 1900
				9		1900 mg/m <sup>3</sup>	mg/m³
						TWA: 1000 ppm	
						TWA: 1900	
						mg/m³	
Methyl alcohol	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm	(Vacated) TWA:	IDLH: 6000 ppm
1	TWA: 262	STEL: 250 ppm	STEL: 250 ppm	TWA: 262	STEL: 250 ppm	200 ppm	TWA: 200 ppm
	mg/m³	Skin	Skin	mg/m³	Skin	(Vacated) TWA:	TWA: 260
	STEL: 250 ppm			STEL: 250 ppm		260 mg/m <sup>3</sup>	mg/m³
	STEL: 328			STEL: 328		(Vacated) STEL:	STEL: 250 ppm
	mg/m³			mg/m³		250 ppm	STEL: 325
	Skin			Skin		(Vacated) STEL:	mg/m³
						325 mg/m <sup>3</sup>	
						Skin	
						TWA: 200 ppm	
						TWA: 260	
						mg/m³	
Acetic acid	TWA: 10 ppm	TWA: 10 ppm	TWA: 10 ppm	TWA: 10 ppm	TWA: 10 ppm	(Vacated) TWA:	IDLH: 50 ppm
	TWA: 25 mg/m <sup>3</sup>	STEL: 15 ppm	STEL: 15 ppm	TWA: 25 mg/m <sup>3</sup>	STEL: 15 ppm	10 ppm	TWA: 10 ppm
	STEL: 15 ppm			STEL: 15 ppm		(Vacated) TWA:	TWA: 25 mg/m <sup>3</sup>
	STEL: 37 mg/m <sup>3</sup>			STEL: 37 mg/m <sup>3</sup>		25 mg/m <sup>3</sup>	STEL: 15 ppm
						TWA: 10 ppm	STEL: 37 mg/m <sup>3</sup>
						TWA: 25 mg/m <sup>3</sup>	

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

### **Engineering Measures**

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

#### Personal protective equipment

**Eye Protection** Goggles

**Hand Protection** Wear appropriate protective gloves and clothing to prevent skin exposure.

Glove material	Breakthrough time	Glove thickness	Glove comments
Nitrile rubber	See manufacturers	-	Splash protection only
	recommendations		

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

#### **Respiratory Protection**

Zinc PVA Fixative

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

When RPE is used a face piece Fit Test should be conducted

#### **Environmental exposure controls**

Local authorities should be advised if significant spillages cannot be contained. Do not allow material to contaminate ground water system. Prevent product from entering drains.

## **Hygiene Measures**

When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

## 9. Physical and chemical properties

**Physical State** Liquid Appearance Clear

Odor No information available **Odor Threshold** No information available Ηд No information available Melting Point/Range No data available Boiling Point/Range

No information available Flash Point 29.4 °C / 84.9 °F **Evaporation Rate** No information available Flammability (solid,gas) Not applicable

Flammability or explosive limits

Upper No data available Lower No data available

**Vapor Pressure** No information available No information available **Vapor Density** No information available **Specific Gravity** Solubility No information available Partition coefficient; n-octanol/water No data available

**Autoignition Temperature** No information available No information available **Decomposition Temperature Viscosity** No information available

VOC Content(%) 36.5

## 10. Stability and reactivity

None known, based on information available **Reactive Hazard** 

Stable under normal conditions. **Stability** 

Heating in air. Keep away from open flames, hot surfaces and sources of ignition. **Conditions to Avoid** 

**Incompatible Materials** Strong oxidizing agents

Hazardous Decomposition Products None under normal use conditions

**Hazardous Polymerization** Hazardous polymerization does not occur.

**Hazardous Reactions** None under normal processing.

## 11. Toxicological information

**Acute Toxicity** 

**Product Information** 

Oral LD50 Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

Zinc PVA Fixative

Dermal LD50 Vapor LC50 Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.

**Component Information** 

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Glycerin	12600 mg/kg ( Rat )	> 10 g/kg (Rabbit)	> 2.75 mg/L/4h ( Rat )(mist)
Ethyl alcohol	LD50 = 7060 mg/kg (Rat)	Not listed	20000 ppm/10H ( Rat )
Methyl alcohol	Calc. ATE 60 mg/kg LD50 > 1187 – 2769 mg/kg ( Rat )	Calc. ATE 60 mg/kg LD50 = 17100 mg/kg ( Rabbit )	Calc. ATE 0.6 mg/L (vapours) or 0.5 mg/L (mists) LC50 = 128.2 mg/L ( Rat ) 4 h
Methyl alcohol  Acetic acid			0.5 mg/L (mists)

**Toxicologically Synergistic** 

No information available

**Products** 

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation No information available

Sensitization No information available

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

This product contains one or more substances which are classified by IARC as

carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly

carcinogenic to humans (Group 2B). Ethanol has been shown to be carcinogenic in long-term studies only when consumed and abused as an alcoholic beverage.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Glycerin	56-81-5	Not listed				
Ethyl alcohol	64-17-5	Group 1	Known	A3	X	Not listed
Methyl alcohol	67-56-1	Not listed				
Acetic acid	64-19-7	Not listed				
Zinc sulfate	7446-20-0	Not listed				
heptahydrate						

IARC: (International Agency for Research on Cancer)

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

ACGIH: (American Conference of Governmental Industrial

Hygienists)

A1 - Known Human Carcinogen A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

Mutagenic Effects No information available

Reproductive Effects

No information available.

Developmental Effects

No information available.

Teratogenicity

No information available.

STOT - single exposure Respiratory system Central nervous system (CNS) Optic nerve

STOT - repeated exposure None known

Aspiration hazard No information available

delayed

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

Zinc PVA Fixative

# 12. Ecological information

## **Ecotoxicity**

Contains a substance which is:. Toxic to aquatic organisms. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Glycerin	Not listed	LC50: 51 - 57 mL/L, 96h static (Oncorhynchus mykiss)	Not listed	EC50: > 500 mg/L, 24h (Daphnia magna)
Ethyl alcohol	EC50 (72h) = 275 mg/l (Chlorella vulgaris)	Fathead minnow (Pimephales promelas) LC50 = 14200 mg/l/96h	Photobacterium phosphoreum:EC50 = 34634 mg/L/30 min Photobacterium phosphoreum:EC50 = 35470 mg/L/5 min	Ç
Methyl alcohol	Not listed	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	EC50 > 10000 mg/L 24h
Acetic acid	-	Pimephales promelas: LC50 = 88 mg/L/96h Lepomis macrochirus: LC50 = 75 mg/L/96h	phosphoreum: EC50 = 8.8	EC50 = 95 mg/L/24h
Zinc sulfate heptahydrate	Not listed	1.9 mg/L LC50 96 h	Not listed	Not listed

**Persistence and Degradability** 

No information available

**Bioaccumulation/ Accumulation** 

No information available.

Mobility

Component	log Pow
Glycerin	-1.76
Ethyl alcohol	-0.32
Methyl alcohol	-0.74
Acetic acid	-0.2

## 13. Disposal considerations

**Waste Disposal Methods** 

Should not be released into the environment. Dispose of in accordance with local regulations.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes	
Methyl alcohol - 67-56-1	U154	-	

# 14. Transport information

DOT

**UN-No** UN1170

Proper Shipping Name ETHANOL SOLUTION

Hazard Class 3
Packing Group III

**TDG** 

**UN-No** UN1170

Proper Shipping Name ETHANOL SOLUTION

Hazard Class 3
Packing Group III

**IATA** 

**UN-No** UN1170

Proper Shipping Name ETHANOL SOLUTION

Hazard Class 3
Packing Group III

IMDG/IMO

UN-No UN1170

Proper Shipping Name ETHANOL SOLUTION

Hazard Class 3
Packing Group III

## 15. Regulatory information

All of the components in the product are on the following Inventory lists: X = listed

#### International Inventories

Component	DSL	NDSL	TSCA	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Glycerin	Х	-	Χ	200-289-5	-		Х	Х	Х	Х	Χ
Ethyl alcohol	Х	-	Х	200-578-6	-		Х	Χ	Χ	Х	Χ
Methyl alcohol	Х	-	Х	200-659-6	-		Х	Х	Χ	Х	Χ
Acetic acid	Х	-	X	200-580-7	-		Х	Х	Χ	Х	Χ
Zinc sulfate heptahydrate	Х	-	-	-	-		Х	-	Χ	Х	-

#### Canada

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

Component	Canada - National Pollutant Release Inventory (NPRI)	Canadian Environmental Protection Agency (CEPA) - List of Toxic Substances	Canada's Chemicals Management Plan (CEPA)
Ethyl alcohol	Part 5, Individual Substances		
Methyl alcohol	Part 1, Group A Substance Part 5, Individual Substances		

## 16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

Creation Date 23-September-2009

Revision Date24-May-2018Print Date24-May-2018

**Revision Summary**This document has been updated to comply with the requirements of WHMIS 2015 to align

with the Globally Harmonised System (GHS) for the Classification and Labelling of

Chemicals.

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

## **End of SDS**