

# **SAFETY DATA SHEET**

Creation Date 03-June-2010 Revision Date 03-January-2025 Revision Number 1

### 1. Identification

Product Name 1-Propanol, ACS

Cat No.: W00402

**CAS-No** 71-23-8

Synonyms n-Propyl Alcohol; Propyl alcohol; n-Propanol

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

### Details of the supplier of the safety data sheet

#### Company

### Importer/Distributor

Fisher Scientific 112 Colonnade Road, Ottawa, ON K2E 7L6,

Canada

Tel: 1-800-234-7437

## **Emergency Telephone Number**

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

## 2. Hazard(s) identification

#### Classification

WHMIS 2015 Classification Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

Flammable liquids Category 2
Serious Eye Damage/Eye Irritation Category 1
Specific target organ toxicity (single exposure) Category 3

Target Organs - Central nervous system (CNS).

# Label Elements

#### Signal Word

Danger

#### **Hazard Statements**

Highly flammable liquid and vapor Causes serious eye damage May cause drowsiness and dizziness



### **Precautionary Statements**

#### Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection/face protection

Use only non-sparking tools

Take action to prevent static discharges

#### Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

IF INHALED: Remove person to fresh air and keep comfortable for breathing

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER/doctor

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

#### Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

#### **Disposal**

Dispose of contents/container to an approved waste disposal plant

# 3. Composition/Information on Ingredients

Component	CAS-No	Weight %
n-Propanol	71-23-8	> 99

#### 4. First-aid measures

**General Advice** If symptoms persist, call a physician.

**Eye Contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

**Inhalation** Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

**Ingestion** Clean mouth with water and drink afterwards plenty of water.

Most important symptoms/effects Difficulty in breathing. Causes eye burns. Causes severe eye damage. Inhalation of high

vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea

and vomiting

Notes to Physician Treat symptomatically

## 5. Fire-fighting measures

Suitable Extinguishing Media CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool

closed containers.

Unsuitable Extinguishing Media Water may be ineffective

Flash Point 15 °C / 59 °F

**Method -** No information available

Autoignition Temperature 405 °C / 761 °F

**Explosion Limits** 

**Upper** 13.7 vol % **Lower** 2.2 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

#### **Specific Hazards Arising from the Chemical**

Flammable. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

#### **Hazardous Combustion Products**

Carbon monoxide (CO). Carbon dioxide (CO2).

### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health	Flammability	Instability	Physical hazards
2	3	0	N/A

### 6. Accidental release measures

Personal Precautions Use personal protective equipment as required. Ensure adequate ventilation. Remove all

sources of ignition. Take precautionary measures against static discharges.

**Environmental Precautions** Should not be released into the environment. See Section 12 for additional Ecological

Information.

**Methods for Containment and Clean** Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. **Up**Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

## 7. Handling and storage

Handling Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on

clothing. Avoid ingestion and inhalation. Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Take precautionary measures against static discharges.

Storage. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

heat, sparks and flame. Flammables area. Incompatible Materials. Strong oxidizing

agents. Strong acids.

### 8. Exposure controls / personal protection

**Exposure Guidelines** 

Component	Alberta	British Columbia	Ontario TWAEV	Quebec	ACGIH TLV	OSHA PEL	NIOSH
n-Propanol	TWA: 200 ppm TWA: 492 mg/m³ STEL: 400 ppm STEL: 984 mg/m³	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm		(Vacated) TWA: 200 ppm (Vacated) TWA: 500 mg/m³ (Vacated) STEL: 250 ppm (Vacated) STEL: 625 mg/m³ TWA: 200 ppm TWA: 500 mg/m³	REL = 200 ppm (TWA) REL = 500 mg/m³ (TWA) STEL: 250 ppm

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

#### **Engineering Measures**

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

#### Personal protective equipment

**Eye Protection** Goggles

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	Glove comments
Nitrile rubber	See manufacturers	-	Splash protection only
Viton (R)	recommendations		

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

#### **Respiratory Protection**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly **Recommended Filter type:** Organic gases and vapours filter Type A Brown conforming to EN14387

When RPE is used a face piece Fit Test should be conducted

#### **Environmental exposure controls**

No information available.

#### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

### 9. Physical and chemical properties

Physical State Liquid Appearance Colorless

Odor Alcohol-like

Odor Threshold<br/>pHNo information available<br/>20% aq. solutionMelting Point/Range-127 °C / -196.6 °F

Boiling Point/Range 97 °C / 206.6 °F @ 760 mmHg

Flash Point 15 °C / 59 °F

Evaporation Rate
No information available
Flammability (solid,gas)
Not applicable

Flammability or explosive limits

 Upper
 13.7 vol %

 Lower
 2.2 vol %

Vapor Pressure25 mbar @ 20 °CVapor Density2.07

Vapor Density 2.07
Specific Gravity 0.800

Solubility
Miscible with water
Partition coefficient; n-octanol/water
Autoignition Temperature
Decomposition Temperature
Viscosity
Miscible with water
No data available
405 °C / 761 °F
No information available
2.2 mPa.s at 20 °C

Viscosity2.2 mPa.sMolecular FormulaC3 H8 OMolecular Weight60.1

# 10. Stability and reactivity

Reactive Hazard None known, based on information available

**Stability** Stable under normal conditions.

Conditions to Avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong acids

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2)

Hazardous Polymerization Hazardous polymerization does not occur.

**Hazardous Reactions** None under normal processing.

## 11. Toxicological information

### **Acute Toxicity**

#### **Product Information**

**Component Information** 

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation		
n-Propanol	LD50 = 1870 mg/kg (Rat)	LD50 = 4049 mg/kg (Rabbit)	LC50 > 33.8 mg/L (Rat) 4 h		

Toxicologically Synergistic No information available

**Products** 

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Irritation** Severe eye irritant

**Sensitization** No information available

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
n-Propanol	71-23-8	Not listed				

Mutagenic Effects No information available

**Reproductive Effects** No information available.

**Developmental Effects** No information available.

**Teratogenicity** No information available.

STOT - single exposure Central nervous system (CNS)

STOT - repeated exposure None known

**Aspiration hazard** No information available

delayed

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting

**Endocrine Disruptor Information** No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

## 12. Ecological information

#### Ecotoxicity

Do not empty into drains. .

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
n-Propanol	Not listed	Pimephales promelas: LC50=4480 mg/L 96h	EC50 = 17700 mg/L 5 min EC50 = 45000 mg/L 5 h EC50 = 8686 mg/L 15 min EC50 = 980 mg/L 12 h	EC50: 3339 - 3977 mg/L, 48h Static (Daphnia magna) EC50: = 3642 mg/L, 48h (Daphnia magna)

**Persistence and Degradability** Persistence is unlikely

**Bioaccumulation/ Accumulation** No information available.

Mobility . Will likely be mobile in the environment due to its water solubility.

Component	log Pow
n-Propanol	0.2

# 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

## 14. Transport information

DOT

UN1274 **UN-No** N-PROPANOL **Proper Shipping Name** 

**Hazard Class Packing Group** 

TDG

UN1274 **UN-No Proper Shipping Name** n-Propanol

**Hazard Class Packing Group** Ш

**IATA** 

UN1274 **UN-No** n-PROPANOL **Proper Shipping Name** 

**Hazard Class Packing Group** Ш

Revision Date 03-January-2025

1-Propanol, ACS

IMDG/IMO

UN-No UN1274
Proper Shipping Name N-PROPANOL

Hazard Class 3
Packing Group II

# 15. Regulatory information

#### **International Inventories**

	Component	CAS-No	DSL	NDSL	TSCA	TSCA Inventory notification - Active-Inactive	EINECS	ELINCS	NLP
n-Propanol 71-23-8 X - X ACTIVE 200-746-9 -	n-Propanol	71-23-8	X	-	Х	ACTIVE	200-746-9	-	-

	Component	CAS-No	IECSC	KECL	ENCS	ISHL	TCSI	AICS	NZIoC	PICCS
Γ	n-Propanol	71-23-8	Х	KE-29362	Х	Х	X	X	Х	Х

#### Legend:

X - Listed '-' - Not Listed

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**ENCS** - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

#### Canada

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

Component	Canada - National Pollutant Release Inventory (NPRI)	Canadian Environmental Protection Agency (CEPA) - List of Toxic Substances	Canada's Chemicals Management Plan (CEPA)
n-Propanol	Part 5, Individual Substances Part 4 Substance		

Legend

NPRI - National Pollutant Release Inventory

### **Other International Regulations**

#### Authorisation/Restrictions according to EU REACH

Component	,	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	• • • • • • • • • • • • • • • • • • • •
n-Propanol	-	Use restricted. See entry 75. (see link for restriction details)	-

#### **REACH links**

https://echa.europa.eu/substances-restricted-under-reach

## Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS-No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
n-Propanol	71-23-8	Listed	Not applicable	Not applicable	Not applicable

Revision Date 03-January-2025

### 1-Propanol, ACS

	Component	CAS-No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
L	n-Propanol	71-23-8	Not applicable	Not applicable	Not applicable	Not applicable

## 16. Other information

Prepared By Product Safety Department

Email: chem.techinfo@thermofisher.com

www.thermofisher.com

Creation Date03-June-2010Revision Date03-January-2025Print Date03-January-2025Revision SummaryInitial Release.

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**